

## KubeCon + CloudNativeCon 2024

Join us for three days of incredible opportunities to collaborate, learn and share with the cloud native community.  
[Buy your ticket now! 12 - 15 November | Salt Lake City](#)



[Kubernetes Documentation](#) / [Reference](#) / [Kubernetes API](#) / [Authorization Resources](#) / [ClusterRole](#)

# ClusterRole


ClusterRole is a cluster level, logical grouping of PolicyRules that can be referenced as a unit by a RoleBinding or ClusterRoleBinding.

```
apiVersion: rbac.authorization.k8s.io/v1
```

```
import "k8s.io/api/rbac/v1"
```

## ClusterRole

ClusterRole is a cluster level, logical grouping of PolicyRules that can be referenced as a unit by a RoleBinding or ClusterRoleBinding.

-  Search this site
- ▶ Documentation

▶ Getting started

▶ Concepts

▶ Tasks

▶ Tutorials

▼ Reference

Glossary

▶ API Overview

▶ API Access Control

▶ Well-Known Labels, Annotations and Taints

▼ Kubernetes API

▶ Workload Resources

▶ Service Resources

▶ Config and Storage Resources

▶ Authentication Resources

▼ Authorization Resources

- **apiVersion:** rbac.authorization.k8s.io/v1
- **kind:** ClusterRole
- **metadata** ([ObjectMeta](#))

Standard object's metadata.
- **aggregationRule** (AggregationRule)

AggregationRule is an optional field that describes how to build the Rules for this ClusterRole. If AggregationRule is set, then the Rules are controller managed and direct changes to Rules will be stomped by the controller.  
*AggregationRule describes how to locate ClusterRoles to aggregate into the ClusterRole*
  - **aggregationRule.clusterRoleSelectors** ([\[\]LabelSelector](#))

*Atomic: will be replaced during a merge*  
ClusterRoleSelectors holds a list of selectors which will be used to find ClusterRoles and create the rules. If any of the selectors match, then the ClusterRole's permissions will be added
- **rules** ([\[\]PolicyRule](#))

*Atomic: will be replaced during a merge*  
Rules holds all the PolicyRules for this ClusterRole

Subject

**ClusterRole**

ClusterRole

Role

RoleBinding

▸ Policy Resources

▸ Extend Resources

▸ Cluster Resources

▸ Common Definitions

Common Parameters

▸ Instrumentation

▸ Kubernetes

*Atomic: will be replaced during a merge*

APIGroups is the name of the APIGroup that contains the resources. If multiple API groups are specified, any action requested against one of the enumerated resources in any API group will be allowed. "" represents the core API group and "\*" represents all API groups.

- **rules.resources** ([]string)

*Atomic: will be replaced during a merge*

Resources is a list of resources this rule applies to. '\*' represents all resources.

- **rules.verbs** ([]string), required

*Atomic: will be replaced during a merge*

Verbs is a list of Verbs that apply to ALL the ResourceKinds contained in this rule. '\*' represents all verbs.

- **rules.resourceNames** ([]string)

*Atomic: will be replaced during a merge*

ResourceNames is an optional white list of names that the rule applies to. An empty set means that everything is allowed.

- **rules.nonResourceURLs** ([]string)

*Atomic: will be replaced during a merge*

NonResourceURLs is a set of partial urls that a user should have access to. \*s are allowed, but only as the full, final step in the path. Since non-resource URLs are not namespaced, this field is only applicable for ClusterRoles referenced from a ClusterRoleBinding. Rules can either apply to API resources (such as "pods" or "secrets") or non-resource URL paths (such as "/api"), but not both.

## ClusterRoleList

ClusterRoleList is a collection of ClusterRoles

- **apiVersion:** rbac.authorization.k8s.io/v1
- **kind:** ClusterRoleList
- **metadata** ([ListMeta](#))

Standard object's metadata.

- **items** ([][ClusterRole](#)), required

Items is a list of ClusterRoles

## Operations

GET /apis/rbac.authorization.k8s.io/v1/clusterroles {name}

### Parameters

- **name** (*in path*): string, required  
name of the ClusterRole
- **pretty** (*in query*): string  
[pretty](#)

### Response

200 ([ClusterRole](#)): OK

401: Unauthorized

### list list or watch objects of kind ClusterRole

### HTTP Request

GET /apis/rbac.authorization.k8s.io/v1/clusterroles

### Parameters

- **allowWatchBookmarks** (*in query*): boolean  
[allowWatchBookmarks](#)
- **continue** (*in query*): string  
[continue](#)
- **fieldSelector** (*in query*): string  
[fieldSelector](#)
- **labelSelector** (*in query*): string  
[labelSelector](#)
- **limit** (*in query*): integer  
[limit](#)
- **pretty** (*in query*): string  
[pretty](#)
- **resourceVersion** (*in query*): string  
[resourceVersion](#)
- **resourceVersionMatch** (*in query*): string  
[resourceVersionMatch](#)
- **sendInitialEvents** (*in query*): boolean  
[sendInitialEvents](#)
- **timeoutSeconds** (*in query*): integer

## Response

200 ([ClusterRoleList](#)): OK

401: Unauthorized

## create create a ClusterRole

## HTTP Request

POST /apis/rbac.authorization.k8s.io/v1/clusterroles

## Parameters

- **body**: [ClusterRole](#), required
- **dryRun** (*in query*): string  
[dryRun](#)
- **fieldManager** (*in query*): string  
[fieldManager](#)
- **fieldValidation** (*in query*): string  
[fieldValidation](#)
- **pretty** (*in query*): string  
[pretty](#)

## Response

200 ([ClusterRole](#)): OK

201 ([ClusterRole](#)): Created

202 ([ClusterRole](#)): Accepted

401: Unauthorized

## update replace the specified ClusterRole

## HTTP Request

PUT /apis/rbac.authorization.k8s.io/v1/clusterroles/{name}

## Parameters

- **name** (*in path*): string, required  
name of the ClusterRole
- **body**: [ClusterRole](#), required
- **dryRun** (*in query*): string  
[dryRun](#)
- **fieldManager** (*in query*): string

- **pretty** (*in query*): string

[pretty](#)

### Response

200 ([ClusterRole](#)): OK

201 ([ClusterRole](#)): Created

401: Unauthorized

## patch partially update the specified ClusterRole

### HTTP Request

PATCH /apis/rbac.authorization.k8s.io/v1/clusterroles/{name}

### Parameters

- **name** (*in path*): string, required

name of the ClusterRole

- **body**: [Patch](#), required

- **dryRun** (*in query*): string

[dryRun](#)

- **fieldManager** (*in query*): string

[fieldManager](#)

- **fieldValidation** (*in query*): string

[fieldValidation](#)

- **force** (*in query*): boolean

[force](#)

- **pretty** (*in query*): string

[pretty](#)

### Response

200 ([ClusterRole](#)): OK

201 ([ClusterRole](#)): Created

401: Unauthorized

## delete delete a ClusterRole

### HTTP Request

DELETE /apis/rbac.authorization.k8s.io/v1/clusterroles/{name}

### Parameters

- **dryRun** *(in query)*: string

[dryRun](#)

- **gracePeriodSeconds** *(in query)*: integer

[gracePeriodSeconds](#)

- **pretty** *(in query)*: string

[pretty](#)

- **propagationPolicy** *(in query)*: string

[propagationPolicy](#)

### Response

200 ([Status](#)): OK

202 ([Status](#)): Accepted

401: Unauthorized

### deletecollection delete collection of ClusterRole

### HTTP Request

DELETE /apis/rbac.authorization.k8s.io/v1/clusterroles

### Parameters

- **body**: [DeleteOptions](#)

- **continue** *(in query)*: string

[continue](#)

- **dryRun** *(in query)*: string

[dryRun](#)

- **fieldSelector** *(in query)*: string

[fieldSelector](#)

- **gracePeriodSeconds** *(in query)*: integer

[gracePeriodSeconds](#)

- **labelSelector** *(in query)*: string

[labelSelector](#)

- **limit** *(in query)*: integer

[limit](#)

- **pretty** *(in query)*: string

[pretty](#)

- **propagationPolicy** *(in query)*: string

- **resourceVersionMatch** (*in query*): string

[resourceVersionMatch](#)

- **sendInitialEvents** (*in query*): boolean

[sendInitialEvents](#)

- **timeoutSeconds** (*in query*): integer

[timeoutSeconds](#)

### Response

200 ([Status](#)): OK

401: Unauthorized

This page is automatically generated.

If you plan to report an issue with this page, mention that the page is auto-generated in your issue description. The fix may need to happen elsewhere in the Kubernetes project.

## Feedback

Was this page helpful?

Yes

No

Last modified August 28, 2024 at 6:01 PM PST: [Update generated API reference for v1.31 \(8ba98c79c1\)](#)



© 2024 The Kubernetes Authors | Documentation Distributed under CC BY 4.0



© 2024 The Linux Foundation ®. All rights reserved. The Linux Foundation has registered trademarks and uses trademarks. For a list of trademarks of The Linux Foundation, please see our [Trademark Usage page](#)

ICP license: 京ICP备17074266号-3