

MITRE

ENGUITY.

Center  
for Threat  
Informed  
Defense

Summitting the  
Pyramid

v1.0.0

Search docs

CONTENTS

Overview

Introduction

Definitions

Model Mapping Pages

Combining Observables

Example Mappings

How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

Original Analytic Scoring

Improved Analytic Scoring #1

Improved Analytic Scoring #2

Service Registry Permissions Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements

Changelog

## Scheduled Task/Job

- [https://github.com/SigmaHQ/sigma/blob/c0332a9d96f6c7804fcc85dd706caed889446a62/rules/windows/process\\_creation/proc\\_creation\\_win\\_schtasks\\_creation.yml](https://github.com/SigmaHQ/sigma/blob/c0332a9d96f6c7804fcc85dd706caed889446a62/rules/windows/process_creation/proc_creation_win_schtasks_creation.yml)

```
title: Scheduled Task Creation
id: 92626ddd-662c-49e3-ac59-f6535f12d189
status: test
description: Detects the creation of scheduled tasks in user session
author: Florian Roth (Nextron Systems)
date: 2019/01/16
modified: 2022/10/09
tags:
  - attack.execution
  - attack.persistence
  - attack.privilege_escalation
  - attack.t1053.005
  - attack.s0111
  - car.2013-08-001
logsource:
  category: process_creation
  product: windows
detection:
  selection:
    Image|endswith: '\schtasks.exe'
    CommandLine|contains: ' /create '
  filter:
    User|contains: # covers many language settings
      - 'AUTHORI'
      - 'AUTORI'
  condition: selection and not filter
fields:
  - CommandLine
  - ParentCommandLine
falsepositives:
  - Administrative activity
  - Software installation
level: low
```

### Original Analytic Scoring

|                                      | Application (A) | User-mode (U)                                | Kernel-mode (K) |
|--------------------------------------|-----------------|--|-----------------|
| Core to (Sub-) Technique (5)         |                 |  |                 |
| Core to Part of (Sub-) Technique (4) |                 |  |                 |
| Core to Pre-Existing Tool (3)        |                 | EventID: 1<br>CommandLine contains: 'create' |                 |
| Core to Adversary-brought Tool (2)   |                 |  |                 |
| Ephemeral (1)                        |                 | Image endswith: 'schtasks.exe'               |                 |

The original analytic detects on the name of a newly-created process in combination with the commandline argument `/create`. The fields references in this analytic exist in Sysmon EventID 1 and not Windows Event ID 4688 for process creation, therefore we know the intent was to

MITRE  
ENGENUITY.

Center  
for Threat  
Informed  
Defense

Summitting the  
Pyramid

v1.0.0

CONTENTS

- Overview
- Introduction
- Definitions
- Model Mapping Pages
- Combining Observables
- Example Mappings
- How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

- Original Analytic Scoring
- Improved Analytic Scoring #1
- Improved Analytic Scoring #2

Service Registry Permissions Weakness Check

Potential Access Token Abuse

Capability Abstraction

- Future Work
- Acknowledgements
- Changelog

use Sysmon data. We have previously scored Sysmon Event ID 1 as operating in user-mode since it is fired when the Win32 API function CreateProcessA is called.

The schtasks executable can be easily copied and renamed by an adversary, `Image|endswith: '\\schtasks.exe'` therefore it is placed at the Ephemeral level. The commandline argument is more challenging for an adversary to evade, since they would likely need the source code to change these arguments. However, since schtasks exists in the OS prior to system compromise and no source code is available, the commandline argument observable is placed at **Core to Pre-existing Tool**. Factoring in StP boolean logic, this analytic ultimately scores at a 1U because an adversary can simply change the Image name and avoid detection.

! Note

The filter in an analytic does not affect the overall robustness score since its purpose is to remove false positives. Studying how filters affect scoring is slated for future research.

We can use existing open source research from SpecterOps to make this analytic more robust. The following capability abstraction highlights several different ways adversaries could schedule a task on a system without firing the original analytic, and our original analytic would only detect the circled implementation.

| T1053 – Scheduled Tasks                      |  |                      |  |   |  |
|--|--|----------------------|--|---|--|
| Tools  | schtasks.exe   | Task Scheduler (GUI) | Remote Registry  | At<br>(Deprecated in Win8)                            | Powershell<br>Register-ScheduledTask       |
| COM Method                                   | ITaskFolder::RegisterTask  |                      |  |   | ITaskFolder::RegisterTask                  |
| Win32 API                                    | CreateFile/RegCreateKey  |                      |  | NetScheduleJobAdd                                     |  |
|  |  |                      |  | CreateFile/RegCreateKey                               |  |
| Registry                                     | HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree<br>OR HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks |                      |  |   |  |
| File   | C:\Windows\System32\Tasks OR C:\Windows\Tasks OR C:\Windows\SYSWOW64\Tasks   |                      |  |   |  |
| RPC<br>Server Code/RPC Server<br>Application | schedsvc.dll   |                      | regsvc.dll   | taskcomp.dll  |  |
| RPC<br>Interface                             | ITaskSchedulerServices<br>(86D35949-83C9-4044-B424-DB363231FD0C)   |                      | [MS-RRP]<br>{338CD001-2244-31F1-<br>AAAA-900038001003} | [ATSvc]<br>{1FF70682-0A51-30E8-<br>076D-740BE8CEE98B} |  |
| RPC<br>Method                                | SchRpcRegisterTask, SchRpcEnumTasks  |                      | BaseRegCreateKey,<br>BaseRegQueryInfoKey               | NetrJobAdd*   |  |
| Network<br>Protocol                          | ITaskSchedulerServices   |                      | winreg<br>Endpoint: \pipe\winreg                       | atsvc<br>Endpoint: \pipe\atsvc                        | WS-Management<br>TCP/5985/5986/Custom Port |

Scheduled Task Capability Abstraction - Created by SpecterOps<sup>1</sup>

Conversely, defenders can use the capability abstraction to create several different analytics, the most robust of which might detect on the invariant registry or file creation activity. As a first attempt at a more robust analytic, we can start with the file creation activity. If we create a scheduled task via the Task Scheduler GUI in a test environment with Sysmon installed, we might expect to generate an Event ID 11: FileCreate.

MITRE  
ENGENUITY.

Center  
for Threat  
Informed  
Defense

Summitting the  
Pyramid

v1.0.0

CONTENTS

Overview

Introduction

Definitions

Model Mapping Pages

Combining Observables

Example Mappings

How to Score an Analytic

|   |
|---|
| Analytics Repository                        |
| Suspicious ADFind                           |
| Scheduled Task/Job                          |
| Original Analytic Scoring                   |
| Improved Analytic Scoring #1                |
| Improved Analytic Scoring #2                |
| Service Registry Permissions Weakness Check |
| Potential Access Token Abuse                |
| Capability Abstraction                      |
| Future Work                                 |
| Acknowledgements                            |
| Changelog                                   |

| Level       | Date and Time       | Source | Event ID | Task Category                |
|-------------|---------------------|--------|----------|------------------------------|
| Information | 6/2/2023 4:56:15 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:56:15 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:55:57 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:53:58 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:52:08 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:52:07 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:52:03 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:52:02 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:52:01 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:52:01 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:52:00 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:52:00 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:52:00 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:52:00 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:51:59 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:51:59 PM | Sysmon | 11       | File created (rule: FileC... |
| Information | 6/2/2023 4:51:59 PM | Sysmon | 11       | File created (rule: FileC... |

Event 11, Sysmon

General

Details

Image: C:\windows\system32\svchost.exe

TargetFilename: C:\Windows\System32\Tasks\test\_task

CreationUtcTime: 2023-06-02 20:53:58.762

Log Name:

Microsoft-Windows-Sysmon/Operational

Source:

Sysmon

Logged:

6/2/2023 4:53:58 PM

Event ID:

11

Task Category:

File created (rule: FileCreate)

Level:

Information

Keywords:

Sysmon Event ID 11: FileCreate

Looks like the hypothesis was correct! An Event ID 11 was generated under the expected `C:\Windows\System32\Tasks` directory.

Note

It is important to note all the false positives. Unfortunately this more robust analytic generates a large amount of false positives and should be combined with other observables or fields to provide context, filter out false positives, and ensure the analytic is not completely ignored by an analyst.

Let’s score this new analytic and see if it is more robust than the original. It’s tough to tell right now where to place Event ID 11, but fortunately open-source references exist that enumerate Windows APIs and the respective Event IDs that are generated:

- Roberto Rodriguez’s [API - To - Event](#)
- Jonny Johnson’s [TelemetrySource](#)

These two spreadsheets indicate which Event IDs are generated by user-mode or kernel-mode APIs. An excerpt of Roberto’s spreadsheet is below, showing the different APIs that generate a Sysmon Event ID 11: FileCreate.

| API Call    | EventID | Event Name | Log Provider             |
|-------------|---------|------------|--------------------------|
| CopyFile    | 11      | FileCreate | Microsoft-Windows-Sysmon |
| CopyFile2   | 11      | FileCreate | Microsoft-Windows-Sysmon |
| CopyFileEx  | 11      | FileCreate | Microsoft-Windows-Sysmon |
| CreateFile2 | 11      | FileCreate | Microsoft-Windows-Sysmon |
| CreateFileA | 11      | FileCreate | Microsoft-Windows-Sysmon |
| CreateFileW | 11      | FileCreate | Microsoft-Windows-Sysmon |
| MoveFile    | 11      | FileCreate | Microsoft-Windows-Sysmon |

Page 3 of 5



Center  
for Threat  
Informed  
Defense

# Summiting the Pyramid

v1.0.0

CONTENTS

- Overview
- Introduction
- Definitions
- Model Mapping Pages
- Combining Observables
- Example Mappings
- How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

- Original Analytic Scoring
- Improved Analytic Scoring #1
- Improved Analytic Scoring #2

Service Registry Permissions Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements

Changelog

|              |    |            |                          |
|--------------|----|------------|--------------------------|
| NtCreateFile | 11 | FileCreate | Microsoft-Windows-Sysmon |
| NtWriteFile  | 11 | FileCreate | Microsoft-Windows-Sysmon |

All the relevant APIs are in user-mode, and since the file activity is invariant behavior across all implementations of task scheduling we can score this analytic at 5U.

Improved Analytic Scoring #1

|                                      | Application (A) | User-mode (U)   | Kernel-mode (K) |
|--------------------------------------|-----------------|---|-----------------|
| Core to (Sub-) Technique (5)         |                 | EventID: 11<br>TargetFileName contains:<br>-<br>“C:\Windows\System32\Tasks”<br>-<br>“C:\Windows\SYSWOW64\Tasks” |                 |
| Core to Part of (Sub-) Technique (4) |                 |   |                 |
| Core to Pre-Existing Tool (3)        |                 |   |                 |
| Core to Adversary-brought Tool (2)   |                 |   |                 |
| Ephemeral                            |                 |   |                 |

So far we have created an analytic using the FileCreate invariant behavior. What if we pivot and use the registry key? Might the registry key approach score at a higher level? Sysmon EventID 12: RegistryEvent (Object create and delete) should be generated when a registry key is created. Roberto’s Event ID to Windows API mapping shows us that Event ID 12 can be generated from kernel-mode APIs, so we can score this analytic as operating in kernel-mode.

| API Call        | EventID | Event Name                               | Log Provider             |
|-----------------|---------|--|--------------------------|
| RegCreateKeyA   | 12      | RegistryEvent (Object create and delete) | Microsoft-Windows-Sysmon |
| RegCreateKeyExA | 12      | RegistryEvent (Object create and delete) | Microsoft-Windows-Sysmon |
| RegCreateKeyExW | 12      | RegistryEvent (Object create and delete) | Microsoft-Windows-Sysmon |
| RegCreateKeyW   | 12      | RegistryEvent (Object create and delete) | Microsoft-Windows-Sysmon |
| ZwCreateKey     | 12      | RegistryEvent (Object create and delete) | Microsoft-Windows-Sysmon |

Since the registry key is invariant behavior, the analytic is placed at the Core to Subtechnique level and we can ultimately score it at 5K. It is important to ensure an adversary can’t evade our analytic by editing an existing registry key value or an renaming an entire registry key/value pair, so we should also integrate Event IDs 13: (Value Set) and 14: (Key and Value Rename) into our analytic logic.

MITRE

ENGUITY.

Center for Threat Informed Defense

Summitting the Pyramid

v1.0.0

CONTENTS

- Overview
- Introduction
- Definitions
- Model Mapping Pages
- Combining Observables
- Example Mappings
- How to Score an Analytic

Analytics Repository

Suspicious ADFind

Scheduled Task/Job

- Original Analytic Scoring
- Improved Analytic Scoring #1
- Improved Analytic Scoring #2

Service Registry Permissions Weakness Check

Potential Access Token Abuse

Capability Abstraction

Future Work

Acknowledgements

Changelog

Filtered: Log: Microsoft-Windows-Sysmon/Operational; Source: ; Event ID: 12. Number of events: 6,471

| Level       | Date and Time        | Source | Event ID | Task Category             |
|-------------|----------------------|--------|----------|---------------------------|
| Information | 7/13/2023 4:59:00 PM | Sysmon | 12       | Registry object added ... |
| Information | 7/13/2023 4:57:56 PM | Sysmon | 12       | Registry object added ... |
| Information | 7/13/2023 4:57:56 PM | Sysmon | 12       | Registry object added ... |
| Information | 7/13/2023 4:57:56 PM | Sysmon | 12       | Registry object added ... |
| Information | 7/13/2023 4:57:56 PM | Sysmon | 12       | Registry object added ... |
| Information | 7/13/2023 4:57:56 PM | Svsmon | 12       | Registrv object added ... |

Event 12, Sysmon

General

Details

Registry object added or deleted:  
RuleName: technique\_id=T1053,technique\_name=Scheduled Task  
EventType: CreateKey  
UtcTime: 2023-07-13 20:59:00.793  
ProcessGuid: {9fd6ec04-60cf-64b0-4100-000000003000}  
ProcessId: 3520  
Image: C:\windows\system32\svchost.exe  
TargetObject: HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\test\_task2  
User: NT AUTHORITY\SYSTEM

Improved Analytic Scoring #2

|                                      | Application (A) | User-mode (U) | Kernel-mode (K)  |
|--------------------------------------|-----------------|---------------|--|
| Core to (Sub-) Technique (5)         |                 |               | EventID:<br>- 12<br>- 13<br>- 14<br>TargetObject\contains:<br>-<br>“HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\test_task2”<br>-<br>“HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\test_task2” |
| Core to Part of (Sub-) Technique (4) |                 |               |  |
| Core to Pre-Existing Tool (3)        |                 |               |  |
| Core to Adversary-brought Tool (2)   |                 |               |  |
| Ephemeral (1)                        |                 |               |  |

Note

It is also possible to implement a similar analytic by placing a SACL on the invariant registry keys and searching for Event IDs 4657 or 4663.

References

[1] <https://posts.specterops.io/abstracting-scheduled-tasks-3b6451f6a1c5>