



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page. [Privacy Statement](#) [Third-Party Cookies](#)

Accept

Reject

Manage cookies

ⓘ We're no longer updating this content regularly. Check the [Microsoft Product Lifecycle](#) for information about how this product, service, technology, or API is supported.

[Return to main site](#)



# AdFind command examples

Article • 01/17/2024

AdFind created by [Joe Richards](#) . He is great Active Directory MVP and created more Free Tools [here](#) .

Here is [AdFind Usage](#) and examples.

Query the schema version

**AdFind -schema -s base objectVersion**

Query wellKnownObjects

**AdFind -default -s base wellknownObjects**

List deleted objects

**AdFind -default -rb "CN=Deleted Objects" -showdel**

List conflict objects

**AdFind -b -gc -f "(Name=\*\\0ACNF:\*)" -dn**

Retrieve all Attributes

**AdFind.exe -schema -f "objectClass=attributeSchema" cn  
IDAPDisplayName -nodn -csv >Attributes.txt**

Retrieve all Classes

**AdFind.exe -schema -f "objectclass=classSchema" cn  
IDAPDisplayName -nodn -csv >Classes.txt**

Find Domain Functional level (for example Domain=Contoso.com)

**AdFind -s Base -b "DC=Contoso,DC=com" msDS-Behavior-Version**

List Subnets

**AdFind -subnets -f (objectCategory=subnet)**

List UPN Suffixes

**AdFind -partitions -s base uPNSuffixes**

List Password Policy

**AdFind -default -s base lockoutduration lockoutthreshold  
lockoutobservationwindow maxpwdage minpwdage minpwdlength  
pwdhistorylength pwdproperties**

Check Tombstone Lifetime

**AdFind -config -f objectclass=ntdsservice tombstoneLifetime**

Query AD for all Groups and Users that have adminCount = 1  
(adminSDholder)

```
AdFind -default -f "(&(|(&(objectCategory=person)  
(objectClass=user)))(objectCategory=group))(adminCount=1))" -dn
```

List all objects in an OU (for example OU=NewYork,  
Domain=Contoso.com)

```
AdFind -b "OU=NewYork,DC=Contoso,DC=com" -s one -dn
```

List all OUs in Domain

```
AdFind -default -f "objectcategory=organizationalUnit" -dn
```

Find disabled accounts

```
AdFind -default -bit -f userAccountControl:AND:=2
```

OR

```
AdFind -s subtree -b DC=Contoso,DC=com -f  
userAccountControl:1.2.840.113556.1.4.803:=2 -dn
```

List Users with expired password

```
AdFind -s subtree -b ,DC=Contoso,DC=com -f  
userAccountControl:1.2.840.113556.1.4.803:=8388608 -dn
```

List Users Display Name in domain

```
AdFind -b DC=Contoso,DC=com -f "objectcategory=person"  
displayName -sl
```

Find User SID History (for example User=Ed.Price)

```
AdFind -default -f name=Ed.Price sIDHistory
```

List Users with Dial-in configuration that have **Allow access** in OU (for  
exampleOU=IT, Domain=Contoso.com)

```
AdFind.exe -b "OU=IT,DC=Contoso,DC=com" -f "(&
(objectCategory=person)(objectClass=user)
(msNPAllowDialin=TRUE))" distinguishedName sAMAccountName
```

List Users with Dial-in configuration that have **Deny** access in OU (for example OU=IT, Domain=Contoso.com)

```
AdFind.exe -b "OU=IT,DC=Contoso,DC=com" -f "(&
(objectCategory=person)(objectClass=user)
(msNPAllowDialin=FALSE))" distinguishedName sAMAccountName
```

List Users with Dial-in configuration that have **Control** access through **Remote Access Policy** in OU (for example OU=IT, Domain=Contoso.com)

```
AdFind.exe -b "OU=IT,DC=Contoso,DC=com" -f "(&
(objectCategory=person)(objectClass=user)(!
(msNPAllowDialin=*)))" distinguishedName sAMAccountName
```

List member of a Group (for example Group=IT\_Support)

```
AdFind -b "CN=IT_Support,CN=Users,DC=Contoso,DC=com"
member
```

Count the number of members of a Group (for example Group=IT\_Support)

```
AdFind -f "sAMAccountName=IT_Support" member -list | AdFind -c
```

List Nested Group members (for example Group=Support, OU=IT, Domain=Contoso.com)

```
AdFind -default -bit -f
"memberof:1.2.840.113556.1.4.1941:=CN=Support,OU=IT,DC=Contos
,DC=com" sAMAccountName -nodn
```

List all Groups in OU ( for example OU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -f "
(objectcategory=group)"
```

List all Universal Distribution Groups in OU (for example OU=IT, Domain=Contoso.com)

```
AdFind -gc -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)(sAMAccountType=268435457)(grouptype:OR:=8))" 1.1
```

List all Universal Security Groups in OU (for example OU=IT, Domain=Contoso.com)

```
AdFind -gc -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)(grouptype:AND:=-2147483640))" 1.1
```

List all Universal Groups (Distribution & Security) in OU (for example OU=IT, Domain=Contoso.com)

```
AdFind -gc -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)(grouptype:OR:=8))" 1.1
```

List all Global Groups (Distribution & Security) in OU (for example OU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)(grouptype:OR:=2))" 1.1
```

List all Global Security Groups in OU (for example OU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)(grouptype:AND:=-2147483646))" 1.1
```

List all Global Distribution Groups in OU (for example OU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)(sAMAccountType=268435457)(grouptype:OR:=2))" 1.1
```

List all Domain Local Groups (Distribution & Security) in OU (for example OU=IT, Domain=Contoso.com)

```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -bit -f "(&(objectcategory=group)(grouptype:OR:=4))" 1.1
```

List all Domain Local Security Groups in OU (for example OU=IT, Domain=Contoso.com)


```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -f "(&(objectcategory=group)(sAMAccountType=536870912))" 1.1
```

List all Domain Local Distribution Groups in OU (for example OU=IT, Domain=Contoso.com)



```
AdFind -b "OU=IT,DC=Contoso,DC=com" -s subtree -f "(&(objectcategory=group)(sAMAccountType=536870913))" 1.1
```

Find all Computer objects in domain and displays cn & createTimeStamp

```
AdFind -b dc=Contoso,dc=com -f "objectcategory=computer" cn createTimeStamp
```

 English (United States)

 Your Privacy Choices


 Theme 

[Manage cookies](#)

[Previous Versions](#)

[Blog](#) 

[Contribute](#)

[Privacy](#) 

[Terms of Use](#)

[Trademarks](#) 

© Microsoft 2024