



We use optional cookies to improve your experience on our websites, such as through social media connections, and to display personalized advertising based on your online activity. If you reject optional cookies, only cookies necessary to provide you the services will be used. You may change your selection by clicking "Manage Cookies" at the bottom of the page.  
[Privacy Statement](#) [Third-Party Cookies](#)

Accept

Reject

Manage cookies

# Microsoft Ignite

Nov 19–22, 2024

Register now >



## Stop-Service

Reference

Feedback

Module: [Microsoft.PowerShell.Management](#)

### In this article

[Syntax](#)

[Description](#)

[Examples](#)

[Parameters](#)

[Show 4 more](#)

Stops one or more running services.

## Syntax

```
Stop-Service
    [-Force]
    [-Nowait]
    [-InputObject] <ServiceController[]>
    [-PassThru]
    [-Include <String[]>]
    [-Exclude <String[]>]
    [-WhatIf]
    [-Confirm]
    [<CommonParameters>]
```

```
Stop-Service
    [-Force]
    [-Nowait]
    [-Name] <String[]>
    [-PassThru]
    [-Include <String[]>]
    [-Exclude <String[]>]
    [-WhatIf]
    [-Confirm]
    [<CommonParameters>]
```

```
Stop-Service
    [-Force]
    [-Nowait]
    [-PassThru]
    -DisplayName <String[]>
    [-Include <String[]>]
    [-Exclude <String[]>]
    [-WhatIf]
    [-Confirm]
    [<CommonParameters>]
```

# Description

This cmdlet is only available on the Windows platform.

The `Stop-Service` cmdlet sends a stop message to the Windows Service Controller for each of the specified services. You can specify the services by their service names or display names, or you can use the `InputObject` parameter to pass a service object that represents the service that you want to stop.

## Examples

### Example 1: Stop a service on the local computer

```
PS C:\> Stop-Service -Name "sysmonlog"
```

This command stops the Performance Logs and Alerts (SysmonLog) service on the local computer.

### Example 2: Stop a service by using the display name

```
PS C:\> Get-Service -DisplayName "telnet" | Stop-Service
```

This command stops the Telnet service on the local computer. The command uses `Get-Service` to get an object that represents the Telnet service. The pipeline operator (`|`) pipes the object to `Stop-Service`, which stops the service.

## Example 3: Stop a service that has dependent services

```
PS C:\> Get-Service -Name "iisadmin" | Format-List -Property
PS C:\> Stop-Service -Name "iisadmin" -Force -Confirm
```

This example stops the IISAdmin service on the local computer. Because stopping this service also stops the services that depend on the IISAdmin service, it is best to precede `Stop-Service` with a command that lists the services that depend on the IISAdmin service.

The first command lists the services that depend on IISAdmin. It uses `Get-Service` to get an object that represents the IISAdmin service. The pipeline operator (`|`) passes the result to the `Format-List` cmdlet. The command uses the **Property** parameter of `Format-List` to list only the **Name** and **DependentServices** properties of the service.

The second command stops the IISAdmin service. The **Force** parameter is required to stop a service that has dependent services. The command uses the **Confirm** parameter to request confirmation from the user before it stops each service.

## Parameters

### -Confirm

Prompts you for confirmation before running the cmdlet.


 Expand table

Type:	SwitchParameter
Aliases:	cf

Position:	Named
Default value:	False
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

**-DisplayName**

Specifies the display names of the services to stop. Wildcard characters are permitted.

 Expand table

Type:	String[]
Position:	Named
Default value:	None
Required:	True
Accept pipeline input:	False
Accept wildcard characters:	True

**-Exclude**

Specifies services that this cmdlet omits. The value of this parameter qualifies the **Name** parameter. Enter a name element or pattern, such as s\*. Wildcard characters are permitted.


 Expand table

Type:	String[]
Position:	Named

Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	True

-Force

Forces the cmdlet to stop a service even if that service has dependent services.

 Expand table

Type:	SwitchParameter
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

-Include

Specifies services that this cmdlet stops. The value of this parameter qualifies the **Name** parameter. Enter a name element or pattern, such as s\*. Wildcard characters are permitted.


 Expand table

Type:	String[]
Position:	Named
Default value:	None

Required:	False
Accept pipeline input:	False
Accept wildcard characters:	True

**-InputObject**

Specifies **ServiceController** objects that represent the services to stop. Enter a variable that contains the objects, or type a command or expression that gets the objects.

 Expand table

Type:	<a href="#">ServiceController[]</a>
Position:	0
Default value:	None
Required:	True
Accept pipeline input:	True
Accept wildcard characters:	False

**-Name**

Specifies the service names of the services to stop. Wildcard characters are permitted.


 Expand table

Type:	<a href="#">String[]</a>
Aliases:	ServiceName
Position:	0
Default value:	None

Required:	True
Accept pipeline input:	True
Accept wildcard characters:	True

**-NoWait**


Indicates that this cmdlet uses the no wait option.

 Expand table

Type:	SwitchParameter
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

**-PassThru**

Returns an object that represents the service. By default, this cmdlet does not generate any output.

 Expand table

Type:	SwitchParameter
Position:	Named
Default value:	None
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False



**-WhatIf**

Shows what would happen if the cmdlet runs. The cmdlet is not run.

 Expand table

Type:	SwitchParameter
Aliases:	wi
Position:	Named
Default value:	False
Required:	False
Accept pipeline input:	False
Accept wildcard characters:	False

# Inputs

**ServiceController**

You can pipe a service object to this cmdlet.

**String**

You can pipe a string that contains the name of a service to this cmdlet.

# Outputs

**None**

By default, this cmdlet returns no output.

**ServiceController**

When you use the **PassThru** parameter, this cmdlet returns a **ServiceController** object representing the service.

# Notes

PowerShell includes the following aliases for `Stop-Service`:

- Windows:
  - `spsv`

This cmdlet is only available on Windows platforms.

`Stop-Service` can control services only when the current user has permission to do this. If a command does not work correctly, you might not have the required permissions.

To find the service names and display names of the services on your system, type `Get-Service`. The service names appear in the **Name** column and the display names appear in the **DisplayName** column.

## Related Links


- [Get-Service](#)
- [New-Service](#)
- [Restart-Service](#)
- [Resume-Service](#)
- [Set-Service](#)
- [Start-Service](#)
- [Suspend-Service](#)
- [Remove-Service](#)

### Collaborate with us on GitHub


The source for this content can be found on GitHub, where you can also create and review issues and pull requests. For more


### PowerShell feedback


PowerShell is an open source project. Select a link to provide feedback:



 [Open a documentation issue](#)

information, see [our contributor guide](#).

 [Provide product feedback](#)

 [English \(United States\)](#)

 [Your Privacy Choices](#)

 [Theme](#) 

[Manage cookies](#)


[Previous Versions](#)

[Blog](#) 

[Contribute](#)

[Privacy](#) 

[Terms of Use](#)

[Trademarks](#) 

© Microsoft 2024