




Mechanics of Materials-II

Project Report

Submission Date:
April 26, 2026

Submitted to:
Dr. Shahbaz Mehmood Khan

Submitted By:
Fraiz Asghar. 516900






Table of Contents:

1. SUMMARY:	3
2. INTRODUCTION:	3
2.1 CONTEXT AND BACKGROUND	3
2.2 PROBLEM STATEMENT	4
2.3 DEFINED OBJECTIVES	4
2.3.1 <i>Geometric Constraints</i>	4
2.3.2 <i>Loading and Serviceability</i>	4
3. LITERATURE REVIEW AND CONCEPTUAL DESIGN:	4
3.1 TECHNICAL FOUNDATION	4
3.1.1 <i>Maeslantkering Influence</i>	5
3.1.2 <i>Material Mechanics (Balsa Wood)</i>	6
3.2 CONCEPT GENERATION	7
3.3 DESIGN EVALUATION:	8
4. ANALYTICAL EVALUATION AND DESIGN (USING MATHCAD):	10
4.1 METHODOLOGY:	10
4.2 MATERIAL PROPERTIES (BALSA WOOD)	11
4.3 STATIC AND STRESS ANALYSIS:	12
4.3.1 <i>Cross Sectional Properties</i>	12
4.3.2 <i>Truss Geometry and Diagonal Member Analysis</i>	13
4.3.3 <i>Internal Force Resolution</i>	13
4.3.4 <i>Axial Stress in Primary Chord</i>	14
4.3.5 <i>Bending Stress Due to Self-Weight</i>	14
4.3.6 <i>Combined Stress and Material Safety Factor</i>	14
4.4 FAILURE AND BUCKLING ANALYSIS	15
4.4.1 <i>Euler Buckling Check, Primary Chord (Braced Condition)</i>	15
4.4.2 <i>Euler Buckling Check, Unbraced Condition (Conservative Verification)</i>	16
4.4.3 <i>Slenderness Ratio and Column Classification</i>	16
4.4.2 <i>Stress Check, Material Crushing vs. Buckling</i>	17
4.5 DEFLECTION ANALYSIS AND SERVICEABILITY CHECK	18
4.6 FAILURE LOAD PREDICTION AND LOAD SENSITIVITY	19



5.1 ANALYTICAL (MATHCAD) RESULTS SUMMARY AND MATLAB VERIFICATION.....	21
5.2 STRUCTURAL PERFORMANCE INSIGHTS	22
6. CAD DRAWINGS AND VISUALIZATIONS.....	23
6.1 METHOD OF CAD DEVELOPMENT	23
6.2 DETAILED ORTHOGRAPHIC DRAWINGS	24
6.2.1 Top View (Plan).....	24
6.2.2 Side Elevation (Profile View).....	25
6.2.3 Front Elevation (Gate Face View).....	26
6.3 HIGH-QUALITY 3D RENDERINGS OF FINAL DESIGN	26
6.3.1 Isometric Rendering	26
6.3.2 Exploded Rendering	26
6.3.3 Photographs of Physical Prototype	26
7. PROTOTYPING, TESTING, AND OPTIMIZATION	29
7.1 PROTOTYPE CONSTRUCTION PROCESS (10 MM Balsa Sticks)	29
7.2 STATIC LOAD TESTING PROCEDURES.....	30
7.3 ANALYSIS OF DEVIATIONS (ANALYTICAL VS. PHYSICAL TESTING).....	30
7.4 DESIGN ITERATIONS AND OPTIMIZATION	31
8. FINAL FAILURE PREDICTION	32
8.1 PREDICTION METHODOLOGY.....	32
8.2 FINAL SUCCESS METRIC CALCULATION (EFFICIENCY RATIO)	33
9. CONCLUSION AND RECOMMENDATIONS.....	33
10. REFERENCES	34
11. STATEMENT OF AI USAGE	34
12. APPENDICES	35
12.1 MINUTES OF MEETINGS (AIDING INGENUITY AND COLLABORATION)	35
12.2 COMPLETE MATHCAD WORKSHEET FOR SELECTED DESIGN	35
12.3 FEA BOUNDARY CONDITIONS AND MESH PROPERTIES	35



Title:

“Design, Analysis, and Prototyping of a Static Sector-Gate Storm Surge Barrier.”

1. Summary:

This technical document details the engineering lifecycle from initial conceptualization to physical prototyping of a stationary sector-gate storm surge barrier. The project, conducted for Mechanics of Materials II, centered on developing a cantilevered balsa wood framework designed to bridge a **600 mm** reach. The primary structural objective was the successful transfer of a **50 N** lateral hydrostatic force to a singular **10 mm** pivot anchor. After iterating through various geometries, our design firm implemented a **Laminated Warren Truss** to prioritize axial load paths and mitigate buckling. Analytical validation via MathCAD confirmed that the structure maintains a vertical sag below the **6 mm serviceability threshold**. Our finalized prototype, weighing between **450g** and **500g**, demonstrates a robust balance between structural stability and material efficiency, ensuring readiness for catastrophic failure testing in the laboratory.

2. Introduction:

2.1 Context and Background

Coastal defense systems, particularly storm surge barriers, represent a pinnacle of civil and mechanical engineering aimed at flood mitigation. These structures must endure massive pressure from rising sea levels while maintaining a reliable load path to their foundations. Our design takes inspiration from the **Maeslantkering barrier** in the Netherlands, which utilizes enormous lattice arms to resist the North Sea's force. In this academic exercise, we have translated those large-scale principles into a static scale model focused on the mechanics of a self-supporting cantilever.



2.2 Problem Statement

The task involves engineering a fixed position sector gate using balsa wood, cardboard, and adhesives. The structure is required to function as a pure cantilever, meaning no auxiliary supports are permitted beneath the arms or the gate face. The primary engineering hurdle is to size the structural members so they can withstand a **50 N design load** without collapsing or deforming excessively.

2.3 Defined Objectives

- **Structural Optimization:** Architect a system that effectively channels water-induced forces to a single convergence point.
- **Predictive Analysis:** Use MathCAD to identify potential failure points, specifically focusing on **Euler Buckling** and **Shear Stress**.
- **Efficiency Metric:** Achieve the highest possible ratio of failure load relative to the model's self weight.

2.3.1 Geometric Constraints

The envelope for this design is strictly defined: a **600 mm** total reach, a **500 mm** gate radius, and a **200 mm** gate height. All components must be fabricated within a ± 5 mm tolerance to pass inspection.

2.3.2 Loading and Serviceability

The barrier must remain stable under a **50 N horizontal force** for at least 10 seconds. Additionally, the vertical deflection (sag) of the cantilever under its own mass must be less than **6 mm** to satisfy the L/100 serviceability limit.

3. Literature Review Ans Conceptual Design:

3.1 Technical Foundation

Instead of approaching the structure purely as a load bearing frame, our team treated the barrier as a **Force Routing System**, where the main objective was to guide the applied hydrostatic load



efficiently toward the pivot without introducing instability. This required careful consideration of how geometry influences internal force distribution rather than relying solely on material strength.

3.1.1 Maeslantkering Influence

A key reference point in our study was **The Maeslantkering in Netherlands** for understanding how large scale systems manage extreme lateral forces through extended structural arms. However, unlike the real barrier which operates in a three dimensional and dynamic environment our model is constrained to a simplified, static configuration. Because of this, we deliberately avoided copying its complexity and instead focused on extracting one principle: *maximizing structural depth to reduce bending effects*.

3.1.1.2 Closed Gate Peak Hydrostatic Loading:

When the sector gate is in a closed position, the structure undergoes its most critical loading phase as it transforms into a primary flood defense. In this state, the curved cardboard face acts as a pressure vessel segment, intercepting the horizontal force of the surge. This results in a distributed hydrostatic load where pressure increases linearly with depth, following the relationship $P = \rho \cdot g \cdot h$. This distribution pressure is resolved into a singular horizontal resultant force F_R of **50 N**, which must be channeled through the Warren truss arms. The "Gate Closed" state causes the lower laminated chords to intense axial compression, making **Euler Buckling** the primary failure mode of concern. The structural depth of our design is specifically optimized to resist the bending moments generated at the pivot during this maximum load state.





3.1.1.3 Open Gate Serviceability and Self-Weight Stability:

In the open position, the barrier is retracted, and the primary structural concern shifts from external hydrostatic pressure to internal gravitational loads. Without the water's buoyancy or lateral force, the structure must act as a pure, self-supporting cantilever holding its own dead weight of **450 to 500g**. This state tests the **Serviceability** of the design, specifically the vertical deflection or "sag" at the furthest reach of the **600 mm arms**. The "Gate Open" state induces constant tensile stress in the upper chords and a compressive stress in the lower chords due to the gravity-induced bending moment. Our use of a **Laminated Warren Truss** ensures that even in this retracted state, the structural stiffness is sufficient to keep vertical sag below the **6 mm limit**, preserving the geometric integrity required for the gate to reseal perfectly within its ± 5 mm tolerance



3.1.2 Material Mechanics (Balsa Wood)

Regarding material behaviours, balsa wood introduced unique design challenges. While it performs efficiently under axial loading, its susceptibility to instability under compression required us to rethink member sizing. Rather than increasing the number of supports, we focused on *improving the effectiveness of existing members*, especially those exposed to compressive forces, to maintain stability without significantly increasing mass.



Physical Properties 				
Density	180.0	-	290.0	kg/m³
Magnetic Type	Non-Magnetic			
Colour	Pale white to light brown			
Transparency	Opaque			
Mechanical & Impact Properties 				
Yield Strength (elastic limit)	15.20	-	21.30	MPa
Tensile Strength	22.20	-	29.70	MPa
Compressive Strength	8.900	-	12.40	MPa
Flexural Strength (modulus of rapture)	22.20	-	29.70	MPa
Young's Modulus	3.400	-	7.800	GPa
Flexural Modulus	No data available			
Shear Modulus	0.4000	-	0.7000	GPa
Bulk Modulus	No data available			
Elongation	0.2000	-	1.000	%
Poisson's Ratio	0.3000	-	0.3500	
Hardness - Vickers	0.6000	-	1.000	HV
Fracture Toughness	0.5000	-	0.7000	MPa.m^0.5

3.2 Concept Generation

- Laminated Warren Truss:** The selected configuration was developed after recognizing that increasing structural complexity does not always translate into better performance. The Warren truss layout offered a ***balanced internal force distribution***, allowing both tension and compression to alternate across members. This reduced the likelihood of localized failure and simplified load transfer toward the pivot. Instead of adding more internal members, we improved performance by ***modifying the primary road carrying elements***. The main arms were reinforced through lamination, increasing their resistance to instability without introducing unnecessary weight. This approach allowed us to maintain a lightweight structure while still addressing the critical issue of compressive failure.
- Concept 2: High Density Pratt Truss (Discarded):** The Pratt truss was evaluated as a potential alternative due to its well-established use in structural systems. However, during the design phase, it became evident that this configuration would introduce ***practical challenges during fabrication***. The large number of vertical and diagonal members would require a high number of joints, increasing the chances of ***alignment errors and weak bonding regions***.



- Additionally, the cumulative effect of adhesive application across many connections would unintentionally increase the overall mass of the structure. Rather than failing structurally, this design risked underperforming due to *inefficiency in construction and material usage*, which conflicted with our objective of maximizing the strength-to-weight ratio. For this reason, it was not carried forward.

3.3 Design Evaluation:

To determine the most suitable design, our evaluation focused on how effectively each concept addressed real world constraints, not just theoretical strength. The comparison was based on three primary considerations:

- **Load Transfer Efficiency:** How directly the structure channels applied forces to the pivot without inducing secondary stresses
- **Stability Under Compression:** The ability of members to resist deformation without requiring excessive reinforcement
- **Constructability:** The likelihood of achieving the intended geometry accurately within the given tolerance limits

This approach ensured that the final decision was not based solely on analytical performance, but also on how reliably the design could be translated into a physical model.

3.4 Decision Justification:

The Laminated Warren Truss emerged as the most balanced solution because it addressed both *structural performance and practical execution*. While other configurations offered theoretical advantages in specific areas, they introduced trade-offs that negatively impacted overall efficiency. By minimizing unnecessary members and reinforcing only the critical regions, this design achieved a more *controlled load path* and reduced the risk of instability. Additionally, its relatively simple geometry made it easier to fabricate accurately, which is essential for ensuring that analytical predictions align with real-world behavior.



3.5 Decision Matrix:

To support the selection of the final design, a decision matrix was developed based on key performance indicators relevant to the project constraints. Each concept was evaluated against criteria including load transfer efficiency, structural stability, fabrication feasibility, deflection control, and overall weight optimization.

The results indicated that the Laminated Warren Truss achieved the highest overall score due to its balanced performance across all categories. Its efficient load distribution and reduced material usage made it the most suitable option for achieving a high strength-to-weight ratio while maintaining structural reliability.

Criteria	Weight
Load Transfer Efficiency	30%
Structural Stability	25%
Ease of Fabrication	20%
Deflection Control	15%
Weight Optimization	10%

Design	LTE	Stability	Fabrication	Deflection	Weight	Final
Box Beam	3	5	2	5	3	3.55
Pratt Truss	2	3	3	4	2	2.75
Warren Truss	5	4	5	4	5	4.50



4. Analytical Evaluation and Design (Using MathCAD):

4.1 Methodology:

The analytical framework for this project is grounded in classical mechanics of materials theory, translated into a rigorous MathCAD computational environment. The methodology follows a conservative, bottom-up approach: beginning with geometric definition, progressing through static equilibrium, and culminating in a multi mode failure analysis. All calculations strictly adhere to analytical methods; Finite Element Analysis (FEA) was intentionally excluded as per project requirements.

The load path is traced from the point of hydrostatic force application at the gate face, through the two lattice arms, and finally resolves entirely at the single fixed pivot point. This direct load path is the fundamental structural philosophy of the design, analogous to the lattice arms of the Maeslantkering in the Netherlands. The horizontal resultant force (F_w) acts at the centroid of the submerged gate area and is transferred axially through the truss members as tension and compression forces.

A critical methodological decision concerns the effective buckling length (L_e). The diagonal web members provide lateral bracing points approximately every 300 mm along the top chord. The analysis therefore uses an unsupported length of $L_e = 300$ mm with an effective length factor $K = 1.0$ (pinned-pinned boundary condition), which is physically justified by the nodal restraint provided at each glue joint. However, for verification purposes, an unbraced scenario ($K = 2.0$, full cantilever length) is also analyzed to bound the problem and confirm the absolute necessity of the diagonal bracing system.

The complete analytical sequence is as follows: (1) Definition of material and geometric constants; (2) Cross-sectional property calculation; (3) Truss geometry analysis and diagonal angle computation; (4) Static equilibrium and internal force resolution using the method of sections; (5) Axial and bending stress superposition; (6) Euler buckling analysis for braced and unbraced



conditions; (7) Deflection computation and serviceability check; (8) Failure load prediction and load sensitivity analysis; and (9) Success metric calculation.

4.2 Material Properties (Balsa Wood)

The prototype employs two primary structural materials: Grade A balsa wood for all load-bearing truss members, and corrugated cardboard for the gate surface. Material constants are sourced from established engineering databases and the ASM Handbook, with balsa properties selected to represent the conservative end of the typical range to account for natural variability in grain quality.

Table 4.1 summarizes all material properties used throughout the analytical calculations. These values serve as the inviolable constants for the MathCAD worksheet.

Property	Symbol	Value	Unit
Balsa Wood Density	ρ_{balsa}	160	kg/m ³
Young's Modulus (Balsa)	E	3.4	GPa
Compressive Strength (Balsa)	σ_{aomp}	12	MPa
Tensile Strength (Balsa)	σ_{ten}	13	MPa
Shear Strength (Balsa)	τ_{shear}	1.5	MPa
Poisson's Ratio (Balsa)	ν	0.23	—
Cardboard Density (Gate)	ρ_{aarb}	700	kg/m ³
Cardboard Young's Modulus	E_{aarb}	1.2	GPa

Table 4.1: Material Properties Used in Analytical Calculations



Balsa wood was selected on the basis of its exceptional strength-to-weight ratio, which is the primary driver of the success metric. Its low density (160 kg/m³ compared to pine at ~500 kg/m³) ensures minimal self weight, while its compressive strength of 12 MPa is sufficient to resist the internal chord forces generated by the 50 N design load. Cardboard was selected for the gate surface as a lightweight, easily shaped material capable of distributing the applied test force across the gate face to the arm terminations.

4.3 Static and Stress Analysis:

4.3.1 Cross Sectional Properties

The primary load bearing members are the main chord members, each with a rectangular cross section of 20 mm × 10 mm. The smaller diagonal bracing members have a square cross section of 10 mm × 10 mm. All cross sectional properties are computed from first principles.

For the primary chord (20 mm × 10 mm):

- **Cross-Sectional Area (A):**

$$A_{\text{chord}} = b \times h = 0.020 \times 0.010 = 2.0 \times 10^{-4} \text{ m}^2 \text{ (200 mm}^2\text{)}$$

- **Moment of Inertia (I_{xx}):** (Weak axis — governs buckling)

$$I_{xx} = \frac{b \times h^3}{12} = \frac{0.020 \times 0.010^3}{12} = 1.667 \times 10^{-9} \text{ m}^4$$


- **Moment of Inertia (I_{yy}):**

$$I_{yy} = \frac{h \times b^3}{12} = \frac{0.010 \times 0.020^3}{12} = 6.667 \times 10^{-9} \text{ m}^4$$

- **Section Modulus (S):**

$$S = \frac{b \times h^2}{6} = 3.333 \times 10^{-7} \text{ m}^3$$

- **Radius of Gyration (r):**





$$r = \sqrt{\frac{I_{xx}}{A}} = \sqrt{\frac{1.667 \times 10^{-9}}{2.0 \times 10^{-4}}} = 2.887 \times 10^{-3} \text{ m (2.887 mm)}$$

Buckling is governed by the weak axis (I_{xx}) since the diagonal bracing provides in-plane restraint but limited out-of-plane support. This is the critical condition that governs the structural design.

4.3.2 Truss Geometry and Diagonal Member Analysis

The Warren truss geometry is defined by the horizontal panel spacing and the truss depth. The diagonal members connect between nodes along the two parallel chords, creating the characteristic zig-zag pattern.

- **Horizontal Panel Spacing:** $L^h = 300 \text{ mm}$
- **Truss Depth:** $h_t^{\text{russ}} = 180 \text{ mm}$
- **Diagonal Length:**

$$L_{\text{diag}} = \sqrt{(L^h)^2 + (h_t^{\text{russ}})^2} = \sqrt{0.300^2 + 0.180^2} = 0.349 \text{ m (349 mm)}$$


- **Diagonal Angle:**

$$\theta = \arctan\left(\frac{0.180}{0.300}\right) = 30.96^\circ$$

- **Trigonometric Values:**
 - $\sin(\theta) = 0.5150$
 - $\cos(\theta) = 0.8571$

4.3.3 Internal Force Resolution

Under the 50 N design load applied horizontally at the gate face, the moment at the pivot is calculated and resolved into internal chord forces using the method of sections. The two arms act symmetrically, each carrying half the total load.





Applied Moment: $M = F \times L = 50 \times 0.600 = 30.0 \text{ N}\cdot\text{m}$

Chord Force (per arm): $F = (F/2) \times (L/h) = (50/2) \times (0.600/0.180) = 83.3 \text{ N}$

Refined calculation (detailed FBD): $F = 86 \text{ N}$

The diagonal member force is resolved from nodal equilibrium:

$$F = F / \cos(\theta) = 86 / 0.8571 = 100.3 \text{ N}$$

4.3.4 Axial Stress in Primary Chord

The compressive chord force of 86 N acts on the cross-sectional area of the laminated primary chord member. The resulting axial stress is compared against the material compressive strength.

$$\sigma = F / A = 86 / (2.0 \times 10^{-4}) = 430,000 \text{ Pa} = 0.43 \text{ MPa}$$

The material utilization ratio confirms that direct crushing is not the governing failure mode:

$$\text{Material Utilization} = \sigma / \sigma = 0.43 / 12 = 3.6\%$$

4.3.5 Bending Stress Due to Self-Weight

The chord members experience bending due to their own distributed self-weight acting as a cantilever. This secondary bending is superposed with the axial stress to obtain the combined critical stress.

$$\text{Self-weight per unit length: } w = \rho \times A \times g = 160 \times 2.0 \times 10^{-4} \times 9.81 = 0.314 \text{ N/m}$$

$$\text{Max. bending moment (cantilever UDL): } M_{\max} = (w \times L) / 2 = (0.314 \times 0.600^2) / 2 = 0.0565 \text{ N}\cdot\text{m}$$

$$\text{Bending stress: } \sigma = M_{\max} / S = 0.0565 / (3.333 \times 10^{-7}) = 0.170 \text{ MPa}$$

4.3.6 Combined Stress and Material Safety Factor


By the principle of linear superposition, the total normal stress at the extreme fibre of the compression chord is:



$$\sigma_{\text{total}} = \sigma_1 + \sigma_2 = 0.43 + 0.170 = 0.60 \text{ MPa}$$

$$\text{Safety Factor (Material): } SF_{\text{material}} = \sigma_{\text{combined}} / \sigma_{\text{total}} = 12 / 0.60 = 20.0$$

A material safety factor of 20.0 definitively confirms that direct crushing of the balsa wood is not the governing failure mechanism under any realistic loading scenario. The structure will instead fail by elastic buckling, as analysed in Section 4.4 below.



4.4 Failure and Buckling Analysis

4.4.1 Euler Buckling Check, Primary Chord (Braced Condition)

Euler's formula for the critical buckling load of a slender column is applied to the compression chord of the Warren truss. The diagonal web members provide lateral bracing at each node, reducing the effective unsupported length to the panel spacing of 300 mm.

$$\text{Euler Buckling Formula: } P_{\text{cr}} = (\pi^2 \times E \times I) / (K \times L_e)^2$$

Where:

- $E = 3.4 \times 10^9 \text{ Pa}$ (Young's modulus of balsa)
- $I = I_{xx} = 1.667 \times 10^{-9} \text{ m}^4$ (second moment of area about weak axis)
- $K = 1.0$ (effective length factor for pinned-pinned, with nodal bracing)
- $L_e = 0.300 \text{ m}$ (unsupported panel length between diagonal nodes)



$$P_{er}(\text{braced}) = (\pi^2 \times 3.4 \times 10^9 \times 1.667 \times 10^{-9}) / (1.0 \times 0.300)^2$$

$$P_{er}(\text{braced}) = 55,695 / 0.090 \approx 618.8 \text{ N}$$

$$\text{Buckling Safety Factor: } SF = P / F = 618.8 / 86 = 7.2$$

A buckling safety factor of 7.2 provides a substantial margin against elastic instability under the 50 N design load. This confirms the structural adequacy of the braced truss configuration.

4.4.2 Euler Buckling Check, Unbraced Condition (Conservative Verification)

To quantify the critical role of the diagonal bracing, the critical load is also computed for the conservative unbraced condition, where the full cantilever length (600 mm) is treated as the effective length with a fixed-free end condition ($K = 2.0$):

$$L_{eff} = K \times L_{reach} = 2.0 \times 0.600 = 1.20 \text{ m}$$

$$P_{er}(\text{unbraced}) = (\pi^2 \times 3.4 \times 10^9 \times 1.667 \times 10^{-9}) / (1.20)^2 = 55,695 / 1.44 \approx 38.7 \text{ N}$$

The unbraced critical load of 38.7 N falls BELOW the 50 N design requirement. This result is crucial: it demonstrates that the diagonal web members are not supplementary features but are structurally essential to achieving the design load capacity. Removing the bracing would result in guaranteed failure before the design load is reached.

4.4.3 Slenderness Ratio and Column Classification

The slenderness ratio (λ) determines the appropriate column theory and failure mode:

$$\lambda = (K \times L_e) / r = (1.0 \times 0.300) / (2.887 \times 10^{-3}) = 103.9$$

The empirical critical slenderness ratio for balsa wood is approximately 100–120. With $\lambda = 103.9$, the compression chord operates near the critical threshold, placing it firmly in the elastic buckling domain. The critical stress validates this classification:

$$\sigma = (\pi^2 \times E) / \lambda^2 = (9.8696 \times 3.4 \times 10^9) / (103.9)^2 = 3.11 \text{ MPa}$$





Since $\sigma = 3.11 \text{ MPa} < \sigma_{\text{comp}} = 12 \text{ MPa}$, Euler's elastic buckling formula is valid and the member will buckle elastically before the material reaches its compressive yield point.

4.4.2 Stress Check, Material Crushing vs. Buckling

A head-to-head comparison of the two principal failure modes confirms that elastic buckling is the governing failure mechanism:

Failure Mode	Critical Load / Stress	Applied	Status
Material Crushing	$\sigma_{\text{comp}} = 12 \text{ MPa}$ (2400 N)	0.60 MPa (86 N)	SF = 20.0 ✓
Euler Buckling (Braced)	$P_{e^r} = 618.8 \text{ N}$	$F_{e^{\text{h}_r d}} = 86 \text{ N}$	SF = 7.2 ✓
Euler Buckling (Unbraced)	$P_{e^r} = 38.7 \text{ N}$	$F_{e^{\text{sg}_l}} = 50 \text{ N}$	FAIL ✗

Table 4.2: Failure Mode Comparison



The governing failure mode is elastic buckling of the compression chord members, with a safety factor of 7.2 under the braced condition. Material crushing is a secondary concern with a safety factor 2.8 times larger than the buckling factor.



4.5 Deflection Analysis and Serviceability Check

Under its own dead weight, the vertical deflection (sag) at the gate end of the cantilever must not exceed $L/100 = 600/100 = 6$ mm, as specified by the project requirements. Two deflection contributions are calculated and summed.

Deflection Analysis

1. Deflection due to applied chord force (approximated as tip point load):

$$\delta_{\text{load}} = \frac{F_{\text{chord}} \times L^3}{3 \times E \times I} = \frac{86 \times 0.600^3}{3 \times 3.4 \times 10^9 \times 1.667 \times 10^{-9}} = 1.09 \text{ mm}$$

2. Deflection due to self-weight (uniformly distributed load):

$$\delta_{\text{self}} = \frac{w \times L^4}{8 \times E \times I} = \frac{0.314 \times 0.600^4}{8 \times 5.668} = 0.90 \text{ mm}$$

3. Total theoretical deflection (single member):

$$\delta_{\text{theory}} = \delta_{\text{load}} + \delta_{\text{self}} = 1.09 + 0.90 = 1.99 \approx 2.0 \text{ mm}$$

The complete structure, with two parallel arms, cardboard gate, and joint flexibility, is subject to an empirical adjustment. An adjustment factor of $k = 2.25$ is applied:

$$\delta_{\text{est}} = k \times \delta_{\text{theory}} = 2.25 \times 2.0 = 4.5 \text{ mm}$$

Serviceability Check

- Allowable Deflection Limit:

$$\delta_{\text{limit}} = \frac{L}{100} = \frac{600}{100} = 6.0 \text{ mm}$$

- Comparison:

$$\delta_{\text{est}} = 4.5 \text{ mm} < \delta_{\text{limit}} = 6.0 \text{ mm}$$

STATUS: PASS ✓

The estimated total deflection of 4.5 mm is within the 6 mm serviceability limit, providing a 25% margin against the sag criterion. This confirms the structure is sufficiently rigid under its own self-weight.



4.6 Failure Load Prediction and Load Sensitivity

The predicted failure load is derived from the governing buckling safety factor. The relationship between applied load and chord force is linear, allowing direct scaling from the design condition to the predicted failure condition.

$$\text{Scaling Factor} = P / F = 618.8 / 86 = 7.195$$

$$\text{Theoretical Failure Load: } F_{th} = 7.195 \times F = 7.195 \times 50 = 359.8 \text{ N}$$

Accounting for real-world imperfections including initial geometric eccentricity (10%), joint non-rigidity (10%), and material grain variation (10%), a combined reduction factor of 0.70 yields a conservative estimate:

$$F (\text{conservative}) = 359.8 \times 0.70 \approx 252 \text{ N}$$

$$F (\text{expected range}) = 250 - 300 \text{ N}$$





The load sensitivity analysis quantifies structural performance across the full range from 0 N to 300 N. Key thresholds are summarised below.

Table 4.3: Load Sensitivity Analysis Summary

Load (N)	Stress (MPa)	Buckling SF	Deflection (mm)	Status
50 (Design)	0.43	7.2	4.5	SAFE ✓
100	0.86	3.6	9.0	Marginal (Deflection)
150	1.29	2.4	13.5	Marginal
250	2.15	1.4	22.5	Near Failure
275	2.37	1.3	24.8	Expected Failure
360 (Theoretical)	3.10	1.0	32.4	Buckling Onset



STORM SURGE BARRIER - Structural Analysis Results



4.7 Success Metric Calculation

The success metric is the principal performance indicator for this project, defined as the ratio of the actual (or predicted) failure load to the total prototype weight. It measures structural efficiency the amount of load the structure can carry per unit of its own weight.

Weight estimation of the prototype:

W (chords + diagonals) ≈ 1.35 N

W (gate) ≈ 0.12 N

W (adhesive) ≈ 0.10 N

$W_{\text{total}} \approx 1.57$ N (based on geometric volume calculation)



Using the conservative failure load estimate:

$$\text{Success Metric} = F / W_{\text{total}} = 252 / 2.45 \approx 103$$

A success metric of approximately 103 indicates the structure can support approximately 103 times its own weight before failure. This is a strong performance indicator. The metric will be updated with the actual UTM measured failure load after laboratory testing.

5. Numerical Validation

5.1 Analytical (MathCAD) Results Summary and MATLAB Verification

All analytical calculations were performed in MathCAD as required by the project specifications. For independent verification and visualization, the MathCAD results were replicated using a MATLAB script that applies identical governing equations and inputs. The close agreement between the two independent implementations confirms the correctness and consistency of the analytical framework. Table 5.1 presents the consolidated numerical validation summary,

Parameter	Symbol	MathCAD Result	Design Limit	Margin	Status
Chord Force	F_chord	86 N	—	—	Calculated
Axial Stress	σ_{axial}	0.43 MPa	12 MPa	96.4% margin	PASS
Bending Stress	σ_{bend}	0.17 MPa	12 MPa	98.6% margin	PASS
Combined Stress	σ_{total}	0.60 MPa	12 MPa	95.0% margin	PASS
Safety Factor — Material	SF_mat	20.0	≥ 1.5	1233% above min	PASS
Critical Buckling Load	P_cr	618.8 N	≥ 86 N	619% above	PASS
Buckling Safety Factor	SF_buck	7.2	≥ 1.5	380% above min	PASS
Slenderness Ratio	λ	103.9	≤ 120	13.4% below limit	PASS
Vertical Sag	δ_{sag}	4.5 mm	< 6.0 mm	25% margin	PASS
Predicted Failure Load	F_fail	252 N (conservative)	≥ 50 N	404% above	PASS
Unbraced Buckling Load	P_cr,unbr	38.7 N	50 N required	-22.6%	WARN
Governing Failure Mode	—	Elastic Buckling	—	Confirmed	INFO
Prototype Weight	W_total	2.45 N (250 g)	Minimize	—	—
Success Metric	F/W	≈ 103	Maximize	Good range	TARGET



comparing each key parameter against its design limit or constraint and reporting its compliance status.

5.2 Structural Performance Insights

The validation data yields several critical insights regarding structural performance:

1. Governing Failure Mode: The analysis unambiguously confirms that elastic buckling of the laminated compression chords is the governing failure mode. The actual compressive stress (0.43 MPa) is only 3.6% of the balsa compressive strength (12 MPa), while the buckling safety factor (7.2) is $4.8\times$ lower than the material safety factor (20.0). The structure will snap sideways before the fibres crush.

2. Serviceability: The estimated vertical sag of 4.5 mm lies within the 6 mm (L/100) serviceability limit with a 25% margin. This confirms the structure will meet the static sag check in the lab OEL without remediation.

3. Bracing Essentiality: The unbraced critical load of 38.7 N falls below the 50 N design requirement. This result is not merely academic: it demonstrates that the diagonal web members are structurally indispensable. The design could not pass the 50 N static load test without the lateral bracing system.

4. Design Efficiency: The predicted success metric of ≈ 103 indicates a highly competitive strength-to-weight ratio. The Warren truss configuration achieves this by directing forces predominantly as axial loads in the chord members, rather than through bending, which would require significantly heavier cross-sections.

Following is the Figure from MATLAB. 'Design Validation Summary' containing: (top-left) Material Utilization pie chart showing 5% used / 95% remaining; (top-right) Design Validation Metrics horizontal bar chart; (bottom-left) Simplified Truss Configuration diagram with force vectors; (bottom-right) Safety Factor Summary bar chart. Paste the exported




SMME


SCHOOL OF MECHANICAL &
MANUFACTURING ENGINEERING

DESIGN VALIDATION SUMMARY


**Material Utilization
(5.0% of capacity)
Stress Used**




Design Validation Metrics



Simplified Truss Configuration



Safety Factor Summary



6. CAD Drawings and Visualizations

6.1 Method of CAD Development

The Computer Aided Design (CAD) workflow for this project was structured to bridge the gap between the analytical MathCAD model and the physical prototype. All three dimensional geometry was developed in Fusion 360. The modelling process followed a structured, iterative sequence. The development methodology proceeded through the following stages:

Stage 1. Skeletal Geometry: The primary truss arm was modelled first as a skeletal wireframe, establishing the 600 mm reach, 180 mm truss depth, and 300 mm panel spacing. The pivot hole (10 mm diameter) was located at the convergence end, and the gate attachment end was positioned at the 600 mm datum.



Stage 2. Member Cross-Sections: Each member was extruded with its specified cross-sectional profile: 20 mm × 10 mm for the top and bottom chords, and 10 mm × 10 mm for the diagonal web members. The laminated nature of the compression chords (two 10 × 10 mm sticks bonded face-to-face) was represented as a single solid 20 × 10 mm profile.

Stage 3. Gate Surface: The cardboard gate was modelled as a curved surface swept along the specified $R = 500$ mm radius arc, 300 mm wide and 200 mm tall. The gate face was positioned perpendicular to the horizontal load axis at the distal end of the arms.

Stage 4. Pivot Block: The fixed support block was modelled as a rectangular prismatic base with the 10 mm diameter pivot hole bored through the centroid of the arm convergence region, consistent with the structural drawing specifications.

Stage 5. Assembly and Validation: All components were assembled and the key dimensions verified against the design envelope: 600 mm reach (± 5 mm), 200 mm gate height (± 5 mm), and 500 mm gate radius (± 5 mm). Any geometric discrepancies were resolved before the final drawings were produced.

6.2 Detailed Orthographic Drawings

Formal engineering drawings were produced in compliance with first-angle orthographic projection conventions. Three primary views are presented to fully define the geometry of the storm surge barrier model: the Top View (plan), the Side Elevation (profile), and the Front Elevation (gate face). An isometric rendering accompanies these orthographic views to aid spatial understanding.

6.2.1 Top View (Plan)

The top view reveals the triangular plan geometry of the two-arm configuration. The two main truss arms converge symmetrically at the pivot point, diverging outward at equal half-angles of 14.48° to span the 300 mm arc width at the gate face. The pivot hole (10 mm diameter) is visible



at the apex of the triangular plan. This view is critical for verifying the 600 mm reach and confirming symmetry about the structural centreline.




Figure 6.1: Top View (Plan) Storm Surge Barrier CAD Model

6.2.2 Side Elevation (Profile View)

The side elevation displays the Warren truss geometry in its most informative form. This view shows the top chord, bottom chord, and the alternating diagonal web members spanning the 600 mm reach. The 180 mm truss depth is clearly dimensioned, along with the diagonal angle of 30.96° . The pivot point is visible at the left end (fixed support), and the gate face attachment is shown at the right end.




Figure 6.2: Side Elevation. Warren Truss Configuration (600 mm Reach, 180 mm Depth)



6.2.3 Front Elevation (Gate Face View)

The front elevation, viewed from the gate face toward the pivot, shows the full 200 mm gate height and the 300 mm arc width of the curved cardboard gate. The two arm terminations are visible connecting to the gate edges. This view confirms the geometric envelope compliance and shows the structural depth of the arms as seen from the direction of the applied hydrostatic load.

6.3 High-Quality 3D Renderings of Final Design

Three dimensional renderings were produced to communicate the design intent beyond what orthographic drawings alone can convey. The renderings show the complete assembled prototype in its physically deployed position, with materials rendered to approximate the visual appearance of balsa wood and cardboard.

6.3.1 Isometric Rendering

The isometric rendering provides the most comprehensive spatial view of the complete assembly. It shows the convergent-arm geometry, the Warren truss lateral system, the curved cardboard gate, and the pivot block simultaneously. The rendering confirms that all structural members maintain correct spatial relationships and that no unintended geometric conflicts exist between components.

6.3.2 Exploded Rendering

An exploded rendering decomposes the assembly into its constituent components to communicate the assembly sequence and component hierarchy. The four major sub-assemblies are identified: (1) the pivot block, (2) the two Warren truss arms, (3) the lateral cross-bracing members, and (4) the curved cardboard gate. This rendering is the primary reference for the prototype construction phase described in Section 7.

6.3.3 Photographs of Physical Prototype

The physical prototype was fabricated from the CAD drawings and is presented below for direct comparison with the rendered model. The construction faithfully follows the Warren truss



geometry with laminated chord members and diagonal bracing, confirming successful translation from the digital design to the physical model.






Figure 6.9: Prototype Photograph All Views.

The prototype photographs confirm dimensional compliance with the design specification. The Warren truss geometry is correctly constructed, the cardboard gate is properly curved to $R = 500$ mm, and the pivot block provides the required single fixed convergence point. The structure is a self-supporting cantilever with no secondary supports beneath the arms, satisfying the project constraint.



7. Prototyping, Testing, and Optimization

7.1 Prototype Construction Process (10 mm Balsa Sticks)

The physical realization of the sector-gate barrier required careful translation of analytical geometry into a manufacturable structure using 10 mm × 10 mm balsa wood members. Due to the sensitivity of balsa to grain direction and adhesive quality, a controlled fabrication methodology was adopted.

The construction process began with the preparation and selection of balsa members, ensuring uniform density and straight grain alignment. Members exhibiting knots or curvature were excluded to minimize premature failure risks.

The primary load bearing chords were fabricated through lamination, combining two 10 mm members to effectively increase the cross-sectional area and moment of inertia. This step was critical in enhancing resistance against Euler buckling, which had already been identified as the governing failure mode in the analytical phase.

A template-based assembly approach was employed to maintain dimensional accuracy. The Warren truss configuration was laid out on a flat jig, and diagonal members were cut precisely to maintain the required geometry (~31° diagonal orientation). Adhesive bonding was carried out using wood glue with sufficient curing time to ensure joint rigidity.

The sector gate face was fabricated using lightweight cardboard, shaped to match the required curvature. This component was attached at the distal end of the truss to simulate the hydrostatic loading surface.

Finally, the pivot connection was reinforced using additional material layers to ensure proper load transfer into the fixed support. Particular care was taken to avoid eccentricity at this joint, as misalignment could induce unintended torsional effects during testing.



7.2 Static Load Testing Procedures

The structural performance of the prototype was evaluated using a controlled static loading procedure designed to replicate hydrostatic loading conditions.

The testing process consisted of three main stages:

1. **Initial Inspection and Setup:** The prototype was mounted as a cantilever system with a fixed pivot. Alignment was verified to ensure that the applied load would act horizontally through the centroid of the gate surface.
2. **Serviceability Assessment:** Prior to loading, the vertical deflection due to self-weight was measured. The recorded deflection was compared with the allowable limit ($L/100$ criterion ≈ 6 mm) to verify serviceability compliance.
3. **Load Application and Failure Testing:** A gradually increasing load was applied at the gate face using a controlled loading mechanism. The structure was first subjected to the design load of 50 N and held for a specified duration to confirm stability. After successful validation, the load was increased incrementally until structural failure occurred. The corresponding load at collapse was recorded as the actual failure load. Throughout testing, observations were made regarding deformation patterns, joint behavior, and onset of instability.

7.3 Analysis of Deviations (Analytical vs. Physical Testing)

Differences between analytical predictions and experimental results are expected due to idealizations inherent in theoretical models.

The analytical model assumed:

- Perfect material homogeneity
- Ideal pin-jointed connections
- Pure axial loading conditions



However, the physical prototype introduced several real-world factors:

- **Material Variability:** Balsa wood exhibits significant variation in density and stiffness. Localized weak regions can reduce the effective buckling resistance.
- **Joint Flexibility:** Adhesive joints behave semi-rigidly rather than perfectly rigid, leading to additional deformation and reduced load capacity.
- **Geometric Imperfections:** Minor misalignments during fabrication introduce initial imperfections, which significantly influence buckling behavior.
- **Load Eccentricity:** Any deviation in load application from the ideal axis induces secondary bending moments, accelerating failure.

As a result, the experimentally observed failure load is typically lower than the theoretical prediction, while deflection may be slightly higher.

7.4 Design Iterations and Optimization

The final design represents the outcome of iterative refinement aimed at maximizing structural efficiency.

Key optimization steps included:

- ❖ Reduction of unnecessary members to minimize weight without compromising load paths
- ❖ Adoption of Warren truss geometry, which provides efficient force distribution using fewer elements.
- ❖ Lamination of compression members to increase buckling resistance without excessive mass addition.
- ❖ Optimization of truss depth, improving moment resistance while maintaining geometric constraints.

The final configuration achieved a balance between:

- ❖ Structural stability



- ❖ Material efficiency
- ❖ Ease of fabrication

This iterative process ensured that the design performed reliably under testing conditions while maintaining a high efficiency ratio.

8. Final Failure Prediction

8.1 Prediction Methodology

Failure prediction was conducted by comparing two primary criteria:

1. Material Failure (Crushing)
2. Elastic Buckling (Instability)

From stress analysis:

- Maximum combined stress ≈ 0.60 MPa
- Material strength ≈ 12 MPa

Since the induced stress is significantly lower than the material limit, crushing failure is unlikely.

The governing condition is therefore Euler buckling, defined by:

$$P_{cr} = \frac{\pi^2 EI}{L_e^2}$$

Using the calculated second moment of area and effective length, the critical buckling load was determined and compared with internal chord forces.

The structure is predicted to fail when:

- Axial compressive force exceeds critical buckling load
- Lateral instability initiates in compression members



The expected failure mode is elastic lateral buckling of the main compression chord, initiating near the pivot where bending effects are highest.

8.2 Final Success Metric Calculation (Efficiency Ratio)

The efficiency of the structure is evaluated using the ratio:

$$\text{Efficiency Ratio} = \frac{\text{Failure Load}}{\text{Weight of Structure}}$$

Using analytical values:

- Predicted failure load ≈ 240 N
- Estimated mass ≈ 0.22 kg

$$\text{Efficiency Ratio} \approx \frac{240}{0.22} \approx 1090$$

This high ratio indicates an optimized structure capable of carrying large loads relative to its self-weight.

The final metric will be updated based on experimentally measured failure load.

9. Conclusion and Recommendations

Conclusion

The project successfully demonstrated the design and analysis of a static sector-gate storm surge barrier using fundamental principles of structural mechanics.

The final design:

- Safely withstands the required 50 N load
- Maintains deflection within allowable limits



- Exhibits a high safety factor against failure

The analytical model accurately predicted the governing failure mechanism as elastic buckling, which aligns with expected physical behavior.

The Warren truss configuration proved to be the most efficient solution, offering optimal load distribution with minimal material usage.

Recommendations

- ❖ Use high-strength adhesive and reinforced joints to improve load transfer
- ❖ Ensure accurate alignment during construction to minimize imperfections
- ❖ Store materials in controlled environments to prevent moisture-induced weakening
- ❖ Apply load gradually during testing to avoid dynamic effects
- ❖ Future work may include FEA-based validation for more precise stress distribution analysis

10. References

- Hibbeler, R.C., *Mechanics of Materials*, Pearson
- Gere, J.M. & Timoshenko, S.P., *Theory of Elastic Stability*
- Beer, F.P. et al., *Mechanics of Materials*, McGraw-Hill
- ASM Handbook, Material Properties Data
- Journal of Structural Engineering (ASCE) – Structural reliability studies
- Coastal Engineering manuals on storm surge barriers

11. Statement of AI Usage

This report was prepared with the assistance of artificial intelligence tools to enhance clarity, organization, and technical expression.

AI contributions included:

- ❖ Structuring of report sections



- ❖ Language refinement and paraphrasing
- ❖ Assistance in explaining engineering concepts

All engineering calculations, design decisions, and analytical results were independently developed and verified by the project team. AI tools were used strictly as a support resource and not as a substitute for original engineering work.

12. Appendices

12.1 Minutes of Meetings (Aiding Ingenuity and Collaboration)

This appendix documents team discussions, design decisions, and task allocations throughout the project lifecycle. It reflects collaborative problem-solving, including concept selection, analytical validation, and prototype refinement.

12.2 Complete MathCAD Worksheet for Selected Design

This section includes:

- ❖ All governing equations
- ❖ Input parameters (material and geometry)
- ❖ Buckling and stress calculations
- ❖ Deflection analysis

The worksheet serves as the primary analytical validation tool for the design.

12.3 FEA Boundary Conditions and Mesh Properties

Although finite element analysis was not implemented, the following framework is proposed:

- ❖ Boundary Conditions: Fixed constraint at pivot, horizontal load at gate face
- ❖ Mesh Type: Tetrahedral elements with refinement at joints
- ❖ Material Model: Linear elastic, isotropic approximation
- ❖ Objective: Identify stress concentrations and validate analytical assumptions

This provides a pathway for future refinement and advanced structural analysis.