



REPORTERMAN

Date: 2026-03-25

Audit performed by Reporterman - an AI-powered pentesting tool



Executive Summary

On 2026-03-25, a comprehensive security audit was executed, with a total execution time of 21 minutes. **The assessment encompassed 1 targets across 2 services**, providing a thorough evaluation of the organization's attack surface. During the audit, **10 possible vulnerabilities were identified**, of which **2 were successfully exploited** to demonstrate potential security risks. These results offer a clear picture of the current security posture, highlighting both critical vulnerabilities that demand immediate remediation and other issues that should be addressed to strengthen overall system resilience. This report serves as a strategic tool for informed decision-making and prioritization of security measures.

This report has been generated by Reporterman, an AI-powered penetration testing tool developed by frajimmor2. The audit followed a structured approach to ensure thorough assessment of all targets. First, a reconnaissance phase was conducted, during which information about the services on each target was collected using nmap. Next, AI models from Ollama analyzed the collected data and selected potential exploits from Metasploit to test vulnerabilities in the different software components of each target. These exploits were then executed in a controlled manner, and all results, including successful and unsuccessful attempts, were carefully recorded. Finally, the gathered information was compiled and formatted to generate this comprehensive audit report, providing a detailed overview of findings, risk levels, and actionable insights.

This report contains sensitive and confidential information regarding the security posture of the assessed systems. The findings, including identified vulnerabilities, exploited paths, and target details, are intended solely for authorized personnel within the organization. Any unauthorized disclosure, distribution, or reproduction of this report or its contents may compromise security and is strictly prohibited. Recipients are responsible for ensuring that all information is handled in accordance with internal security policies and applicable data protection regulations.



Audit Methodology

This audit has follow a methodology divided in 4 phases. Reconnaissance, Data Analysis, Execution and Reporting.

Reconnaissance

This phase is based on the MITRE ATT&CK technique [Active Scanning](#), specially on the subtechniques Scanning IP Blocks and Vulnerability Scanning.

The process begins by gathering information from each target using Nmap. Initially, an operating system scan is performed to identify the target's OS, obtain its corresponding [CPE](#) (Common Platform Enumeration), and collect general system information. This step uses the command `nmap -sV -O target`, which combines service detection with OS fingerprinting.

Once the initial information is collected, the discovered open ports are analyzed and a more detailed enumeration is carried out. A targeted version scan is then executed on the identified ports to determine the specific software and service versions running on each one. This is achieved using the command `nmap -p ports -sVC target`, enabling both version detection and the execution of default scripts for deeper inspection.

Finally, a vulnerability assessment is conducted to identify potential security issues associated with the detected services. This phase leverages known vulnerability databases by running the `vulners` script, which correlates service versions with publicly disclosed vulnerabilities. The command `nmap -sVC -p ports --script vulners target` is used to perform this analysis, allowing the detection of known weaknesses that may be exploitable due to outdated software versions or misconfigurations.

Data Analysis

During the Data Analysis phase, the information collected in the reconnaissance stage is processed and enriched using three AI models deployed through Ollama. These models analyze the detected services, versions, CPE data, and potential vulnerabilities to identify relevant attack vectors and prioritize targets based on their risk level. By correlating the gathered data with known exploitation techniques and security databases, the models are able to suggest the most suitable exploits for each identified service. This multi-model approach enhances accuracy and coverage, reducing false positives while improving the likelihood of identifying viable exploitation paths. The output of this phase serves as the foundation for the subsequent execution stage, where the selected exploits are tested against the targets.

The three Ollama models perform complementary analyses to enhance the accuracy and effectiveness of the audit. First, they evaluate whether the detected software can be considered obsolete or outdated, identifying components that should be upgraded or replaced with more secure and supported alternatives. Second, the models analyze the identified services and their versions to select potential exploits that could be used to perform attacks based on known behaviors and characteristics of



the software. Finally, they correlate previously identified vulnerabilities with publicly available exploit data to determine additional attack vectors specifically linked to known security issues. This combined analysis enables a more comprehensive and prioritized selection of exploitation strategies for the subsequent phase.

In addition to the primary analysis models, an additional Ollama model is used to review and assist with the output generated by the exploit selection process. This model does not independently select exploits, but instead acts as a supporting component that helps organize, validate, and refine the information produced by the other models. Its role is to improve data processing, reduce inconsistencies, and ensure that the suggested exploitation options are presented in a clearer and more structured manner before moving to the execution phase. This additional verification step contributes to a more reliable and efficient analysis workflow.

Execution

The Execution phase consists of carrying out the exploitation attempts based on the results obtained during the data analysis stage. In this phase, the selected exploits are executed against the identified targets in a controlled manner, incorporating different payload variations to maximize the chances of success and adapt to the specific conditions of each system. These variations may include changes in configuration parameters, delivery methods, or payload types, allowing the tool to explore multiple attack paths for a given vulnerability. Throughout the process, each execution attempt is carefully monitored to determine whether the exploit was successful, partially successful, or unsuccessful. Relevant information such as response behavior, error messages, and any obtained access or data is systematically collected and recorded. This evaluation not only confirms the existence of exploitable vulnerabilities but also provides practical insight into their real-world impact, forming a critical foundation for the final reporting phase.

It is important to note that only exploits available within the Metasploit framework are used during this phase. This ensures a standardized, reliable, and well-documented set of exploitation techniques, reducing the risk of unstable or unverified attack methods while maintaining consistency throughout the assessment process.

Reporting

The audit concludes with the automatic generation of this report, which documents the entire assessment process and presents the results in a structured and comprehensive manner. This final report consolidates all collected data, analysis outcomes, and exploitation results, providing clear insights into vulnerabilities, potential risks, and recommended remediation steps for the organization.



System 192.168.1.37

Collected Information

This target has been analyzed detecting 2 software services and **10 vulnerabilities**, **2 of them exploited**. This is the obtained information from the system obtained via nmap:

vendor: linux

product: linux_kernel

version: 2.6

other info: OS details: Linux 2.6.9 - 2.6.33 Service Info: Hosts: metasploitable.localdomain, irc.Metasploitable.LAN; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Software Services Information

The system 192.168.1.37 has 2 software services currently running which available information will be displayed in the following section.

Note: When a software service is labeled as obsolete, it means that a newer or alternative software exists that performs the same tasks more efficiently, securely, or reliably. Using the obsolete software may not provide the best performance or protection compared to its modern counterpart.

Port 21/tcp

product: ftp

version: vsftpd 2.3.4

other info: | ftp-syst: | STAT: | FTP server status: | Connected to 192.168.1.36 | Logged in as ftp | TYPE: ASCII | No session bandwidth limit | Session timeout in seconds is 300 | Control connection is plain text | Data connections will be plain text | vsFTPD 2.3.4 - secure, fast, stable |_End of status |_ftp-anon: Anonymous FTP login allowed (FTP code 230)

obsolete: No

Port 3306/tcp

product: mysql

version: MySQL 5.0.51a-3ubuntu5



other info: | mysql-info: | Protocol: 10 | Version: 5.0.51a-3ubuntu5 | Thread ID: 43 | Capabilities flags: 43564 | Some Capabilities: Speaks41ProtocolNew, LongColumnFlag, SwitchToSSLAfterHandshake, SupportsTransactions, SupportsCompression, Support41Auth, ConnectWithDatabase | Status: Autocommit | _ Salt: >|wa`=OU?ygwAzfo|CwP

obsolete: No

Vulnerabilities

10 vulnerabilities were identified and 2 of them were exploited. Each attack has been performed using an exploit from Metasploit. For every selected exploit, between one and three different payloads have been executed in order to increase the chances of a successful compromise and to evaluate different exploitation scenarios. This approach allows for a more comprehensive assessment of the target system's vulnerabilities, as different payloads may trigger different behaviors or bypass certain protections.

CVE-2011-2523

Description: vsftpd 2.3.4 downloaded between 20110630 and 20110703 contains a backdoor which opens a shell on port 6200/tcp.

links: <https://vulners.com/cve/CVE-2011-2523> <https://nvd.nist.gov/vuln/detail/CVE-2011-2523>

Exploited: YES

auxiliary/gather/avtech744_dvr_accounts

Attempt with **payload:** , **success:** YES

Attempt with **payload:** payload/aix/ppc/shell_bind_tcp, **success:** YES

Attempt with **payload:** payload/aix/ppc/shell_find_port, **success:** YES

CVE-2017-15945

Description: The installation scripts in the Gentoo dev-db/mysql, dev-db/mariadb, dev-db/percona-server, dev-db/mysql-cluster, and dev-db/mariadb-galera packages before 2017-09-29 have chown calls for user-writable directory trees, which allows local users to gain privileges by leveraging access to the mysql account for creation of a link.

links: <https://vulners.com/cve/CVE-2017-15945> <https://nvd.nist.gov/vuln/detail/CVE-2017-15945>

Exploited: NO



CVE-2009-4028

Description: The `vio_verify_callback` function in `viosslfactories.c` in MySQL 5.0.x before 5.0.88 and 5.1.x before 5.1.41, when OpenSSL is used, accepts a value of zero for the depth of X.509 certificates, which allows man-in-the-middle attackers to spoof arbitrary SSL-based MySQL servers via a crafted certificate, as demonstrated by a certificate presented by a server linked against the yaSSL library.

links: <https://vulners.com/cve/CVE-2009-4028> <https://nvd.nist.gov/vuln/detail/CVE-2009-4028>

Exploited: NO

CVE-2010-1621

Description: The `mysql_uninstall_plugin` function in `sql/sql_plugin.cc` in MySQL 5.1 before 5.1.46 does not check privileges before uninstalling a plugin, which allows remote attackers to uninstall arbitrary plugins via the `UNINSTALL PLUGIN` command.

links: <https://vulners.com/cve/CVE-2010-1621> <https://nvd.nist.gov/vuln/detail/CVE-2010-1621>

Exploited: YES

auxiliary/gather/avtech744_dvr_accounts

Attempt with **payload:** , **success:** YES

Attempt with **payload:** `payload/aix/ppc/shell_bind_tcp`, **success:** YES

Attempt with **payload:** `payload/aix/ppc/shell_find_port`, **success:** YES

CVE-2015-2575

Description: Unspecified vulnerability in the MySQL Connectors component in Oracle MySQL 5.1.34 and earlier allows remote authenticated users to affect confidentiality and integrity via unknown vectors related to Connector/J.

links: <https://vulners.com/cve/CVE-2015-2575> <https://nvd.nist.gov/vuln/detail/CVE-2015-2575>

Exploited: NO

CVE-2008-2079

Description: MySQL 4.1.x before 4.1.24, 5.0.x before 5.0.60, 5.1.x before 5.1.24, and 6.0.x before 6.0.5 allows local users to bypass certain privilege checks by calling `CREATE TABLE` on a MyISAM table with modified (1) `DATA DIRECTORY` or (2) `INDEX DIRECTORY` arguments that are within the MySQL home data directory, which can point to tables that are created in the future.



links: <https://vulners.com/cve/CVE-2008-2079> <https://nvd.nist.gov/vuln/detail/CVE-2008-2079>

Exploited: NO

CVE-2010-3682

Description: Oracle MySQL 5.1 before 5.1.49 and 5.0 before 5.0.92 allows remote authenticated users to cause a denial of service (mysqld daemon crash) by using EXPLAIN with crafted "SELECT ... UNION ... ORDER BY (SELECT ... WHERE ...)" statements, which triggers a NULL pointer dereference in the Item_singlerow_subselect::store function.

links: <https://vulners.com/cve/CVE-2010-3682> <https://nvd.nist.gov/vuln/detail/CVE-2010-3682>

Exploited: NO

CVE-2010-3677

Description: Oracle MySQL 5.1 before 5.1.49 and 5.0 before 5.0.92 allows remote authenticated users to cause a denial of service (mysqld daemon crash) via a join query that uses a table with a unique SET column.

links: <https://vulners.com/cve/CVE-2010-3677> <https://nvd.nist.gov/vuln/detail/CVE-2010-3677>

Exploited: NO

exploit/windows/scada/igss9_igssdataserver_rename

Attempt with **payload:** , **success:** NO

Attempt with **payload:** payload/generic/custom, **success:** NO

Attempt with **payload:** payload/generic/debug_trap, **success:** NO

CVE-2009-0819

Description: sql/item_xmlfunc.cc in MySQL 5.1 before 5.1.32 and 6.0 before 6.0.10 allows remote authenticated users to cause a denial of service (crash) via "an XPath expression employing a scalar expression as a FilterExpr with ExtractValue() or UpdateXML()," which triggers an assertion failure.

links: <https://vulners.com/cve/CVE-2009-0819> <https://nvd.nist.gov/vuln/detail/CVE-2009-0819>

Exploited: NO



CVE-2007-5925

Description: The `convert_search_mode_to_innobase` function in `ha_innodb.cc` in the InnoDB engine in MySQL 5.1.23-BK and earlier allows remote authenticated users to cause a denial of service (database crash) via a certain `CONTAINS` operation on an indexed column, which triggers an assertion error.

links: <https://vulners.com/cve/CVE-2007-5925> <https://nvd.nist.gov/vuln/detail/CVE-2007-5925>

Exploited: NO



LLM Stats

This section provides detailed information to evaluate the actual performance of the Ollama models. During the testing phase, the models attempted a total of 195 executions. Out of these, 180 attempts were unsuccessful, resulting in a **92.31% failure rate**. The analysis of these failures helps to identify potential weaknesses in the model's decision-making process and highlights areas where improvements could be made. Furthermore, tracking both successful and failed attempts provides a comprehensive overview of the model's reliability and consistency under different conditions. This performance overview is essential for understanding the robustness of the models and for planning further optimizations or adjustments in the workflow.

We would like to sincerely thank you for using Reporterman. Your trust in our tool allows us to continuously improve and provide efficient, reliable solutions for audit automation. We hope this report helps you gain clear insights and supports your decision-making process. Your feedback is always welcome, as it helps us enhance the experience and functionality of Reporterman for all users.