Lists

25 more points to get your next star!

Rank: 767203 | Points: 195/220

Problem Submissions Leaderboard Editorial Tutorial

RATE THIS CHALLENGE

Consider a list (`list = []`). You can perform the following commands:

1. `insert i e`: Insert integer e at position i.
2. `print`: Print the list.
3. `remove e`: Delete the first occurrence of integer e.
4. `append e`: Insert integer e at the end of the list.
5. `sort`: Sort the list.
6. `pop`: Pop the last element from the list.
7. `reverse`: Reverse the list.

Initialize your list and read in the value of n followed by n lines of commands where each command will be of the 7 types listed above. Iterate through each command in order and perform the corresponding operation on your list.

Example

$N = 4$

append 1

append 2

insert 1 3

print

- **append 1**: Append 1 to the list, $arr = [1]$.
- **append 2**: Append 2 to the list, $arr = [1, 2]$.
- **insert 1 3**: Insert 3 at index 1. $arr = [1, 3, 2]$.
- **print**: Print the array.

  Output:

```
[1, 3, 2]
```

Input Format

The first line contains an integer, n, denoting the number of commands.

Each line i of the n subsequent lines contains one of the commands described above.

Constraints

- The elements added to the list must be integers.

Output Format

For each command of type `print`, print the list on a new line.

Sample Input 0

```
12
insert 0 5
insert 1 10
insert 0 6
print
remove 6
append 9
```

```
append 1
sort
print
pop
reverse
print
```

Sample Output 0

```
[6, 5, 10]
[1, 5, 9, 10]
[9, 5, 1]
```

Change Theme Language Pypy 3

```
1  if __name__ == '__main__':
2      N = int(input())
```

Line: 2 Col: 21

Upload Code as File Test against custom input Run Code Submit Code

Blog | Scoring | Environment | FAQ | About Us | Helpdesk | Careers | Terms Of Service | Privacy Policy