

# *Analysis and Synthesis of Algorithms*

## *Design of Algorithms*

### Maximum Flow Algorithms

#### Maximum Flow Application to Maximal Bipartite Matching

Copyright 2025, Pedro C. Diniz, all rights reserved.

Students enrolled in the DA class at Faculdade de Engenharia da Universidade do Porto (FEUP) have explicit permission to make copies of these materials for their personal use.

# Maximal Bipartite Matching


---

- Undirected Graph  $G = (V, E)$
- **Matching:**
  - $M \subseteq E$ , such that for any vertex  $v \in V$  *at most* one edge in  $M$  is incident on  $v$
- **Maximal Matching:**
  - Matching of Maximal Cardinality (in  $M$ )
- **Bipartite Graph:**
  - Graph can be divided in  $V = L \cup R$ , where  $L$  and  $R$  are disjoint and all edges in  $E$  are between  $L$  and  $R$
- **Maximal Bipartite Graph:**
  - Maximal Matching in which  $G$  is Bipartite


# Maximal Bipartite Matching

- **Bipartite graph:** a graph  $(V, E)$ , where  $V = L \cup R$ ,  $L \cap R = \emptyset$ , and for every  $(u, v) \in E$ ,  $u \in L$  and  $v \in R$ .
- Given an undirected graph  $G=(V,E)$ , a **matching** is a subset of edges  $M \subseteq E$  such that for all vertices  $v \in V$ , at most one edge of  $M$  is incident on  $v$ .
- We say that a vertex  $v \in V$  is matched by **matching**  $M$  if some edge in  $M$  is incident on  $v$ ; otherwise,  $v$  is unmatched.
- A **maximum matching** is a matching of maximum cardinality, that is, a matching  $M$  such that for any matching  $M'$ , we have  $|M| \geq |M'|$ .

# Bipartite Matching: Examples



(a)



(b)

A bipartite graph  $G=(V,E)$  with vertex partition  $V=L\cup R$ .


(a) A matching with cardinality 2.

(b) A maximum matching with cardinality 3.

# Maximal Bipartite Matching

- Using Maximum Flow Algorithms
  - Build an auxiliary graph  $G'$
  - Define edge capacities
- Build  $G'$ :
  - $V' = V \cup \{s, t\}$
  - $E' = \{(s, u) : u \in L\}$   
 $\cup \{(u, v) : u \in L, v \in R, \text{ and } (u, v) \in E\}$   
 $\cup \{(v, t) : v \in R\}$
  - Assign **unit** capacity to each edge in  $E'$
- Maximal Bipartite Matching in  $G$  is equivalent to finding a maximum flow in  $G'$

# Recasting as a Max-Flow Problem



- (a) The bipartite graph  $G=(V,E)$  with vertex partition  $V=L\cup R$ .  
A maximum matching is shown by shaded edges.
- (b) The corresponding flow network. Each edge has unit capacity.  
Shaded edges have a flow of 1, and all other edges carry no flow.

# Maximal Bipartite Matching

- Given  $G$  and  $G'$ :
  1. If  $M$  is a matching in  $G$ , exists an integer flow  $f$  in  $G'$ , with  $|f| = |M|$ 
    - Let  $M$  be a matching, and  $(u,v) \in M$ .
      - Define  $f$  using edges of  $M$ ,  $f(s,u) = f(u,v) = f(v,t) = 1$ .
      - For the remainder edges  $(u,v) \in E'$ ,  $f(u,v) = 0$
    - The paths  $s \rightarrow u \rightarrow v \rightarrow t$  for all  $(u,v) \in M$  are disjoint in terms of vertices with the exception of  $s$  and  $t$
    - As there are  $|M|$  paths, each of which with a single unit contribution to the flow for a total of flow  $f$ ,  $|f| = |M|$

# Maximal Bipartite Matching

---

- Given  $G$  and  $G'$ :
  2. If  $|f|$  is an integer flow in  $G'$ , then there exists a matching  $M$  in  $G$ , with  $|M| = |f|$
- Define  $M = \{(u,v): u \in L, v \in R \text{ and } f(u,v) > 0\}$ 
  - For each  $u \in L$ , exists at most one  $v \in R$  such that  $f(u,v)=1$ 
    - Only a single edge with capacity 1
    - Capacities are integer
  - Similarly for  $v \in R$
- Therefore  $M$  is a matching
- $|M| = f(L,R) = f(s,L) = |f|$



# Maximal Bipartite Matching

---

- If all edge capacities are integers, then the maximum flow  $|f|$  is an integer
  - Induction on the number of iterations of the Ford-Fulkerson algorithm
- Maximal Bipartite Matching  $|M|$  in  $G$  corresponds to  $|f|$ , where  $f$  is the maximum flow in  $G'$ 
  - If  $|M|$  is a maximal bipartite matching in  $G$ , and  $|f|$  is not maximal in  $G'$ , then there exists  $f'$  which is maximal
  - $f'$  is integer,  $|f'| > |f|$
  - $f'$  corresponds to a matching  $|M'|$ , with  $|M'| > |M|$  a contradiction
  - ...

# Maximal Bipartite Matching

---

- Using the generic Ford-Fulkerson algorithm leads to a complexity  $O(E |f^*|)$
- Maximal bipartite matching is not greater than  $\min(|L|, |R|) = O(V)$  and is an integer
  - i.e., in the worst case,  $|f^*| = O(V)$
- The complexity of the maximal bipartite matching is  $O(V E)$