

Expected delivery of lab_07.zip must include:

- zipped project folder of the exercises 1 and 2
- this document compiled possibly in pdf format.



Exercise 1)

A videogame speedrunner is tracking their daily attempts at speedrunning a game, recording both their best times and their total attempts per day. Write a program in **ARM assembly** language that analyzes their **speedrunning performance data**.

```
Days                DCB 0x01, 0x02, 0x03, 0x04, 0x05, 0x06, 0x07

Best_times          DCD 0x06, 1300, 0x03, 1700, 0x02, 1200, 0x04, 1900,
                    DCD 0x05, 1110, 0x01, 1670, 0x07, 1000

Failed_runs         DCD 0x02, 50, 0x05, 30, 0x06, 100, 0x01, 58,
                    DCD 0x03, 40, 0x04, 90, 0x07, 25

Num_days            DCB 7
```

`Days` is a table where each entry consists of a day of the week (e.g., 0x01 is Monday, 0x02 Tuesday, ..)

`Best_times` is a table where each entry consists of two integer values: the ID of the day (4 bytes) and the best time (in seconds) achieved that day by the speedrunner (4 bytes).

`Failed_runs` is a table where each entry consists of two integer values: the ID of the day (4 bytes) and the number of times the player had to reset the game (4 bytes). Notice that not all days he plays videogames.

`Num_days` is a 1-byte constant and indicates the number of days in a week.

Compute the **total number of days** the speedrunner best time was better or equal to 1300 and store it in register R11. Then for each day this time was better or equal to 1300 sum the number of `Failed_runs` and store it in register R10.

Note: The constant data section must be defined in the code section, with a 2byte alignment and 4096 boundary zero bytes.

Example:

```
...
// ALIGNMENT
// BOUNDARY (SPACE ....)
MY DATA
// BOUNDARY (SPACE ....)
..
```

Exercise 2)

Save in two separate vectors `Best_times_ordered` and `Failed_runs_ordered`, the ID of the days in descending order by best times and failed runs, respectively.

For example at the end the vectors would be ordered as follows:

```
Best_times_ordered      DCD    0x04,0x03,0x01,0x06,0x02,0x05, 0x07
Failed_runs_ordered     DCD    0x06,0x04,0x01, 0x02, 0x03, 0x05, 0x07
```

Then, save in `R11` the ID of the worst “best_time” day.

Compute the needed bytes for the above vectors.

| Vector | Size [bytes] |
|----------------------------------|--------------|
| <code>Best_times_ordered</code> | 28 |
| <code>Failed_runs_ordered</code> | 28 |

Report the following program characteristics (Hint: See the build output window in Keil).

| | Size [bytes] |
|-----------------------|--------------|
| Program Size | 8596 |
| Read Only data | 764 |
| Read Write data | 0 |
| Zero Initialized data | 624 |

And provide a brief explanation about which directives can influence the previous program characteristics.

| |
|--|
| Program size: può essere influenzata da <code>AREA</code> che definisce le sezioni dei programmi |
| Read Only data: può essere influenzata da <code>DCD</code> , <code>DCB</code> e <code>DCW</code> che definiscono dati costanti; da <code>ALIGN</code> che può aumentare o diminuire la dimensione per allineare i dati; <code>LDR</code> con costanti più grandi |
| Read Write data: può essere influenzato da <code>DCD</code> , <code>DCB</code> che creano variabili inizializzate |
| Zero Initialized Data: può essere influenzato da <code>SOACE</code> che riserva spazio per dati non inizializzati |