

vide — session launcher (shell)

<code>vide -n NAME</code>	Start or reattach the tmux session vide_NAME
<code>vide -q NAME</code>	Terminate session NAME
<code>vide -l</code>	List active vide sessions (Attached/Detached)
<code>vide -d DIR</code>	Set working directory (default: cwd)
<code>vide -h</code>	Show help

Top pane: Vim (75%). Bottom pane: console (25%). If a file under DIR matches NAME it opens directly, else main or the first .py/.tex.

tmux — prefix is `Ctrl-a`

<code>Ctrl-a</code>	Prefix key (replaces <code>Ctrl-b</code>)
<code>Ctrl-a Ctrl-a</code>	Send a literal <code>Ctrl-a</code> through
<code>Ctrl-a X</code>	Kill current session (confirm y/n)
mouse	Enabled: click panes, drag borders, scroll
<code>v / y</code>	copy-mode-vi: begin selection / yank & cancel

Panes collapse when unfocused; Tagbar & file explorer expand on entry.

IDE core — `,c` maps (all buffers)

<code>,cp</code>	Open / reset IDE layout (Tagbar + Editor + Files)
<code>,cf</code>	Find all occurrences of word under cursor
<code>,cg</code>	Jump to file+line of occurrence under cursor
<code>,cr</code>	Write find-list edits back to source files
<code>,cu</code>	Refresh the file explorer
<code>,cm</code>	Fetch OpenRouter free models, pick a default
<code>,f</code>	Open file path under cursor in editor window

Tagbar: double-click or `↩` jumps to the definition.

Find & replace workflow

- `,cf` — grep word under cursor across .py .tex .cpp .h .hpp under cwd; results shown as an editable list.
- Edit list lines in place to change the text.
- `,cr` — write modified lines back to their files.
- `,cg` — jump to the file/line of the row under cursor.

Screen layout

```
vide_NAME / window "code"
+-----+
| Tagbar| Editor | Files |
| symbol| main edit | netrw |
+-----+
| IPython console (slime) |
| or plain bash           |
+-----+
```

Top = pane 0 (75%), console = pane 1 (25%). Tagbar & Files shrink to 2 cols when unfocused, expand on entry. `,cp` rebuilds the layout anytime.

First run

<code>./install.sh</code>	Deploy vimrc, tmux.conf, plugins, ~/bin/vide
<code>./install.sh -l</code>	Also install LaTeX system deps (texlive, okular)
<code>./install.sh -u</code>	Uninstall, restore .orig backups
<code>vide -n proj</code>	Launch / attach the IDE for session proj

Needs ~/.config/ai/openrouter.token for AI features. If cLaude CLI is logged in, AI routes to it by default.

Editor — clipboard & motion

<code>ay</code>	visual: yank selection to system clipboard (xclip)
<code>ap</code>	normal: paste from system clipboard
<code>↑ ↓</code>	Move by display line (gk/gj), wrap-aware
<code>Home End</code>	Display-line start / end

Commenting (all filetypes)

<code>zc</code>	Comment selected / current lines
<code>zv</code>	Uncomment selected / current lines
<code>:Comment</code>	Comment a : '<', '>' range
<code>:Uncomment</code>	Uncomment a range
<code>\$</code>	TeX: reformat indent of selected comment block

Git grep

<code>\g</code>	Git grep whole-word for word under cursor
<code>\t</code>	Return to previous location after a grep jump
<code>:GG pat</code>	Git grep arbitrary pattern
<code>:GGw pat</code>	Git grep whole-word
<code>:GGi pat</code>	Git grep case-insensitive

Buffers & misc

<code>:Bdi</code>	Close all hidden (non-visible) buffers
<code>:DirDiff</code>	Directory diff (vim-dirdiff)
<code>\mm</code>	visual: add HTML anchors to Markdown headings
auto-save	All buffers written on focus lost
marks	Shown in sign column (vim-signature)
indent	4 spaces, expandtab; alternating indent guides

Python — IPython (vim-slime)	
\ss	Start IPython, Qt backend (--pylab qt)
\as	Start IPython, Agg backend (non-interactive)
\hh	n: send current line x: send selection
\aa	As \hh, then advance cursor one line
\rr	Run whole script (%run)
\RR	Run whole script and report run time
\dd	Debug current script (%run -d)
\qq	Exit debug mode / IPython (exit)
\QQ	Restart IPython
\hh / \aa are blocked with a warning unless IPython sits at an empty In [n]: prompt.	

Python — code cells (# %%)	
\cc	Execute the current cell
\vv	Execute cell verbosely, jump to next cell
\ll	Clear console, execute cell, jump to next
\LL	Clear the IPython console
\xx	Close all Matplotlib figure windows
[c] /]c	Jump to previous / next cell header
F9	Insert cell header above + insert mode
F10	Insert cell header below + insert mode

Python — ALE lint / fix	
Ctrl-k	Previous lint error (wrapping)
Ctrl-j	Next lint error (wrapping)
Ctrl-f	Auto-fix file: black · isort · autoimport
Ctrl-h / +BS	Show hover documentation at cursor
Ctrl-x	Close the ALE hover / preview window
Linters: pylsp (flake8, mypy/dmypy) + jedi ls. black line length 90. Saving a .py updates its paired .ipynb (jupyterxtext).	

Shell buffers (filetype sh)	
\ss	Send echo "connect" to the console pane
\hh	n: send line x: send region to console
\aa	Send line / region, then advance one line

LaTeX (vimtex)	
§	Reformat indent of selected comment block
F9	insert mode: trigger LaTeX completion
\ll	Toggle latexmk continuous compilation
\lv	Forward search: view PDF in Okular
\lk / \lc	Stop compiler / clean aux files
\le / \lt	Show errors / toggle table of contents
Compiler: latexmk (bibtex, syntex, shell-escape, nonstop). Okular inverse search → vim --servername vim. All folds open. ALE off per-buffer.	

AI — vim-ai commands	
:AI prompt	Generate / complete text at cursor
:AIEdit instr	Edit selection / context in place
:AIChat	Open the AI chat scratch buffer
:AIRedo	Redo the last AI response
,cm	Pick a free OpenRouter model as default
Add a role after the command, e.g. :AIChat /cc or :AIEdit /cc fix the bug.	

AI — model roles	
/cc /claudecode	Local claude CLI (Pro/Max billing)
/free	openrouter/free (OpenRouter default)
/gemini	google/gemini-3-flash-preview
/gpt	openai/gpt-4o
/gpt5	gpt-5.4
/claude	anthropic/claude-sonnet-4.6
/opus	anthropic/claude-opus-4.6
If claude is logged in at install, plain :AI* routes to /cc and OpenRouter becomes /free.	

AI — prompt roles (on selection)	
/refine	Rewrite text for clarity and flow
/translate	Translate text to English
/professional	Rewrite in a professional, expert tone
/simplify	Simplify language, drop jargon
/clarity	Make text direct and unambiguous
/code	Improve & format code (79-col)
/refactor	Refactor for clarity & maintainability
/optimize	Optimize for speed & memory
/comment	Add comments and docstrings
/enhance-docstring	Rewrite docstrings, Google format
/enhance-comments	Add & improve inline comments + docstrings
/reformat-comments	Reflow comments to 79 chars