

Command Prompt

```
Casco Packet Tracer PC Compand Line 1.0
C:\> pane 192,168,1.5
Pinging 192,168,1,5 with 32 bytes of detail
Reply from 192,168,1,5: hytes=32 time<1ms TTL=128 Reply from 192,168,1,5: hytes=32 time<1ms TTL=128 Reply from 192,168,1,5: hytes=32 time<1ms TTL=128
Reply from 192,168,1,5; bytes=32 time<1ms TTL=128
Fing Statistics for 192,168,1,5:
     Packets: Sent - 4. Received - 4. Lost - 8 (0% loss),
 Approximate round trip times in milli-seconds:
     Minimum - Oms. Naximum - Oms. Average - Oms
 C:\> 192.168.1.2
 Invalid Command.
 Crloping 192,168,1,2
 Pinging 192,168,1,2 with 32 bytes of data:
 Reply from 192,168,1.2: hytes=32 time<1ms TTL=128
 Reply from 192.168.1.2: hyten=32 time<1ms TTL=128
  Reply from 192,168,1,2: hytes-32 time<1ms TTL-128
Reply from 192,168,1,2: hytes-32 time<1ms TTL-128
  Fing statistics for 192,168,1,2:
  Packets: Sent = 4. Received = 4. Lost = 0 (04 loss).
Approximate round trip times in milli-seconds:
       Minimum - Ons, Maximum - Ons, Average - Ons
   Top
```



Toggle PDU List Window







