

Figure 1: Examples of reconstructions from VGIA on CIFAR10 for a batch of $B = 1024$ samples



(a) VGIA V.S. $\text{CTP}_{=}$ (b) VGIA V.S. $\text{CTP}_{>}$

Figure 2: Attack performance of VGIA and the CTP baselines when the target client trains a three-layer fully connected neural network on a random subset of Imagenet (size 1024) using full-batch FedSGD. (a,b) Number of correct samples and reconstruction error under varying attack-round budgets. $\text{CTP}_{=}$ presents a baseline with knowledge of $\varepsilon_{\mathbf{w}} =$ (the minimum absolute distance between the projections of any two samples along direction $\mathbf{w}$). $\text{CTP}_{>}$ presents a optimistic setup on ε, s.t., $\varepsilon = 10^{-3} > \varepsilon_{\mathbf{w}}$.



(a) Resnet (b) Resnet

(c) Transformer (d) Transformer

Figure 3: Comparison of our attack (VGIA) with Shi et al. (2025) (Scale-MIA) on a Resnet and a Transformer architecture. For both models, the attack layer contains $N = 512$ neurons. (a,c) Fraction of samples correctly isolated between two consecutive hyperplanes and fraction of images reconstructed with $PSNR > 18$ under different batch sizes. For VGIA, isolation is verified through Eq. 12, while for Scale-MIA we assume an oracle with access to the projection of the isolated embedding. (b,d) Average $PSNR$ across different batch sizes.



(a) HARUS (b) CIFAR10

Figure 4: Number of reconstructed inputs from a batch of dimension $B = 1024$ using a three-layers fully connected neural network, under different level of gaussian noise with standard deviation σ. The attack layeer has $N = 1000$ neurons.(a) Results on HARUS dataset. (b) Results on CIFAR10.

$$[0.2393, -0.0243, -0.0959, -0.9904, -0.9930, -0.9937, -0.9909, -0.9932, -0.9957, -0.9408]$$

(a)

$$[0.2684, -0.0200, -0.1046, -0.9904, -0.9880, -0.9903, -0.9906, -0.9874, -0.9901, -0.9392]$$

(b)

Figure 5: Examples of perfect (a) and incorrect (b) reconstructions from a batch of $B = 2048$ samples from the HARUS dataset. The first 10 feature values are shown. The incorrect reconstruction is a convex combination of the original samples, with all its features lying within the bounds of the inputs $[-1, 1]$.