



Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	Recently the organization had a DoS attack that compromised the internal network for 2 hours, the organization network stopped responding due to a flood of ICMP packets. Normal internal network traffic could not access any network resources. The incident management team responded by blocking incoming ICMP packets, stopping all non-critical network services offline, and restoring critical network services.
Identify	By investigating, they found that a malicious actor had sent a flood of ICMP pings into the company's network through an unconfigured firewall. This vulnerability allowed the malicious attacker to overwhelm the company's network through a DoS attack.
Protect	The cybersecurity team implemented a new firewall rule to limit the rate of incoming ICMP packets and an IDS/IPS system to filter out some ICMP traffic based on suspicious characteristics.
Detect	The cybersecurity team configured source IP address verification on the firewall to check for spoofed IP addresses on incoming ICMP packets and implemented network monitoring software to detect abnormal traffic patterns.

Respond	For future events, the cybersecurity team will isolate affected systems to prevent further disruption to the network. They will attempt to restore any critical systems and services that were disrupted by the event. Then, the team will analyze network logs to check for suspicious and abnormal activity. The team will also report all incidents to upper management and appropriate legal authorities, if applicable.
Recover	To recover from a DDoS attack by ICMP flooding, access to network services need to be restored to a normal functioning state. In the future, external ICMP flood attacks can be blocked at the firewall. Then, all non-critical network services should be stopped to reduce internal network traffic. Next, critical network services should be restored first. Finally, once the flood of ICMP packets have timed out, all non-critical network systems and services can be brought back online.

Reflections/Notes: