### **Personal Care**

# MIRASIL<sup>®</sup> C-DML LV

Provisional technical data sheet - DRAFT

| Description              | C.T.F.A. / I.N.C.I. Name: Cyclopentasiloxane (and) Dimethiconol CAS N° 541–02–6 (and) 70131–67–8   |  |  |  |
|--------------------------|--|--|--|--|
|                          | MIRASIL C-DML is a solution of a Dimethiconol gum of very high viscosity at 11% in Cyclopentasiloxane.  Easy to handle blend of high molecular weight Dimethiconol.                            |  |  |  |
|                          |  |  |  |  |
| Examples of applications | In skin care applications, <b>MIRASIL C-DML LV</b> will impart a smooth dry feel on the skin and can help to improve water-resistance properties and long lasting effect in sun care products. |  |  |  |
|                          | Confers antistatic and gloss effects to hair and leaves the hair with a soft, silky feel.  |  |  |  |
|                          | MIRASIL C-DML LV will contribute to improve both wet and dry combing.  |  |  |  |
|                          | MIRASIL C-DML LV is recommended in cuticle coat products, for its protecting action on split ends.   |  |  |  |
|                          | Recommended use levels : 3 – 10% in skin or hair care products.  |  |  |  |
|                          | 60% min. in cuticle coat products.   |  |  |  |
| Advantages               | The Cyclopentasiloxane part will rapidly evaporate, while the Dimethiconol part will remain on the skin or on hair providing an increased substantivity and conditioning effect.               |  |  |  |
| Characteristics          | Appearance (Standard SH-1)Clear liquid visibly free from suspended matter Colour (Standard SH-42), Hazen   |  |  |  |
|                          | OdourNone to slight  |  |  |  |
|                          | Identity, I.R. Spectrum (Standard SH-73)   |  |  |  |
|                          | Viscosity, at 25°C (Standard SH-13), mPa.s, approx   |  |  |  |
|                          | Solid content, 150°C - 1 g -2 h (Standard SH-6), %, approx   |  |  |  |
|                          | Specific gravity at 25°C, kg/m3, approx  |  |  |  |
|                          | Refractive Index (Standard SH-9), 25°C   |  |  |  |
|                          | Heavy metals (Standard SH-70), ppm Pb  |  |  |  |
|                          | Freezing point (°C)<-30  |  |  |  |
|                          | Octamethylcyclotetrasiloxane content (%)   |  |  |  |



## MIRASIL® C-DML LV

Provisional technical data sheet - DRAFT

### Characteristics (cont')

| Solubility of Mirasil C-DML LV with various cosmetic ingredients |       |     |      |  |
|--|-------|-----|------|--|
| Type of material   | 1/10* | 1/1 | 10/1 |  |
| Water  | I     | I   | - 1  |  |
| Hydrocarbons   |       |     |      |  |
| Mineral oil  |       | 1   | S    |  |
| Isododecane  | S     | S   | S    |  |
| Alcohols & glycols   |       |     |      |  |
| Ethanol  |       | I   | S    |  |
| Glycerol   |       | I   | I    |  |
| Dipropylene glycol   | I     | - 1 | I    |  |
| Propylene glycol   | ļ     | 1   | I    |  |
| Octyl dodecanol  |       | I   | S    |  |
| Oils   |       |     |      |  |
| Jojoba oil   | I     | I   | S    |  |
| Almond oil   |       | I   | I    |  |
| Castor oil   |       | I   | I    |  |
| Wheat germ oil   |       | I   | I    |  |
| Esters   |       |     |      |  |
| Isopropyl myristate  | S     | S   | S    |  |
| Isopropyl palmitate  | I     | S   | S    |  |
| C <sub>12-</sub> C <sub>15</sub> Alkyl benzoate                  | I     | I   | S    |  |
| Caprylic triglycerides   | I     | 1   | S    |  |
| Sunscreens   |       |     |      |  |
| Octyl methoxycinnamate   | l     | I   | I    |  |
| Silicones  |       |     |      |  |
| DMCO (PEG/PPG 22/24 Dimethicone)                                 | l     | I   | I    |  |
| CM5 (Cyclopentasiloxane)   | S     | S   | S    |  |
| ADMH 395 (Propoxytetramethylpiperidinyl dimethicone)             | S     | S   | S    |  |
| PTM (Phenyl Trimethicone)  | S     | S   | S    |  |
| ADME-P (Water,amodimethicone (and) Trideceth-6)                  | I     | 1   | 1    |  |
| C-DMP (Cyclopentasiloxane (and) PEG/PPG 18/18 Dimethicone)       | S     | S   | S    |  |
| DM 5 (dimethicone low viscosity)                                 | S     | S   | S    |  |
| DM 350 (dimethicone medium viscosity)                            | S     | S   | S    |  |
| *=10% of Mirasil C-DML LV and 90% of tested material S= Soluble  |       |     |      |  |
| I= Completely or partially insoluble                             |       |     |      |  |



## MIRASIL® C-DML LV

MIRASIL C-DML LV is available in: **Packaging** 

- 4 Plastic drums 200 kg / Pal. 800 kg

- 900 kg IBC

Storage and shelf life When stored in its original unopened packaging, at a temperature below +40°C, the

MIRASIL C-DML LV may be stored for up to 36 months from the date of manufacture

clearly marked on the packaging.

Beyond this date, Bluestar Silicones no longer guarantees that the product meets

the sales specifications.

Safety Please consult the Safety Data Sheet of MIRASIL C-DML LV.

Visit our website www.bluestarsilicones.com

### EUROPE

Bluestar Silicones France 21 Avenue Georges Pompidou F69486 Lyon Cedex 03 **FRANCE** Tel. (33) 4 72 13 19 00 Fax (33) 4 72 13 19 88

### NORTH AMERICA

Bluestar Silicones USA 2 Tower Center Boulevard Suite 1601 East Brunswick, NJ 08816-1100 **United States** Tel. (1) 732 227-2060 Fax. (1) 732 249-7000

### A LATIN AMERICA

Bluestar Silicones Brazil Ltda. Av. Maria Coelho Aguiar, 215 Bloco G – 1°andar 05804-902- Sao Paulo -SP- Brazil Tel. (55) 11 37477887



### ASIA PACIFIC

Bluestar Silicones Hong Kong Trading Co. Ltd 29th Floor, 88 Hing Fat Street Causeway Bay Hong Kong Tel. (852) 3106 8200 Fax (852) 2979 0241

### Warning to the users

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. BLUESTAR SILICONES guarantees that its products comply with its sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for given use. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and BLUESTAR SILICONES is at their disposal to supply any additional information.

