

 Texapon® ALS Benz
 Valid since Revision 1.1
 22.07.2021

 PRD 30530367
 WF-No. 27832
 27832

 Page 1 of 4

Anoinics

Chemical description

Ammonium lauryl sulfate

Physical form:

Liquid

Molecular weight

297 g/mol

CASR-No. Ingredient Remark

68081-96-9 Sulfuric acid, mono-C10-16-alkyl esters, ammonium salts

90583-11-2 Sulfuric acid, mono-C12-14-alkyl esters, ammonium salts

REACH registration

Characteristic values

The specifications stated in the paragraphs 'Quality control data' and 'Additional product descriptive data' finally and conclusively describe the properties of the product.

Quality control data

(Data which is used for quality release and is certified for each batch.)

Test property
Appearance
Odor at room temperature
Anionic surfactant (MW 297)
pH value 20 °C (10 % in water)
Ammonium chloride
Color Hazen/APHA
Slightly yellow viscous liquid
Corresponds to the standard
27.0 - 28.0 %
4.0 - 5.0
max. 0.5 %
max. 250

Specific methods used for batch release see Certificate of Analysis.





® = registered trademark of BASF in many countries	™ = Trademark of BASF	Care Cher	Care Chemicals	
PRD 30530367		WF-No. Page	27832 2 of 4	
Texapon® ALS Benz		Valid since Revision	22.07.2021 1.1	

™ = Trademark of BASF

Storage information

® = registered trademark of BASF in many countries

Shelf life

12 months

Storage temperature

Between + 15 °C and + 40 °C

Storage conditions

In original sealed containers and protected from moisture

Additional information

At temperatures below + 15 °C, crystallization may occur, in some cases accompanied by phase separation. This crystallisation and separation process is reversible when the product is heated and simultaneously stirred. In order to accelerate the dissolving process, Texapon® ALS Benz can be heated to 40 °C without impairing the product quality. Texapon® ALS Benz should only be stored in heatable rooms or tanks in air-conditioned rooms.

The product will be irreversibly damaged at temperatures above 50 °C.

Under no circumstances may steam or an electric heating system be used to raise the temperature of the product. This will cause local surface overheating and irreversible damage to the product and storage tank. To raise the temperature of the product a warm water or similar system is recommended set to 10 °C above the desired temperature, maximum 60 °C.

Products containing preservative or which have been preserved should be stored at the minimum possible temperature for handling to reduce depletion to a minimum.

Depending on the storage temperature, the pH may decrease with time.

If it is intended to store the product for an extended period at raised temperature the product should be monitored appropriately.





Texapon® ALS Benz

Valid since 22.07.2021
Revision 1.1

PRD 30530367

Revision 1.1

WF-No. 27832

Page 3 of 4

Stabilising additives / Auxiliaries

Preservatives

Benzoic acid

Antioxidants

not present

Solvents

not present

Others

not present

General information

Raw material basis

Vegetable: (coconut / palm kernel oil)

Inorganic: (NH₄OH, SO₃)

Composition hints for finished product label

INCI Components

INCI Name (US/EU/CN) Content
Ammonium Lauryl Sulfate 20 - 40 %

Auxiliaries

INCI Name (US/EU/CN)

Benzoic Acid *

Content
approx. 0.5 %

* At the ph-value of the product in question Ammonium Benzoate are likely to be present.

Water Content Content

60 - 80 %





e = registered trademark of BASF in many countries	™ = Trademark of BASF	Care Chemicals	
PRD 30530367		WF-No. Page	27832 4 of 4
Texapon® ALS Benz		Revision	22.07.2021 1.1

Miscellaneous information

Example of use

The product is manufactured from fatty alcohols of natural origin by sulphation. Owing to its good foaming properties, the product is suited for use as a basic surfactant in cosmetic cleansing preparations such as shampoos, shower gels and foam baths.

Intended for use as cosmetic and home care ingredient

Disclaimer

This document, or any answers or information provided herein by BASF, does not constitute a legally binding obligation of BASF. While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It does not relieve our customers from the obligation to perform a full inspection of the products upon delivery or any other obligation.NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE.

