

Product specification

Material DERMOFEEL PA-12
Spec.Code K00 STANDARD

Inspection Characteristics	Method	Limits	Units	Z
Appearance				C
Loss on drying		15.00-36.00	%	X
pH-Value 1 %		9.0-12.0	pH-Value	X
Chloride		<=0.02	%	C
Sulphate		<=0.02	%	C
Calcium content		<=0.02	%	C
Arsenoxide As ₂ O ₃		<=0.0003	%	C
Heavy Metals		<=0.001	%	C
Total Phosphorus content		13.80-25.00	%	X
Inorganic Phosphorus		0.0000-0.0200	%	X

Appearance white powder or crystals

Report on inspection certificate: X = specific/actual value, C = unspecific value/conformity, T = not reported

This document is computer printed and therefore valid without signature.

All warranty claims in respect of the conformity of our product are subject to our General Terms and Conditions of Sale and Delivery. The data listed above reflects the criteria for our internal quality tests. We do not hereby make any express or implied warranty, whether for specific properties or for fitness for any particular application or purpose. All values are valid for the product when despatched from the works.

The Standard Test Methods can be obtained from specialized publishers. Evonik's test methods are available on request.

Material: DERMOFEEL PA-12		Spec-Code: K00 STANDARD	Page 1 from 1
Print date: 03.03.2020	Valid from:	Version:	