

EMET - Quick Start Guide

EMET Development Team

May 6, 2026

Introduction

EMET is a defensive-first vulnerability orchestration platform focused on evidence, provenance, and analyst workflows. This guide covers how to set up and run the EMET platform, either via Docker or manually.

1 Docker Quick Start (Recommended)

Using Docker Compose is the easiest way to start the EMET stack, which includes the frontend, backend, worker, and necessary databases.

1. Setup the Environment:

Copy the example environment variables file to create your own configuration.

```
cp .env.example .env
```

2. Start the Stack:

Build and start all services in detached mode.

```
docker compose up --build -d
```

3. Access the Application:

Once the containers are running, you can access the following services:

- **Frontend GUI:** <http://localhost:3000>
- **Backend Health Check:** <http://localhost:8000/api/health>
- **Backend Readiness:** <http://localhost:8000/api/readiness>

4. Demo Credentials:

Use the following accounts to log into the frontend dashboard:

- Analyst: `analyst@emet.local` / Password: `emet`
- Guest (Read-Only): `guest` / Password: `emet`

2 Manual Startup (Without Docker)

If you prefer to run the components directly on your host machine, you will need to start the Frontend, Backend API, and Backend Worker separately.

2.1 Frontend

```
cd frontend
npm install
npm run dev
```

The UI will be available at <http://localhost:3000>.

2.2 Backend API

```
cd backend
python3 -m venv .venv
source .venv/bin/activate
pip install -r requirements.txt
uvicorn main:app --reload --host 0.0.0.0 --port 8000
```

2.3 Backend Worker

In a separate terminal window, start the task worker to process scan jobs.

```
cd backend
source .venv/bin/activate
python worker.py
```

3 Optional Services

Graph Mode (Neo4j)

If you are testing Attack Paths and require Neo4j to be running:

```
docker compose --profile graph up -d neo4j
```

Important Notes

- EMET is defensive-only and does not generate exploit code.
- Private/internal targets are blocked by default. To scan internal networks, you must set `ALLOW_INTERNAL_SCANNING=` in your `.env` file.
- If AI model keys are missing, RAG capabilities and evaluation will continue to run in an explicit fallback mode.