

An Analysis of GloVe word embeddings

GloVe word embeddings

GloVe word embeddings -- Part 1

Software Software for training and using word embeddings includes Tomáš Mikolov's Word2vec, Stanford University's GloVe, GN-GloVe, Flair embeddings, AllenNLP's ELMo, BERT, fastText, Gensim, Indra, and Deeplearning4j. Principal Component Analysis (PCA), Uniform manifold approximation and projection (UMAP), and T-Distributed Stochastic Neighbour Embedding (t-SNE) are used to reduce the dimensionality of word vector spaces and visualize word embeddings and clusters.

GloVe word embeddings -- Part 2

Game design Word embeddings with applications in game design have been proposed by Rabii and Cook as a way to discover emergent gameplay using logs of gameplay data. The process requires transcribing actions that occur during a game within a formal language and then using the resulting text to create word embeddings. The results presented by Rabii and Cook suggest that the resulting vectors can capture expert knowledge about games like chess that are not explicitly stated in the game's rules.

GloVe word embeddings -- Part 3

Polysemy and homonymy Historically, one of the main limitations of static word embeddings or word vector space models is that words with multiple meanings are conflated into a single representation (a single vector in the semantic space). In other words, polysemy and homonymy are not handled properly. For example, in the sentence "The club I tried yesterday was great!", it is not clear if the term club is related to the word sense of a club sandwich, clubhouse, golf club, or any other sense that club might have. The necessity to accommodate multiple meanings per word in different vectors (multi-sense embeddings) is the motivation for several contributions in NLP to split single-sense embeddings into multi-sense ones. Most approaches that produce multi-sense embeddings can be divided into two main categories for their word sense representation, i.e., unsupervised and knowledge-based. Based on word2vec skip-gram, Multi-Sense Skip-Gram (MSSG) performs word-sense discrimination and embedding simultaneously, improving its training time, while assuming a specific number of senses for each word. In the Non-Parametric Multi-Sense Skip-Gram (NP-MSSG) this number can vary depending on each word. Combining the prior knowledge of lexical databases (e.g., WordNet, ConceptNet, BabelNet), word embeddings and word sense disambiguation, Most Suitable Sense Annotation (MSSA) labels word-senses through an unsupervised and knowledge-based approach, considering a word's context in a pre-defined sliding window. Once the words are disambiguated, they can be used in a standard word embeddings technique, so

multi-sense embeddings are produced. MSSA architecture allows the disambiguation and annotation process to be performed recurrently in a self-improving manner. The use of multi-sense embeddings is known to improve performance in several NLP tasks, such as part-of-speech tagging, semantic relation identification, semantic relatedness, named entity recognition and sentiment analysis. As of the late 2010s, contextually-meaningful embeddings such as ELMo and BERT have been developed. Unlike static word embeddings, these embeddings are at the token-level, in that each occurrence of a word has its own embedding. These embeddings better reflect the multi-sense nature of words, because occurrences of a word in similar contexts are situated in similar regions of BERT's embedding space.

GloVe word embeddings -- Part 4

The idea has been extended to embeddings of entire sentences or even documents, e.g. in the form of the thought vectors concept. In 2015, some researchers suggested "skip-thought vectors" as a means to improve the quality of machine translation. A more recent and popular approach for representing sentences is Sentence-BERT, or SentenceTransformers, which modifies pre-trained BERT with the use of siamese and triplet network structures.

GloVe word embeddings -- Part 5

In natural language processing, a word embedding is a representation of a word. The embedding is used in text analysis. Typically, the representation is a real-valued vector that encodes the meaning of the word in such a way that the words that are closer in the vector space are expected to be similar in meaning. Word embeddings can be obtained using language modeling and feature learning techniques, where words or phrases from the vocabulary are mapped to vectors of real numbers. Methods to generate this mapping include neural networks, dimensionality reduction on the word co-occurrence matrix, probabilistic models, explainable knowledge base method, and explicit representation in terms of the context in which words appear. Word and phrase embeddings, when used as the underlying input representation, have been shown to boost the performance in NLP tasks such as syntactic parsing and sentiment analysis.

GloVe word embeddings -- Part 6

Development and history of the approach In distributional semantics, a quantitative methodological approach for understanding meaning in observed language, word embeddings or semantic feature space models have been used as a knowledge representation for some time. Such models aim to quantify and

An Analysis of GloVe word embeddings

GloVe word embeddings

categorize semantic similarities between linguistic items based on their distributional properties in large samples of language data. The underlying idea that "a word is characterized by the company it keeps" was proposed in a 1957 article by John Rupert Firth, but also has roots in the contemporaneous work on search systems and in cognitive psychology. The notion of a semantic space with lexical items (words or multi-word terms) represented as vectors or embeddings is based on the computational challenges of capturing distributional characteristics and using them for practical application to measure similarity between words, phrases, or entire documents. The first generation of semantic space models is the vector space model for information retrieval. Such vector space models for words and their distributional data implemented in their simplest form results in a very sparse vector space of high dimensionality (cf. curse of dimensionality). Reducing the number of dimensions using linear algebraic methods such as singular value decomposition then led to the introduction of latent semantic analysis in the late 1980s and the random indexing approach for collecting word co-occurrence contexts. In 2000, Bengio et al. provided in a series of papers titled "Neural probabilistic language models" to reduce the high dimensionality of word representations in contexts by "learning a distributed representation for words". A study published in NeurIPS (NIPS) 2002 introduced the use of both word and document embeddings applying the method of kernel CCA to bilingual (and multi-lingual) corpora, also providing an early example of self-supervised learning of word embeddings. Word embeddings come in two different styles, one in which words are expressed as vectors of co-occurring words, and another in which words are expressed as vectors of linguistic contexts in which the words occur; these different styles are studied in Lavelli et al., 2004. Roweis and Saul published in Science how to use "locally linear embedding" (LLE) to discover representations of high dimensional data structures. Most new word embedding techniques after about 2005 rely on a neural network architecture instead of more probabilistic and algebraic models, after foundational work done by Yoshua Bengio and colleagues. The approach has been adopted by many research groups after theoretical advances in 2010 had been made on the quality of vectors and the training speed of the model, as well as after hardware advances allowed for a broader parameter space to be explored profitably. In 2013, a team at Google led by Tomas Mikolov created word2vec, a word embedding toolkit that can train vector space models faster than previous approaches. The word2vec approach has been widely used in experimentation and was instrumental in raising interest for word embeddings as a technology, moving the research strand out of specialised research into broader experimentation and eventually paving the way for practical application.