

Foundations of Image super-resolution

[Image super-resolution]

1.0 Content Block

Some object features, though beyond the diffraction limit, may be known to be associated with other object features that are within the limits and hence contained in the image. Then conclusions can be drawn, using statistical methods, from the available image data about the presence of the full object. The classical example is Toraldo di Francia's proposition of judging whether an image is that of a single or double star by determining whether its width exceeds the spread from a single star. This can be achieved at separations well below the classical resolution bounds, and requires the prior limitation to the choice "single or double?" The approach can take the form of extrapolating the image in the frequency domain, by assuming that the object is an analytic function, and that we can exactly know the function values in some interval. This method is severely limited by the ever-present noise in digital imaging systems, but it can work for radar, astronomy, microscopy or magnetic resonance imaging. More recently, a fast single image super-resolution algorithm based on a closed-form solution to $\ell_2 - \ell_2$ problems has been proposed and demonstrated to accelerate most of the existing Bayesian super-resolution methods significantly.

2.0 Content Block

Probing near-field electromagnetic disturbance Super-resolution microscopy is generally discussed within the realm of conventional optical imagery. However, modern technology allows the probing of electromagnetic disturbance within molecular distances of the source, which has superior resolution properties. See also evanescent waves and the development of the new super lens.

3.0 Content Block

Super-resolution imaging (SR) is a class of techniques that improve the resolution of an imaging system. In optical SR the diffraction limit of systems is transcended, while in geometrical SR the resolution of digital imaging sensors is enhanced. In some radar and sonar imaging applications (e.g. magnetic resonance imaging (MRI), high-resolution computed tomography), subspace decomposition-based methods (e.g. MUSIC) and compressed sensing-based algorithms (e.g., SAMV) are employed to achieve SR over standard periodogram algorithm. Super-resolution imaging techniques are used in general image processing and in super-resolution microscopy.

4.0 Content Block

Other related work Curtis, Craig H.; Milster, Tom D. (October 1992). "Analysis of Superresolution in Magneto-Optic Data Storage Devices". *Applied Optics*. 31 (29): 6272–6279. Bibcode:1992ApOpt..31.6272M. doi:10.1364/AO.31.006272. PMID 20733840. Zalevsky, Z.; Mendlovic, D. (2003). *Optical Superresolution*. Springer. ISBN 978-0-387-00591-1. Caron, J.N. (September 2004). "Rapid supersampling of multiframe sequences by use of blind deconvolution". *Optics Letters*. 29 (17): 1986–1988. Bibcode:2004OptL...29.1986C. doi:10.1364/OL.29.001986. PMID 15455755. Clement, G.T.; Huttunen, J.; Hynynen, K. (2005). "Superresolution ultrasound imaging using back-projected reconstruction". *Journal of the Acoustical Society of America*. 118 (6): 3953–3960. Bibcode:2005ASAJ..118.3953C. doi:10.1121/1.2109167. PMID 16419839. Geisler, W.S.; Perry, J.S. (2011). "Statistics for optimal point prediction in natural images". *Journal of Vision*. 11 (12): 14. doi:10.1167/11.12.14. PMC 5144165. PMID 22011382. Cheung, V.; Frey, B. J.; Jojic, N. (20–25 June 2005). Video epitomes (PDF). *Conference on Computer Vision and Pattern Recognition (CVPR)*. Vol. 1. pp. 42–49. doi:10.1109/CVPR.2005.366. Bertero, M.; Boccacci, P. (October 2003). "Super-resolution in

computational imaging". *Micron*. 34 (6–7): 265–273. doi:10.1016/s0968-4328(03)00051-9. PMID 12932769. Borman, S.; Stevenson, R. (1998). "Spatial Resolution Enhancement of Low-Resolution Image Sequences – A Comprehensive Review with Directions for Future Research" (Technical report). University of Notre Dame. Borman, S.; Stevenson, R. (1998). Super-resolution from image sequences — a review (PDF). Midwest Symposium on Circuits and Systems. Park, S. C.; Park, M. K.; Kang, M. G. (May 2003). "Super-resolution image reconstruction: a technical overview". *IEEE Signal Processing Magazine*. 20 (3): 21–36. Bibcode:2003ISPM...20...21P. doi:10.1109/MSP.2003.1203207. S2CID 12320918. Farsiu, S.; Robinson, D.; Elad, M.; Milanfar, P. (August 2004). "Advances and Challenges in Super-Resolution". *International Journal of Imaging Systems and Technology*. 14 (2): 47–57. doi:10.1002/ima.20007. S2CID 12351561. Elad, M.; Hel-Or, Y. (August 2001). "Fast Super-Resolution Reconstruction Algorithm for Pure Translational Motion and Common Space-Invariant Blur". *IEEE Transactions on Image Processing*. 10 (8): 1187–1193. Bibcode:2001ITIP...10.1187E. CiteSeerX 10.1.1.11.2502. doi:10.1109/83.935034. PMID 18255535. Irani, M.; Peleg, S. (June 1990). Super Resolution From Image Sequences (PDF). International Conference on Pattern Recognition. Vol. 2. pp. 115–120. Sroubek, F.; Cristobal, G.; Flusser, J. (2007). "A Unified Approach to Superresolution and Multichannel Blind Deconvolution". *IEEE Transactions on Image Processing*. 16 (9): 2322–2332. Bibcode:2007ITIP...16.2322S. doi:10.1109/TIP.2007.903256. PMID 17784605. S2CID 6367149. Calabuig, Alejandro; Micó, Vicente; Garcia, Javier; Zalevsky, Zeev; Ferreira, Carlos (March 2011). "Single-exposure super-resolved interferometric microscopy by red–green–blue multiplexing". *Optics Letters*. 36 (6): 885–887. Bibcode:2011OptL...36..885C. doi:10.1364/OL.36.000885. PMID 21403717. Chan, Wai-San; Lam, Edmund; Ng, Michael K.; Mak, Giuseppe Y. (September 2007). "Super-resolution reconstruction in a computational compound-eye imaging system". *Multidimensional Systems and Signal Processing*. 18 (2–3): 83–101. Bibcode:2007MSySP...18...83C. doi:10.1007/s11045-007-0022-3. S2CID 16452552. Ng, Michael K.; Shen, Huanfeng; Lam, Edmund Y.; Zhang, Liangpei (2007). "A Total Variation Regularization Based Super-Resolution Reconstruction Algorithm for Digital Video". *EURASIP Journal on Advances in Signal Processing*. 2007 074585. Bibcode:2007EJASP2007..104N. doi:10.1155/2007/74585. hdl:10722/73871. Glasner, D.; Bagon, S.; Irani, M. (October 2009). Super-Resolution from a Single Image (PDF). International Conference on Computer Vision (ICCV).; "example and results". Ben-Ezra, M.; Lin, Zhouchen; Wilburn, B.; Zhang, Wei (July 2011). "Penrose Pixels for Super-Resolution" (PDF). *IEEE Transactions on Pattern Analysis and Machine Intelligence*. 33 (7): 1370–1383. Bibcode:2011ITPAM..33.1370B. CiteSeerX 10.1.1.174.8804. doi:10.1109/TPAMI.2010.213. PMID 21135446. S2CID 184868. Berliner, L.; Buffa, A. (2011). "Super-resolution variable-dose imaging in digital radiography: quality and dose reduction with a fluoroscopic flat-panel detector". *Int J Comput Assist Radiol Surg*. 6 (5): 663–673. doi:10.1007/s11548-011-0545-9. PMID 21298404. Timofte, R.; De Smet, V.; Van Gool, L. (November 2014). A+: Adjusted Anchored Neighborhood Regression for Fast Super-Resolution (PDF). 12th Asian Conference on Computer Vision (ACCV).; "codes and data". Huang, J.-B.; Singh, A.; Ahuja, N. (June 2015). Single Image Super-Resolution from Transformed Self-Exemplars. *IEEE Conference on Computer Vision and Pattern Recognition*.; "project page". CHRISTENSEN-JEFFRIES, T.; COUTURE, O.; DAYTON, P.A.; ELDAR, Y.C.; HYNENEN, K.; KIESSLING, F.; O'REILLY, M.; PINTON, G.F.; SCHMITZ, G.; TANG, M.-X.; TANTER, M.; VAN SLOUN, R.J.G. (2020). "Super-resolution Ultrasound Imaging". *Ultrasound Med. Biol.* 46 (4): 865–891. doi:10.1016/j.ultrasmedbio.2019.11.013. PMC 8388823. PMID 31973952.

5.0 Content Block

Technical implementations There are many both single-frame and multiple-frame variants of SR. Multiple-frame SR uses the sub-pixel shifts between multiple low resolution images of the same scene. It creates an improved resolution image fusing information from all low resolution images, and the created higher resolution images are better descriptions of the scene. Single-frame SR methods attempt to magnify the image without producing blur. These methods use other parts of the low resolution images, or other unrelated images, to guess what the high-resolution image should look like. Algorithms can also be divided by their domain: frequency or space domain. Originally, super-resolution methods worked well only

on grayscale images, but researchers have found methods to adapt them to color camera images. Recently, the use of super-resolution for 3D data has also been shown.