

TECHNICAL DATA SHEET

BUILDING MATERIALS & MINERALS

High-Grade Pure Gypsum & Construction Plaster

(Plaster of Paris)

Ultra-refined white gypsum plaster formulated for smooth internal wall plastering, cornices, decorative ceilings (staff), and medical casting applications.

ORIGIN	DESTINATION
Mediterranean & Southern Europe Mineral Basins	Port of Douala Construction Terminal

CERTIFIED TECHNICAL SPECIFICATIONS

- Chemical Purity: $\text{CaSO}_4 \cdot \frac{1}{2} \text{H}_2\text{O}$ > 95% Pure Hemihydrate
- Whiteness: > 92% L-Value Optical Brightness
- Fineness: 250 - 300 Mesh Residue < 0.2%
- Setting Time: Initial 6-9 min, Final 12-18 min
- Compressive Strength: > 14 MPa after 2 hours hydration

LOGISTICS & COMMERCIAL TERMS

Container Payload	27 Metric Tons per 20ft FCL (1,080 x 25kg valve bags)
Packaging Type	25kg or 40kg Multi-Ply Kraft Paper Valve Bags, Polyethylene Lamination
Minimum Order Quantity	1x 20ft FCL (27 Metric Tons)
HS Code	2520.20.10
Discharge Incoterms	CIF Port of Douala · FOB Valencia / Genoa / Marseille · CFR Port of Douala
Certifications	EN 13279-1 European Building Standard · ISO 9001 Factory Quality Control · SGS Chemical Assay Certificate

Ready to request a quote? Contact our procurement desk at quotes@sofomeutex.com or submit a container requisition via the Sofomeutex website Request-a-Quote form to receive a formal proforma invoice under CIF Douala or CIP inland terminal conditions.