

Utilizing Crowd Intelligence for Online Detection of Emotional Distress

Master's Thesis Presentation

Siddhant Goel

Advisor: Han Xiao

Supervisor: Prof. Dr. Claudia Eckert

Chair for IT Security
Technische Universität München

March 11, 2013

Outline

- Introduction
 - Introduction
 - Problem Definition
- Theoretical Background
 - Machine Learning and Text Classification
 - Support Vector Machines
 - Ensemble Learning methods
- Experimental Results
 - Experiments
 - Results
- Conclusion

Introduction

Introduction

- Millions of people die every year because of suicide
- Most people are between 15 to 29 years old
- Rise of social media - Twitter, Facebook, Reddit, Wordpress
- Reddit - “/r/happy” and “/r/suicidewatch”
- People are not afraid of posting their inner feelings on the web

Introduction




Figure : Happiness on Twitter as a function of time

- Study conducted in 2011
- 46 billion words collected over 33 months
- Negativity on Twitter has been on the rise
- Words include *death*, *hate*, and even *suicide*

Motivation



- Last tweet of Twitter user “@CapitalSTEEZ_” ¹
- Some accounts have lots of followers, some don't
- Lives can be saved if there is a surveillance system of suicide
- Public sentiment information available on the web + No analysis possible = Disconnect

¹http://twitter.com/CapitalSteez_

Problem Definition

- Evaluate machine learning algorithms (including support vector machines and ensemble learning methods) that can be used for text classification
- Build a web based system that can
 - tap into crowd intelligence to incrementally improve the classifiers
 - detect content on the web that indicates that its author is depressed or suicidal

Theoretical Background

Machine Learning

- Algorithms that can learn from data
- Construct a model from a given dataset, and then perform the required task on another dataset
- **Supervised Learning** - Train the models on the training data, and predict on the test data
- **Unsupervised Learning** - No distinction between training and test data

Text Classification

- Subset of machine learning algorithms (we focus on supervised text classification)
- Given some pieces of text, put future pieces of text into two or more categories
- Dataset $(\mathbf{x}_n, y_n)_{n=1}^N$ containing N instances
- Each instance (\mathbf{x}_n, y_n) is of the form $[(x_{n,1}, x_{n,2}, \dots, x_{n,D}), y_n]$
- Supervised learning - calculate y_n of test data given information about y_n from training data
- Unsupervised learning - calculate y_n given only information about \mathbf{x}_n

Support Vector Machines

- Fairly popular class of algorithms in binary classification
- Given training data in D dimensional space, find a decision boundary (hyperplane) that separates the two classes
- Maximize the distance of the boundary from any data point
- Decision function depends on a (usually small) subset of points called support vectors
- Distance function between two points is expressed using a kernel function

Linear kernel SVM




Figure : Classifying two subsets of a dataset using a linear kernel SVM

Kernel functions




Figure : A dataset that cannot be classified using a linear kernel SVM

Kernel functions




Figure : Add the third dimension as $\sqrt{x_1^2 + x_2^2}$ to transform the dataset into 3D

Ensemble Learning

- Class of machine learning methods that combine models to obtain better predictions
- Performance not guaranteed to be better than constituent classifiers
- Ensemble methods still usually outperform individual classifiers

Bagging

- Combine M classifiers to form a single classifier
- To predict, obtain predictions from all constituent classifiers, and take majority vote
- Requirement - classifiers should change for even small changes in underlying classifiers
- Two main approaches for training individual classifiers
 - Sample split - each classifier is trained using a random subset of the samples
 - Feature split - each classifier is trained using a random subset of the features