

■■ CYBERSHIELD

Administrator Manual

Document CS-ADM-004 — Version 1.0

CS-ADM-004 · v1.0 · 28/05/2026 · CONFIDENTIAL

Francisco José Jiménez Pozo · fjjpozo075@gmail.com | github.com/franjmenezz

1. Prerequisites

Requirement	Specification
ODOO Version	18.0 Community Edition
Python	3.10 or higher
PostgreSQL	15 or higher
Docker	24.0+ with Docker Compose v2
RAM	Minimum 4GB (8GB recommended with Wazuh Stack)
Disk	Minimum 50GB SSD
OS (recommended)	Ubuntu Server 22.04 LTS
Network	HTTPS (port 443) reachable from all agent endpoints

2. Installation

2.1 Copy Module to ODOO Addons

- Extract the cyber_shield folder from the release ZIP
- Copy the inner cyber_shield/ directory to your ODOO addons path:

```
cp -r cyber_shield/cyber_shield /path/to/odoo/addons/
```

2.2 Update ODOO Configuration (odoo.conf)

```
addons_path = /path/to/odoo/addons
```

2.3 Install the Module

- Go to Apps → Remove the 'Apps' filter → Search 'CyberShield'
- Click Install and wait for completion
- Navigate to the CyberShield menu in the top navigation bar

3. Initial Configuration

3.1 Assign User Roles

Go to Settings → Users and assign CyberShield roles to your team members:

Role	Recommended For	Key Permissions
CyberShield Administrator	IT Security Lead	Full access including agent token management and configuration
Senior Analyst	Experienced security staff	Full operational access, report generation — no configuration
Analyst	Security team members	Create and manage alerts and incidents

Auditor	Compliance / audit team	Read-only access + report generation
Read Only	Management / stakeholders	Dashboard and alert overview only

3.2 Register Devices

1. Go to CyberShield → Configuration → Manage Devices → New
2. Fill in: Device Name (e.g. 'Diseño EQ1'), Type, Department, Criticality
3. Save — the system generates a unique Agent Token automatically
4. Copy the Agent Token (Admins only) — you will need it for the agent installer
5. The device will appear as 'Unregistered' until the agent connects for the first time

3.3 Configure Notification Channels

1. Go to CyberShield → Notification Center → Channels
2. The default 'ODOO Internal — Administrators' channel is pre-configured
3. For email: create new channel → Email → enter addresses → Save → Test
4. For webhook (Telegram/Slack/etc.): select Webhook → enter URL and payload template
5. Always use 'Send Test Notification' to verify the channel works before relying on it

4. Installing Agents

4.1 Windows Agent (PowerShell)

Run as Administrator in PowerShell:

```
.\install_agent.ps1 -ServerURL "https://your-server.com" -AgentToken "token" -DeviceName "Diseño EQ1"
```

4.2 Linux Agent (Bash)

Run as root:

```
sudo bash install_agent.sh --server "https://your-server.com" --token "token" --name "Servidor Web 01"
```

4.3 What the Agents Monitor

Event Category	Windows	Linux
Login / Logout	Event IDs 4624, 4634	auth.log / PAM
Failed logins	Event ID 4625	auth.log + lastb
Privilege escalation	Event ID 4672	sudo via auditd
Process creation	Sysmon + Event 4688	auditd execve
Network connections	Sysmon NetworkConnect	ss established
USB devices	Sysmon RawAccessRead	udev events

Remote access (RDP/SSH)	qwinsta sessions	SSH auth.log
File changes	Sysmon FileCreate	auditd file rules
User management	Events 4720, 4726, 4728	auditd useradd/del

5. Operations Guide

5.1 Daily Tasks

- Review Dashboard for any Critical or High open alerts
- Check Notification Center → Failed Notifications and retry if needed
- Verify no SLA-breached alerts are unattended

5.2 Weekly Tasks

- Review all open vulnerabilities and update patch status
- Verify agent connectivity for all registered devices
- Generate a weekly security report

5.3 Monthly Tasks

- Generate and approve a monthly audit report
- Review and update escalation rules if needed
- Perform a full backup restoration test
- Review device inventory for any decommissioned assets
- Review user roles and revoke access for any leavers

5.4 Troubleshooting — Agent Not Connecting

Symptom	Likely Cause	Solution
Agent status: Never Connected	Agent not installed or not started	Run the installer and check scheduled task (Windows) or systemctl status (Linux)
Agent status: Disconnected	Server unreachable or token invalid	Check network connectivity to server URL and verify the agent token in the config file
Notifications: Failed	Webhook URL unreachable or invalid payload	Test channel from CyberShield → Channels → Send Test Notification and check error details
API: Rate limit exceeded	Agent sending too many events	Check agent configuration — reduce poll frequency or filter event types