Integrations, Webhooks, Background Jobs, and Data Processing

FICTIONAL TRAINING DOCUMENT — designed for RAG/agent testing; no real company, policy, SLA, customer, or price is represented.

Webhook delivery

Northstar sends HTTPS POST webhooks. Delivery succeeds on any 2xx within 10 seconds; redirects are not followed. Failed deliveries retry on an approximate schedule: immediate, +1m, +5m, +30m, +2h, +8h, +24h final. Failed deliveries remain visible for 30 days; manual redelivery may be available.

Security

Requests include timestamp and HMAC signature. Customers compute the documented canonical payload with their signing secret; recommended timestamp tolerance is five minutes.

Never request the webhook signing secret. Ask for signature header, timestamp, delivery/request ID, and sanitized payload.

Common failures

Symptom	Likely cause / action
401/403	Customer auth/firewall rejects Northstar; validate endpoint policy.
404	Wrong/retired callback path.
408/504	Endpoint too slow; acknowledge quickly and process asynchronously.
Signature mismatch	Wrong secret/canonicalization/clock; rotate if exposed.
TLS handshake	Certificate chain/protocol problem.

Background jobs

Large imports, exports, document processing and automations run asynchronously: Queued, Running, Succeeded, Failed, Cancelled. Capture Job ID (e.g., JOB-803194). Investigate when oldest-message age rises continuously, worker errors increase, or completion time exceeds normal range >15 minutes.

Idempotency

Supported create operations accept idempotency keys. Same key + same body returns prior result within a 24-hour window; same key + materially different content returns conflict. This prevents duplicates during safe retries.

Import troubleshooting

• Validate file type, encoding, size, schema, required columns and unique IDs.

• Determine all rows vs subset; capture Job ID and representative validation errors.

• Do not repeatedly resubmit a large import while the previous job is running.

Dependency isolation

Determine whether Northstar cannot send, customer endpoint cannot receive, or a third party is failing. Compare customers/regions before concluding a shared service is unhealthy.

Escalation package

• Account/integration/job/webhook-delivery ID; UTC timestamp and region.

• HTTP status/error; sanitized headers and payload shape.

• Manual retry result; whether other endpoints/customers fail.

• Recent certificate, DNS, firewall, configuration, or deployment changes.

Cross-agent scenarios

If Northstar shows successful webhook delivery but the customer's business process failed, Technical explains delivery evidence while Support helps with product usage. If a verified Northstar outage affected an SLA-eligible service, Technical supplies incident facts and Billing evaluates credit.

Operational patterns

Growing queue but stable oldest-message age: likely healthy burst processing. **Oldest-message age and failures rise together:** worker/dependency incident. **Repeated webhook 504 only for one customer:** likely customer endpoint latency. **Failures across many customers/regions:** investigate shared Northstar sender/dependency.

Customer-safe guidance

Do not expose internal worker names, private infrastructure addresses, credentials, or raw secrets. Provide delivery IDs, documented retry behavior, public error meaning, and verified mitigation.