



SCREW SIZE	HEAD DIMENSIONS				
	D		H		DRIVE
	MAX.	MIN.	MAX.	MIN.	SIZE
8	.384	.364	.102	.088	HSI5
10	.448	.425	.118	.103	HS20
12	.511	.487	.134	.118	HS25
1/4	.573	.546	.150	.133	HS27
5/16	.698	.666	.183	.162	HS40
3/8	.823	.787	.215	.191	HS45
7/16	.948	.907	.248	.221	HS45
1/2	1.073	1.028	.280	.250	HS50

© COPYRIGHT 2011 PHILLIPS SCREW COMPANY. ALL RIGHTS RESERVED.

THIS DRAWING EMBODIES A CONFIDENTIAL AND PROPRIETARY DESIGN OWNED BY PHILLIPS SCREW COMPANY AND MAY NOT BE COPIED OR REPRODUCED. IN WHOLE OR IN PART, IN ANY FORM WHATSOEVER WITHOUT THE EXPRESS WRITTEN PERMISSION OF PHILLIPS SCREW COMPANY. THIS DRAWING AND DESIGN IS PROVIDED UNDER A CONFIDENTIAL RELATIONSHIP FOR A SPECIFIC PURPOSE AND THE RECIPIENT AGREES TO USE IT ONLY FOR SUCH PURPOSE. ALL PATENT, TRADEMARK, AND OTHER RIGHTS IN AND TO THIS DRAWING AND DESIGN ARE EXPRESSLY RESERVED BY PHILLIPS SCREW COMPANY, BURLINGTON, MASSACHUSETTS, U.S.A.

TITLE:

HEXSTIX®
TRUSS HEAD (INCH)

DRAWING NUMBER

PSC-H-IO3-W

SHEET I OF I

CONTACT: INFO@PHILLIPS-SCREW.COM

PHILLIPS II PHILLIPS POZIDRIV ACR POZISQUARE PHILLIPS SQUARE-DRIV TORQ-SET TRI-WING MORTORQ HEXSTIX AND POZILOCK ARE REGISTERED TRADEMARKS OF THE PHILLIPS SCREW COMPANY