



THREAD SIZE TENSION HEAD	DIMENSIONS		RECESS AND DRIVER SIZE
	ØA REF	J REF.	
.0600-80	.082	.031	0
.0730-64	.098	.037	1
.0860-56	.115	.043	2
.0990-56	.132	.049	3
.1120-40	.148	.055	4
.1380-32	.182	.066	6
.1640-32	.215	.078	8
.1900-32	.248	.090	10
.2500-28	.325	.118	1/4
.3125-24	.357	.122	5/16
.3750-24	.427	.145	3/8
.4375-20	.498	.169	7/16
.5000-20	.568	.193	1/2
.5625-18	.638	.217	9/16
.6250-18	.708	.241	5/8
.7500-16	.849	.288	3/4
.8750-14	.989	.336	7/8
1.000-12	1.130	.383	1"

© COPYRIGHT 2011 PHILLIPS SCREW COMPANY.
ALL RIGHTS RESERVED.

THIS DRAWING EMBODIES A CONFIDENTIAL AND PROPRIETARY DESIGN OWNED BY PHILLIPS SCREW COMPANY AND MAY NOT BE COPIED OR REPRODUCED, IN WHOLE OR IN PART, IN ANY FORM WHATSOEVER WITHOUT THE EXPRESS WRITTEN PERMISSION OF PHILLIPS SCREW COMPANY. THIS DRAWING AND DESIGN IS PROVIDED UNDER A CONFIDENTIAL RELATIONSHIP FOR A SPECIFIC PURPOSE AND THE RECIPIENT AGREES TO USE IT ONLY FOR SUCH PURPOSE. ALL PATENT, TRADEMARK, AND OTHER RIGHTS IN AND TO THIS DRAWING AND DESIGN ARE EXPRESSLY RESERVED BY PHILLIPS SCREW COMPANY, BURLINGTON, MASSACHUSETTS, U.S.A.

TITLE:

ACR[®] MULTI-RIBBED TORQ-SET[®]
100° FLUSH TENSION HEAD

DRAWING NUMBER

PSC-2000-WI

SHEET 1 OF 1

CONTACT: INFO@PHILLIPS-SCREW.COM

PHILLIPS II[®] PHILLIPS[®] POZIDRIV[®] ACR[®] POZISQUARE[®] PHILLIPS SQUARE-DRIV[®] TORQ-SET[®] TRI-WING[®] MORTORQ[®] HEXSTIX[®]
AND POZILOCK[®] ARE REGISTERED TRADEMARKS OF THE PHILLIPS SCREW COMPANY