



## MACHINE AND TAPPING SCREWS

SCREW SIZE	HEAD DIMENSIONS		DRIVER SIZE
	$\phi A$ THEO.	O MAX.	
2	.172 .156	.066	1
3	.199 .181	.076	
4	.225 .207	.085	
5	.252 .232	.096	2
6	.279 .257	.105	
7	.305 .283	.115	
8	.332 .308	.124	
9	.358 .334	.134	
10	.385 .359	.143	
12	.438 .410	.163	3
14	.491 .461	.183	
1/4	.507 .477	.189	
16	.544 .512	.202	
18	.597 .563	.222	4
5/16	.635 .600	.237	
3/8	.762 .722	.282	

© COPYRIGHT 2011 PHILLIPS SCREW COMPANY.  
ALL RIGHTS RESERVED.

THIS DRAWING EMBODIES A CONFIDENTIAL AND PROPRIETARY DESIGN OWNED BY PHILLIPS SCREW COMPANY AND MAY NOT BE COPIED OR REPRODUCED, IN WHOLE OR IN PART, IN ANY FORM WHATSOEVER WITHOUT THE EXPRESS WRITTEN PERMISSION OF PHILLIPS SCREW COMPANY. THIS DRAWING AND DESIGN IS PROVIDED UNDER A CONFIDENTIAL RELATIONSHIP FOR A SPECIFIC PURPOSE AND THE RECIPIENT AGREES TO USE IT ONLY FOR SUCH PURPOSE. ALL PATENT, TRADEMARK, AND OTHER RIGHTS IN AND TO THIS DRAWING AND DESIGN ARE EXPRESSLY RESERVED BY PHILLIPS SCREW COMPANY, BURLINGTON, MASSACHUSETTS, U.S.A.

TITLE:

PHILLIPS II<sup>®</sup>  
100° OVAL HEAD SCREWS

DRAWING NUMBER

P2HSI5-W

SHEET 1 OF 1

CONTACT: INFO@PHILLIPS-SCREW.COM

PHILLIPS II<sup>®</sup> PHILLIPS<sup>®</sup> POZIDRIV<sup>®</sup> ACR<sup>®</sup> POZISQUARE<sup>®</sup> PHILLIPS SQUARE-DRIV<sup>®</sup> TORQ-SET<sup>®</sup> TRI-WING<sup>®</sup> MORTORQ<sup>®</sup> HEXSTIX<sup>®</sup>  
AND POZILOCK<sup>®</sup> ARE REGISTERED TRADEMARKS OF THE PHILLIPS SCREW COMPANY