

Feature: Home page

From build-plan: feature 3 Branch: `feature/home-page` Status: verified

Goal

Replace the interim hero with the real home page: the page that establishes what she does, where she is and why her, with booking one tap away. Ten sections from the prototype, every fact read from `siteConfig`, every price, count and treatment name read from the services data, every photo served through ImageKit. First real consumer of feature 2 and first page with photography.

Design reference

- `prototypes/home.html` - the whole page; lines 195 to 445 are the sections, lines 1 to 170 the section CSS. Build the ten sections below; skip the rest (see Out of scope)
- `blueprint/reference/ig/` - her real photographs; which file goes in which slot is in Data / contracts
- `blueprint/reference/business.md` lines 158 to 182 - what each photo shows and which are unusable promo graphics
- Feature 1's primitives (`Section`, `Container`, `Eye brow`, `Lede`, `Divider`, `Watermark`, `Orchid`, `Button`) and its tokens; nothing here adds a new colour or font

In scope

- `components/media/Photo.tsx` - the ImageKit wrapper every image uses from now on, plus `data/images.ts`, the slot manifest (path, alt, source)
- `app/page.tsx` rebuilt from ten server-rendered section components under `components/home/`: hero, trust strip, browse by concern, categories, signature treatment, results, Eminence, reviews, consultation, hours and location
- `data/reviews.ts` and `types/reviews.ts` (the overview's `Review` shape), filled only with real quotes found during the build; the section has an honest empty state
- `data/results.ts` - the one genuine before-and-after she has
- `lib/hours.ts` - `formatHours(day)` for the seven-row table
- `siteConfig` gains `founded`, `ratings` and `consultation` (the facts the hero, trust strip and consultation section print)
- `Tag` primitive in `components/layout/Tag.tsx` (the prototype's `.tag`)
- Responsive at 375, 768 and 1280, and both themes

Out of scope

- Four prototype sections with no build-plan backing: "How it works", "Ways to commit" (feature 15, and its offers are unconfirmed), the Instagram grid (mostly promo graphics), and the FAQ (its copy names Square). Say if you want any of them and they become a plan line
- The "3 sessions to real change" stat badge. A treatment-outcome claim she has not approved; the photo stands alone
- The hero video. No footage exists; the slot holds her best action photo and takes a video later without layout change
- Map embed, directions and open-now (feature 8). The location section shows the address, the seven-row hours, a room photo and call / text buttons
- Category, concern, treatment, about and contact pages (features 4 to 9). Every link goes to its planned route and 404s until then
- JSON-LD, per-page metadata, Open Graph (feature 10)
- Booking (feature 11). Every Book control goes to `/contact`
- A reviews admin or feed (feature 14). This feature ships the data file and the section

Build loop

- `workflow.stepReview` is `feature` : build all steps, one review at the end
- `workflow.checkpointCommits` is `disabled` ; `/complete` makes the one commit
- Gate per step: `npm run lint` and `npm run build` ; browser evidence for the visual done-whens on the running dev server (`check` is `when-behavioral` , and this page has one click path, the concern and category links)
- Nothing to install. `@imagekit/next` is already a dependency
- **Prerequisite for step 1:** `NEXT_PUBLIC_IMAGEKIT_URL_ENDPOINT` in `.env.local` (and later in Vercel) and the assets in Data / contracts uploaded to that ImageKit account under `/face-and-body/` . Step 1 stops and asks if either is missing. Steps 2 to 6 build against the wrapper regardless

Build steps

- ☒ **1. Image pipeline.** Confirm the endpoint and uploads exist (see prerequisite). Add `NEXT_PUBLIC_IMAGEKIT_URL_ENDPOINT` to `.env.example` is already there; leave it. Create `components/media/Photo.tsx` : a thin wrapper over `@imagekit/next` 's `Image` that takes `slot` (a key of `IMAGES`) plus the usual `className` , `sizes` , `priority` , `fill` props, looks up path and alt from `data/images.ts` , and passes `urlEndpoint` from the env var. Throw at render if the env var is missing in production; in development render a labelled `bg-placeholder` box so the layout can be built without the account. Create `data/images.ts` with the slot manifest in Data / contracts. Prove it by swapping the interim hero to use `<Photo slot="hero" />` . **Done when:** `npm run lint` and `npm`

`run build` pass; on `/` the hero image request goes to `ik.imagekit.io` and returns 200, checked in the network log; the `<img>` has a non-empty `alt`.

- ☒ **2. Hero and trust strip.** `components/home/Hero.tsx` : two columns at `lg`, copy left with the watermark, photo right with the Eminence badge (orchid, "Eminence Organics stockist", "Certified organic skincare, in every facial"); eyebrow, the three-line headline with copper `work`, lede from `siteConfig.description`, `Book a treatment` and `Free consultation` controls to `/contact`, and the proof row: five copper stars with `siteConfig.ratings` ("5.0 on Facebook and Google") and "Licensed since {founded}". No follower count. `components/home/TrustStrip.tsx` : four items on a surface band, borders between, two columns below `lg` : licensed since {founded} / City of Calgary registered clinic; {SERVICES.length} treatments / Face, body, skin and massage; Free consultation / {consultation.durationMin} minutes, no commitment; Free parking at the door / {address.unit}, {address.street}. Replace the interim `app/page.tsx` with these two. **Done when:** build and lint pass; `/` shows the hero photo, the badge, the proof row and four trust items; the trust strip's treatment count equals `SERVICES.length` (40, read it from the DOM); at 375px the hero stacks copy over photo and the trust strip is two columns.
- ☒ **3. Browse by concern and categories.** `components/home/Concerns.tsx` : eyebrow "Start with the concern", heading "I'm interested in treating", the prototype lede, then one pill per `CONCERNS` entry linking to `/concerns/{slug}` with the label and `getConcernCount(slug)` as the small count ("9 treatments" on the first, bare number after, as the prototype does). `components/home/Categories.tsx` on the sand tone: eyebrow "Or browse by treatment", heading "What we do", five cards linking to `categoryHref`, each with its `Photo` (3:4.2 portrait), the copper line that grows on hover, `label`, `blurb` (Facials shows "{n} treatments" from `getServicesByCategory().length` instead of its blurb, as the prototype does), and the from-price line: `getCategoryFromPrice` as "from \$X", or "Consult for pricing" when null. Five across at `lg`, two below. **Done when:** build and lint pass; the concern pills' counts match `getConcernCount` for each slug (spot-check two from the DOM); the Laser card reads "Consult for pricing" and Facials reads "from \$60"; every pill and card href is a planned route.
- ☒ **4. Signature, divider, results, Eminence.** `components/home/Signature.tsx` : photo left (4:5), copy right: eyebrow "Signature treatment", heading "Microneedling collagen induction", the lede from `getService("microneedling-face").description`, a three-row list from the three `skin` microneedling services (name, price or "Priced at consultation", duration), and a ghost button "About microneedling" to `/treatments/skin/microneedling-face`. Then `<Divider />`. `components/home/Results.tsx` : eyebrow "Real results", heading "Before and after", one card per `RESULTS` entry: the photo, `Tag`s from its concerns, the caption, and the source line. `components/home/Eminence.tsx` on sand: eyebrow "Products we trust", heading "Authorised Eminence Organics stockist", the prototype lede, a `Shop the range` link only if the stockist URL check finds one (see Data / contracts), and the three-photo grid (one 2:1 across the top, two squares). **Done when:** build and lint pass; the signature list prints \$290, \$350 and "Priced at consultation" read from data, not typed; the results section renders exactly `RESULTS.length` cards; the Eminence photos load from ImageKit.

- 5. **Reviews, consultation, hours and location.** Check: try to read her Google Business Profile reviews in the browser (search "Face and Body Wellness Centre Calgary" on Google Maps). Record any full quote with its source URL and reviewer initial in `data/reviews.ts`. If none are readable, leave `REVIEWS` empty; never type a quote from the prototype, those were placeholders. (Result: three full reviews were readable; verbatim sentence excerpts are in the data. Per-review stars are not printed because their star counts were not readable as text.) `components/home/Reviews.tsx` on the dark tone: eyebrow "Client love", heading "What clients say" (the prototype's "Five stars, every review" is untrue at 4.7), the quote cards only when `REVIEWS.length > 0`, and always the source strip built from `siteConfig.ratings` ("5.0 Google", "5.0 Facebook") plus "Client Love highlights on Instagram" linking to `social.instagram`. `components/home/Consultation.tsx`: photo left (5:4), eyebrow "Not sure where to start", heading "Book a free consultation", the three prototype bullets with the duration read from `siteConfig.consultation`, primary button "Book a consultation" to `/contact`. `lib/hours.ts` exports `formatHours(entry: DayHours): string` returning `Closed` or `4:00 - 8:00 p.m.` style text (a.m./p.m. once per side, "12:00 p.m." for noon). `components/home/Location.tsx`: eyebrow "Find us", heading "Midnapore, Calgary SE", address from `siteConfig`, a seven-row table from `siteConfig.hours` through `formatHours`, ghost buttons `Call {display} (tel:)` and `Text us (sms:)`, and the room photo right. Assemble `app/page.tsx` in prototype order. **Done when:** build and lint pass; the hours table has seven rows in Monday-first order with Sunday reading "Closed" and Monday "4:00 - 8:00 p.m."; the reviews section shows the source strip and either real quote cards or none; the call and text hrefs equal `siteConfig.phone` values; no string on the page comes from the prototype's placeholder reviews, offers or follower count.
- 6. **Responsive and theme pass.** Walk the page at 375, 768 and 1280 in light and dark. Fix stacking, overflow and contrast only. Confirm every image has `alt`, the page has one `h1`, section headings are `h2`, and the console is clean. **Done when:** no horizontal scroll at 375; no console errors; `document.querySelector("h1").length === 1`; every `img` has a non-empty `alt`; screenshots at the three widths in both themes recorded in the handoff.

Files / areas

| Path | Action | Note | |---|---|---| | `components/media/Photo.tsx` | new | the ImageKit wrapper; every later image uses it | | `data/images.ts` | new | slot manifest | | `data/reviews.ts`, `types/reviews.ts` | new | real quotes only, may be empty | | `data/results.ts` | new | one entry | | `data/siteConfig.ts` | extend | `founded`, `ratings`, `consultation` | | `lib/hours.ts` | new | `formatHours` | | `components/layout/Tag.tsx` | new | pill tag | | `components/home/Hero.tsx`, `TrustStrip.tsx`, `Concerns.tsx`, `Categories.tsx`, `Signature.tsx`, `Results.tsx`, `Eminence.tsx`, `Reviews.tsx`, `Consultation.tsx`, `Location.tsx` | new | one server component per section | | `app/page.tsx` | rewrite | assembles the ten | | `.env.local` | Frank creates | `NEXT_PUBLIC_IMAGEKIT_URL_ENDPOINT`, never committed | | `blueprint/reference/business.md` | append | the stockist URL if found, the source of any review quote |

Data / contracts

Photo and the manifest

```
// data/images.ts
export type ImageSlot = keyof typeof IMAGES;
export const IMAGES = {
  hero:      { path: "/face-and-body/hero-led.jpg",      alt: "...", source: "instagr
  catFacial: { path: "/face-and-body/cat-facial.jpg",    alt, source: "instagr
  catSkin:   { path: "/face-and-body/cat-skin.jpg",      alt, source: "instagr
  catBody:   { path: "/face-and-body/cat-body.jpg",      alt, source: "instagr
  catMassage: { path: "/face-and-body/cat-massage.jpg", alt, source: "pexels
  catLaser:  { path: "/face-and-body/cat-laser.jpg",     alt, source: "pexels,
  signature: { path: "/face-and-body/signature.jpg",     alt, source: "instagr
  resultRedness: { path: "/face-and-body/result-redness.jpg", alt, source: "instagr
  eminenceWide: { path: "/face-and-body/eminence-1.jpg", alt, source: "pexels
  eminenceA:   { path: "/face-and-body/eminence-2.jpg", alt, source: "pexels
  eminenceB:   { path: "/face-and-body/eminence-3.jpg", alt, source: "pexels
  consultation: { path: "/face-and-body/consultation.jpg", alt, source: "pexels
  room:        { path: "/face-and-body/room.jpg",        alt, source: "instagr
} as const;
```

`path` is the ImageKit path under the account's URL endpoint. `w` and `h` are the intrinsic pixel size, read from the file when uploading, so `Image` can reserve space and avoid layout shift. `alt` describes the photo, never the treatment's outcome. `source` is a comment-grade credit for the sign-off doc; stock is Pexels only (free licence, commercial use allowed), per Frank on 2026-09-18, and never a portrait that could be mistaken for her or a client result.

`Photo` props: `slot: ImageSlot`, `className?`, `sizes?`, `priority?`, `fill?`. It renders `@imagekit/next`'s `Image` with `urlEndpoint={process.env.NEXT_PUBLIC_IMAGEKIT_URL_ENDPOINT}`, `src=path`, `alt`, `width / height` unless `fill`, and `transformation` left to the component defaults (responsive `srcset` is built by the SDK). Missing env var: throw when `VERCEL=1` (a deploy without it is a mistake), placeholder box otherwise, so `npm run build` still passes before the account exists. `Image` is a client component inside the SDK; `Photo` itself stays a server component.

Assets to upload (once, to ImageKit under `/face-and-body/`)

| Slot | File | Where it comes from | |---|---|---| | hero-led | `blueprint/reference/ig/post-04.jpg` | her, LED device on a client | | cat-facial | `ig/post-03.jpg` | man mid-facial | | cat-skin | `ig/post-02.jpg` | abdomen skin texture | | cat-body | `ig/post-05.jpg` | body treatment, towels | | signature | `ig/post-`

06.jpg | body treatment, towels (second) | | result-redness | ig/post-01.jpg | her one genuine before and after | | room | ig/post-09.jpg | the treatment room | | cat-massage | Pexels 7233264 | massage, portrait crop | | cat-laser | Pexels, chosen at build | laser or IPL handpiece, no face | | eminence-1, 2, 3 | Pexels 4482931, 7440140, 21528800 | skincare product shots | | consultation | Pexels 6135650 | consultation, no identifiable face if possible |

Pexels files are downloaded at build time only with Frank's yes, sized at their original resolution, and uploaded by Frank through the ImageKit dashboard (or by a script he runs with his private key; the key never goes through Claude). Her Instagram photos are hers to publish.

siteConfig additions

```
founded: 2023,  
ratings: [{ source: "google", value: 4.7, count: 79 }, { source: "facebook", value: 5,  
consultation: { durationMin: 15, price: 0 },
```

ratings renders as "4.7 on Google, 79 reviews" in the hero (the first entry is the one quoted) and as the source strip in Reviews. Corrected during the build: the public Maps listing shows 4.7 from 79, so project-plan.md's "5.0 across every public review" is wrong and should be edited by Frank.

Review and Result

```
// types/reviews.ts  
export type Review = {  
  quote: string;  
  source: "google" | "facebook" | "instagram";  
  sourceUrl: string; // where the quote can be read  
  author: string; // first name and initial as shown publicly, e.g. "Maria K.  
  treatment: string | null;  
};  
  
// data/reviews.ts  
export const REVIEWS: readonly Review[] = []; // filled only with real quotes found  
  
// data/results.ts  
export type Result = {  
  slot: ImageSlot; // one image that already contains before and after  
  concerns: readonly ConcernSlug[];  
  caption: string; // factual, no outcome claim: "Facial redness. Before and a  
  source: string; // "instagram post-01"  
  treatment: string | null;
```

```
};  
export const RESULTS: readonly Result[] = [ { slot: "resultRedness", concerns: ["acne"
```

`treatment` stays `null` until she says which treatment the photo shows.

`formatHours`

Input `DayHours` . Output examples: `{ open: "16:00", close: "20:00" }` gives `4:00 - 8:00 p.m.` ; `{ open: "10:00", close: "13:00" }` gives `10:00 a.m. - 1:00 p.m.` ; `{ open: "12:00", close: "15:30" }` gives `12:00 - 3:30 p.m.` ; `{ closed: true }` gives `Closed` . Rule: the meridiem is written once when both ends share it, on the close time; twice when they differ. Pure string work, no `Date` . Feature 8 reuses it.

Routes linked from this page

`/concerns/{slug}` (feature 6), `/treatments/{segment}` (feature 4), `/treatments/skin/microneedling-face` (feature 5), `/contact` (feature 9), `siteConfig.social.instagram` . Nothing else. The Eminence "Shop the range" link appears only if the stockist URL is found: check `business.md` says she "has an official spa link"; look for it on the Eminence Organics spa locator during step 4 and record it in `business.md` ; if not found, no link.

Copy

Section eyebrows, headings, ledes and bullets are the prototype's, verbatim, except where a fact is now data (counts, prices, hours, phone, address, founded year, ratings, consultation length). Every string awaits her sign-off with the rest (project-plan blocker 6). No em dashes.

Testing

- No unit test runner; `formatHours` is the one piece of pure logic and is the first candidate when `/tests` is set up. Its four example cases above are the acceptance table
- Gate per step: `npm run lint` and `npm run build`
- Browser evidence on the dev server at each step's done-when: network log for ImageKit requests, DOM reads for counts and hrefs, screenshots at 375 / 768 / 1280 in both themes for step 6
- Nothing here persists data or calls an API beyond image delivery

Notes for the AI

- **Facts come from data, never typed into JSX.** Counts from `SERVICES.length` and the accessors, prices from `getCategoryFromPrice` and the services, hours through `formatHours` , phone and

address from `siteConfig` . If a number appears literally in a component, it is wrong

- **The prototype's numbers were guesses.** It says "45 treatments", "from \$150" for skin, "458 following". The data says 40, and skin's from-price is whatever `getCategoryFromPrice("skin")` returns (\$40, Thermo-Coagulation). Render the data; if it reads oddly, that is a data question for her, not a reason to type a nicer number
- **Photos are hers or Pexels.** No stock portrait of a woman as "the aesthetician", no stock before-and-after pairs of different people presented as results. The one result is her real post
- **Server components throughout.** Nothing on this page needs state; the concern filter is feature 4's. `Photo` wraps a client component from the SDK but is itself a server component
- **Section order is the prototype's:** hero, trust, concerns, categories, signature, divider, results, Eminence, reviews, consultation, location. Tones alternate as the prototype does: default, surface band, default, sand, default, sand, dark, default, default
- **Dark mode:** sand bands become `bg-secondary` , the dark reviews band stays `Section tone="dark"` (it is a brand band), photos are unchanged
- **sizes on every Photo** so the SDK's srcset does not ship a 1600px image to a 375px phone. Hero `priority`
- No em dashes anywhere, including alt text

Open questions

1. **ImageKit account and endpoint.** Blocks step 1 only. Frank creates the free account, puts `NEXT_PUBLIC_IMAGEKIT_URL_ENDPOINT=https://ik.imagekit.io/<id>` in `.env.local` and in Vercel, and uploads the thirteen files above into a `face-and-body` folder. The Pexels downloads need his yes first. 2. **Real review quotes.** None are in the repo and Yelp blocks reading. Step 5 tries Google Maps; if that fails too, the section ships with the rating strip only, and the quotes come when she or feature 14 supplies them. 3. **"Free parking at the door."** From the prototype, not from a verified source. Confirm, or the trust item becomes the plain address. 4. **What post-01 shows.** It is her one real before-and-after (facial redness). Which treatment, so the caption can name it. 5. **Four prototype sections left out** (How it works, Ways to commit, Instagram grid, FAQ). Confirm they stay out of feature 3.

Implementation walkthrough

Image pipeline (`components/media/Photo.tsx` , `data/images.ts`) - the first ImageKit wrapper and the slot manifest every later page reuses. `Photo` takes a slot name, looks up path, alt and intrinsic size, and renders the SDK's `Image` with the public URL endpoint from `NEXT_PUBLIC_IMAGEKIT_URL_ENDPOINT` . Without the endpoint it renders a labelled placeholder box, except on Vercel (`VERCEL=1`) where it throws, because a deploy without the variable is a mistake and a local build without it is just the account not existing yet. That is a deliberate softening of the spec's "throw in production": `npm run build` had to keep passing before the account was created. Her seven usable Instagram photos (480x640 at best) and

six Pexels stock shots were staged in `blueprint/reference/upload/`, which `.gitignore` now excludes, and uploaded by Frank to `/face-and-body/` in the ImageKit media library. The endpoint is `https://ik.imagekit.io/b5xayf4mq`.

Facts corrected during the build. The public Google Maps listing shows **4.7 from 79 reviews**, not the "5.0 across every public review" the project plan asserts. `siteConfig.ratings` now carries value and count per source (Google first, Facebook 5.0 from 3), the hero prints "4.7 on Google, 79 reviews", and the prototype heading "Five stars, every review" became "What clients say". Recorded in `business.md`; the project plan line is Frank's to correct. The listing also gave the owner's name, Sandra, for the About page.

Reviews (`data/reviews.ts`, `types/reviews.ts`, `components/home/Reviews.tsx`) - three full Google reviews were readable in the browser (Yelp returned 403 and `WebFetch` sees only titles on these JavaScript pages), so the cards carry verbatim sentence excerpts with the listing URL and the author shortened to first name and initial. Per-review stars are not printed because star counts were not readable as text. The section renders its rating strip regardless and the cards only when `REVIEWS` has entries.

Sections (`components/home/*`) - ten server components in prototype order, assembled in `app/page.tsx`. Every number is a data read: `SERVICES.length` for "40 treatments" (the prototype said 45), `getConcernCount` for the pills, `getCategoryFromPrice` for the cards (Laser prints "Consult for pricing" because its from-price is `null`; Skin prints "from \$40", which is Thermo-Coagulation and a data question rather than a reason to type a nicer number), `getService` for the three microneedling rows, `formatHours` for the seven-row table. The "3 sessions" badge, the follower count and the four prototype sections without plan backing (how it works, offers, Instagram grid, FAQ) were left out.

Results (`data/results.ts`) - one entry, her only genuine before-and-after, with a factual caption and `treatment: null` until she names it. No stock pairs presented as results.

Hours (`lib/hours.ts`) - `formatHours` is pure string work: the meridiem is written once when both ends share it ("4:00 - 8:00 p.m."), twice when they differ ("10:00 a.m. - 1:00 p.m."). Feature 8 reuses it for open-now.

Dark mode - the responsive pass found the reviews band vanishing in dark mode (`#1c1a17` on `#1c1a17`). `Section tone="dark"` now becomes `dark-surface` in dark mode and its cards take the page colour, so the band still reads as a band. The trust strip drops to one column under 440px, the first real use of the `xsm` breakpoint.

Checks run - `npm run lint` and `npm run build (/ static)`. Browser on the dev server: one `h1`, eight `h2`s, all counts and prices read from the DOM and matched to the accessors, seven hour rows, tel and sms hrefs, three review cards, 13 `<img>`s all served from `ik.imagekit.io` with alts, no horizontal scroll at 375 / 768 / 1280, dark mode with the band fix, fresh loads with every request 200. All 13 ImageKit files return 200 with a 400px transform (hero 28 KB).