

Feature: Tenant zero ready: AgentsWeb

From build-plan: feature 10

Branch: `feature/10-tenant-zero-ready-agentsweb`

Size: light, decided 2026-10-10: settings, packaging and one small command; the rest of the feature runs as one step, reviewed once at `/complete` (`AGENTS.md` , "Each feature is heavy or light").

Status: verified 2026-10-10: every step built (10.3 and 10.4 as one); backend 887, shared 172 and booking component 76 tests pass, the frontend builds.

Goal

The agency's own business, AgentsWeb, can take real bookings through Scheduleads, and any website, in any repo, can install the booking window built in feature 9 as one shared package. When this feature is done, the agency business exists with its services, hours and questions, the package is published privately and proved to install outside this repo, and a real call is booked into AgentsWeb through that window on the laptop.

Wiring the agency site's own pages (installing the package, its Book a call card opening the window) is the agency site's own item 12, in `agency-site-app` , built in a session opened there. The first production deploy is its own item, 10b.

Decisions

Settled with Frank on 2026-10-09, while planning this feature.

1. **Every site installs the booking window as one shared package** (the library way, like `zod`), built into the site's own files when the site is built. Never a widget, an embed, an iframe or a script loaded on a visit: the only thing fetched on demand is data (free times, the booking). Rejected: a copy pasted into each site (a fix pasted into every site again) and any third-party style embed (slow, and the reason Frank wants his own). The look stays each site's: its colours, font and corners are its own `--sa-*` tokens (feature 9), and the logo, name, phone, services and questions come from the CRM while the customer books. Colours set from the CRM are Settings, feature 12 (feature 9's design review). 2. **A business is set up from a setup file, run once by a command**, until Settings (feature 12) exists. The file describes the business's services, people, hours and questions in the shape the dev seed already uses; the command writes what is missing and never changes or deletes what is there. Rejected: building part of Settings before this feature (a large piece of feature 12 pulled forward, holding the agency back). This is the build plan's "decide here" for item 10. 3. **Feature 10 ends on the laptop; the first deploy is its own item, 10b**. Railway and Vercel are provisioned but nothing has gone out for real use, and the agency site's own launch waits on texts and QuickBooks. Rejected: deploying inside this feature (a live API nobody can use yet, and Railway and real data deserve their own reviewed item). 4. **Split by repo**. This feature does everything Scheduleads owns. The agency site's item 12 does the site side, in its own repo, with its own branch, reviews and build log; its plan line "real free times behind our booking window" changes there to the shared window (decision 1). Rejected: one feature reaching across both repos from here. 5. **The package is published to GitHub Packages, privately**, under the account's scope, `@frankdmosquera/booking-component` : GitHub Packages requires the scope to be the owner's name, every repo here is already on that account, and it

keeps the package private. The standard way for a private package from a monorepo. Rejected: a git dependency (npm cannot install one folder of a repo), a tarball copied into each site (the paste way again), and the public npm registry (private code). Each site installs it with a read token from the environment; its `.npmrc` names the variable, never the token. Amended 2026-10-09 at step 10.2 (Frank): the first publish waits until a site needs to install from GitHub (the agency site's item 12, or 10b at the latest). Granting `gh` the packages permission through the device login failed twice, and the point of 10.2, that the package installs with nothing from this repo, is proved by a packed file instead. 6. **The published package carries everything it needs.** Today it reads five small helpers and the booking schema from `@scheduleads-app/shared` and its route types from `backend/app-type`, neither of which leaves this repo. The build bundles that code into the package's own JavaScript and its route types into its own declarations, using `tsgdown`, the standard bundler for a TypeScript library (a dev dependency: installed only on Frank's yes at step 10.1). Amended 2026-10-09 before 10.1: the spec first named `tsup`, whose own npm page now says it is no longer maintained and points to `tsgdown`, its successor (0.23.0, September 2026). Rejected: publishing `@scheduleads-app/shared` as well (it carries the database schema and Drizzle, which no website should install) and copying the helpers into the package by hand (two copies that drift).

In scope

- The plans: item 10 rewritten to these decisions, item 10b (the first deploy) added, the overview's lines for both and its fingerprint refreshed.
- The package renamed, bundled so it needs nothing from this repo, published privately, and proved to install and typecheck from a folder outside it.
- The setup file's schema and the command that applies it, sharing the dev seed's code for describing a business, so there is one way to bring a business to its described shape.
- AgentsWeb set up on the local database: made through the existing client setup screen, then its setup file applied.
- `WIDGET_ORIGINS` allowing the agency site's local address, so item 12 there can call the API from its dev server.

Out of scope

- Any change in `agency-site-app`, including its plan: its item 12, in a session opened there.
- Deploying anything, Railway or Vercel, and running the command against a live database: item 10b.
- Settings screens, and the owner changing anything the file set: feature 12.
- A visit (Frank going to a business in a city): the agency site's own flow; this feature books calls only.
- Text messages for AgentsWeb: it has no Twilio number, so no text settings.

Build loop

`workflow.stepReview` is `every` and `checkpointCommits` is `enabled`.

After the green light, nothing stops until the review. Each step's plan gets Frank's yes just before it is built. From that yes the step runs straight through: build, tests and checks, tick the box, the build log entry, commit and push to `feature/10-tenant-zero-ready-agentsweb`, `/audit` scoped to the step, the independent review. The planned stop is after the review, where the findings are talked through. Earlier stops only for: the agreed plan proving wrong, a line only Frank crosses (a package install, publishing the package, Railway or real data, `main`, a merge, a force push, deleting anything), or blocking findings left unfixed. Steps 10.1 and 10.2 each hold one such line, named in the step.

Build steps

- [x] **10.1 The package needs nothing from this repo.** Plans: build-plan item 10 rewritten to decisions 1 to 4 ("Tenant zero ready: AgentsWeb"), item 10b added after it ("First deploy": the API and the dashboard out on Railway and Vercel, the first-deploy checks F-176, F-179, `X-Real-IP` and `NODE_ENV=production`, the setup file applied to the live database, timed with the agency site's launch), the overview's item lines and tenants line updated and its fingerprint recomputed. Package: renamed `@frankdmosquera/booking-component` (the preview page's import follows); `tsdown` installed as its dev dependency on Frank's yes; its build bundles the shared helpers and the booking schema into `dist/` and inlines `PublicAppType`'s declarations into `dist/index.d.ts`, keeping `"use client"` at the top of the client entry; `react` and `react-dom` stay peer dependencies, `hono` and `zod` become its runtime dependencies, `@scheduleads-app/shared` and `backend` build-time only. `private` comes off, `publishConfig` names the GitHub Packages registry, version `0.1.0`. A test reads every file in `dist/` and fails on any import outside an allow-list: `react`, `react-dom`, `hono` and `zod` (and their subpaths), so a database or Drizzle type dragged in by the route types fails it too. If the route types cannot be carried without such an import, the step stops and says so before going on. Amended at build (2026-10-09): the allow-list check is the build's last step, `check-dist-imports.mjs`, not a Vitest test. A Vitest test reading files needs Node's type definitions, which this browser package does not declare; as a build step a leak can never be built, and the tests build first. It reads every built file at any depth, triple-slash references included, and checks the `"use client"` first line. The build type-checks the package with its tests first (the old `tsc` build was its only check), and `prepublishOnly` rebuilds before any publish. Shared's files are marked free of side effects for the bundle, so schemas the window never uses are left out. **Done when:** the package builds; that check passes and is shown able to fail (an import put back); the package's 76 tests pass; the frontend builds and the booking preview page still opens the window on clinic-dev; suites pass.

- [x] **10.2 Ready to publish, and installed from outside this repo.** `npm publish` of `0.1.0` to GitHub Packages, on Frank's yes at that moment (publishing; the `gh` token needs the `write:packages` scope, which Frank grants with `gh auth refresh -s write:packages` if it is missing). Then, in a throwaway folder outside both repos, on Frank's yes: an `.npmrc` pointing the scope at GitHub Packages with the token from the environment, an install of the package with React, and a TypeScript file that imports `BookingProvider`, `useBooking` and `BookNowTrigger` and the CSS path, which typechecks with no reference to this repo. The folder is deleted after. How a site installs it (the `.npmrc` line, the token as an environment variable, the CSS import, the `--sa-*` tokens, wrapping the layout in `BookingProvider`) goes into the package's `index.ts` header and the Commands in `AGENTS.md`, beside the publish command, so the agency site's session finds it. Amended at build (2026-10-09, Frank): no publish in this step. The device login that grants `gh` the packages permission failed twice, so the throwaway folder installs the package from a file made by `npm pack`, which is exactly what a publish would send. The package is linked to the private repo (`repository`), `publish.npmrc` and the publish command are ready, and a dry run of the publish lists the four files it would send. The first real publish is done when a site first needs it from GitHub. **Done when:** the publish dry run lists only the CSS, `dist/index.js`, `dist/index.d.ts` and `package.json`; the throwaway install from the packed file, its strict typecheck and a Node import pass, with output recorded; `AGENTS.md` names the publish and install commands.

- [x] **10.3 The setup file and its command, AgentsWeb set up, and a real call booked.** Amended 2026-10-10 (Frank, the feature is light): the spec's 10.3 and 10.4 are built as this one step, reviewed at `/complete` . The shared function lives in `packages/shared/client-setup/` (compiled, so the seed and the command import the same code); a dry run runs the apply and rolls it back, so it reports exactly what an apply would add. AgentsWeb asks no booking questions: the card asks only a name and an email or phone, which the window asks itself. Its notice is 0 minutes (the card sets none). Found while booking: the window always asks for an address and "What would you like done?", which a call does not need (raised with Frank). Shared: a setup file's schema (Zod) in the seed's existing business shape: the business's slug, time zone, weekly hours, horizon, questions, people, services (name, duration, buffers, description, layout, who picks, step) and who does what, each field required where the seed's is, with no defaults invented for a business. The seed's code that brings a business to its described shape moves into one function both the seed and the command call, so their rules cannot drift. The command, `npm run client:setup --workspace=@scheduleads-app/shared -- <file>` : reads and checks the file, finds the business by slug (made first by the client setup screen; a missing business is refused, never made), and prints what it would add. Nothing is written without `--apply` . It adds only what is missing, never changes or deletes an existing row, and lists every difference between the file and the database so a hand edit is seen, not overwritten. Everything is written in one transaction. It refuses any database that is not local and `*_dev` , through the same guard as the seed (`assert-local-dev-database.ts`); opening it to the live database is item 10b. **Done when:** tests on throwaway businesses show a refused file, a missing business refused, a dry run writing nothing, an apply making every row, a second apply changing nothing, a hand-changed row kept and reported, and a non-local database refused; the dev seed still builds both dev businesses; suites pass.

- [x] **10.4 Merged into 10.3 (2026-10-10).** AgentsWeb made on the local database through the existing client setup screen (`/admin/client-setup`), its owner's login and email details as that screen asks. Its setup file in the repo, with every value read from the agency site's own data and listed in this step's plan for Frank's yes: the services its Book a call card offers (a video call and a phone call), their length from the card's step, the weekdays and first and last start times, how far ahead, the time zone of Frank's current base, Frank as the one person, the business assigning him, and the questions the card asks. No text settings. The command applied. The root `.env` and `.env.example` list the agency site's local address in `WIDGET_ORIGINS` . **Done when:** the second apply reports nothing to add; the public routes answer AgentsWeb's services, questions and times in its time zone; on the booking preview page for AgentsWeb a call is booked, and the booking, the contact and the lead with its answers are in the database; a preflight from the agency site's local address is allowed and one from another is not; suites pass.

Files / areas

- `blueprint/build-plan.md` , `blueprint/context/project-overview.md` (10.1). - `packages/booking-component/package.json` , a new `tsdown.config.ts` , its `index.ts` header, a new `check-dist-imports.mjs` ; `frontend/package.json` and the booking preview page's imports (the rename). - `packages/shared/scripts/seed-dev.ts` , a new shared function for applying a business's shape, a new `packages/shared/scripts/apply-client-setup.ts` , the setup file schema under `packages/shared/zod-validation/` , a folder for setup files (`packages/shared/client-setups/`),

`packages/shared/package.json` (the script), and their tests. - `AGENTS.md` (Commands), `.env.example`.

Data / contracts

- Package: `@frankdmosquera/booking-component@0.1.0` on GitHub Packages, private. Exports unchanged from feature 9: `BookingProvider({ apiUrl, slug, children })`, `useBooking()`, `BookNowTrigger`, and `./booking-component.css`. Peer: `react`, `react-dom` 19. Its `dist/` imports only `react`, `react-dom`, `hono` and `zod`. - Setup file: a TypeScript module default-exporting one object checked by the setup schema; it holds no secret and no customer data. The business it names must already exist. - Command result: a list of rows to add and differences found, then "applied" or "dry run, nothing written"; exit code non-zero on a refused file, database or business. - `WIDGET_ORIGINS`: comma-separated origins, as the public CORS middleware reads it today.

Testing

- Package: the build's `dist/` import check (amended at 10.1), plus feature 9's 76 Vitest tests. - Shared (Vitest, local `scheduleads_dev`): the setup schema and the command's rules on throwaway businesses, removed after, refusing any non-local database. - Backend: unchanged suites rerun every step. - The install outside the repo (10.2) and the booking on the preview page (10.4) are checked by hand, with their output and screenshots in the step's log; no browser test harness exists.

Notes for the AI

- Never edit `agency-site-app` from this feature. What its session needs is written in `AGENTS.md` and the package's `index.ts` header. - The token for GitHub Packages never goes into a committed file, a log or the chat; `.npmrc` reads it from the environment. - AgentsWeb's values come from the agency site's data, read at 10.4; never invent one. Nothing in the setup file is a default for other businesses. - The seed and the command share one function; the seed keeps creating the dev logins and businesses, the command never creates a business or a login.

Open questions

None. Decisions 1 to 4 were settled with Frank on 2026-10-09; 5 and 6 are the standard way for 1 and are named here so the choice is visible.

Implementation walkthrough

Feature 10 was planned as four steps and finished as three: on 2026-10-10 Frank set the rule that each feature is heavy or light, this one was marked light, and the spec's 10.3 and 10.4 were built as one step with a single review at `/complete`.

packages/booking-component: a package any site installs (10.1, 10.2)

Renamed `@frankdmosquera/booking-component` and built with `tsdown`, which bundles the five shared helpers and the booking schema into `dist/index.js` and inlines the public route types into `dist/index.d.ts`, so a site needs nothing from this repo. `react` and `react-dom` are peers (`^19.0.0`, so Primo's 19.0.0 installs it: F-302), `hono` and `zod` its own dependencies. The build's last step, `check-dist-imports.mjs`, reads every built file, triple-slash references included, and fails on any import but `react`, `react-dom`, `hono` and `zod`, and on a missing `"use client"` first line; it is a build step rather

than a Vitest test because the package declares no Node types. The build type-checks the package with its tests first, and `prepublishOnly` rebuilds before any publish. The package is linked to the private repo, `publish.npmrc` and the publish command are in `AGENTS.md`, and a dry run lists exactly the CSS, the two `dist/` files and `package.json`. The first real publish waits until a site needs it from GitHub (decision 5, amended): the `gh` device login for the packages scope failed twice. Instead a throwaway folder outside both repos installed the `npm pack` file, type-checked strictly and imported it in Node. The install note names a classic token with `read:packages`, the only kind GitHub's npm registry accepts (F-303).

packages/shared: a business from its setup file (10.3)

`client-setup-validation-schema.ts` describes a business the way the seed already did: who picks the person, questions, the business's hours (reusing the business hours schema, with `resourceId` added before parsing), people and places, services and who does what. It is strict, so an unknown field is refused, and nothing in it has a default for a business.

`client-setup/apply-business-shape.ts` is the one function that brings a business to that shape, moved out of the seed: questions only when the business has none, its hours row only when missing, each person or place by name, their own hours, standby dates and worker texts only when missing, each service by slug, and only the missing who-does-what ticks. It never updates or deletes a row. It lives in a compiled folder (`./client-setup` export) so the seed and the command import the same built code.

`client-setup/run-client-setup.ts` finds the business by slug and refuses one that does not exist: a business and its owner's login only ever come from `/admin/client-setup`. It reads the differences first (business hours, questions, each service's fields, each person's kind), compared as JSON with sorted keys because Postgres stores jsonb keys in its own order, then applies the shape inside one transaction. A dry run is the same apply rolled back, so it reports exactly what an apply would add. `scripts/apply-client-setup.ts` is the command: it refuses any database but a local `*_dev` one through `assertLocalDevDatabase`, loads the file, parses it, prints what it adds and every difference kept, and writes only with `--apply`.

The seed keeps its own work (the dev logins, businesses, email and text details, pipeline stages, the first person's login link) and its catch-ups for databases seeded before a setting existed (holiday picks, who picks the person), and calls the shared function for the rest.

AgentsWeb set up and a call booked (10.3)

AgentsWeb was made on `/admin/client-setup` with test addresses on the dev database, then `client-setups/agentsweb.ts` was applied: a video call and a phone call of 30 minutes, every 30 minutes, Monday to Friday 8:00 to 18:00 (last start 17:30), 21 days ahead, America/Bogota, the business assigning its one person. Every value comes from the agency site's Book a call card and its base. It asks no questions, because the card asks only a name and an email or phone, which the window asks itself, and its notice is 0 minutes, because the card sets none. `WIDGET_ORIGINS` lists the agency site's dev server, `http://localhost:3000`.

Settled after the steps

- Booking a call showed the window always asks for an address (required) and "What would you like done?", for every business. A call needs neither. Taken out of feature 10 as its own fix, next: about 25 files

read the booking's address, emails, calendar events and worker texts among them. - The rule that sizes the process (heavy or light per feature) was written into `AGENTS.md`, the workflow skills and the build log guide here, and into the workspace and other projects' instructions.

Findings

10/F-298 [P3] closed - The package carries every shared validation schema into each site, not only the booking form's

File: packages/booking-component/booking-window/booking-form/read-booking-form.ts:5; packages/shared/zod-validation/index.ts; packages/shared/package.json **Found:** 2026-10-09 by independent review of step 10.1 (scope: c786f7e..17264c3; lenses: quality, security, performance, tests) **Why it matters:** read-booking-form.ts imports `createBookingValidationSchema` from the `@scheduleads-app/shared/zod-validation` barrel, and shared's package.json has no `"sideEffects": false`, so tsdown keeps every module the barrel re-exports with its top-level `z.object(...)` calls. The built dist/index.js (lines 314 to 516, about 11 kB of its 57 kB) holds the sign-in code schema, the client setup schema, the Resend key format, the email sending schema, the availability rule schemas and the text settings schema; the booking form needs only the create-booking, contact, booking-link-id and textable phone pieces (about 3 kB). The package's own package.json has no `sideEffects` either, so a site's bundler cannot drop them: every visitor of every client site downloads and runs about 8 kB of admin and dashboard validation it never uses. Nothing secret is in it (validation rules and messages), so this is size and tidiness, not exposure. **Suggested fix:** Mark `packages/shared` side-effect free (`"sideEffects": false` in its package.json, after checking none of its modules relies on an import for its effect), or import the create-booking schema through a narrow subpath. Then confirm `emailSendingKeyValidationSchema` and the text settings schema are gone from dist/index.js and the 76 tests still pass. **Resolution:** Fixed 2026-10-09 in 10.1's review fixes: tsdown.config.ts marks the shared package's built files free of side effects for the bundle (`treeshake.moduleSideEffects`, matching both slash kinds, since a first try during the build matched only `/` and changed nothing on Windows). dist/index.js went from 56.98 kB (13.49 kB gzipped) to 48.55 kB (11.18 kB); the shared regions left are tel-href, the email-address, contact, booking-link-id and create-booking schemas, textable-phone-number, local-date and add-days, each used by the window. On the preview page, Book on an empty form still shows each field's own error with the focus on Name. Closed 2026-10-09 by re-review of 10.1's fixes (scope: e9e21d0..7cad72a): the rebuilt dist/index.js is 48.55 kB (11.18 kB gzipped) and its only shared regions are tel-href, email-address, contact, booking-link-id, textable-phone-number, create-booking, local-date and add-days; no sign-in code, client setup, sending key, text settings or weekly hours schema is left. No shared source module has a top-level statement other than a declaration, and none calls `.meta`, `.register` or `z.config`, so marking shared's files side-effect free drops nothing the window needs; the bundle loads in Node (exports `BookNowTrigger`, `BookingProvider`, `useBooking`), the 76 tests pass and the frontend builds against it. The regex matches the resolved Windows path, as the drop in size shows.

10/F-299 [P3] closed - The allow-list became a build check, but the spec and tsdown.config.ts still name a test

File: packages/booking-component/tsdown.config.ts:4; blueprint/context/current-feature.md:7, 131-137, 205, 232 **Found:** 2026-10-09 by independent review of step 10.1 (scope: c786f7e..17264c3; lenses: quality, security, performance, tests) **Why it matters:** Step 10.1 and Testing say "a test reads every file in dist/" and "Package (Vitest): the new dist/ import allow-list test, plus feature 9's 76", and Files / areas lists "a new test over dist/". What was built is `check-dist-imports.mjs`, the last command of the package's build (which `pretest` runs, so `npm test` still enforces it); the suite is 76 tests, not 77. The spec was not amended to say so, and tsdown.config.ts:4 points the reader to `dist-imports.test.ts`, a file that does not exist. The spec's Status line also still reads "step 10.1's plan with him next" while 10.1 is ticked. A later reader looking for the test, or counting 77, is sent the wrong way. **Suggested fix:** Amend step 10.1, Testing and Files / areas to the build check (and why it is a build step rather than a Vitest test), update the Status line, and change the comment in tsdown.config.ts to name `check-dist-imports.mjs`. **Resolution:** Fixed 2026-10-09: the spec records the change at 10.1 (the check is the build's last step; why a Vitest test would have needed Node's types; the type check and prepublishOnly), its Done when says "that check", Files / areas and Testing name check-dist-imports.mjs, and the Status line says 10.1 is built and reviewed. tsdown.config.ts's header now names check-dist-imports.mjs. The package's suite stays 76; the build log already marks the piece "changed" with the reason. Closed 2026-10-09 by re-review of 10.1's fixes (scope: e9e21d0..7cad72a): step 10.1 carries an accurate amendment (the build's last step, why not Vitest: tsconfig.json has types [] and includes the tests, pretest builds first, the use client check, prepublishOnly, the side-effect marking), Done when says that check, Files / areas and Testing name check-dist-imports.mjs, the Status line says built and reviewed, and tsdown.config.ts names check-dist-imports.mjs; no reference to dist-imports.test.ts or a 77th test remains.

10/F-300 [P3] closed - The dist import check reads only top-level .js and .d.ts files and skips triple-slash type references

File: packages/booking-component/check-dist-imports.mjs:11-20 **Found:** 2026-10-09 by independent review of step 10.1 (scope: c786f7e..17264c3; lenses: quality, security, performance, tests) **Why it matters:** The check uses a non-recursive `readdirSync(dist)` filtered by `/\.(js|d\.ts)$/`, and its patterns have no form for `/// <reference types="..." />`. Run on a copy outside the repo, each of these passed while carrying a forbidden import: `import "drizzle-orm" in dist/sub/a.js`, the same in `dist/chunk.mjs`, and `/// <reference types="node" />` in `index.d.ts`. Every other form tried failed as it should (`export ... from`, minified `export from "x"`, a side effect import, default plus namespace import, a type `import("x")`, a lookalike name such as `reactx`, a single-quoted directive). Today's output is two top-level files with none of these, so nothing slips through now. A switch to `.mjs` alone (tsdown's default when `platform` is `node`) would fail loudly, since `index.js` would be missing; the silent gaps are a nested output file (an `unbundle` build or a nested entry) and a triple-slash reference, which the check exists to catch. **Suggested fix:** Walk dist/ recursively, match `\.(c|m)?js$` and `\.d\. (c|m)?ts$`, and add a pattern for `/// <reference types="...">`. Relative specifiers (a split chunk importing `./x.js`) are reported as problems today; allow those explicitly if code splitting is ever turned on. **Resolution:** Fixed 2026-10-09: check-dist-imports.mjs reads every file under dist/ at any depth (`readdirSync recursive`) ending in `.js`, `.mjs`, `.cjs`, `.d.ts`, `.d.mts` or `.d.cts`, and also reads `/// <reference types|path=...>`. Shown with the reviewer's three cases planted in dist/: `sub/a.js` importing `@scheduleads-app/shared`, `chunk.mjs` re-exporting `drizzle-orm` and `extra.d.ts` referencing `node`

each failed (exit 1, all three named); removed, the check passed with the real 2 files. Closed 2026-10-09 by re-review of 10.1's fixes (scope: e9e21d0..7cad72a): on a copy of the real dist/ outside the repo the check passed clean (2 files), then failed with exit 1 naming all four planted files: sub/deeper/a.js (drizzle-orm), sub/b.cjs (export from shared, minified), sub/c.d.mts (reference types node) and d.mjs (require pg). Recursive readdirSync returns backslash-separated paths on Windows and join and the extension filter handle them (Node 26.7.0).

10/F-301 [P3] closed - Nothing builds the package before a publish, so npm publish ships whatever dist/ is on disk

File: packages/booking-component/package.json:19-24 **Found:** 2026-10-09 by independent review of step 10.1 (scope: c786f7e..17264c3; lenses: quality, security, performance, tests) **Why it matters:** The package now has `publishConfig` and `files: ["dist", "booking-component.css"]`, but no `prepublishOnly` or `prepack` script. `dist/` is gitignored, so `npm publish` (step 10.2) packs whatever the last build on that machine left, without the type check or the dist import check; `npm pack --dry-run` here packed the existing `dist/` with no build run. A build left from another branch, or a `dist/` edited by hand, would be published and installed by every site. **Suggested fix:** Add `"prepublishOnly": "npm run build"`, so a publish always rebuilds from the checked-out source and runs `check-dist-imports.mjs` first. **Resolution:** Fixed 2026-10-09: the package's scripts gain `"prepublishOnly": "npm run build"`, so `npm publish` runs prebuild (shared, the backend's types), the type check, tsdown and the import check before anything is sent; a failing check stops the publish. Closed 2026-10-09 by re-review of 10.1's fixes (scope: e9e21d0..7cad72a): `npm run prepublishOnly`, both through `--workspace` from the root and from inside the package folder, ran prebuild (shared, the backend's build:types), the tsc type check, tsdown and `check-dist-imports.mjs`, exit 0; no `.npmrc` sets ignore-scripts.

10/F-302 [P2] closed - The install note says React 19, but the package refuses any React below 19.2.8, which is what Primo Painters runs

File: packages/booking-component/package.json:33-36 (and index.ts:11, AGENTS.md install line) **Found:** 2026-10-09 by independent review of step 10.2 (scope: 8db88e6..bd39c2c; lenses: quality, security, performance, tests) **Why it matters:** 10.2 documents the install as needing "react and react-dom 19", but the peer range is `^19.2.8`. The built `dist/index.js` imports only `createContext`, `useCallback`, `useContext`, `useEffect`, `useId`, `useMemo`, `useRef`, `useState` and the JSX runtime, nothing newer than React 18. `primo-painters/package.json` pins `react` and `react-dom` to `19.0.0`; installing the packed `0.1.0` into a throwaway folder with those two versions fails with `npm error code ERESOLVE ... peer react@"^19.2.8" from @frankdmosquera/booking-component@0.1.0`. A tenant named in the plan cannot install it as documented without upgrading React or using `--legacy-peer-deps`. `agency-site-app`, `face-and-body` and `the-latam-painters` are on 19.2.8 and are unaffected. **Suggested fix:** Before the first publish, widen the peers to `^19.0.0` (what the code actually needs), or keep `^19.2.8` and make the `index.ts` header and `AGENTS.md` say React 19.2.8 or later. **Resolution:** Fixed 2026-10-09 in 10.2 review fixes: the peer range is `react` and `react-dom ^19.0.0`, so Primo Painters (react 19.0.0) can install it; the package 76 tests and the build check pass. Closed 2026-10-10 by independent review of feature 10 (scope: current, c786f7e..d9e4709; lenses: quality, security, performance, tests): `packages/booking-component/package.json` and the lockfile hold `react` and `react-dom ^19.0.0`, and the

rebuilt dist/index.js imports only createContext, useCallback, useContext, useEffect, useId, useMemo, useRef, useState and react/jsx-runtime, all in React 19.0; index.ts and AGENTS.md say React 19, which now matches.

10/F-303 [P3] closed - The install note says any GitHub token that can read packages, but GitHub Packages npm accepts only a classic token

File: packages/booking-component/index.ts:9-10 (and AGENTS.md install line) **Found:** 2026-10-09 by independent review of step 10.2 (scope: 8db88e6..bd39c2c; lenses: quality, security, performance, tests)

Why it matters: The header says NODE_AUTH_TOKEN is "a GitHub token that can read packages", set in the shell and in Vercel. GitHub's npm registry page states "GitHub Packages only supports authentication using a personal access token (classic)." A fine-grained token, the kind GitHub now offers first, would fail the site's install on Vercel with an auth error at the agency site's item 12, with nothing in the note pointing at the cause. Locally the `gh auth token` OAuth token works, so the gap only shows on the host.

Suggested fix: Say "a classic personal access token with `read:packages`" for the host's build settings in both places. **Resolution:** Fixed 2026-10-09: the package index.ts header and AGENTS.md now say a personal access token (classic) with `read:packages`, the only kind the GitHub npm registry takes. Closed 2026-10-10 by independent review of feature 10 (scope: current, c786f7e..d9e4709; lenses: quality, security, performance, tests): packages/booking-component/index.ts:9-10 and AGENTS.md:562 both name a personal access token (classic) with `read:packages`; the change is comments and docs only.

Independent review

Status: passed **Target commit:** d9e4709fb476ae02b7d303e59527ad93601cc0f2 **Base commit:** c786f7ec8290b31984cc12a8a7f3b3ed24daab57 **Base ref:** main **Spec hash:** 916ad6e5b89d3c5b9593ee3e4ce58116333544917f10d92f239216d88fd06a3c **Prepared by:** claude **Builder model:** claude-opus-5-5 **Requested reviewer:** claude **Requested model:** runtime default (exact model not known until reviewer starts) **Requested execution:** automatic **Requested at:** 2026-10-10T04:14:19Z **Workflow:** regular **Check required:** no **Reviewer adapter:** claude **Reviewer model:** claude-opus-5-5 **Reviewer context:** fresh subagent **Actual execution:** automatic **Reviewed at:** 2026-10-10T04:18:32Z **Scope:** current **Lenses:** quality, security, performance, tests **Verdict:** passed **Check result:** not-required

Handoff

Review the active spec and the complete

`c786f7ec8290b31984cc12a8a7f3b3ed24daab57..d9e4709fb476ae02b7d303e59527ad93601cc0f2` delta in a fresh session or isolated subagent without the builder conversation. Run all Audit lenses from scratch. Run Check when required above. Do not edit product code, accept findings, or reuse the existing findings as the review scope.

Commands

- `npm run test --workspace=@frankdmosquera/booking-component` (prebuild, tsc type check with tests, tsdown, check-dist-imports.mjs, then Vitest): pass, 76 tests; check reports dist/ imports only react, react-dom, hono, zod (2 files) - `npm run test --workspace=@scheduleads-app/shared` : pass, 172 tests (includes run-client-setup.test.ts against local scheduleads_dev) - `npm run test --`

`workspace=backend` : pass, 887 tests in 78 files - `npm run build --workspace=frontend` : pass - `tsc -p packages/shared/tsconfig.json` (editor view, incl. scripts, client-setups and tests): fail, six errors, all in `client-setup/run-client-setup.test.ts` (F-305, F-306); `seed-dev.ts`, `apply-client-setup.ts` and `agentsweb.ts` are clean - Type probe outside the repo against `packages/shared/dist`:

`ClientSetupInputType["hours"]` accepts any value; a wrong `personChoice` is refused (F-305)

Evidence

- Freshness: HEAD d9e4709 equals Target commit; merge-base of main and HEAD is c786f7e; current-feature.md SHA-256 matches; only review.md modified and the untracked personal ai-voice-proposal.md, which is outside the code scope. - Setup command: `runClientSetup` refuses a missing business without making one, runs `findDifferences` before `applyBusinessShape` inside one transaction and rolls the dry run back by throwing; `apply-client-setup.ts` calls `assertLocalDevDatabase` before it loads the file or opens a connection. Tests cover a refused file, a missing business, a dry run writing nothing, an apply, a second apply adding nothing, and a hand-changed hours and service row kept and reported. - Seed refactor: questions, hours, people, standby dates, worker texts, services and ticks now go through `applyBusinessShape` with the same only-if-missing rules; the holiday catch-up and the `personChoice` catch-up still read their rows before the shape is applied. One widening: the `personChoice` catch-up now updates every service of the business rather than only the seed-described ones, under the same all-still-business_assigns condition, which matches its own comment (decided for the whole business). - AgentsWeb setup file: weekdays 1 to 5, 8:00 to 18:00 at a 30-minute step (last start 17:30), 21 days ahead and America/Bogota match `agency-site-app/data/contactData.ts` `contactBookingData` and `siteConfig` base colombia. - Package: `dist/index.d.ts` exposes only `BookingProvider`, `useBooking`, `BookNowTrigger` and their prop types (no route types to inline); `dist/index.js` starts with "use client" and imports only `react`, `react/jsx-runtime`, `hono/client` and `zod`; files limits the publish to dist and the CSS; `publish.npmrc` and the install note read the token from `NODE_AUTH_TOKEN`, no secret in a committed file. - F-302 and F-303 re-examined and closed (peer range ^19.0.0 with only React 19.0 APIs used; classic token named in `index.ts` and `AGENTS.md`).

Findings

- F-304 [P2] open: the setup command does not list differences in a person's own hours, worker-text settings or hand-added ticks - F-305 [P3] open: a setup file's hours are typed unknown, so the editor checks nothing in them - F-306 [P3] open: `run-client-setup.test.ts` fails the shared package's editor typecheck with six errors - F-302 and F-303 moved from fixed to closed

Remaining risk

- `npm run db:seed --workspace=@scheduleads-app/shared` was not run (it writes the dev database); the seed refactor was reviewed by reading and by its typecheck only, and the builder's claim that it still builds both dev businesses was not re-proved here. - `npm run client:setup` itself was not run; its guard call is covered by the existing `assert-local-dev-database` tests, not by a test of the command. - The package install from outside the repo (10.2) and the AgentsWeb booking on the preview page (10.4) were not repeated; Check was not required. - Nothing typechecks `packages/shared`'s tests or scripts in a command, so F-306-style errors can recur unseen.