

Plots_and_analysis

April 29, 2019

1 1. Chris's original plot

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
import matplotlib as mpl
import pandas
mpl.rcParams['figure.dpi'] = 300

chris_table = np.loadtxt('output_chris.txt', skiprows=0)
#print chris_table

#set the upper and lower bound for reading table
lower_bound = 800
upper_bound = 1524

In [2]: j = chris_table[lower_bound:upper_bound,0]
j5DNHI = chris_table [lower_bound:upper_bound,1]
y1H = chris_table[lower_bound:upper_bound,2]
y1He = chris_table[lower_bound:upper_bound,3]
EH = chris_table[lower_bound:upper_bound,4]
Te = chris_table[lower_bound:upper_bound,5]

j5DNHI = j5DNHI/1e+18
Te = Te/10000

In [3]: fig, ax1 = plt.subplots()

#get the plot
list1, = ax1.plot(j5DNHI, Te, 'b-', label='Temperature')
ax1.set_xlabel("$\mathregular{N_H[10^{18}cm^{-2}]}$")
ax1.set_ylabel("$\mathregular{Temperature[10^4K]}$")
plt.grid(linestyle = '--')

#align ticks
major_tickx = np.arange(22, 39, 2)
major_ticky = np.arange(0, 3.2, 0.4)
ax1.set_xticks(major_tickx)
```

```

ax1.set_yticks(major_ticky)

#twinx to create multiple y axis
ax2 = ax1.twinx()
list2, = ax2.plot(j5DNHI, y1H, 'r-', label='H neutral frac')
ax2.set_ylabel("Neutral fraction")
minor_ticky = np.arange(0, 1.6, 0.2)
ax2.set_yticks(minor_ticky)

ax3 = ax1.twinx()
list3, = ax3.plot(j5DNHI, y1He, 'g-', label = 'He neutral frac')
ax3.set_yticks(minor_ticky)


# #add top tick
# ax4 = ax3.twinx()
# ax4.plot(j5DNHI, y1He)
# ax4.set_xticks(major_tickx)
# ax4.set_yticks(minor_ticky)
# ax4.cla()

#change tick direction
axs = [ax1, ax2, ax3]
for ax in axs:
    ax.tick_params(direction = 'in')

#add legend
lists = [list1, list2, list3]
ax1.legend(lists, [list.get_label() for list in lists], loc='upper right')

fig.tight_layout()
plt.savefig("chris.pdf")
plt.show()

```



2 2. NaN bug

2.1 The NaN bug comes from negative temperature when subtracting a temperature constant.

3 dEH inconsistent issue

3.0.1 For dEH[3], we track the difference between the one with cooling function and the one without.

```
In [4]: dEH3_cool_file = '../output/grid3/020419_5/2y_0_dEH50_dEHgrid3.txt'
        dEH3_cool = np.genfromtxt(dEH3_cool_file, dtype = 'f16', skip_header = 1, usecols = (2,
        print(dEH3_cool)

        dEH3_no_cool_file = '../output/grid3/020419_6/2y_0_dEH50_dEHgrid3_no_cool.txt'
        dEH3_no_cool = np.genfromtxt(dEH3_no_cool_file, dtype = 'f16', skip_header=1, usecols=
        print(dEH3_no_cool)

[6.57527062e-19 6.54969356e-19 6.52411180e-19 ... 5.57753988e-34
 5.56287144e-34 5.54824158e-34]
[6.57527062e-19 6.54969356e-19 6.52411180e-19 ... 5.57753988e-34
 5.56287144e-34 5.54824158e-34]
```


3.0.2 For dEH[1245], we track the difference between the one with cooling function and the one without.

```
In [5]: dEH1245_cool_file = '../output/grid1245/020419_1/2y_0_dEH50_dEHgrid1245.txt'
dEH1245_cool = np.genfromtxt(dEH1245_cool_file, dtype = 'f16', skip_header = 1, usecols=(0,1))
print(dEH1245_cool)

dEH1245_no_cool_file = '../output/grid1245/020419_2/2y_0_dEH50_dEHgrid1245_no_cool.txt'
dEH1245_no_cool = np.genfromtxt(dEH1245_no_cool_file, dtype = 'f16', skip_header=1, usecols=(0,1))
print(dEH1245_no_cool)

[1.36621218e-25  1.36715173e-25  1.36809211e-25 ...  8.43112538e-21
 8.44738860e-21  8.46368973e-21]
[1.36621218e-25  1.36715173e-25  1.36809211e-25 ...  8.43112538e-21
 8.44738860e-21  8.46368973e-21]
```

```
In [6]: #dEH1245_cool = [x - 1e-38 for x in dEH1245_cool]
fig_cool, ax_cool = plt.subplots()
ax_cool.set_yscale('log')
ax_cool.set_xscale('log')
list_dEH3, = ax_cool.plot(dEH3_no_cool[0:] - dEH3_cool[0:], 'b-', label='$\Delta$ dEH3_{cool}')
list_dEH1245 = ax_cool.plot(dEH1245_no_cool[0:] - dEH1245_cool[0:], 'r-', label='$\Delta$ dEH1245_{cool}')
ax_cool.set_xlabel("Time step")
ax_cool.set_ylabel("$\Delta$ dEH")
ax_cool.legend(["$\Delta$ dEH3_{cool}", "$\Delta$ dEH1245_{cool}"])
plt.grid(linestyle = '--')
plt.show()
```




3.0.3 Cooling function comparison for all grids at time step 12000

```
In [7]: Te_cool = np.genfromtxt(dEH3_cool_file, dtype = 'f16', skip_header = 12008, usecols =
      Te_no_cool = np.genfromtxt(dEH3_no_cool_file, dtype = 'f16', skip_header = 12008, usecols =
      NH = chris_table[:, 1]/1e+18
      print(Te_cool[:20])
      print(Te_no_cool[:20])
      print(NH[:20])
```

```
[14467.4 14676.9 14881.1 15080.   15273.5 15461.5 15643.9 15820.7 15991.9
 16157.4 16317.5 16472.   16621.1 16764.9 16903.5 17036.9 17165.3 17288.9
 17407.8 17522. ]
[14497.2 14711.9 14922.1 15127.7 15328.4 15524.3 15715.4 15901.5 16082.7
 16258.9 16430.3 16596.8 16758.4 16915.3 17067.6 17215.2 17358.3 17497.
 17631.3 17761.4]
[0.0125 0.0375 0.0625 0.0875 0.1125 0.1375 0.1625 0.1875 0.2125 0.2375
 0.2625 0.2875 0.3125 0.3375 0.3625 0.3875 0.4125 0.4375 0.4625 0.4875]
```

```
In [8]: fig_cool_Te, ax_cool_Te = plt.subplots()
      ax_cool_Te.set_yscale('linear')
      ax_cool_Te.plot(NH[:, abs(Te_cool[:] - Te_no_cool[:])], 'b-')
      ax_cool_Te.set_xlabel("$\mathregular{N_H[10^{18}cm^{-2}]}$")
      ax_cool_Te.set_ylabel("$\Delta Te\mathregular{[10^4K]}$")
      plt.grid(linestyle = '--')
      plt.show()
```



4 3. Plot tauHIIe

4.1 At timestep 12000

```
In [9]: dEH_cool = np.genfromtxt(dEH3_cool_file, dtype = 'f16', skip_header = 12008, usecols =
tauHIIe_cool = np.genfromtxt('../output/tauHIIe/tau_1_time_12000.txt', dtype = 'f16',
print(dEH_cool[:])
print(tauHIIe_cool[:])
print(len(NH))
print(len(tauHIIe_cool))
```

```
[5.23168547e-34 5.33405851e-34 5.43954697e-34 ... 2.34918980e-24
2.33024405e-24 2.31145651e-24]
[-4.73545359e-30 -4.66637009e-30 -4.60069139e-30 ... -3.19991373e-20
-5.13054954e-20 -7.07959026e-20]
2000
2000
```

```
In [10]: fig_tauHIIe_cool, ax_tauHIIe_cool = plt.subplots()
list_tauHIIe_cool, = ax_tauHIIe_cool.plot(NH[:], abs(tauHIIe_cool[:]), 'b-', label='HII')
list_dEH_cool, = ax_tauHIIe_cool.plot(NH[1:], dEH_cool[1:], 'r-', label='d EH_no_energy')

ax_tauHIIe_cool.set_xlabel("$\mathregular{N_H[10^{18}\text{cm}^{-2}]}$")
```

```


ax_tauHIIe_cool.set_ylabel("energy_change_rate")

lists=[list_tauHIIe_cool, list_dEH_cool]
ax_tauHIIe_cool.legend(lists, [list.get_label() for list in lists], loc='lower right')

plt.grid(linestyle = '--')

ax_tauHIIe_cool.set_yscale('log')
plt.show()

```



4.2 Compare Temperature evolution when including tauHIIe

```

In [11]: Te_HIIe = np.genfromtxt('../output/tauHIIe/tau_1_time_12000.txt', dtype='f16', skip_h
        THII_HIIe = np.genfromtxt('../output/tauHIIe/tau_1_time_12000.txt', dtype='f16', skip
        print(len(Te_HIIe), len(THII_HIIe), len(NH), len(Te_cool))

```

```

(2000, 2000, 2000, 2000)

```

```

In [12]: fig_T_HIIe, ax_T_HIIe = plt.subplots()
        start_index = 800
        list_original_Te, = ax_T_HIIe.plot(NH[start_index:], Te_cool[start_index:]/1e4, 'g-', l
        list_Te, = ax_T_HIIe.plot(NH[start_index:], Te_HIIe[start_index:]/1e4, 'b-', label='Te')
        list_THII, = ax_T_HIIe.plot(NH[start_index:], THII_HIIe[start_index:]/1e4, '-r', label='

```


```

ax_T_HIIe.set_xlabel("$\mathregular{N_H[10^{18}\text{cm}^{-2}]}$")
ax_T_HIIe.set_ylabel("$\mathregular{Temperature[10^4K]}$")

lists=[list_original_Te, list_Te, list_THII]
ax_T_HIIe.legend(lists,[list.get_label() for list in lists], loc='upper right')

plt.grid(linestyle='--')
ax_T_HIIe.set_yscale('log')
plt.show()

```



5 Stiff Solver

```

In [13]: from math import *
         x=7
         for iter in range(10):
             print iter,x,x+log(x)
             x+=7-(x+log(x))

```

```

0 7 8.94591014906
1 5.05408985094 6.67428763794
2 5.37980221301 7.06245382312
3 5.31734838988 6.98832314603
4 5.32902524385 7.00219358423

```



```

5 5.32683165962 6.99958828571
6 5.32724337391 7.00007728766
7 5.32716608625 6.99998549189
8 5.32718059436 7.00000272342
9 5.32717787094 6.99999948877

```

```

In [17]: Te_exp = np.genfromtxt('../output/output_chris.txt', dtype='f16', usecols=(5))
        Te_HIIE_imp = np.genfromtxt('../output/stiff_solver/inverse_analytic2.txt', dtype='f16', usecols=(5))
        THII_HIIE_imp = np.genfromtxt('../output/stiff_solver/inverse_analytic2.txt', dtype='f16', usecols=(5))
        print(len(Te_exp), len(Te_HIIE_imp), len(THII_HIIE_imp))

```

```

(2000, 2000, 2000)

```

```


In [18]: fig_T_implicit, ax_T_implicit = plt.subplots()
        start_index = 500
        #list_original_Te, = ax_T_implicit.plot(NH[start_index:], Te_exp[start_index:]/1e4, 'g-')
        list_Te, = ax_T_implicit.plot(NH[start_index:], (Te_HIIE_imp[start_index:] - THII_HIIE_imp[start_index:])/1e4, 'g-')
        #list_THII, = ax_T_implicit.plot(NH[start_index:], THII_HIIE_imp[start_index:]/1e4, 'r-')

        ax_T_implicit.set_xlabel("$\mathregular{N_H[10^{18}\text{cm}^{-2}]}$")
        ax_T_implicit.set_ylabel("$\mathregular{\text{Temperature}[10^4\text{K}]}$")

        lists=[list_Te]
        ax_T_implicit.legend(lists, [list.get_label() for list in lists], loc='upper right')

        plt.grid(linestyle='--')
        ax_T_implicit.set_yscale('linear')
        plt.savefig("Temperature_difference.png", dpi=300, bbox_inches='tight')
        plt.show()

```




```
In [19]: fig_T_implicit_ev, ax_T_implicit_ev = plt.subplots()
start_index = 500
list_original_Te, = ax_T_implicit_ev.plot(NH[start_index:], Te_exp[start_index:]/1e4, 'g')
list_Te, = ax_T_implicit_ev.plot(NH[start_index:], (Te_HIIe_imp[start_index:])/1e4, 'b-')
list_THII, = ax_T_implicit_ev.plot(NH[start_index:], THII_HIIe_imp[start_index:]/1e4, 'r-')

ax_T_implicit_ev.set_xlabel("$\mathregular{N_H[10^{18}cm^{-2}]}$")
ax_T_implicit_ev.set_ylabel("$\mathregular{Temperature[10^4K]}$")

lists=[list_original_Te, list_Te, list_THII]
ax_T_implicit_ev.legend(lists, [list.get_label() for list in lists], loc='upper right')

plt.grid(linestyle='--')
ax_T_implicit.set_yscale('linear')

plt.savefig("Temperature_evolution.png", dpi=300, bbox_inches='tight')
plt.show()
```



In []: