Frankie
DP1-2

1.

(a)
9
15
5
11
-5

(b)

i	a[i] before	total after	a[i] after
0	2	2	2
1	2	8	8
2	5	13	13
3	8	21	21

Output: 8 21

(c) The programme will terminate because it runtime error, ~~the location of the array is memorized, not the value~~ is out of boundary

(d) Because only the value is received, not the reference. What the student managed to change is the local ones, but he/she would fail to double every value the original array will remain unchanged.

2.

(a)
```
public static int countEven(int[] data)
    int count = 0
    int[] data = {2, 6, 5, 8};
    for (int i = 0; i < a.length; i++){
     if (data[i] % 2 = 0);
     count++;
    {
{
    return count;
```

write this margi

(b)

```
import java.util.Scanner;
public class Tp;
public static void main(String[] args){
  Scanner scan1 = new Scanner(System.in);
    int[] tp = new int[8];

  System.out.println("Enter 8 temperatures: ");
  for (int i=0;i<8;i++){
        tp[i]=scanner.nextInt();

  double avg = average(tp);
  System.out.println(avg);

  for (int i=0, i<8, i++){
  if(tp[i] > avg){
      System.out.print(tp[i]+" ");
  }

  public static double average(int[] data){
    int sum = 0;
    for(int i=0;i<data.length;i++){
        sum+=data[i];
    }
    return (double) sum/data.length;
  }
```

Frankie DPI-2

write in this margin

3.(a) [Di, eve, cy]
3
Di

(b) 18

(c)
```
public static void removeBelowArrayList<Integer> nums, int limit){
    for (Integer num :nums) {
        if (num <limit){
            num.remove(num);
    }
}
```

(d)

(i) Removing one element will cause all other elements move to the left by one unit subsequently if you run the loop forward.

(ii) Primitive data does not work in Java, only objects are OK.