

Functions in Python

Part 1

Prof. Pai H. Chou
National Tsing Hua University

Outline

- Terminology
 - return values
 - calls and passing parameters
- Function as object
- Variable-length arguments
 - by position (tuple), by keywords (dictionary)
 - Unpacking arguments by `*tuple` and `**dict`

Function

- a *callable* object
 - pass parameters to it, if any
 - get a return value, or **None**

```
>>> def hello():  
...     print('hello world')  
...  
>>> res = hello()  
hello world  
>>> print(res)  
None
```

Terminology

- function name:
 - Double
- formal parameter:
 - x
- actual parameter:
 - 23 (when you call Double(23))
 - 35 (when you call Double(27-5+13) which is Double(35))
 - i.e., expressions get evaluated before being passed as params
- "argument", "parameters" are interchangeable

```
>>> def Double(x):  
...     return 2 * x  
...  
>>> Double(23)  
46  
>>> Double(27 - 5 + 13)  
70
```

Return value

- can be any type
 - can even be another function as an object!
 - can return multiple objects -- as a tuple
 - returns **None** by default if you don't do anything
- Example: prompt user for name & passwd

```
def getNamePassword():  
    userName = input('Username: ')  
    passwd = input('Password: ')  
    return userName, passwd # this is a tuple!  
    # same as (userName, passwd)
```

- caller can do unpacking assignment
 - name, passwd = getNamePassword()

Function object vs. function call

- *functionName* references function object
- *functionName()* is a function call

```
>>> getNamePassword    # this references the function object
<function getNamePassword at 0x10ca9bb70>
>>> getNamePassword() # the () makes the call
Username: Mary
Password: Little Lamb
('Mary', 'Little Lamb')
```

- Both are expressions
 - *functionName* is a "callable object" (code)
 - function call evaluates to the return value of the call

function assignment

- you can assign a function object to another name
- Be careful!! You can redefine a function name to another value!

```
>>> p = print # print is a built-in function
>>> p('hello world') # this calls the built-in print function
hello world
>>> print = getNamePassword # print is like a variable
>>> print() # this doesn't call print; calls getNamePassword()!!
Username: Mary
Password: Little Lamb
('Mary', 'Little Lamb')
>>> print('hello world') # this doesn't call the built-in print()!
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: getNamePassword() takes 0 positional arguments but 1
was given
```

two ways of passing parameters: *by position* and *by name*

- Example: built-in function `open(file, mode)`
- By position: ordering must match
 - `fh = open('myfile.txt', 'r')`
i.e., `'myfile.txt'` for name, `'r'` for mode
- By name: explicitly name the formal params
 - `fh = open(file = 'myfile.txt', mode='r')`
 - `fh = open(mode='r', file='myfile.txt')`
same thing: ordering doesn't matter!!

Why pass parameters *by name*?

- Better readability
 - "self-documenting" code
 - be more specific, say what you mean
- Less likely to make mistakes
 - some functions may have a long list of parameters
 - keywords help programmers match up actual params with formal params
- Especially useful for functions with optional parameters (i.e., with default values)

Optional Parameters with Default Values

- Example: `open(file, mode)`
 - the mode defaults to `'r'` (reading)
 - can override the default value
- Declaration:
 - assign default value to the formal parameter

```
>>> def withTax(price, rate=0.05):  
...     return price * (1 + rate)  
...  
>>> withTax(100)  
105.0  
>>> withTax(200, 0.07)  
214
```

Restrictions on ordering of optional parameters


- Optional parameters must be declared after the required parameters

- Good:



```
def withTax(price, rate=0.05):
```

- Not good



```
def withTax(rate=0.05, price):
```

- because you can't say
`withTax(, 100)` just to use the default rate



Evaluation of default parameter

- the default value is evaluated **once for all**

```
import random
def withTax(price, rate=random.randint(1,100)/100.):
    return price * (1 + rate)
```




- the default tax rate is randomly chosen **at the time the function is defined**
 - it does not generate a new random tax rate each time you call it!
- This also means default expression **cannot involve another parameter**
 - e.g., `def F(a, b=a)` is bad!



Variable-length argument list

- want to pass a variable number of arguments to a call
 - they don't necessarily have a default parameter
- example: `total()`, `max()`, `average()`, ...
 - don't want to necessarily pass a list or tuple

- example: suppose we want a function
`totalTax(0.05, 10, 20, 23, 18)`


Declaring variable-length arguments

- Put a ***** in front of the var-length argument
- They appear to the function as a **tuple**
- The caller pass them as variable-length arguments

```
def totalTax(rate, *priceArgs):  
    sum = 0  
    for i in priceArgs: # iterate over elements of tuple  
        sum = sum + i  
    return(1 + rate) * sum
```

- Call it as a flat list,
not as a tuple

```
totalTax(0.05, 10, 20, 23, 18)
```



```
totalTax(0.05, (10, 20, 23, 18))
```



passing variable-keyword arguments by name

- conceptually like a dictionary, but flatten

- example: `def totalTaxByItem(rate, priceDict):`

- if implemented as a dictionary, call it as

```
totalTaxByItem(rate=0.05, priceDict={'eggs': 10, 'soap': 20, 'bread': 25})
```

- but it is awkward to pass an inline dictionary
- want name=value style as in function calls, rather than key:value style as in dictionary

```
totalTaxByItem(rate=0.05, eggs = 10, soap = 20, bread = 25)
```

these names are chosen by the caller, not the function itself!!

Declaring variable-keyword parameter list

- Put ****** in front of the variable-keyword formal parameter


```
def totalTax(rate, **priceDict):  
    sum = 0  
    for i in priceDict.values():  
        sum = sum + i  
    return(1 + rate) * sum
```

- in this case, the caller can use its own name=value words; we don't care what words they pass
- In general, the function may need to examine the keys and give special interpretation

Combining default value, variable length, and variable keyword arguments

- Order:
 - default value first
 - followed by variable-length tuple
 - followed by variable-keyword dict
- Can check this with a simple example

```
>>> def f(a, b=3, *c, **d):  
...     print(a,b,c,d)  
>>> f(1,2,3,4,5,me=6, you=7)  
1 2 (3, 4, 5) {'me': 6, 'you': 7}
```



* Unpacking a sequence for parameters

- want to print 0 1 2 3 4 5 6 7 8 9
 - but want to use range(10) or list to generate

```
>>> L = range(10)
>>> print(range(10)) # first attempt
range(0, 10)
>>> print(list(L))
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
```

- Solution: * unpacking
 - unpacks a sequence into separate actual params

```
>>> print(*L) # effectively print(0, 1, 2, 3, 4, 5, 6, 7, 8, 9)
0 1 2 3 4 5 6 7 8 9
```

Example of unpacking parameters from sequence

- try out different #arguments to range()

```
>>> L = [(1, ), (1, 6), (1, 9, 2), (10, 0, -2)]
>>> for R in L:
...     print(list(range(*R)))
...
[0]
[1, 2, 3, 4, 5]
[1, 3, 5, 7]
[10, 8, 6, 4, 2]
```

- would not work without the *

```
>>> for R in L:
...     print(list(range(R)))
...
Traceback (most recent call last):
  File "<stdin>", line 2, in <module>
TypeError: 'tuple' object cannot be interpreted as an integer
```

Unpacking multiple sequences as parameters to a call

- OK to use several * unpacking expressions within a call
- they just get joined together as parameter list

```
>>> A = (1, 2)
>>> B = (3, 4, 5)
>>> max(A, B)      # max((1, 2), (3, 4, 5))
(3, 4, 5)
>>> max(*A, *B)    # max(1, 2, 3, 4, 5)
5
```

**** Unpacking dictionary as named parameters**

- Put ** in front of dictionary to unpack the key-value pairs as name=value parameters

```
>>> D = {'file': 'arg.py', 'mode': 'r' }  
>>> fh = open(**D)  
>>> data = fh.read()  
>>> fh.close()
```

- fh = open(**D) in this case is the same as
fh = open(file='arg.py', mode='r')

Summary

- Function definition
 - formal parameters
 - default value, variable-length, variable-keyword
 - return type
- Function invocation (call)
 - actual parameters, positional vs. named
 - unpacking sequence for positional parameter
 - unpacking dictionary for named parameters