

MATLAB

Quality plots

1




Requirements

- Produce high quality figures (e.g. for a paper)
- Fonts, line widths, etc. to be a specified size (e.g. 12pts)
- Fonts and symbols identical in figure and text
- Automate process as much as possible; figure regeneration
 - Collect additional data
 - Reuse the figure in a new publication, talk, grant etc.
 - Minor cosmetic alterations (require small amount of work)
- Reuse visualisation code

Taken from <http://www.gatsby.ucl.ac.uk/~turner/TeaTalks/matlabFigs/matlabFig.pdf>

3



5

Approach

As proposed by Turner / Rajashekar (<http://www.gatsby.ucl.ac.uk/~turner/TeaTalks/matlabFigs/matlabFig.pdf>)

Do NOT

- Modify figure properties using the mouse
- Export figures using the "export" menu function

Avoid

- Using third party graphics programs where possible

Do

- Use functions and scripts to generate plots: Reuseability
- Specify fonts, line styles, axis positions, figure sizes as variables
- Export using the print command

See also: <http://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1003833>

KU LEUVEN

6



plotting your data


- If only previewing or exploring data, steps 1 and 3 may be all you need.
- If creating presentation graphics, you may want to finetune your graph by positioning it on the page, setting line styles and colors, adding annotations, and making other such improvements.
- *File: first_plot*

1. Prepare your data	<pre>x = 0:0.2:12; y1 = bessell(1,x); y2 = bessell(2,x);</pre>
2. Select a window and position a plot region within the window	<pre>figure(1) subplot(2,2,1)</pre>
3. Call elementary plotting function	<pre>h = plot(x, y1, x, y2)</pre>
4. Select line and marker Characteristics	<pre>set(h, 'LineWidth', 2, {'LineStyle'}, ... {'--'; ':'}) set(h, {'Color'}, {'r'; 'b'})</pre>
5. Set axis limits, tick marks, and grid lines marks, and grid lines	<pre>axis([0 12 -0.5 1]) grid on</pre>
6. Annotate the graph with axis labels, legend and text	<pre>xlabel('Time') ylabel('Amplitude') legend(h, 'First', 'Second')</pre>



figure

- figure: fundamental container for plotting – a graph is created in a figure window
- separate from the Command Window
- can contain menus, toolbars, user-interface objects, context menus, axes, or any other type of graphics object.
- to create a new figure, use the **figure** function





plot command

- `plot(Y)` : plots the columns of `Y` versus their index if `Y` is a real number.
- `plot(X1, Y1, ...)` : plots all lines defined by `Xn` versus `Yn` pairs.
- `plot(X1, Y1, LineSpec, ...)` : plots all lines defined by the `Xn, Yn, LineSpec` triples, where `LineSpec` is a line specification for line type, marker symbol, and color of the plotted lines.
- `plot(..., 'PropertyName', PropertyValue, ...)` : sets properties to the specified property values for all line graphics objects created by `plot`.



plot: line specs

line specifications:

- **LineStyle:**
 - solid line (default)
 - dashed line
 - : dotted line
 - . dash-dot line
- **Marker:** Marker symbol.
+ o * x(cross) s(square) d(diamond) ^ > < p(pentagram) h(hexagram)
- **Color:**
y m g r c b (=blue) k (= black) w





plot

- File:
plot2D_simple.m
plot2D_simple_02.m
plot2D_plot_2.m

```
x=0:0.05:5;  
y=sin(x.^2);  
plot(x,y);
```

```
plot(x,y,'--rs',...  
     'LineWidth',2,...  
     'MarkerEdgeColor','k',...  
     'MarkerFaceColor','g',...  
     'MarkerSize',10)
```




KU LEUVEN

11



plot3

- `plot3` displays a three-dimensional plot of a set of data points.
- File: *plot3D_plot3_1.m*




KU LEUVEN

12



Extra information

- `xlabel`, `ylabel`, `zlabel`:
 - Label the x-, y-, and z-axis
- `title`:
 - places a title on your plot
- `legend`:
 - adds a legend to your plot
- File: *plot2D_extra*
plot2D_legend



KU LEUVEN

13



Extra information

- `text`:
 - creates a text object in current axes
- `grid on/off`
 - adds/removes grid lines
- `box on/off`
 - adds/removes axes box
- File: *plot2D_extra2.m*

KU LEUVEN

14



axes control

- `axis([xmin xmax ymin ymax])`: sets the limits for the x- and y-axis of the current axis
- `axis auto`: default behavior of computing the current axes' limits automatically,
- `axis tight`: sets the axis limits to the range of the data.
- `axis square`: square dimensions
- `axis equal`: equal unit spacing on x and y axes; ensures correct aspect ratio
- `axis off`: hides the axes, tickmarks, labels
- File: *plot2D_axis.m*




multiple graphs

- In the same axes: `hold on`
- In the same window: `subplot`
- In different windows: `figure`
- Change between windows: `figure(figure_number)`
- Clear the graphics: `clf`, `cla`
- Close a window: `close(figure_number)`, `close all`
- Files:
plot2D_multiple.m
demo_differentfont.m



subplot

- multiple plots can be set in 1 figure using `subplot`
- `subplot(m,n,p)` creates an axes in the pth pane of a figure divided into an m-by-n matrix of rectangular panes.
- *Files:*
 - `plot2D_subplot`
 - `plot2D_subplot_extra`



KU LEUVEN

18



export

- Print a figure with `print`, usually providing a better quality than `saveas`
- Check the documentation
- *File:* `demo_print_figure.m`
- Look at `exportgraphics`
 - <https://nl.mathworks.com/help/matlab/ref/exportgraphics.html>

KU LEUVEN

19



Quality prints



- Check paper Damiano Varagnolo
<http://staff.www.ltu.se/~damvar/Matlab/HowToMakePrettyFiguresWithMatlab.pdf>
- <https://dgleich.wordpress.com/2013/06/04/creating-high-quality-graphics-in-matlab-for-papers-and-presentations/>
- <http://steventhornton.ca/publication-quality-plots-with-matlab/>
- <http://blogs.mathworks.com/loren/2007/12/11/making-pretty-graphs/>
- <http://fundamentalthinking.blogspot.com/2012/01/generating-publication-quality-figures.html>

KU LEUVEN

20



Quality prints



- Check out Matlab Central
 - Oliver Woodward / Yair Altman: export_fig
https://nl.mathworks.com/matlabcentral/fileexchange/23629-export_fig
https://github.com/altmany/export_fig
 - Peder Axenstein: savefig
<https://nl.mathworks.com/matlabcentral/fileexchange/10889-savefig>

KU LEUVEN

21