

# Python

A quickstart into the key concepts of programming  
Basic syntax

## Thank You

- <https://github.com/gibex/training-material/tree/master/Python>
- *Whirlwind Tour of Python* by Jake VanderPlas (O'Reilly).  
Copyright 2016 O'Reilly Media, Inc., 978-1-491-96465-1.  
<https://www.oreilly.com/programming/free/files/a-whirlwind-tour-of-python.pdf>
- University of Virginia, Advanced Research Computing Services, Python Quickstart  
<https://arcs.virginia.edu/python-quickstart>
- <http://www.cs.cornell.edu/courses/cs1110/2018sp/>
- [https://fabienmaussion.info/scientific\\_programming/html/00-introduction.html](https://fabienmaussion.info/scientific_programming/html/00-introduction.html)

## See also

- <https://www.math.ubc.ca/~pwalls/math-python/>
- <http://troll.cs.ua.edu/ACP-PY/index.html>
- <https://data-flair.training/blogs/python-lambda-expressions/>
- <http://pages.physics.cornell.edu/~myers/teaching/ComputationalMethods/GettingStarted.html>
- <https://anh.cs.luc.edu/python/hands-on/3.1/handsonHtml/index.html>
- <https://www2.cs.duke.edu/courses/spring18/compsci101/index.php>
- <https://github.com/parrt/msan501>
- <https://docs.python-guide.org/intro/learning/>

## Key concepts in programming

- Variables (*integers, strings, dates, etc.*)
- Flow control (*if then, loop, etc.*)
- Functions (*list of steps the code will follow*)

# Python: basic syntax

basic\_syntax.ipynb

5

## Python files

- Python scripts are saved with `.py`
- Jupyter notebook files: `.ipynb`
- Naming convention
  - lowercase, with words separated by underscores as necessary to improve readability
  - [https://visualgit.readthedocs.io/en/latest/pages/naming\\_convention.html](https://visualgit.readthedocs.io/en/latest/pages/naming_convention.html)

6

## Python syntax

- *Syntax*:
  - refers to the structure of the language
  - i.e., what constitutes a correctly formed program.
- *Semantics*:
  - involve the meaning of the statements

## Comment

- Comments are marked by #
- Anything on the line following the hash sign is ignored by the interpreter
- `x += 2 # shorthand for x = x + 2`
- no syntax for multiline comments

## Statement

- A statement is one complete *sentence* in the language. It contains one complete instruction.

```
B = A
surfC = math.pi*r**2
```

## End-of-Line Terminates a Statement

```
midpoint = 5
```

- continue to the next line, it is possible to use the \ marker

```
In [2]: x = 1 + 2 + 3 + 4 + \
5 + 6 + 7 + 8
```

- Semicolon can optionally terminate a statement (discouraged)

```
lower = []; upper = []
```

## Code blocks

- Statements can be grouped into *blocks*
  - a *block* of code is a set of statements that should be treated as a unit.
  - Structures that introduce a block end with a colon :
- Blocks are indicated by **indentation level**.
- Indent each block by however many spaces you wish, but each block level must be indented by exactly the same number.
  - Do not use tabs.
  - Some editors (e.g. Spyder) will automatically indent the next statement to the same level as the one before it.

11


## Multiple Variables Assignment

- Declare multiple variables and assign values to each variable in a single statement. Assignment of values to variables must be in the same order in they declared.
- ```
>>> x, y, z = 10, 20, 30
```
- Declare different types of values to variables in a single statement, as shown below.
- ```
>>> x, y, z = 10, 'Hello', True
```

12

## Code blocks

```
from math import sqrt
my_list = [1,2,3,4]
result = 0
for i in my_list:
    if i%2 == 0:
        result += sqrt(i)
print(result)
```



<http://www.dbs.ifi.lmu.de/lehre/MaschiLernen/SS2017/Orga/U01-Slides.pdf>

## Indentation: Whitespace Matters

- In C, code blocks are denoted by curly braces:

```
// C code
for(int i=0; i<100; i++)
{
    total += i;
}
```

- In Python, code blocks are denoted by *indentation*:

```
for i in range(100):
    # indentation indicates code block
    total += i
```

- In Python, indented code blocks are always preceded by a colon (:) on the previous line.
- The Python standard is to use **four white spaces** to indent code.

## Indentation

```
>>> if x < 4:
...     y = x * 2
...     print(x)
```

- `print(x)` is in the indented block, and will be executed only if `x` is less than 4.
- File: `check_whitespace.py`

```
>>> if x < 4:
...     y = x * 2
... print(x)
```

- `print(x)` is outside the block, and will be executed regardless of the value of `x`,

## Whitespace

- *amount* of whitespace used for indenting code blocks is up to the user, as long as it is consistent throughout the script.
- Whitespace *within* lines does not matter

```
In [4]: x=1+2
        x = 1 + 2
        x   =   1   +           2
```