

# Python

A quickstart into the key concepts of programming  
Built-in atomic data types



## Key concepts in programming

- Variables (*integers, strings, dates, etc.*)
- Flow control (*if then, loop, etc.*)
- Functions (*list of steps the code will follow*)



# Built-in atomic data types

basic\_datatypes.ipynb



## Built-in types

Type	Example	Description
int	In [1]: x = 1 type(x) Out [1]: int	Integers (i.e., whole numbers)
float	x = 1.0	Floating-point numbers (i.e., real numbers)
complex	x = 1 + 2j	Complex numbers (i.e., numbers with a real and imaginary part)
bool	x = True	Boolean: True/False values
str	x = 'abc'	String: characters or text
NoneType	x = None	Special object indicating nulls



# Integer

- Most basic numerical type.
- Any number without a decimal point is an integer.
- Note: Python integers are variable-precision, not limited as in C, Matlab to 4 or 8 bytes.
- `2**200` # is possible



# Float point number

- The floating-point type can store fractional numbers.
- standard decimal notation, or in exponential notation

```
x = 0.000005
```

```
y = 5e-6
```

- Note: limited precision

```
0.1 + 0.2 == 0.3
```

```
False
```

- *Tip: never* rely on exact equality tests with floating-point values.



# Complex Numbers: j

- A complex number consists of 2 doubles:

```
complex(1, 2)
```

```
c1 = 3 + 5.3j
```

```
c1.imag
```

```
5.3
```

```
c1.real
```

```
3.0
```

```
c2 = 3.3 + a*1j
```

- It accepts either J or j but the numerical value of the imaginary part must immediately precede it. If the imaginary part is a variable as in these examples, the 1 must be present.



# Boolean

- Simple type with two possible values: True and False (capital T and F!)

```
result = (4 < 5)
```

```
result
```

```
True
```

```
type(result)
```

```
bool
```

- Booleans can be constructed using the `bool()` object constructor

```
x = ' '
```

```
y = 15
```

```
print(bool(x))
```

```
print(bool(y))
```

```
True
```

```
True
```



# Type conversions

- If a variable is of one type but it needs to be of a different type, it is necessary to do a *type conversion* aka a *cast*.

```
R=float(I)
```

```
I=int(R)
```

```
Z=complex(r1,r2)
```



# Strings

- A *string* is a (ordered) sequence of characters
- Created with single ' or double quotes "
- Many useful string functions and methods
  - Check with `dir`
- Strings are *immutable* and cannot be changed. They can only be overwritten.

```
a = 'help'
```

```
a[1] = 'a'
```

```
TypeError Traceback (most recent call last)
```

```
<ipython-input-43-294a43332c98> in <module>
```

```
1 a = 'help'
```

```
----> 2 a[1] = 'a'
```

- Operators: + and [ : ] (Concatenation and Slicing)



# Strings

- Some useful methods
- **Syntax:** `<string name>.<method name> (...)`
- `S = 'Hello String'`
- `S.upper()` : transform to upper case
- `S.index(sub)` : position of the first occurrence of sub in S
- `S.count(sub)` : number of times sub appears inside S
- `S.strip()` : Returns a copy of S with white-space removed at ends
- *File: string\_intro.py*



## character

- `ord()` takes a string argument of a single Unicode character and returns its integer Unicode code point value.

```
ord('a')
```

```
97
```

- `chr()` function takes integer argument and returns the string representing a character.

# Docstrings

- Documentation strings or “docstrings” use a special form of comment.
- The lines are enclosed in triple double quotes  
`""" """`
- Everything within triple double quotes is treated as a literal string and a comment, including line breaks.
- Docstrings are placed at the top of program units, just under the declaration of the unit name (if present).
- If they are correctly placed, certain automated tools are available to display the documentation.

# type

- If you are not sure what class a value falls into, Python has a function called `type`

```
type("Hello")
```

```
type(3.14)
```



# None

- A special type, the `NoneType`, which has only a single possible value: `None`.

```
In [24]: type(None)
```

```
Out [24]: NoneType
```

- Most commonly used as the default return value of a function.

```
In [25]: return_value = print('abc')
```

```
abc
```

```
In [26]: print(return_value)
```

```
None
```

