

Script : import.tcl Purpose : Automate design import flow:

- Load technology & user settings
- Create Milkyway library
- Read netlist and constraints
- Configure routing layers
- Run basic sanity and QoR checks

Tool : Synopsys ICC2 / Fusion Compiler style flow

Author : Franklin Moses

Read Technology Settings

```
source -e -v ./scripts/tech_setup.tcl
```

Read User Settings

```
source -e -v ./scripts/user_setup.tcl
```

Multi-CPU Setting

```
set_host_options -max_cores $max_core
```

Create MW Lib

```
if { [file exists "db/${ndm_lib_name}"] } {  
    set date [exec date +%m_%d_%H_%M_%S]  
    file rename -force db/${ndm_lib_name}  
db/${ndm_lib_name}_$date  
    puts "\nInfo : 'db/${ndm_lib_name}' exists."  
    puts "\tInfo : Renaming it to  
'db/${ndm_lib_name}_$date'\n"  
}
```

```
create_lib -technology $tech_file_path -ref_libs $ndm_libs  
db/${ndm_lib_name}
```

```
# Read the Verilog Netlist  
read_verilog $netlist_path
```

```
# Read SDC & Configure the MW Lib  
source -e -v ./scripts/tech_mw.tcl  
current_scenario func_${setup_corner}.cworst
```

```
# Assign Metal routing direction  
suppress_message ATTR-12 ; # suppressing unwanted  
warnings  
set_attribute [get_layers M1] routing_direction horizontal  
set_attribute [get_layers M2] routing_direction vertical  
set_attribute [get_layers M3] routing_direction horizontal  
set_attribute [get_layers M4] routing_direction vertical  
set_attribute [get_layers M5] routing_direction horizontal  
set_attribute [get_layers M6] routing_direction vertical  
set_attribute [get_layers M7] routing_direction horizontal  
set_attribute [get_layers M8] routing_direction vertical  
set_attribute [get_layers M9] routing_direction horizontal  
set_attribute [get_layers M10] routing_direction vertical
```

```
# Routing Layer Setting  
set_ignored_layers -min_routing_layer $min_route_layer -  
max_routing_layer $max_route_layer
```

```
# Save the Blocks
```

```
save_block -as ${design}_import_done  
save_block
```

```
# Perform Sanity Checks  
if { $do_sanity_qor_check }{
```

```
    set
```