

post_cts.tcl

Description : Post-CTS optimization script (hold / cleanup after CTS).

Tool : Synopsys ICC2 (or similar implementation tool)

#

Requirements :

- tech_setup.tcl, user_setup.tcl

- \${design}_cts_done block already created

#

Key Variables (from user_setup.tcl):

max_core - Max CPU cores

ndm_lib_name - Library name under db/

design - Top-level design name

allow_lvt_post_cts - If 0, disable LVT usage in post-CTS

clk_fanout_target - Max clock fanout

enable_ccd_post_cts - Enable CCD for post-CTS (0/1)

cts_cong_effort - (optional) congestion effort

cts_hold_fix_effort - (optional) hold fix effort

min_route_layer - Min routing layer

max_route_layer - Max routing layer

setup_uncertainty_cts - % of period used as setup uncertainty

hold_uncertainty_cts - % or factor for hold uncertainty

stop_after_post_cts - If 1, stop after post-CTS

Read Technology & User Settings

source -e -v ./scripts/tech_setup.tcl

source -e -v ./scripts/user_setup.tcl

Multi-CPU Setting

set_host_options -max_cores \$max_core

Open NDM Library and Create Post-CTS Block

if { [file exists "db/\${ndm_lib_name}"] } {

puts "\n[INFO] Library 'db/\${ndm_lib_name}' exists, opening...\n"

open_lib db/\${ndm_lib_name}

copy_block -from \${design}_cts_done -to \${design}_post_cts_done

current_block \${design}_post_cts_done

link

} else {