

ÉCOLE CENTRALE DE NANTES

MASTER CORO-IMARO
“CONTROL AND ROBOTICS”

2020 / 2021

Master Thesis - Midterm Report

Presented by

Selvakumar Hastham Sathiya Satchi Sadanandam

On 17 May 2021

**Realtime human motion imitation by humanoid robot
with balance constraint**

Supervisor(s): Dr. Sophie Sakka Assistant Professor (LS2N, ECN)

Laboratory: Laboratoire des Sciences du Numérique de Nantes LS2N

Abstract

Humanoid robots are made as mirror to the humans. Consequently, the humanoid motion is also expected to be real as human and it is natural to use human motion as an input to generate humanoid motion like a child learning from recognizing an action and imitating. This process in robots is called motion imitation and there are several challenges posed due to kinematics and dynamics of the robot over the past decades. Although the work on the kinematic challenges is actively improving and notably better than dynamics, it allows the robot only to move and imitate slow actions. For the fast paced motions, *momentum* gets build up and needs dynamics to be taken into account. Due to the differences in redundancy between humanoid robots and humans, real-time imitation in humanoid robots while keeping balance and support changes is still an interesting problem that need to be addressed.

On this research, motion retargetting or the motion imitation based on dynamic balance and support with dynamic filtering is planned to be implemented on humanoid robot *NAO v5*, from Aldebaran Robotics. The imitation will be carried out online using marker-based motion capture suit from *Xsens*, specifically *Xsens MVN Analyze* system.

The captured motion from the inertial suit will be preprocessed for its representation in operational space and will be scaled to the robot's dimensions. From this scaled motion, for this thesis, a set of actions are taken and will be addressed for the balance problem in *NAO* robot. The joint, CoM and the ZMP data of the human actor will be mapped to the robot using the scaling function directly. To ensure the stability and to keep up the speed with the human actor, an additional dynamic filter and multi-inverted pendulum based posture control will be implemented.

Notations

CoM

Centre of Mass

Abbreviations

CoM	Centre of Mass
DoF	Degrees of Freedom
ZMP	Zero Moment Point

Contents

1	Introduction	9
1.1	Service Robotics	10
1.2	Humanoid robots	11
1.3	Measuring Human Movement	13
1.4	Challenges in Motion Imitation	14
1.5	Problem Statement	15
1.6	Thesis Organisation	16
2	State of the Art	17
2.1	Approaches in Humanoid Robot Control	17
2.1.1	Motion Planning	17
2.1.2	Kinematics Approach	20
2.1.3	Dynamics Approach	24
2.1.4	Optimal Control	27
2.2	Approaches in Humanoid Balance Control	28
2.2.1	Linear Inverse Pendulum Approach	29
2.2.2	Double Inverse Pendulum Approach	30
2.2.3	Cart Table Model	32
2.2.4	Spherical Inverse Pendulum Approach	32
2.3	Approaches in Posture Control and Motion Retargetting	32
2.3.1	Mansard's work	32
2.3.2	D. Gucci's work	32
2.3.3	Kumar Munirathinam's work	32

3	Dynamics Based Whole Body Imitation	33
3.1	Dynamic Considerations	33
3.1.1	Rigid body constraints	33
3.1.2	Multi body constraints	33
3.1.3	ZMP	34
3.1.4	Dynamic Model of humanoid robot	34
3.1.5	Simplified dynamic model using LIPM	34
3.2	Control Approach	34
3.2.1	Balance Control	34
3.2.2	Posture Control	34
3.2.3	Acceleration Control	34
3.3	Task Specification Approach	34
3.3.1	Joint trajectory tracking	34
3.3.2	Balance Control	34
3.3.3	Posture Control	34
3.3.4	Joint Limits Avoidance	34
4	Implementation	35
4.1	NAO robot	35
4.1.1	NAOqi C++ SDK	35
4.1.2	CopelliaSim support	35
4.2	Xsens MVN Analyze	35
4.2.1	Sensor Setup	35
4.2.2	Xsens Networking Protocol	35
4.2.3	Network Streaming	35
	Conclusion	36
	Bibliography	36

List of Figures

1.1	Humanoid robots over decades	12
1.2	Human Locomotion using Differential Equations	14
1.3	A motion imitation performance by HRP-2 humanoid robot	15
2.1	Sampling based motion planning of NASA Valkyrie [1]	19
2.2	Simple Inverse Pendulum Model	29
2.3	Double Inverse Pendulum Model	30
3.1	A rigid-body representation of humanoid robot	33

List of Tables

Introduction

The interest of humans in building, controlling and researching complex machines that look and behave like humans is not recent; it started very early in humanity. There has always been numerous models of human-like machines over the centuries crafted by the engineers, mathematicians and craftsman that prove the existence of human-alike machines. After the development of Unimate and Shakey, the robotics has been widely boosted. Indeed, the first Industrial revolution of robotics only considered arm manipulators and wheeled platforms in a structured and defined environments. The interest towards human-like robots or humaniod robots has always grown instead of being only in science fiction. The recent researches and development has proved the possiblity of building humanoid robots or simply humanoids, becoming reality, although not powerful or autonomy as desired.

In order to develop more autonomous interactions in humanoid robots, one of the major and main objective is that it should be able to imitate human motions precisely. This would be a major milestone to be achieved in the field of humanoid robots. Scientists and researchers, over the past decades are thriving to make the humanoid robot movements as close as human motions. Recently, the ability of the humanoid robots to teleoperate increases rapidly. To imitate the motion perfectly, the robot should be able to understand the motion; hence, the importance of motion capture systems has widely increased in robotics especially in humanoid robots.

Nowadays, a variety of technologies exist that allow for high accurate capturing of human motions with high frequency. By imitating captured motion, humanoid robots can be teleoperated and also learn new skills resembling human actions. However, there is a catch because the direct imitation of captured movements is impossible due to the differences in the

degree of freedoms and the weight distributions between humans and humanoids. Depending on the complexity of the motion, the challenge of motion generation increases due to various humanoid's constraints including the constraints in stability and the extended period of imitation. This chapter presents the brief introduction on the humanoid robots, their development and behaviour towards human-like motions.

1.1 Service Robotics

According to *International Federation of Robotics (IFR)*, a service robot is defined as a machine that performs useful tasks for humans or equipment excluding industrial automation applications. These robots are mainly dedicated to accompany humans with possibly reduced capabilities and to assist them in dull, dangerous or repetitive tasks. Moreover, *IFR* divides the service robots into two possible categories.

- *Personal Service Robots* - These robots are used for non-commercial and social tasks. The robots are usually trained to operate with non-trained sociologist rather engineers or roboticists.
- *Professional Service Robots* - These robots are used for a commercial task and are usually operate with well-trained operators. The robots tend to work in a professional or well-defined environments are built based on the stack of specialized tasks.

The service robots that are mentioned previously tend to be application-depending and are able to designed to satisfy the specific needs. One of the main aim of the service robots is to co-exist with humans alongside and to help them with any tasks that humans may need assist. However, typical human environments are completely different to the environments that robots experience currently. The robot environments are well-defined with a set of deterministic or stochastic variables that allows the robots for better estimations. Though the robots are able to estimate the environment to an extent, it's abilities are nowhere near for human capabilities. Another important problem is to build a robot that can perform multiple tasks and hold multiple applications. Hence, for a robot to exist among humans and to interact naturally with people, one robot must overcome all these difficulties to some degree of autonomy. Therefore, one of the major challenges in service robotis it to build a general robot that can succeed in all

the areas where human beings can. Equivalently, there is a challenge to build robots that also act and behave as humans.

1.2 Humanoid robots

Humanoid robots are expected to exist and work in a close relationship with human beings in the everyday world and to serve the needs of physically handicapped people. These robots must be able to cope with the wide variety of tasks and objects encountered in dynamic unstructured environments. Imagining an humanoid robot collaborates with humans to execute some daily tasks, learn actions from humans and even improve it's ability to teleoperate [2]. When a humanoid robot works in collaboration with human, the interaction through gestures and cooperation is essential.

Besides the satisfaction of human curiosity and imagination, the integration of humanoid robots in our daily lives makes sense for a variety of practical reasons. Robots resembling us would make human-robot interaction more natural and thus more intuitive and pleasurable. Moreover, if robots are to assist people in daily chores, they have to fit the human environment, which is suitable for *human morphology* [3]. Performing tasks with two hands, handling tools, climbing stairs, reaching shelves - to name only a few tasks - require our assistants to have a similar morphology to ours, so robots can adapt to human lives, instead of us having to do the opposite. Furthermore, research in humanoid robots directly contributes to the field of prosthesis and exoskeletons.

The challenges in creating such machines are numerous. Human bodies are energy efficient machines with extremely elaborated mechanics and incredible cognitive and perceptual abilities. Thus, the creation of humanoid robots requires advances in more areas than one, from the improvement of sensors and processing of information, to efficient control techniques and suitable mechanical structures with constraints in shape, size and weight to improve the resemblance to human beings.

The idea of building machines which look and move like humans has been explored by philosophers and mathematicians since antiquity. Nowadays, the concepts of such machines are a part of research in robotics. Humanoid robots can be thought of as mechanical, actuated devices that can perform human-like manipulation, including locomotion as their main skill for




Figure 1.1: Some Bipedal Android robots over decades [4] (a) First humanoid robot by Leonardo Da vinci (b) Steam Mam in 1865 (c) Electric man in 1885 (d) ELEKTRO in 1938 (e) BIPER - 4 in 1984 (f) Tron-XM in 1997 (g) H6 Humanoid robot in 2000 (h) Robot JACK in 2000 (i) GuRoo in 2002 (j) QRIO, Sony in 2003 (k) Partnar Robot, Toyoto in 2004 (l) TwentyOne in 2007 (m) REEM-A in 2007 (n) REEM-B in 2008 (o) NAO in 2008.

displacement. Well before the first modern humanoid robot, one of the biggest steps towards this objective was achieved in 1956 with the first commercial robot manipulator, *Unimate*, from *Unimation*. The automotive industry was the first to benefit from these kinds of manipulator robots. Recently, the development of humanoid robots for education, research and services has proved the work in multiple ways.

Current goals of research in humanoid robots include industrial and social applications in day-to-day life. A study was conducted by Tanie, [5] and is briefed below

- maintenance tasks of industrial plants,
- security service for home and offices,
- human care, teleoperation of construction machines.
- cooperative work

Since many studies have explored this aspect of robot motion and how to make robots more *human-like* and *human-aware*. Human Robot Interaction (HRI) is now a challenging research field and studies on the efficacy of humanoid robots in human environments are further proceeded.

1.3 Measuring Human Movement

Kinesiology is defined as the scientific study of human movement. To access human motion, Kinesiology involves principles and methods from *biomechanics*, *anatomy*, *physiology* and *motor learning*. Its range of application includes health promotion, rehabilitation, ergonomics, health and safety in industry, disability management, among others. The measurement of human movement is one of the tools that is central in this research field. In 19th century, various devices were built to produce the moving pictures, among those exists the most advanced technique named *chronophotography*. This device allowed to study fast paced human motions by recording and reproducing the captured motion [6]. Another major contribution in motion study is the study on the path of center of mass during human displacement [7].

The first experimental studies of human gait [7], i.e. determining physical quantities like inertial properties, were conducted by Christian W. Braune (1831-1892) and Otto Fischer (1861-



Figure 1.2: Computation of human locomotion using differential equations by Weber Brothers [7]. The coordination between arms and legs was observed clearly.

1917). They considered the human body as rigid bodies in form of dynamic links in series. The work of Nicholas Bernstein (1896-1966) in Moscow introduced the 3D analysis based on cameras. The methods for measuring human movement continued improving with the advent of new technologies like electronics and magnetic devices, up until today's motion capture systems based on reflective markers, magnetic or inertial devices. Recently, there has been a huge development in the motion capture systems which evolved the motion study to newer dimensions (discussed in the later chapter).

1.4 Challenges in Motion Imitation

Given the resemblance between humanoid robots and human beings, it is natural to look for inspiration in human movements in order to generate motion for the humanoid. The most straightforward way is to have the robot observe what the human does and reproduce that behaviour, i.e. perform imitation. After all, even human beings themselves are able to acquire skills by imitation and learning.

If humanoid robots are to interact with human beings, it is imperative that their gestures are human-like since much of human communication is non-verbal. Programming each aspect of the motion detail by detail in order to make it human-like is time-consuming and not fit to handle the immense variety and complexity of human behaviours. Thus, imitation comes as a more natural and intuitive alternative to classical methods, since more information can be transmitted directly.

Human motion cannot be directly transferred to the robot without choosing beforehand which affects the ocean or what is transferring. The most advanced human robots cannot move



Figure 1.3: A performance based on motion imitation done by HRP-2 humanoid robot

completely like a human being. The robots are limited by differences to human counterparts such as the number of degrees of freedom, link lengths, motor torques, etc. Robots which tried to reproduce the whole human body inevitably have never taken dynamic differences from the human body they are trying to represent.

While performing imitations, the physical differences have to be taken into account when mapping the register home movements to the robot morphology. This was addressed by Pollard et al. [5], who limited the captured human motion to a range achievable by the robot by locally scaling angles and velocities in order to preserve as much as possible local variations in the motion imitated by the Sarcos robot.

1.5 Problem Statement

Recently, almost every humanoid robots are able to walk and balance in flat indoor environments and there are robots proved walking on rugged terrains and uneven planes are possible and achievable. A lot of effort is being done to make them more autonomous by incorporating the perception, planning and action loop. One of the ultimate objective of the humanoid robot, as mentioned before is to create the humanoid motion more human-precise. In this sense, robots require real-time imitation processed be higher reactivity compensating the unpredictable na-

ture of human motion.

In humans, imitation is an advanced behavior whereby an individual observes and replicates the action of another human arguably with more accuracy and precision. However in humanoid robots, these kind of motion imitations are possible up to kinematic level through perception; the robot can also be able to imitate the action posture dynamically using its predefined configurations and controllers to an extent. But for a complete imitation at dynamic level, humanoid robots are still struggling to approximately copy the dynamic parameters applied during the action. Presently, to copy the action at dynamic level, feedback data from human during motion or action is mandatory. The motion data from human action is transferred using *Xsens MVN Analyze*. The main objective of the thesis is to define realtime dynamic balance constraint during motion imitation and validate it experimentally using an affordable humanoid robot, *NAO* from *Aldebaran Robotics*. The balancing constraint of the robot is controlled using an Hierarchical Quadratic Programming (HQP) and validated on both simulation and real robot.

1.6 Thesis Organisation

State of the Art

The research and interest in humanoid robotics has greatly increased over the last few years, but inspite of the current abundance of the humanoid robots, their utility is still very limited. One of the most important trials, *DARPA Robotics Challenge (DRC)* in 2013 listed a pack of capabilities and robustness that humanoid robots lacked when performing different tasks. Each task of this challenge should last only up to 30 minutes. These tasks will take less than a minute for a human to complete which explains the powerlessness of the robots. This chapter briefly explains different control strategies that has been carried to keep balance and to handle robot dynamics in humanoid robots.

2.1 Approaches in Humanoid Robot Control

Different methods has been used to make a robot move depending on the application, the complexity of the task, and even the specific nature of the robot. The main control methods used for the humanoid robots are as follows: Motion planning, Kinematic Approach, Dynamic Approach and Optimal Control. Each of the methods and its recent development are discussed below.

2.1.1 Motion Planning

Motion Planning as the name suggests a method where a robot automatically finds its desired or goal state from its initial configuration. For instance, consider a hand moving from it's current pose to another pose, motion planning allows to move to goal pose considering the presence of obstacles and consumption of time and energy. Currently, there are many applications in

industrial robots and mobile robots where the robot motion is planned within both structured and non-structured environment.

Even though, motion planning and its researches are progressing majorly within past decades, the recent approaches are combined with artificial intelligence, advantages of computer technology and mathematics. The main approaches can be found in books such as [8, 9]. An desirable concept in motion planning is *Configuration Space (CS)*, which is the set of all possible configurations for a robot to attain. For a robot with n independent degrees of freedom, CS is an n -dimensional manifold \mathbb{M} that contains all the desired configurations $q \in \mathbb{M}$ of the robot. The importance of CS is that changes the problem of moving a body in $SE(3)$ to moving a point in CS . The summary of this section is sourced from the literature work [10]. Then there exists,

- CS_{obs} is the *Obstacle Configuration Space* formed to generate self-collision or obstacle collision free set of configurations such that $CS_{obs} \in CS$.
- CS_{free} is the *Free Configuration Space* which holds the set of configurations for a freely roaming robot such that $(CS_{free} \cup CS_{obs}) \cap CS$.

Using these configurations, the problem of motion planning can be stated as finding the continuous path $p(t)$ through the desirable configurations from initial state $q(0)$ to goal state $q(f)$ avoiding collisions, that is $p : [0, 1] \rightarrow CS_{free}$ where t defines time parameterization.

Generic methods

The solution to motion planning problem can be processed through classical approaches using deterministic, sampling-based or path optimization algorithms. Each of the types are briefed below.

1. *Deterministic algorithms* - The deterministic algorithms are developed such that it computes the valid path everytime knowing almost all the variables of the environment. Methods such as *cellular decomposition*, *Voronoi diagrams*, *visibility graphs*, *potential fields* and *Canny's algorithms* rely on mathematical construction of the environment with the obstacles and provide CS_{obs} . Although these algorithms are complete, the computation of high-dimensional space is expensive and the environments are always not deterministic.




Figure 2.1: Sampling based motion planning of NASA Valkyrie [1]

2. *Sampling based algorithms* - These algorithms mostly approximate the connectivity of CS_{free} through random sampling configurations from CS and rejecting the configurations using boolean collision detection techniques. The main examples are *Probabilistic Maps* and *Rapidly-exploring Random Trees(RRT)* in combination with Voronoi diagrams promotes the obstacle avoidance configurations for a robot. The main advantage of sampling based algorithms are to handle the higher dimensional configuration space recovering a higher degree of completeness.
3. *Path optimization algorithms* - These algorithms provide optimization in terms of path planning and trajectory planning starting from a valid initial state to its goal position with the desired configurations. *Greedy optimization* tries to directly connect the start configuration to its goal state that generates a collision free shortest path by discretizing the path into n closest goal configuration relative to previous configuration.

Motion Planning in Humanoid robots

Classical motion planning techniques determine collision free trajectories considering only the geometric model of the robot. However the control of polyarticulated system needs the synthesis of robot models that describe the effect of joint variations on the whole robot configuration. In both the case, for instance considering an arm moving to it's goal position, the robot tends to make it more unusual, inefficient and unnatural movements. To overcome these problems, geometric models are replaced with kinematic models, dynamic models or optimal control and trajectories are generated. Additional constraints like multiple contacts and dynamic balance

of the system are considered. For instance, motion primitives that have been predefined by a human expert based on prior knowledge can be used to guide the planner [11].

In case of humanoid walking, the planner can be generated using deterministic approaches with dynamic alterations of the foot transition model considering the smooth transition of the trajectories for posture transitions. For these cases, sampling-based algorithms are considered to improve the degree of completeness. Either way, the higher dimensional configuration space is handled so that the problem is solved successively. An example is presented in [12] where a 36 degree of freedom robot is reduced to a 3 degrees of freedom bounding box and a PRM is applied for the path planning problem of the box. Another example is to present the constraints in the form of sub-manifolds of CS where a union of separate manifolds like contact limb position and static balance constraints can be used to plan the configuration space. In such cases, static balance control in humanoid robots and other legged robots can be obtained [13].

2.1.2 Kinematics Approach

Generally, *kinematics* is defined as a branch of science which deals with the study of the position, velocity and acceleration of a mechanical system without considering forces and the dynamic properties of the system (such as mass or inertia) that generate the motion. In humanoid and manipulator robots, the system is represented as rigid bodies composed of actuators and sensors. In contrast with the manipulators, the humanoid robots are not fixed to any environment and are highly mobile. This makes the humanoids (or humanoid robots) more redundant than the manipulators. This section briefs the state of the art and concepts of kinematic approach used in humanoid control.

Basic Concepts

The *joint space* is also called as *configuration space*, of a robot with n degrees of freedom (DoF) is a n -dimensional manifold Q containing all the possible joint values for a joint q can take. For humanoid robots, this space can be generalized to the operational points [14], which can represent any part of the body that may be of interest. In robotics, there exists four subdomains of kinematics namely, (i) *forward kinematics (or direct geometry)*, (ii) *inverse kinematics (or inverse geometry)*, (iii) *forward differential kinematics (or simply forward kinematics)*, and (iv)

inverse differential kinematics (or simply inverse kinematics).

- **Direct Geometric Model:** For a robot with n DoF in a n -dimensional joint space such that $q \in Q$, there exist a pose $x \in SE(\mathcal{B})$ represented as

$$x = f(q)$$

described by a map $f : Q \rightarrow SE(\mathcal{B})$.

- **Inverse Geometric Model:** For a robot with n DoF in a n -dimensional joint space with $q \in Q, x \in SE(\mathcal{B})$, the joint space can be represented from a given pose for a certain operational point as

$$q = f^{-1}(x)$$

described by a map $f : SE(\mathcal{B}) \rightarrow Q$. But there is a possibility for non-unique solution or non-existing solution (known as singularity).

- **Forward Kinematic Model:** For a robot with n DoF in a n -dimensional joint space such that $q \in Q, x \in SE(\mathcal{B})$, the operational twist $\xi \in SE(\mathcal{B})$ due to the joint variation \dot{q} is described as

$$\xi = J(q)\dot{q}$$

Here, J is the basic Jacobian such that $J : T_q(Q)$ where $T_q(Q)$ is the tangent space of the Q space. Instead, the Jacobian J can be formulated analytically using the pose variation \dot{x} and joint variation \dot{q} as

$$\dot{x} = \frac{\partial x}{\partial q}\dot{q} \quad or \quad \dot{x} = J\dot{q}$$

then J is the task Jacobian.

- **Inverse Kinematic Model:** For a robot with n DoF in a n -dimensional joint space such that $q \in Q, x \in SE(\mathcal{B})$, finding the joint variations \dot{q} that produce a pose variation \dot{x} of the end effector as

$$\dot{q} = J^{-1}\dot{x}$$

and it can be solved iteratively.

Kinematic Control of Redundant robots

In general, the kinematic control involves a reference planner or trajectories $q_{ref}(t)$ in $SE(3)$ for which the robot joint trajectory $q(t)$ is evaluated against attaining the objective. Consider a task i in a robot with n DoF, then the Jacobian is of size $m \times n$ and the robot is redundant when $(n > m)$ [15]. The joint variations \dot{q} can be represented if

- $(n > m)$. For task i , there exists a degree of redundancy $n - m$ for which the joint variation based on least square method can be given by

$$\dot{q} = J_i^+ \dot{x}_i + (I_n - J_i^+ J_i) z_i$$

where $J_i^+ = J_i^T (J_i J_i^T)^{-1}$ is the pseudo inverse of J_i , I_n is the identity matrix of size n and z_i is an n -dimensional arbitrary vector. The first term in the above equation is to minimize the norm solution while the second term is to find all possible solutions.

- $(n = m)$. The degree of redundancy is 0 and the joint variation can be defined as

$$\dot{q} = J^{-1} \dot{x}$$

Note that the Jacobian here is a non-singular matrix.

- $(n < m)$. There doesn't exist any redundancy and no solution is found in this case.

For multiple tasks, the probability of finding a suitable solution decreases as the preceding tasks influence the current task, in other words, consider two tasks 1 and 2 for a redundant robot. There exist a solution for two tasks $x_1 = f_1(q)$ and $x_2 = f_2(q)$ with task priority for x_1 and x_2 respectively. First the variation q that solves the task according to the priority is determined from the differential equations by,

$$\delta x_1 = J_1 \delta q \tag{2.1}$$

$$\delta x_2 = J_2 \delta q \tag{2.2}$$

Then the joint variation δq for task 1 has infinitely many solutions and is given by

$$\dot{q} = J_i^+ \dot{x}_i + (I_n - J_i^+ J_i) z_i \quad (2.3)$$

Solving 2.3 and 2.2 for z_1 arbitrary vector,

$$z_1 = \hat{J}_2^+ (\delta x_2 - J_2 J_1^+ \delta x_1) + (I_n - \hat{J}_2^+ \hat{J}_2) z_2 \quad (2.4)$$

where $\hat{J}_2 = J_2(I_n + J_1^+ J_1)$ and z_2 is an n -dimensional arbitrary vector. Then the solution of joint variation for the two priority tasks can be given by

$$\delta q = J_1^+ \delta x_1 + \hat{J}_2^+ (\delta x_2 - J_2 J_1^+ \delta x_1) + (I_n - J_1^+ J_1)(I_n - \hat{J}_2^+ \hat{J}_2) z_2 \quad (2.5)$$

Generalized form of Task Priority

Kinematic Control in humanoid robots

Humanoid robots as a rigid body representation, from a kinematic point of view present a tree-like structure that includes multiple connected chains, and a high number of DoF. This results in higher degree of redundancy with respect to most tasks, in which case the robot is said to be under-constrained. Therefore, methods developed for generic redundant robots are usually applied in humanoid robotics with some adaptations or additions. Due to the complexity of the kinematic configuration, closed-form solutions for the IK problem are usually very complex, but recently some classical methods have been used and modified, to obtain closed equations for specific humanoid robots which are treated as a composition of several kinematic chains. However, methods based on instantaneous IK, which compute an increment in q , are usually preferred. This linearization of the problem offers an infinite number of feasible solutions for humanoid robots: there exist different joint updates that achieve the same task. This leads to the possibility of performing different tasks at the same time, and the IK control must be capable of properly handling them.

Methods based on task-prioritization solve these problems and have become the preferred techniques in IK control. They can even be considered as the current “state of the art” in humanoid robotics control due to their relatively low computational cost, their straightforward implementation, and the maturity of the approach. Several works with different humanoid

platforms use this methodology to solve the redundant IK problem at the velocity level using only equality constraints [16, 17, 18]. For imposing inequality constraints to the control framework at any hierarchical level, a sequence of optimal resolutions for each priority level has been proposed in [19], a more efficient computation based on orthogonal decompositions can be found in [20] and a smooth interchange between priority of consecutive prioritized tasks is introduced in [21].

2.1.3 Dynamics Approach

Dynamics is the study of the relation between the robot motion and the generalized forces that act on the robot generating that motion. This relation considers parameters such as lengths, masses and inertia of the elements composing the robot.

Basic Concepts

In the dynamic model, the motion is represented through joint variables acceleration \ddot{q} , or operational points acceleration \ddot{x} . For rotational joints, the generalized forces are equivalent to the joint torques, and for prismatic joints they are the joint forces. There are two main problems in dynamics:

- **Forward Dynamics:** It expresses the motion of the robot as a function of the generalized forces applied to it.
- **Inverse Dynamics:** It expresses the generalized forces acting on a robot as a function of the robot motion.

There exist two main formulations to compute the robot dynamic model: the Lagrange approach, and the Newton-Euler approach. The Lagrange approach's main advantage is the clear separation of each component of the model; but in general, it is computationally expensive. The Newton-Euler approach does not provide a clear separation of the terms but due to its recursivity a lower computation time can be obtained. Thus, it is the preferred implementation for computer calculations. The most used algorithms for this approach can be found in [22, 23]. The Lagrange method and Newton Euler's method are detailed below

1. Lagrange Formulation

The Lagrange formulation describes the behaviour of a dynamic system in terms of work and energy stored in the system. The Lagrange equations are written in the form:

$$\tau = \frac{d}{dt} \left(\frac{\partial L}{\partial \dot{q}} \right)^T - \left(\frac{\partial L}{\partial q} \right)^T \quad (2.6)$$

where τ is the generalized forces on the system, q is the joint vector, \dot{q} represent the joint velocities and $L = K - U$ is the Lagrangian function with K as kinetic energy and U as potential energy respectively.

The kinetic energy K for body i is expressed in the form,

$$K_i = \frac{1}{2} \int v_{m_i}^T v_{m_i} dm \quad (2.7)$$

where $v_{m_i} = v_i + \omega_i \times r_{m_i}^{\rightarrow}$ is the velocity of point m_i on the body i which can be expressed as a function of twist, $\xi = [v_i^T, \omega_i^T]$

The potential energy U for body i is defined as,

$$U_i = -m_i \mathbf{g}^T r_{CoM_i}^{\rightarrow} \quad (2.8)$$

where \mathbf{g} is the gravity vector and $r_{CoM_i}^{\rightarrow}$ is the distance vector to CoM of body i . The equation 2.6 can be put in a matrix form as

$$\tau = M(q) \cdot \ddot{q} + c(q, \dot{q}) \quad (2.9)$$

where $M(q)$ is the generalized robot inertia matrix and $c(q, \dot{q})$ is the vector of Coriolis, centrifugal and gravity effects. This model is called as inverse dynamic model.

2. Newton Euler Formulation

Newton Euler (NE) equations allow computation of the sum of external forces $\sum f_j$ and moments $\sum m_{CoM_i}$ (including the gravity effects) is represented as

$$\begin{aligned}\sum f_i &= m_i v_{CoM_i} \\ \sum m_{CoM_i} &= \mathbf{I}_{CoM_i} \dot{\omega}_i + \omega_i \times (\mathbf{I}_{CoM_i} \omega_i)\end{aligned}\tag{2.10}$$

where v_{CoM_i} is the acceleration of the CoM of body i ; $\dot{\omega}_i$ is the angular acceleration of the body i and \mathbf{I}_{CoM_i} is the inertia matrix of body i . These equations are usually recursive algorithms [23, 22] which make the computation less expensive when a computer involves.

The introduction of centroidal momentum and centroidal dynamics based on the Centre of Mass (CoM) of a system is particularly a import concept since the humanoids build large momenta(so far only angular momentum is larger and linear momentum on legger humanoids are not upto the mark). The dynamic model of a robot can be expressed in two ways depending on the spaces that are used to describe the motion and the control input. The two approaches are: the joint space formulation, and the operational space (or task space) formulation. The joint space formulation is the classical approach and uses the joint space acceleration to specify the motion, and the generalized forces acting on the actuated joints to describe the control. The operational space formulation represents the motion directly using the task space acceleration, which needs a reformulation of the forces as task space generalized forces.

Dynamic Control in Humanoid Robots

For a humanoid robot, classical dynamic control techniques are not sufficient since coordination of the motion is required, environmental forces need to be considered, and balance has to be kept at all time. For the robot balance, a stability criterion such as keeping the CoM or the ZMP inside the support polygon must be enforced. For planar surfaces, the constraint on the ZMP implies a control of the contact forces. Thus, the interaction with the environment is always present since the feet are in contact with the ground and additional contacts of other parts of the robot body might also be necessary. These contacts generate an effect on the joints generalized forces, which cannot be controlled using only kinematic methods but with dynamic approaches. The dynamic control ensures the physical feasibility of the motion and allows for faster movements without losing balance.

The Operational Space Inverse Dynamics (OSID) is a more specific framework for controlling

the whole-body of humanoid robots considering contacts and a set of different constraints. This approach proposed in [24, 25] is based on a two stage mapping to obtain consistent contact forces and is equivalent to successive projections onto the nullspaces of the previous tasks. Therefore, new tasks can be added without dynamically interfering with higher priority tasks. Other methods use the OSID within frameworks that involve some type of optimization to find the local solution. The most popular approaches use Quadratic Programming (QP), which allows for the specification of both equality and inequality constraints. The latter type of constraints is fundamental in humanoid robotics to directly model unilateral contacts, and it is also important to properly specify some particular tasks. Although the previous approaches exploit the full robot dynamics, the angular momentum is not explicitly controlled within these frameworks. Nevertheless, it has been shown that the angular momentum is a natural and important part of human motion, specially when performing complex and fast movements [26].

2.1.4 Optimal Control

Optimal control, also known in robotics as trajectory optimization or trajectory filtering, consists in finding a trajectory and its associated control law (policy) that satisfies some predefined optimality criterion. In general mathematical terms, it concerns the properties of control functions which, when inserted into a differential equation, give solutions that minimize a cost or measure of performance. But it also concerns optimization problems with dynamic constraints which might be functional differential equations, difference equations, partial differential equations or equations with another form. This section is summarized from the literature work [10] which provides a brief overview of optimal control in humanoid robots.

Optimal Control in Humanoid Robots

In robotics, optimal control can be used to find the trajectories from an initial posture to a final desired posture, specified as a whole or as a set of sub-objectives, satisfying certain constraints. Very fast and powerful movements can be generated with optimal control, which can comprehend the problems of inverse kinematics or inverse dynamics and can therefore produce better movements. The problem with IK and OSID alone is their inability to properly handle the CoM accelerations, thus overrestricting the motion. A solution typically relies

on a dedicated submodel, like a linearized inverted pendulum [27] to capture the future of the system, but this ad-hoc resolution increases the control architecture complexity. Thus, using these schemes the future states of the system can be somehow predicted, but dedicated submodels would need to be developed for each case. However, optimal control is the most suitable approach that allows to take into account all the constraints at the same time. In fact, optimal control can automatically generate the proper trajectory for the CoM in order to achieve fast movements: it acts as a classical pattern generator used for walking schemes, but additionally incorporating whole-body motion. A serious challenge to optimization-based approaches in robotics is that the timescales of the dynamics are faster than in other applications and need a faster response. Currently, the main problem is the computational time, due to the high number of DoF, that forbids its use in real-time applications.

The main drawback of optimal control is the curse of dimensionality, which is particularly important for humanoid robots whose state space is so large that no control scheme can explore all of it in advance and prepare suitable responses for every situation. It would be desirable to obtain optimal control in real time; however, currently there is no approach that can achieve this: the solutions are very time consuming and generic solvers tend to get stuck into local minima or they even return trivial solutions. The problem of finding the proper formulation and resolution of optimal control is still an open issue in robotics.

2.2 Approaches in Humanoid Balance Control

There has been various control strategies that has been implemented on the humanoid robot for various tasks but, the balance control strategies are the dominant task when it comes to legged humanoids. The balance strategies are mostly based on the centroidal momentum and centroidal dynamics for the complex structured humanoids. These single point mass systems are less computational expensive considering point approximation method of Centre of Mass (CoM). Note that the concepts of CoM and ZMP will be discussed later in chapter 3. The balance control approaches based on single point masses will be discussed in this section among which the most common methods are

1. Linear Inverted Pendulum Model

2. Double Inverted Pendulum Model
3. Cart Table Model
4. Spherical Inverted Pendulum Model (Simple and Double)

2.2.1 Linear Inverse Pendulum Approach

Consider a simple inverted pendulum model as in figure [2.2] with mass m and link length l_1 , the kinematics and dynamics for the model can be represented as,




Figure 2.2: Simple Inverse Pendulum Model

Position:

$$\begin{aligned} x_1 &= -l_1 \sin q_1 \\ y_1 &= l_1 \cos q_1 \end{aligned} \tag{2.11}$$

Velocity:

$$\begin{aligned} \dot{x}_1 &= -l_1 \cos(q_1) \dot{q}_1 \\ \dot{y}_1 &= -l_1 \sin(q_1) \dot{q}_1 \end{aligned} \tag{2.12}$$

Acceleration:

$$\begin{aligned} \ddot{x}_1 &= l_1 \sin(q_1) \dot{q}_1^2 - l_1 \cos(q_1) \ddot{q}_1 \\ \ddot{y}_1 &= -l_1 \cos(q_1) \dot{q}_1^2 - l_1 \sin(q_1) \ddot{q}_1 \end{aligned} \tag{2.13}$$

Forces and Torques:

$$m_1 \ddot{x}_1 = F_{x1} \quad (2.14)$$

$$m_1 \ddot{y}_1 = F_{y1} - m_1 g$$

$$\tau_1 = m_1 l_1^2 \ddot{q}_1 + m_1 g l_1 \sin q_1 \quad (2.15)$$

where F_{x1} and F_{y1} represent the reaction forces on the link from the fixed point.

2.2.2 Double Inverse Pendulum Approach

Consider a double inverted pendulum model as in figure [2.3] with mass m and link lengths l_1 and l_2 , the kinematics and dynamics for the model can be represented as,




Figure 2.3: Double Inverse Pendulum Model

Position:

$$x_1 = -l_1 \sin q_1 \quad (2.16)$$

$$y_1 = l_1 \cos q_1$$

$$x_2 = -l_1 \sin q_1 - l_2 \sin (q_1 + q_2) \quad (2.17)$$

$$y_2 = l_1 \cos q_1 + l_2 \cos (q_1 + q_2)$$

Velocity:

$$\begin{aligned} \dot{x}_1 &= -l_1 \cos(q_1) \dot{q}_1 \\ \dot{y}_1 &= -l_1 \sin(q_1) \dot{q}_1 \end{aligned} \quad (2.18)$$

$$\begin{aligned} \dot{x}_2 &= -l_1 \cos(q_1) \dot{q}_1 - l_2 \cos(q_1 + q_2) (\dot{q}_1 + \dot{q}_2) \\ \dot{y}_2 &= -l_1 \sin(q_1) \dot{q}_1 - l_2 \sin(q_1 + q_2) (\dot{q}_1 + \dot{q}_2) \end{aligned} \quad (2.19)$$

Acceleration:

$$\begin{aligned} \ddot{x}_1 &= l_1 \sin(q_1) \dot{q}_1^2 - l_1 \cos(q_1) \ddot{q}_1 \\ \ddot{y}_1 &= -l_1 \cos(q_1) \dot{q}_1^2 - l_1 \sin(q_1) \ddot{q}_1 \end{aligned} \quad (2.20)$$

$$\begin{aligned} \ddot{x}_2 &= -l_1 \cos(q_1) \ddot{q}_1 + l_1 \sin(q_1) \dot{q}_1^2 - l_2 \cos(q_1 + q_2) (\ddot{q}_1 + \ddot{q}_2) + l_2 \sin(q_1 + q_2) (\dot{q}_1 + \dot{q}_2)^2 \\ \ddot{y}_2 &= -l_1 \sin(q_1) \ddot{q}_1 + l_1 \cos(q_1) \dot{q}_1^2 - l_2 \sin(q_1 + q_2) (\ddot{q}_1 + \ddot{q}_2) + l_2 \cos(q_1 + q_2) (\dot{q}_1 + \dot{q}_2)^2 \end{aligned} \quad (2.21)$$

Forces and Torques:

$$\begin{aligned} m_1 \ddot{x}_1 &= F_{x1} + F_{x2} \\ m_1 \ddot{y}_1 &= F_{y1} + F_{y2} - m_1 g \end{aligned} \quad (2.22)$$

$$\begin{aligned} m_2 \ddot{x}_2 &= F_{x2} \\ m_2 \ddot{y}_2 &= F_{y2} - m_2 g \end{aligned} \quad (2.23)$$

where F_{x1}, F_{x2}, F_{x3} and F_{y1}, F_{y2}, F_{y3} represent the reaction forces on the link from the fixed point.

$$\begin{aligned} \tau_1 &= m_1 l_1^2 \ddot{q}_1 + m_1 g l_1 \sin q_1 \\ \tau_2 &= m_2 l_2^2 (\ddot{q}_1 + \ddot{q}_2) + m_2 g l_2 \sin(q_1 + q_2) \end{aligned} \quad (2.24)$$

2.2.3 Cart Table Model

2.2.4 Spherical Inverse Pendulum Approach

2.3 Approaches in Posture Control and Motion Retargeting

2.3.1 Mansard's work

2.3.2 D. Gucci's work

2.3.3 Kumar Munirathinam's work

Dynamics Based Whole Body Imitation

3.1 Dynamic Considerations

3.1.1 Rigid body constraints

3.1.2 Multi body constraints




Figure 3.1: A rigid-body representation of humanoid robot

3.1.3 ZMP

3.1.4 Dynamic Model of humanoid robot

3.1.5 Simplified dynamic model using LIPM

3.2 Control Approach

3.2.1 Balance Control

CoM tracking and scaling

ZMP tracking and scaling

3.2.2 Posture Control

Multi-Double Inverted Pendulum Model (M-DIP)

3.2.3 Acceleration Control

3.3 Task Specification Approach

3.3.1 Joint trajectory tracking

3.3.2 Balance Control

3.3.3 Posture Control

3.3.4 Joint Limits Avoidance

Implementation

4.1 NAO robot

4.1.1 NAOqi C++ SDK

4.1.2 CopelliaSim support

4.2 Xsens MVN Analyze

4.2.1 Sensor Setup

4.2.2 Xsens Networking Protocol

4.2.3 Network Streaming

Conclusion

Bibliography

- [1] Y. Yang, V. Ivan, W. Merkt, and S. Vijayakumar, “Scaling sampling-based motion planning to humanoid robots,” in *2016 IEEE International Conference on Robotics and Biomimetics (ROBIO)*, 2016, pp. 1448–1454.
- [2] N. Fukaya, S. Toyama, T. Asfour, and R. Dillmann, “Design of a humanoid hand for human friendly robotics applications,” in *Human Friendly Mechatronics*, E. Arai, T. Arai, and M. Takano, Eds. Amsterdam: Elsevier Science, 2001, pp. 273 – 278. [Online]. Available: <http://www.sciencedirect.com/science/article/pii/B9780444506498500462>
- [3] C. C. Kemp, P. Fitzpatrick, H. Hirukawa, K. Yokoi, K. Harada, and Y. Matsumoto, *Humanoids*. Berlin, Heidelberg: Springer Berlin Heidelberg, 2008, pp. 1307–1333. [Online]. Available: https://doi.org/10.1007/978-3-540-30301-5_57
- [4] M. Akhtaruzzaman and A. Shafie, “Evolution of humanoid robot and contribution of various countries in advancing the research and development of the platform,” 11 2010, pp. 1021 – 1028.
- [5] K. Tanie, “Humanoid robot and its application possibility,” in *Proceedings of IEEE International Conference on Multisensor Fusion and Integration for Intelligent Systems, MFI2003.*, 2003, pp. 213–214.
- [6] B. Rosenhahn, R. Klette, D. Metaxas, and D. N. Metaxas, *Human Motion Understanding, Modelling, Capture, and Animation / edited by Bodo Rosenhahn, Reinhard Klette, Dimitris Metaxas.*, 1st ed., ser. Computational Imaging and Vision, 36. Dordrecht: Springer Netherlands : Imprint: Springer, 2008.

- [7] M. Eadweard, *Muybridge's complete human and animal locomotion : all 787 plates from the 1887 animal locomotion / by Eadweard Muybridge ; introd. to the Dover ed. by Anita Ventura Mozley,...*, ser. Collections of fine art in Dover books. New York: Dover.
- [8] J. Barraquand and J.-C. Latombe, "Robot motion planning: A distributed representation approach," *The International Journal of Robotics Research*, vol. 10, no. 6, pp. 628–649, 1991. [Online]. Available: <https://doi.org/10.1177/027836499101000604>
- [9] S. LaValle, "Planning algorithms," 2006.
- [10] O. E. Ramos Ponce, "Generation of the whole-body motion for humanoid robots with the complete dynamics," Theses, Universite Toulouse III Paul Sabatier, Oct. 2014. [Online]. Available: <https://tel.archives-ouvertes.fr/tel-01134313>
- [11] Y. Zhang, J. Luo, K. Hauser, H. A. Park, M. Paldhe, C. G. Lee, R. Ellenberg, B. Killen, P. Oh, J. H. Oh *et al.*, "Motion planning and control of ladder climbing on drc-hubo for darpa robotics challenge," in *2014 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, 2014, pp. 2086–2086.
- [12] E. Yoshida, C. Esteves, I. Belousov, J.-P. Laumond, T. Sakaguchi, and K. Yokoi, "Planning 3-d collision-free dynamic robotic motion through iterative reshaping," *IEEE Transactions on Robotics*, vol. 24, no. 5, pp. 1186–1198, 2008.
- [13] K. Hauser and J.-C. Latombe, "Multi-modal motion planning in non-expansive spaces," *The International Journal of Robotics Research*, vol. 29, no. 7, pp. 897–915, 2010.
- [14] O. Khatib, "A unified approach for motion and force control of robot manipulators: The operational space formulation," *IEEE Journal on Robotics and Automation*, vol. 3, no. 1, pp. 43–53, 1987.
- [15] Y. Nakamura, *Advanced robotics: redundancy and optimization*. Addison-Wesley Longman Publishing Co., Inc., 1990.
- [16] M. Gienger, H. Janssen, and C. Goerick, "Task-oriented whole body motion for humanoid robots," in *5th IEEE-RAS International Conference on Humanoid Robots, 2005*. IEEE, 2005, pp. 238–244.

- [17] E. Yoshida, O. Kanoun, C. Esteves, and J.-P. Laumond, “Task-driven support polygon reshaping for humanoids,” in *2006 6th IEEE-RAS International Conference on Humanoid Robots*. IEEE, 2006, pp. 208–213.
- [18] N. Mansard and F. Chaumette, “Task sequencing for high-level sensor-based control,” *IEEE Transactions on Robotics*, vol. 23, no. 1, pp. 60–72, 2007.
- [19] O. Kanoun, F. Lamiroux, P.-B. Wieber, F. Kanehiro, E. Yoshida, and J.-P. Laumond, “Prioritizing linear equality and inequality systems: application to local motion planning for redundant robots,” in *2009 IEEE international conference on robotics and automation*. IEEE, 2009, pp. 2939–2944.
- [20] A. Escande, A. Kheddar, and S. Miossec, “Planning contact points for humanoid robots,” *Robotics and Autonomous Systems*, vol. 61, no. 5, pp. 428–442, 2013.
- [21] G. Jarquín, A. Escande, G. Arechavaleta, T. Moulard, E. Yoshida, and V. Parra-Vega, “Real-time smooth task transitions for hierarchical inverse kinematics,” in *2013 13th IEEE-RAS International Conference on Humanoid Robots (Humanoids)*. IEEE, 2013, pp. 528–533.
- [22] R. Featherstone and D. Orin, “Robot dynamics: equations and algorithms,” in *Proceedings 2000 ICRA. Millennium Conference. IEEE International Conference on Robotics and Automation. Symposia Proceedings (Cat. No. 00CH37065)*, vol. 1. IEEE, 2000, pp. 826–834.
- [23] R. Featherstone, *Rigid body dynamics algorithms*. Springer, 2014.
- [24] O. Khatib, L. Sentis, J. Park, and J. Warren, “Whole-body dynamic behavior and control of human-like robots,” *International Journal of Humanoid Robotics*, vol. 1, no. 01, pp. 29–43, 2004.
- [25] L. Sentis and O. Khatib, “Control of free-floating humanoid robots through task prioritization,” in *Proceedings of the 2005 IEEE International Conference on Robotics and Automation*. IEEE, 2005, pp. 1718–1723.

- [26] M. Popovic, A. Hofmann, and H. Herr, “Angular momentum regulation during human walking: biomechanics and control,” in *IEEE International Conference on Robotics and Automation, 2004. Proceedings. ICRA '04. 2004*, vol. 3. IEEE, 2004, pp. 2405–2411.
- [27] S. Kajita, F. Kanehiro, K. Kaneko, K. Fujiwara, K. Harada, K. Yokoi, and H. Hirukawa, “Biped walking pattern generation by using preview control of zero-moment point,” in *2003 IEEE International Conference on Robotics and Automation (Cat. No. 03CH37422)*, vol. 2. IEEE, 2003, pp. 1620–1626.