

Introduction to Computers and Programming

Lecture 6 –
All about pointer
Chap 11 & 12

Tien-Fu Chen



Dept. of Computer Science and
Information Engineering
National Yang Ming Chiao Tung Univ.



Basic pointer

Pointer Variables

- ❑ The address of the first byte is said to be the address of the variable.
- ❑ The address of the variable `short int i` is 2000:
- ❑ Addresses can be stored in special ***pointer variables***.
- ❑ When we store the address of a variable `i` in the pointer variable `p`:
`p` “points to” `i`.




The Address Operator

- ❑ C provides a pair of operators for pointers.
 - Use the `&` (address) operator to get the address
 - Use the `*` (***indirection***) operator to gain access to the object.
- ❑ Initialize: Assign the address of a variable to a pointer variable

```
int i, *p;
```

```
...
```

```
p = &i;
```



The Indirection Operator

- ❑ If `p` points to `i`, we can print the value of `i` as follows:

```
printf("%d\n", *p);
```

- ❑ Applying `&` to a variable produces a pointer to the variable. Applying `*` to the pointer takes us back to the original variable:

```
j = *&i;    /* same as j = i; */
```

- ❑ When `p` points to `i`, `*p` is an ***alias*** for `i`.
 - `*p` has the same value as `i`.
 - Changing the value of `*p` changes the value of `i`.

Pointer Assignment

- Assume that the following declaration is in effect:

```
int i, j, *p, *q;
```


- Example of pointer assignment:

```
p = &i;
```

- Another example of pointer assignment:

```
q = p;
```


q now points to the same place as p:




Pointer Assignment

- If p and q both point to i , we can change i by assigning a new value to either $*p$ or $*q$:

$*p = 1;$



$*q = 2;$




- Any number of pointer variables may point to the same object.

Pointer Assignment

```
p = &i;
```

```
q = &j;
```


```
i = 1;
```



```
q = p;
```

pointer assignment

```
*q = *p;
```




Pointers as Arguments

- ❑ A call of `decompose`:



```
decompose(3.14159, &i, &d);
```

- ❑ As a result of the call, `int_part` points to `i` and `frac_part` points to `d`:



Pointers as Arguments

```
*int_part = (long) x;  
*frac_part = x - *int_part;
```



Pointers as Arguments

- ❑ Although `scanf`'s arguments must be pointers, it's not always true that every argument needs the `&` operator:

```
int i, *p;
```

```
...
```

```
p = &i;
```

```
scanf("%d", p);
```

- ❑ Using the `&` operator in the call would be wrong:

```
scanf("%d", &p);    /* ** WRONG ** */
```

Pointers as Return Values

- ❑ Functions are allowed to return pointers:

```
int *max(int *a, int *b)
{
    if (*a > *b)
        return a;
    else
        return b;
}
```

- ❑ A call of the `max` function:

```
int *p, i, j;
...
p = max(&i, &j);
```

After the call, `p` points to either `i` or `j`.

Quiz

A swap function is to exchange the values of two variables:

```
void swap (int *i, int *j)
{
    int temp = i;
    i = j;
    j = temp;
}
```

```
int A, B;
swap(A, B);
```

- (a) Which variables are automatically allocated?
- (b) Correct the above statements to make swapping A and B.



Pointer and array


Pointer Arithmetic

- ❑ A pointer variable can point to array elements:

```
int a[10], *p;
```

```
p = &a[0];
```

- ❑ A graphical representation:




Pointer Arithmetic

- ❑ We can now access `a[0]` through `p`; for example, we can store the value 5 in `a[0]` by writing

`*p = 5;`

- ❑ An updated picture:




Pointer Arithmetic

- ❑ If p points to an element of an array a , the other elements of a can be accessed by performing ***pointer arithmetic*** (or ***address arithmetic***) on p .
- ❑ C supports three forms of pointer arithmetic:
 - Adding an integer to a pointer
 - Subtracting an integer from a pointer
 - Subtracting one pointer from another


Adding an Integer to a Pointer

❑ Example of pointer addition:


```
p = &a[2];
```



```
q = p + 3;
```




```
p += 6;
```



Adding an Integer to a Pointer

- ❑ Adding an integer j to a pointer p yields a pointer to the element j places after the one that p points to.
- ❑ More precisely, if p points to the array element $a[i]$, then $p + j$ points to $a[i+j]$.




Subtracting an Integer from a Pointer


❑ If p points to $a[i]$, then $p - j$ points to $a[i - j]$.

❑ Example:


```
p = &a[8];
```



```
q = p - 3;
```



```
p -= 6;
```




Subtracting One Pointer from Another

- ❑ Subtraction = the distance between the pointers
 - measured in array elements
- ❑ If p points to $a[i]$ and q points to $a[j]$, then $p - q$ is equal to $i - j$.
- ❑ Example:

```
p = &a[5];
```

```
q = &a[1];
```



```
i = p - q;    /* i is 4 */
```

```
i = q - p;    /* i is -4 */
```

Subtracting Pointer from Another

- ❑ Operations that cause undefined behavior:
 - Performing arithmetic on a pointer that doesn't point to an array element
 - Subtracting pointers unless both point to elements of the same array

Comparing Pointers

- ❑ Pointers can be compared via relational operators ($<$, $<=$, $>$, $>=$) and the equality operators ($==$ $!=$).
 - Using relational operators is meaningful only for pointers to elements of the same array.
- ❑ The outcome of the comparison depends on the relative positions of the two elements in the array.
- ❑ After the assignments

```
p = &a[5];
```

```
q = &a[1];
```

the value of $p <= q$ is 0

the value of $p >= q$ is 1.

Pointers to Compound Literals (C99)

- ❑ It's legal for a pointer to point to an element within an array created by a compound literal:

```
int *p = (int []) {3, 0, 3, 4, 1};
```

- ❑ Using a compound literal saves us the trouble of first declaring an array variable and then making `p` point to the first element of that array:

```
int a[] = {3, 0, 3, 4, 1};
```

```
int *p = &a[0];
```


Using Pointers for Array Processing

- ❑ Use pointer arithmetic to visit the elements of an array by repeatedly incrementing a pointer variable.
- ❑ A loop that sums the elements of an array `a`:

```
#define N 10
```

```
...
```

```
int a[N], sum, *p;
```

```
...
```


```
sum = 0;
```

```
for (p = &a[0]; p < &a[N]; p++)
```


```
    sum += *p;
```

Using Pointers for Array Processing


At the end of the first iteration:



At the end of the second iteration:



At the end of the third iteration:



Using Pointers for Array Processing

- ❑ The condition `p < &a[N]` in the `for` statement deserves special mention.
- ❑ It's legal to apply the address operator to `a[N]`, even though this element doesn't exist.
- ❑ Pointer arithmetic may save execution time.
- ❑ However, some C compilers produce better code for loops that rely on subscripting.

Combining the * and ++ Operators

- ❑ C programmers often combine the * (indirection) and ++ operators.
- ❑ A statement that modifies an array element and then advances to the next element:

```
a[i++] = j;
```

- ❑ The corresponding pointer version:

```
*p++ = j;
```

- ❑ Because the postfix version of ++ takes precedence over *, the compiler sees this as

```
*(p++) = j;
```

Combining the * and ++ Operators

- Possible combinations of * and ++:

Expression

Meaning

*p++ or * (p++) Value of expression is *p before increment;
increment p later

(*p) ++ Value of expression is *p before increment;
increment *p later

*++p or * (++p) Increment p first;
value of expression is *p after increment

++*p or ++ (*p) Increment *p first;
value of expression is *p after increment

Combining the * and ++ Operators

- ❑ The most common combination of * and ++ is *p++, which is handy in loops.
- ❑ Instead of writing

```
for (p = &a[0]; p < &a[N]; p++)  
    sum += *p;
```

to sum the elements of the array a, we could write

```
p = &a[0];  
while (p < &a[N])  
    sum += *p++;
```

Combining the * and ++ Operators

- ❑ The * and -- operators mix in the same way as * and ++.
- ❑ For an application that combines * and --, let's return to the stack example of Chapter 10.
- ❑ The original version of the stack relied on an integer variable named `top` to keep track of the “top-of-stack” position in the `contents` array.
- ❑ Let's replace `top` by a pointer variable that points initially to element 0 of the `contents` array:

```
int *top_ptr = &contents[0];
```

Combining the * and ++ Operators

- ❑ The new push and pop functions:

```
void push(int i)
{
    if (is_full())
        stack_overflow();
    else
        *top_ptr++ = i;
}

int pop(void)
{
    if (is_empty())
        stack_underflow();
    else
        return *--top_ptr;
}
```


Using an Array Name as a Pointer

- ❑ Pointer arithmetic is one way in which arrays and pointers are related.
- ❑ Another key relationship:
The name of an array can be used as a pointer to the first element in the array.
- ❑ This relationship simplifies pointer arithmetic and makes both arrays and pointers more versatile.

Using an Array Name as a Pointer

- ❑ Suppose that `a` is declared as follows:

```
int a[10];
```

- ❑ Examples of using `a` as a pointer:

```
*a = 7;    /* stores 7 in a[0] */
```

```
*(a+1) = 12; /* stores 12 in a[1] */
```

- ❑ In general, `a + i` is the same as `&a[i]`.

- Both represent a pointer to element `i` of `a`.

- ❑ Also, `*(a+i)` is equivalent to `a[i]`.

- Both represent element `i` itself.

Using an Array Name as a Pointer

- ❑ The fact that an array name can serve as a pointer makes it easier to write loops that step through an array.
- ❑ Original loop:

```
for (p = &a[0]; p < &a[N]; p++)  
    sum += *p;
```

- ❑ Simplified version:

```
for (p = a; p < a + N; p++)  
    sum += *p;
```

Using an Array Name as a Pointer

- ❑ Although an array name can be used as a pointer, it's not possible to assign it a new value.
- ❑ Attempting to make it point elsewhere is an error:

```
while (*a != 0)
    a++;                /* ** WRONG ** */
```

- ❑ This is no great loss; we can always copy `a` into a pointer variable, then change the pointer variable:

```
p = a;
while (*p != 0)
    p++;
```

Program: Reversing a Series of Numbers

- ❑ The `reverse.c` program of Chapter 8 reads 10 numbers, then writes the numbers in reverse order.
- ❑ The original program stores the numbers in an array, with subscripting used to access elements of the array.
- ❑ `reverse3.c` is a new version of the program in which subscripting has been replaced with pointer arithmetic.

reverse3.c

```
/* Reverses a series of numbers (pointer version) */

#include <stdio.h>

#define N 10

int main(void)
{
    int a[N], *p;

    printf("Enter %d numbers: ", N);
    for (p = a; p < a + N; p++)
        scanf("%d", p);

    printf("In reverse order:");
    for (p = a + N - 1; p >= a; p--)
        printf(" %d", *p);
    printf("\n");

    return 0;
}
```

Another example about the pointer and address

Here is sample output:

```
// pnt_add.c -- pointer addition
```

```
#include <stdio.h>
```

```
#define SIZE 4
```

```
int main(void)
```

```
{
```

```
    short dates [SIZE];
```

```
    short * pti;
```

```
    short index;
```

```
    double bills[SIZE];
```

```
    double * ptf;
```

```
    pti = dates;    // assign address of array to pointer
```

```
    ptf = bills;
```

```
    printf("%23s %15s\n", "short", "double");
```

```
    for (index = 0; index < SIZE; index ++)
```


```
        printf("pointers + %d: %10p %10p\n",  
               index, pti + index, ptf + index);
```

```
    return 0;
```

```
}
```

	short	double
pointers + 0:	0x7fff5fbff8dc	0x7fff5fbff8a0
pointers + 1:	0x7fff5fbff8de	0x7fff5fbff8a8
pointers + 2:	0x7fff5fbff8e0	0x7fff5fbff8b0
pointers + 3:	0x7fff5fbff8e2	0x7fff5fbff8b8

pointer addition increase by 2
since `pti` is type `int`



```
int dates[y], *pti;  
pti = dates; (or pti = & dates[0];)
```



pointer variable `pti` is assigned the
address of the first element of the array `dates`

As a result of C's cleverness, we have the following equalities:

```
dates + 2 == &date[2]           // same address  
*(dates + 2) == dates[2]        // same value
```


Array Arguments (Revisited)

- ❑ When passed to a function, an array name is treated as a pointer.

- ❑ Example:

```
int find_largest(int a[], int n)
{
    int i, max;

    max = a[0];
    for (i = 1; i < n; i++)
        if (a[i] > max)
            max = a[i];
    return max;
}
```

- ❑ A call of `find_largest`:

```
largest = find_largest(b, N);
```

This call causes a pointer to the first element of `b` to be assigned to `a`; the array itself isn't copied.

Consequences of Array Arguments

- ❑ *Consequence 1:* When an ordinary variable is passed to a function, its value is copied; any changes to the corresponding parameter don't affect the variable.
 - In contrast, an array used as an argument isn't protected against change.

- ❑ *Consequence 2:* The time required to pass an array to a function doesn't depend on the size of the array.
 - There's no penalty for passing a large array, since no copy of the array is made.

- ❑ *Consequence 3:* An array parameter can be declared as a pointer if desired.

Array Arguments (Revisited)

- ❑ For example, the following function modifies an array by storing zero into each of its elements:

```
void store_zeros(int a[], int n)
{
    int i;

    for (i = 0; i < n; i++)
        a[i] = 0;
}
```

Array Arguments (Revisited)

- ❑ To indicate that an array parameter won't be changed, we can include the word `const` in its declaration:

```
int find_largest(const int a[], int n)
{
    ...
}
```

- ❑ If `const` is present, the compiler will check that no assignment to an element of `a` appears in the body of `find_largest`.

Array Arguments (Revisited)

- ❑ *Consequence 3*: An array parameter can be declared as a pointer if desired.

- ❑ `find_largest` could be defined as follows:

```
int find_largest(int *a, int n)
{
    ...
}
```

- ❑ Declaring `a` to be a pointer is equivalent to declaring it to be an array

Array Arguments (Revisited)

- ❑ Although declaring a *parameter* to be an array is the same as declaring it to be a pointer, the same isn't true for a *variable*.
- ❑ The following declaration causes the compiler to set aside space for 10 integers:

```
int a[10];
```

- ❑ The following declaration causes the compiler to allocate space for a pointer variable:

```
int *a;
```

Array Arguments (Revisited)

- ❑ The following declaration give a pointer variable:

```
int *a;
```

- ❑ `a` is not an array; attempting to use it as an array can have disastrous results.
- ❑ For example, the assignment

```
*a = 0;    /* ** WRONG ** */
```

will store 0 where `a` is pointing.

- ❑ Since we don't know where `a` is pointing, the effect on the program is undefined.

Array Arguments (Revisited)

- ❑ *Consequence 4*: A function with an array parameter can be passed an array “slice”—a sequence of consecutive elements.
- ❑ An example that applies `find_largest` to elements 5 through 14 of an array `b`:

```
largest = find_largest(&b[5], 10);
```


Using a Pointer as an Array Name

- ❑ C allows us to subscript a pointer as though it were an array name:

```
#define N 10
```

```
...
```

```
int a[N], i, sum = 0, *p = a;
```

```
...
```


```
for (i = 0; i < N; i++)
```

```
    sum += p[i];
```

The compiler treats `p[i]` as `*(p+i)`.

Processing the Elements of a Multidimensional Array

- ❑ C stores two-dimensional arrays in row-major order.
- ❑ Layout of an array with r rows:



- ❑ If p initially points to the element in row 0, column 0, we can visit every element in the array by incrementing p repeatedly.

Processing Multidimensional Array

- ❑ Consider the problem of initializing all elements of the following array to zero:

```
int a[NUM_ROWS][NUM_COLS];
```

- ❑ The obvious technique would be to use nested `for` loops:

```
int row, col;
```

```
...
```

```
for (row = 0; row < NUM_ROWS; row++)
```

```
    for (col = 0; col < NUM_COLS; col++)
```

```
        a[row][col] = 0;
```

- ❑ If we view `a` as a one-dimensional array of integers, a single loop is sufficient:

```
int *p;
```

```
...
```

```
for (p = &a[0][0]; p <= &a[NUM_ROWS-1][NUM_COLS-1]; p++)
```

```
    *p = 0;
```

Processing Multidimensional Array

- ❑ A pointer variable `p` can also be used for processing the elements in just one *row* of a two-dimensional array.
- ❑ To visit the elements of row `i`, we'd initialize `p` to point to element 0 in row `i` in the array `a`:

```
p = &a[i][0];
```

or we could simply write

```
p = a[i];
```

Processing the row of Multidimensional Array

- ❑ For any two-dimensional array a , the expression $a[i]$ is a pointer to the first element in row i .

```
int a[20][10];
```

- ❑ Why? $a[i]$ is equivalent to $*(a + i)$.
- ❑ Thus, $\&a[i][0]$ is the same as $\&(* (a[i] + 0))$, which is equivalent to $\&*a[i]$.
- ❑ This is the same as $a[i]$, since the $\&$ and $*$ operators cancel.

Processing the row of Multidimensional Array

- ❑ A loop that clears row i of the array a :

```
int a[NUM_ROWS][NUM_COLS], *p, i;
```

```
...
```

```
for (p = a[i]; p < a[i] + NUM_COLS; p++)  
    *p = 0;
```

- ❑ Since $a[i]$ is a pointer to row i of the array a , we can pass $a[i]$ to a function that's expecting a one-dimensional array as its argument.
- ❑ A function designed to work with one-dimensional arrays will also work with a row belonging to a two-dimensional array.

Processing Row of a Multidimensional Array

- ❑ Consider `find_largest`, which was originally designed to find the largest element of a one-dimensional array.
- ❑ We can just as easily use `find_largest` to determine the largest element in row `i` of the two-dimensional array `a`:

```
largest = find_largest(a[i], NUM_COLS);
```

Processing the row of Multidimensional Array

- ❑ Processing the elements in a *column* of a two-dimensional array isn't as easy, because arrays are stored by row, not by column.

- ❑ A loop that clears column *i* of the array *a*:

```
int a[NUM_ROWS][NUM_COLS], (*p)[NUM_COLS], i;  
...  
for (p = &a[0]; p < &a[NUM_ROWS]; p++)  
    (*p)[i] = 0;
```


Using the Name of a Multidimensional Array as a Pointer

- ❑ The name of *any* array can be used as a pointer, regardless of dimensions, but some care is required.

- ❑ Example:

```
int a[NUM_ROWS][NUM_COLS];
```

`a` is *not* a pointer to `a[0][0]`; instead, it's a pointer to `a[0]`.

- ❑ C regards `a` as a one-dimensional array whose elements are one-dimensional arrays.
- ❑ When used as a pointer, `a` has type `int (*)[NUM_COLS]` (pointer to an integer array of length `NUM_COLS`).

Using the Name of a Multidimensional Array as a Pointer

- ❑ `a` points to `a[0]` is useful for simplifying loops that process the elements of a two-dimensional array.
- ❑ Instead of writing

```
for (p = &a[0]; p < &a[NUM_ROWS]; p++)  
    (*p)[i] = 0;
```

to clear column `i` of the array `a`, we can write

```
for (p = a; p < a + NUM_ROWS; p++)  
    (*p)[i] = 0;
```

Pointers and Variable-Length Arrays (C99)

- ❑ Pointers are allowed to point to elements of variable-length arrays (VLAs).
- ❑ An ordinary pointer variable would be used to point to an element of a one-dimensional VLA:

```
void f(int n)
{
    int a[n], *p;
    p = a;
    ...
}
```

Pointers and Variable-Length Arrays (C99)

- ❑ When the VLA has more than one dimension, the type of the pointer depends on the length of each dimension except for the first.
- ❑ A two-dimensional example:

```
void f(int m, int n)
{
    int a[m][n], (*p)[n];
    p = a;
    ...
}
```

Since the type of `p` depends on `n`, which isn't constant, `p` is said to have a ***variably modified type***.

Pointers and Variable-Length Arrays (C99)

- ❑ The validity of an assignment such as `p = a` can't always be determined by the compiler.
- ❑ The following code will compile but is correct only if `m` and `n` are equal:

```
int a[m][n], (*p)[m];
```

```
p = a;
```

- ❑ If `m` is not equal to `n`, any subsequent use of `p` will cause undefined behavior.