

SQL Cheat Sheet: Basics

Command	Syntax	Description	Example
SELECT	SELECT column1, column2, ... FROM table_name;	SELECT statement is used to fetch data from a database.	SELECT city FROM placesInterests;
WHERE	SELECT column1, column2, ... FROM table_name WHERE condition;	where clause is used to extract only those records that fulfill a specified condition.	SELECT * FROM placesInterests WHERE city = 'Rome' ;
COUNT	SELECT COUNT * FROM table_name ;	count is a function that takes the name of a column as argument and counts the number of rows when the column is not NULL.	SELECT COUNT(country) FROM placesInterests WHERE country='Canada' ;
DISTINCT	SELECT DISTINCT columnname FROM table_name;	distinct function is used to specify that the statement is a query which returns unique values in specified columns.	SELECT DISTINCT country FROM placesInterests WHERE type='historical';
LIMIT	SELECT * FROM table_name LIMIT number;	limit is a clause to specify the maximum number of rows the result set must have.	SELECT * FROM placesInterests WHERE category='person' LIMIT 10;
INSERT	INSERT INTO table_name (column1,column2,column3,...) VALUES(column1,column2,column3,...);	insert is used to insert new rows in the table.	INSERT INTO placesInterests (name,type,city,country,airport) VALUES('Napaea Waterfalls','Nature','Toronto','Canada','Pearson');
UPDATE	UPDATE table_name SET (column1)=(value1) WHERE (condition);	update used to update the rows in the table.	UPDATE placesInterests SET name = 'Napaea Falls' WHERE name = 'Napaea Waterfalls' ;
DELETE	DELETE FROM table_name WHERE (condition);	delete statement is used to remove rows from the table which are specified in the WHERE condition.	DELETE FROM placesInterests WHERE city IN ('Rome','Vienna');

Author(s)
[Mehdi Saeidi](#)

