

SQL Cheat Sheet: JOIN statements

Joins			
Type	Syntax	Description	Example
Cartesian Join	SELECT column_name(s) FROM table1 CROSS JOIN table2;	The CROSS JOIN is used to generate a paired combination of each row of the first table with each row of the second table.	SELECT EMP1_ID,EMP1_LAST_NAME,EMP1_DEPT_NAME FROM EMP1,EMP2;
Inner Join	SELECT column_name(s) FROM table1 INNER JOIN table2 ON (table1.column_name = table2.column_name WHERE condition);	You can use the inner join in a SELECT statement to retrieve only the rows that satisfy the join conditions on every specified table.	SELECT E.EMP_ID,E.EMP_LAST_NAME,DEPT_NAME FROM EMPLOYEES AS E,DEPARTMENTS AS D ON E.DEPT_ID=D.DEPT_ID WHERE E.EMP_ID > 5;
Left Outer Join	SELECT column_name(s) FROM table1 LEFT OUTER JOIN table2 ON (table1.column_name = table2.column_name WHERE condition);	The LEFT OUTER JOIN will return all records from the left side table and the matching records from the right table.	SELECT E.EMP_ID,E.EMP_LAST_NAME,DEPT_NAME FROM EMPLOYEES AS E LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEPT_ID=D.DEPT_ID;
Right Outer Join	SELECT column_name(s) FROM table1 RIGHT OUTER JOIN table2 ON (table1.column_name = table2.column_name WHERE condition);	The RIGHT OUTER JOIN returns all records from the right table, and the matching records from the left table.	SELECT E.EMP_ID,E.EMP_LAST_NAME,DEPT_NAME FROM EMPLOYEES AS E RIGHT OUTER JOIN DEPARTMENTS AS D ON E.DEPT_ID=D.DEPT_ID;
Full Outer Join	SELECT column_name(s) FROM table1 FULL OUTER JOIN table2 ON (table1.column_name = table2.column_name WHERE condition);	The FULL OUTER JOIN clause results in the inclusion of rows from two tables. If a value is missing when rows are joined, that value is NULL in the result table.	SELECT E.EMP_ID,E.EMP_LAST_NAME,DEPT_NAME FROM EMPLOYEES AS E FULL OUTER JOIN DEPARTMENTS AS D ON E.DEPT_ID=D.DEPT_ID;
Self Join	SELECT column_name(s) FROM table1 T1, table2 T2 WHERE condition;	A self join is regular join but it can be used to joined with itself.	SELECT E.EMP_ID FROM EMPLOYEES AS E JOIN EMPLOYEES AS D ON E.MANAGER_ID = D.EMP_ID WHERE E.EMP_ID < D.EMP_ID;
Joins in MySQL using phpMyAdmin			
Full Outer Join	SELECT column_name(s) FROM table1 LEFT OUTER JOIN table2 ON (table1.column_name = table2.column_name WHERE condition) UNION SELECT column_name(s) FROM table1 RIGHT OUTER JOIN table2 ON (table1.column_name = table2.column_name WHERE condition);	The UNION operator is used to combine the result-set of two or more SELECT statements.	SELECT E.EMP_ID,E.EMP_LAST_NAME,DEPT_NAME FROM EMPLOYEES AS E LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEPT_ID=D.DEPT_ID UNION SELECT E.EMP_ID,E.EMP_LAST_NAME,DEPT_NAME FROM EMPLOYEES AS E RIGHT OUTER JOIN DEPARTMENTS AS D ON E.DEPT_ID=D.DEPT_ID;

Author(s)

DM Nisha

