

Hands-on Lab: Using Views in MySQL using phpMyAdmin



Estimated time needed: 20 minutes

In this lab, you will learn about using views. In SQL, a view is an alternative way of representing data that exists in one or more tables. Just like a real table, it contains rows and columns. The fields in a view are fields from one or more real tables in the database. Though views can be queried like a table, views are dynamic; only the definition of the view is stored, not the data.

Objectives

After completing this lab, you will be able to:

- Create a View and show a selection of data for a given table
- Update a View to combine two or more tables in meaningful ways
- Drop a created View

Software Used in this Lab

In this lab, you will use [MySQL](#). MySQL is a Relational Database Management System (RDBMS) designed to efficiently store, manipulate, and retrieve data.



To complete this lab you will utilize MySQL relational database service available as part of IBM Skills Network Labs (SN Labs) Cloud IDE. SN Labs is a virtual lab environment used in this course.

Database Used in this Lab

The database used in this lab is a sample HR database. This HR database schema consists of five tables called `EMPLOYEES`, `JOB_HISTORY`, `JOBS`, `DEPARTMENTS`, and `LOCATIONS`. Each table has a few rows of sample data. The following diagram shows the tables for the HR database:

SAMPLE HR DATABASE TABLES

EMPLOYEES

EMP_ID	F_NAME	L_NAME	SSN	B_DATE	SEX	ADDRESS	JOB_ID	SALARY	MANAGER_ID	DEP_ID
E1001	John	Thomas	123456	1976-01-09	M	5631 Rice, OakPark,IL	100	100000	30001	2
E1002	Alice	James	123457	1972-07-31	F	980 Berry Ln, Elgin,IL	200	80000	30002	5
E1003	Steve	Wells	123458	1980-08-10	M	291 Springs, Gary,IL	300	50000	30002	5

JOB_HISTORY

EMPL_ID	START_DATE	JOBS_ID	DEPT_ID
E1001	2000-01-30	100	2
E1002	2010-08-16	200	5
E1003	2016-08-10	300	5

JOBS

JOB_ID	JOB_TITLE	MIN_SALARY	MAX_SALARY
100	Sr. Architect	60000	100000
200	Sr.SoftwareDeveloper	60000	80000
300	Jr.SoftwareDeveloper	40000	60000

DEPARTMENTS

DEPT_ID_DEP	DEP_NAME	MANAGER_ID	LOC_ID
2	Architect Group	30001	L0001
5	Software Development	30002	L0002
7	Design Team	30003	L0003

LOCATIONS

LOC_ID	DEP_ID_LOC
L0001	2
L0002	5
L0003	7

Follow the steps below to create the database and the tables.

1. Open the MySQL interface from Skills Network menu.
2. Create a new database and name it HR.
3. Load and execute the script shared in the link below to create the necessary tables.

[HR_Database_Create_Tables_Script.sql](#)

4. Load all the tables with the data available in the CSV files shared below.

[Departments.csv](#)

[Employees.csv](#)

[Jobs.csv](#)

[Locations.csv](#)

[JobsHistory.csv](#)

Note: Please refer to the instruction in the lab ["Create and Load Tables using SQL Scripts"](#) for instructions regarding loading scripts in MySQL.

Task 1: Create a View

In this exercise, you will create a View and show a selection of data for a given table.

1. Let's create a view called `EMPSALARY` to display salary along with some basic sensitive data of employees from the HR database. To create the `EMPSALARY` view from the `EMPLOYEES` table, Copy the code below and paste it to the textarea of the **SQL** page. Click **Go**.

```
CREATE VIEW EMPSALARY AS
SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, SALARY
FROM EMPLOYEES;
```

```
1 CREATE VIEW EMP_SALARY AS
2 SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, SALARY
3 FROM EMPLOYEES;
```

COLUMNS
EMP_ID
F_NAME
L_NAME
SSN
B_DATE
SEX
ADDRESS
JOB_ID
SALARY
MANAGER_ID
DEP_ID

SELECT * SELECT INSERT UPDATE DELETE Clear Format Get auto-saved query

☐ Bind parameters

Delimiter ;] ☐ Show this query here again ☐ Retain query box ☐ Rollback when finished ☒ Enable foreign key checks Go

Hide query box

✓ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0116 seconds.)

CREATE VIEW EMP_SALARY AS SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, SALARY FROM EMPLOYEES

[Edit inline] [Edit] [Create PHP code]

2. Using SELECT, query the EMP_SALARY view to retrieve all the records. Use the following statement.

```
SELECT * FROM EMP_SALARY;
```

✓ Showing rows 0 - 9 (10 total, Query took 0.0014 seconds.)

SELECT * FROM EMP_SALARY

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code]

☐ Show all | Number of rows: 25 | Filter rows: Search this table

+ Options

				EMP_ID	F_NAME	L_NAME	B_DATE	SEX	SALARY
☐	Edit	Copy	Delete	E1001	John	Thomas	1976-09-01	M	100000.00
☐	Edit	Copy	Delete	E1002	Alice	James	1972-07-31	F	80000.00
☐	Edit	Copy	Delete	E1003	Steve	Wells	1980-10-08	M	50000.00
☐	Edit	Copy	Delete	E1004	Santosh	Kumar	1985-07-20	M	60000.00
☐	Edit	Copy	Delete	E1005	Ahmed	Hussain	1981-04-01	M	70000.00
☐	Edit	Copy	Delete	E1006	Nancy	Allen	1978-06-02	F	90000.00
☐	Edit	Copy	Delete	E1007	Mary	Thomas	1975-05-05	F	65000.00
☐	Edit	Copy	Delete	E1008	Bharath	Gupta	1985-06-05	M	65000.00
☐	Edit	Copy	Delete	E1009	Andrea	Jones	1990-09-07	F	70000.00
☐	Edit	Copy	Delete	E1010	Ann	Jacob	1982-03-30	F	70000.00

☐ Check all | With selected: Edit Copy Delete Export

Task 2: Update a View

In this exercise, you will update a View to combine two or more tables in meaningful ways.

Assume that the EMP_SALARY view we created in Task 1 doesn't contain enough salary information, such as max/min salary and the job title of the employees. For this, we need to get information from other tables in the database. You need all columns from EMPLOYEES table used above, except for SALARY. You also need the columns JOB_TITLE, MIN_SALARY, MAX_SALARY of the JOBS table. The command to be used is as follows:

```
CREATE OR REPLACE VIEW EMP_SALARY AS
SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, JOB_TITLE,
MIN_SALARY, MAX_SALARY
FROM EMPLOYEES, JOBS
WHERE EMPLOYEES.JOB_ID = JOBS.JOB_ID;
```

Run SQL query/queries on table HR.EMPLOYEES: ⓘ

```
1 CREATE OR REPLACE VIEW EMP_SALARY AS
2 SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, JOB_TITLE, MIN_SALARY, MAX_SALARY
3 FROM EMPLOYEES, JOBS
4 WHERE EMPLOYEES.JOB_ID = JOBS.JOB_ID;
```

Columns

EMP_ID
F_NAME
L_NAME
SSN
B_DATE
SEX
ADDRESS
JOB_ID
SALARY
MANAGER_ID
DEP_ID

SELECT *
SELECT
INSERT
UPDATE
DELETE
Clear
Format
Get auto-saved query

☐ Bind parameters ⓘ

[Delimiter
;
]]

☐ Show this query here again
☐ Retain query box
☐ Rollback when finished
☒ Enable foreign key checks

Go

Hide query box

✔ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0461 seconds.)

```
CREATE OR REPLACE VIEW EMP_SALARY AS SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, JOB_TITLE, MIN_SALARY, MAX_SALARY FROM EMPLOYEES, JOBS WHERE EMPLOYEES.JOB_ID = JOBS.JOB_ID
```

[\[Edit inline\]](#) [\[Edit\]](#) [\[Create PHP code\]](#)

NOTE: The technique used here to combine data from two tables is called implicit inner join. You will learn more about joins later on. For now, just assume you are combining the data of two different tables, EMPLOYEES and JOBS by connecting their respective columns JOB_ID and JOB_IDENT, since both the columns contain common unique data. You can have a look at the database description, shared at the beginning of the lab, to verify this.

2. Using SELECT, query the updated EMP_SALARY view to retrieve all the records. Copy the code below and paste it to the textarea of the **SQL** page. Click go.

```
SELECT * FROM EMP_SALARY;
```

✔ Showing rows 0 - 9 (10 total, Query took 0.0019 seconds.)

```
SELECT * FROM EMP_SALARY
```

☐ Profiling [\[Edit inline\]](#) [\[Edit\]](#) [\[Explain SQL\]](#) [\[Create PHP code\]](#) [\[Refresh\]](#)

☐ Show all

Number of rows: 25

Filter rows: Search this table

+ Options

EMP_ID

F_NAME

L_NAME

B_DATE

SEX

JOB_TITLE

MIN_SALARY

MAX_SALARY

☐	Edit	Copy	Delete	E1001	John	Thomas	1976-09-01	M	Sr. Architect	60000.00	100000.00
☐	Edit	Copy	Delete	E1002	Alice	James	1972-07-31	F	Sr. Software Developer	60000.00	80000.00
☐	Edit	Copy	Delete	E1003	Steve	Wells	1980-10-08	M	Jr. Software Developer	40000.00	60000.00
☐	Edit	Copy	Delete	E1004	Santosh	Kumar	1985-07-20	M	Jr. Software Developer	40000.00	60000.00
☐	Edit	Copy	Delete	E1005	Ahmed	Hussain	1981-04-01	M	Jr. Architect	50000.00	70000.00
☐	Edit	Copy	Delete	E1006	Nancy	Allen	1978-06-02	F	Lead Architect	70000.00	100000.00
☐	Edit	Copy	Delete	E1007	Mary	Thomas	1975-05-05	F	Jr. Designer	60000.00	70000.00
☐	Edit	Copy	Delete	E1008	Bharath	Gupta	1985-06-05	M	Jr. Designer	60000.00	70000.00
☐	Edit	Copy	Delete	E1009	Andrea	Jones	1990-09-07	F	Sr. Designer	70000.00	90000.00
☐	Edit	Copy	Delete	E1010	Ann	Jacob	1982-03-30	F	Sr. Designer	70000.00	90000.00

☐ Check all With selected: [Edit](#) [Copy](#) [Delete](#) [Export](#)

Task 3: Drop a View

In this exercise, you will drop the created View EMP_SALARY. Use the code below.

```
DROP VIEW EMP_SALARY;
```

Run SQL query/queries on table HR.EMPLOYEES: ⓘ

1 DROP VIEW EMP_SALARY;

Columns
EMP_ID
F_NAME
L_NAME
SSN
B_DATE
SEX
ADDRESS
JOB_ID
SALARY
MANAGER_ID
DEP_ID

SELECT * SELECT INSERT UPDATE DELETE Clear Format Get auto-saved query

☐ Bind parameters ⓘ

[Delimiter ;] ☐ Show this query here again ☐ Retain query box ☐ Rollback when finished ☒ Enable foreign key checks Go

Hide query box

✓ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0056 seconds.)

DROP VIEW EMP_SALARY

[Edit inline] [Edit] [Create PHP code]

Console

Using SELECT, you can verify whether the EMP_SALARY view has been deleted or not. Copy the code below and paste it to the textarea of the SQL page. Click Go.

```
SELECT * FROM EMP_SALARY;
```

9
10
11 SELECT * FROM EMP_SALARY;

MANAGER_ID
DEP_ID

SELECT * SELECT INSERT UPDATE DELETE Clear Format Get auto-saved query

☐ Bind parameters ⓘ

[Delimiter ;] ☐ Show this query here again ☐ Retain query box ☐ Rollback when finished ☒ Enable foreign key checks Go

Hide query box

Error

SQL query: [Copy](#) ⓘ

SELECT * FROM EMP_SALARY LIMIT 0, 25

MySQL said: ⓘ

#1146 - Table 'HR.EMP_SALARY' doesn't exist

Console

Practice Problems

Try to solve the following practice problems based on your learning in this lab.

1. Create a view "EMP_DEPT" which has the following information.

EMP_ID, FNAME, LNAME and DEP_ID from EMPLOYEES table

► [Click here for the solution](#)

```
CREATE VIEW EMP_DEPT AS  
SELECT EMP_ID, F_NAME, L_NAME, DEP_ID  
FROM EMPLOYEES;
```

2. Modify "EMP_DEPT" such that it displays Department names instead of Department IDs. For this, we need to combine information from EMPLOYEES and DEPARTMENTS as follows.

EMP_ID, FNAME, LNAME from EMPLOYEES table and
DEP_NAME from DEPARTMENTS table, combined over the columns DEP_ID and DEPT_ID_DEP.

► [Click here for the solution](#)

```
CREATE OR REPLACE VIEW EMP_DEPT AS  
SELECT EMP_ID, F_NAME, L_NAME, DEP_NAME  
FROM EMPLOYEES, DEPARTMENTS  
WHERE EMPLOYEES.DEP_ID = DEPARTMENTS.DEPT_ID_DEP;
```

3. Drop the view "EPM_DEPT".

► Click here for the solution

```
DROP VIEW EMP_DEPT
```

Conclusion

Congratulations on completing this lab. You now have hands-on knowledge of how to use Views in SQL.

You have now learned how to:

- Create a new View as per the requirement
- Modify a view to include data from multiple tables in the data set
- Drop a view

Author(s)

[Lakshmi Holla](#)

[Malika Singla](#)

Additional Contributor(s)

[Abhishek Gagneja](#)

© IBM Corporation 2023. All rights reserved.