

SECTION 3: PYTHON OBJECT AND DATA STRUCTURE BASICS, 2 hrs 2 mins, 33 parts

• 22/36 Dictionaries in Python

○ theory

- -> unordered mappings for storing objects
 - key value pairing (rather than indices)
 - {'key1':'value1', 'key2':'value2'}
- -> dictionaries -> objects retrieved by key name
 - a dictionary can't be sorted -> it puts key value pairs wherever is more efficient
 - -> but lists can be retrieved by location / ordered / indexed / slices

○ in JN

- -> my_dict = {'key1':'value1', 'key2':'value2'}
- -> we want to return values from the dictionary
 - -> my_dict['key1'] <- this returns the value stored at the key called key1
 - -> **the indexes are replaced with keys**
 - -> e.g you could store the value of apple at the key apple -> then it would return the cost of apples when it was called
- -> they can store many different datatypes
 - -> integers
 - -> arrays
 - -> **nested dictionaries -> then to return the value of the element at that index, it would be []**
 - -> d['k3']['insidekey']
- -> arrays and dictionaries
 - **you can set an element stored at the key an entire array**
 - -> **to extract this, it's name_of_dictionary['key_is_stored_at']**
 - -> this is the array -> which you can then [extract a value with the index typed in these brackets]
 - -> you can then letter.upper() <- operate on the element you've extracted
 - -> in another example -> he's [] called two keys next to each other
 - -> **d['key'][2].upper() -> this returns C**
 - in this example, he's taking the second element in the list stored under 'key' (which is the letter c) and is making it uppercase
- -> adding in a new key value pair
 - -> **d = {'k1':100, 'k2':200}**
 - -> if we want to add a k3
 - **d['k3'] = 300**
 - -> you can also change the value stored at k1
 - d['k1']='NEW VALUE'
 - -> then it's appearing when d is called
- -> methods on dictionaries
 - we have a dictionary called d
 - **d.keys() <- this returns all of the keys**
 - **d.values() <- this returns the values**
 - **d.items() <- this returns all of the items**
- -> summary
 - the syntax
 - you can change the value of the element stored at the key
 - -> you can nest objects inside a dictionary