


• How convolutional networks / layers work

- -> in this example there is an image
- -> the image is made of pixels which can be divided into a grid
- **properties of convolutional maps**
 - -> a feature map / filter
 - -> properties of the convolutional map
 - the input size <- the number of filters and the same size of the filters
 - -> each of the filters is looking for a pattern in the image (e.g the presence of paws)
 - -> the filters are found by the convolutional neural network
- **how we look for filters in the image**
 - -> one filter might look for a diagonal line, a horizontal line or a straight line
 - -> there are 32 different ones in this example
 - -> there is a filter size
 - -> 3x3 spots in the image
 - -> defining how closely those spots match
 - -> doing the dot product of the filter with the image we have
 - -> the component of that feature in the direction of this image
 - -> and each filter is looking for the presence of a different feature in the image
 - -> you can store the outputs of the filters (different dot products with the image we have) in a matrix
 - -> this is a response map
 - -> there are 3x3 samples -> r, g, b




- -> it's telling you about the presence of features in the image
- -> this is done for many different features -> computationally heavy

• Pooling

- -> there is an output feature map
- -> running the calculations is computationally heavy
- -> looking at for example - the presence of different line types, to the combinations of different lines which we have -> pooling the information about the different lines which we have
 - -> we are building up to this, first from determining if lines are present - and then to finding correlations between those different lines which are present -> to identify the presence of e.g eyes in an image

- -> **you can add padding around the image**

- -> so that you can draw a square which makes the pixels on the edge in the centre
- -> this allows you to include the pixels which are on the edge of the image



- -> **stride**

- -> this is how much the sample box is moved each time
- -> for example 2px -> moving the sample box by 2px each time the calculations are ran

- -> **a pooling operation**

- -> min
- -> max
- -> average
- -> taking specific values from a sample of the output feature
- -> sampling 2x2 areas of the feature map
 - -> taking the min / max / average values of those points
- -> **pooling is taking an average from multiple filters**
 - -> the filter contains a matrix of dot products for a different feature with the pixels in the image
 - -> run that multiple times with different filters that check for the lines
 - -> then take the average of them and put them into another matrix -> this is pooling
 - -> this is done with a stride of 1 (in this example)
 - -> max pooling can be done
 - -> whether the feature exists
- -> **min / max / average tell you different things**
 - -> it's a way of combining the different matrices
 - -> the average presence of the feature, does the feature exist, does the feature not exist
 - -> the three main properties of each convolutional layer are the input size, the number of filters, and the sample size of the filters