Tottie Master Documentation

NKNGO AI Labs

October 26, 2026

Contents

I Documentation Standards 1

1 Agent Documentation Standards 2
- 1.1 Core Documentation Mandate . . . 2
  - 1.1.1 Rule 1: The LaTeX Mandate . . . 2
  - 1.1.2 Rule 2: The Unified Root (`master.tex`) . . . 2
  - 1.1.3 Rule 3: Post-Implementation Documentation Mandate . . . 2
- 1.2 Process Flow Mapping Standards (The Cookbook Format) . . . 2
  - 1.2.1 Structuring the `process_flows/` Directory . . . 3
  - 1.2.2 The Process Cookbook Format . . . 3
- 1.3 Local Orchestration and Observability Standards (`orch-cli`) . . . 3

II Vision 5

2 Why Tottie Exists 6
- 2.1 The Problem: Agents Have Amnesia . . . 6
- 2.2 The Thesis: Intelligence at Write Time . . . 6
- 2.3 Positioning Against the 2026 Field . . . 6
- 2.4 Why It Matters (the human framing) . . . 6

III The Cognition Model 8

3 The Cognition Model: What to Remember, and How a Cue Recalls 9
- 3.1 The Core Realisation: RAG Is One Leg, Not the Animal . . . 9
- 3.2 What Is Worth Remembering: The Salience Gate . . . 9
- 3.3 The Taxonomy of Memory Kinds . . . 9
- 3.4 Memory Becomes Judgment: The `principle` Field . . . 10
- 3.5 How a Cue Retrieves: Typing, Spreading, Completing . . . 10
  - 3.5.1 Cue Typing — "What question is `implement feature A`?" . . . 10
  - 3.5.2 Spreading Activation and Pattern Completion . . . 10
  - 3.5.3 Three Legs, Not One . . . 11
- 3.6 Consolidation: The Sleep Job . . . 11
- 3.7 Reconsolidation: Updating on Access . . . 11
- 3.8 The Ten Minds . . . 11
- 3.9 Neuroscience Basis . . . 11

IV Business and Hackathon 13

4 Hackathon Rules, Dates, and Judging 14
- 4.1 Problem Statements . . . 14
- 4.2 Mandatory Meta Tooling . . . 14

4.3 Dates (all times Eastern) . . . 14
4.4 Hard Rules . . . 14
4.5 Sample Anti-Projects (things to avoid resembling) . . . 15
4.5.1 How Tottie differs from the banned “Basic RAG Application” . . . 15
4.6 Judging Rubric (equally weighted, 0–10) . . . 15
4.7 Prizes We Target . . . 15

5 Hackathon Compliance Ledger **16**
5.1 Statement of Original Contribution . . . 16
5.2 Feature → Commit Ledger . . . 16
5.3 Reuse Disclosure . . . 16

V System Architecture **17**

6 System Architecture **18**
6.1 Overview . . . 18
6.2 The Ten Components . . . 18
6.3 The Tier Model . . . 19
6.4 Write Path (summary) . . . 19
6.5 Recall Path (summary) . . . 19
6.6 Reuse Map (patterns, not files) . . . 19

7 Data Model and Storage **20**
7.1 Storage Decision (documented exception) . . . 20
7.2 Schema . . . 20
7.3 Indexes . . . 21
7.4 Why `memory_links` Exists . . . 21
7.5 Temporal Correctness . . . 22
7.6 Owner Scoping . . . 22
7.7 Embeddings . . . 22

8 Model Providers and the Intelligence Layer **23**
8.1 Provider Abstraction . . . 23
8.2 Component Model Choices . . . 23
8.3 Cost Control . . . 23
8.4 Optional: MCP Sampling (flagged, off by default) . . . 23

9 MCP Surface **25**
9.1 Tools . . . 25
9.2 Resources . . . 25
9.3 Prompt . . . 25
9.4 Dual-Path Recall (the design answer) . . . 25
9.5 Retrieval Is Cue-Typed, Not Just Similar . . . 26

10 Tottie UI and the Live Memory Panel **27**
10.1 Layout . . . 27
10.2 The Panel Is a Live Stream of `memory_events` . . . 27
10.3 The Sleep Button . . . 27
10.4 Tottie Avatar — Drop-In Sprite (frame sets per state) . . . 28
10.5 Ablation Toggle . . . 28

VI Process Flows **29**

11 Process Flow: The Write Path **30**
11.1 The User Says Something Durable . . . 30
11.2 The Observer Decides . . . 30
11.3 The Scribe Structures and Embeds . . . 30
11.4 Reconcile, Route, and Persist . . . 31
11.5 Why This Order Matters . . . 31

12 Process Flow: The Recall Path **32**
12.1 A New Turn Arrives . . . 32
12.2 The Identity Slice Is Always Included . . . 32
12.3 Hybrid Search . . . 32
12.4 The Procedural Slice . . . 32
12.5 The Curator Builds the Context Card . . . 33
12.6 The Deliberate Probe . . . 33
12.7 Ablation . . . 33

13 Process Flow: Cue Typing, Spreading Activation, and Pattern Completion **34**
13.1 The User Types an Instruction, Not a Question . . . 34
13.2 Seeding the Associative Network . . . 34
13.3 Spreading Activation . . . 34
13.4 Pattern Completion . . . 34
13.5 Curate and Inject . . . 35
13.6 Inhibition and Abstention . . . 35

14 Process Flow: Reconcile and Temporal Correctness **36**
14.1 The Decision Table . . . 36
14.2 Worked Example: “I’m vegetarian now” . . . 36
14.3 Why This Is Hard and Why It Wins . . . 37

15 Process Flow: Reconsolidation on Access **38**
15.1 A Memory Is Retrieved . . . 38
15.2 The User Contradicts It . . . 38
15.3 Why It Is Different . . . 38

16 Process Flow: Consolidation (the Sleep Job) **39**
16.1 The User Presses “Sleep” . . . 39
16.2 Semanticisation . . . 39
16.3 Pruning and Scaling . . . 39
16.4 Why This Beat Exists . . . 39

17 Process Flow: The Demo Click-Path **40**
17.1 Beat 1 — Cold Open (Amnesia) . . . 40
17.2 Beat 2 — Tottie Wakes (Identity Pinning) . . . 40
17.3 Beat 3 — Write-Time Magic (Supersede) . . . 40
17.4 Beat 4 — Three Bodies (Cross-Agent Recall) . . . 40
17.5 Beat 5 — Autosave a Mistake . . . 40
17.6 Beat 6 — Restart + Ablation . . . 41
17.7 Beat 7 — The Joke and the Pitch . . . 41

VII Planning **42**

18 Roadmap **43**
18.1 Scope Tiers (9 days, solo, alongside work and study) . . . 43
18.2 Phase Schedule . . . 43
18.3 Gating . . . 44
18.4 Mandates Honoured During the Build . . . 44

19 Master Todo **45**
19.1 Phase 0 — Scaffold . . . 45
19.2 Phase 1 — Documentation . . . 45
19.3 Phase 2 — Deck . . . 45
19.4 Phase 3 — Core Engine . . . 45
19.5 Phase 4 — MCP . . . 45
19.6 Phase 5 — Round-Trip . . . 45
19.7 Phase 6 — UI . . . 46
19.8 Phase 7 — Reconcile / Tags / Identity / Lessons . . . 46
19.9 Phase 8 — Integration + Eval . . . 46
19.10 Phase 9 — Film . . . 46
19.11 Phase 10 — Submit . . . 46

20 Demo Script (3 minutes, screen capture + captions + music) **47**
20.1 Shot List . . . 47
20.2 Narration Captions (verbatim) . . . 47
20.3 Music and Pacing . . . 48

21 Plan Audit (Numbered Outline and Method) **49**
21.1 Audit Method . . . 49
21.2 Independent-Review Questions (for third-party judges) . . . 49
21.3 The Numbered Outline . . . 49
21.4 Audit Ledger . . . 50

Part I

Documentation Standards

Chapter 1

Agent Documentation Standards

1.1 Core Documentation Mandate

This document serves as the absolute source of truth for any Autonomous AI Agent (including Gemini, Loid3, or other models) operating across the ENTIRE NKNGO Portals Ecosystem (including NKNGO-LANG, LearnersQuizNamibia, Pattern, and all future projects). When asked to write, update, or analyze documentation, you MUST adhere to the following universal standardization rules without exception.

1.1.1 Rule 1: The LaTeX Mandate

- **No Markdown Allowed:** All architectural, system, and process flow documentation MUST be written in LaTeX(`.tex`) format.
- **Exceptions:** The **only** Markdown files permitted in the root directory are `README.md` (for GitHub previews) and `GEMINI.md` (the immutable core system prompt for agents).
- **Deletion Clause:** If an agent generates or discovers standalone `.md` files containing system documentation, they must convert them to `.tex`, move them into the `docs/` directory, and permanently delete the `.md` file.

1.1.2 Rule 2: The Unified Root (`master.tex`)

- All documentation lives inside the `/docs` directory.
- You must never create isolated `.tex` files. Every new file must be logically categorized into a subdirectory (e.g., `process_flows/`, `business/`, `system/`) and formally imported via an `\input{}` command inside `docs/master.tex`.

1.1.3 Rule 3: Post-Implementation Documentation Mandate

- Whenever an agent implements a new feature, refactors a system, or writes new code, they MUST immediately document the flows and architecture in the appropriate LaTeX files. Do not wait for the user to ask for documentation after coding; it is an automatic, mandatory requirement.

1.2 Process Flow Mapping Standards (The Cookbook Format)

When mapping flows, DO NOT generate massive dumps of raw code, line-by-line syntax, or meaningless high-level abstractions. Documentation must represent the **Human/System Process Journey**. We are writing cookbooks that map how a user gets from A to B so we can understand the architecture before coding.

1.2.1 Structuring the `process_flows/` Directory

Flows must be organized by logical **Domains**, not arbitrarily by file name. Example structure:
- `docs/process_flows/tasks_and_projects.tex`
- `docs/process_flows/finance_and_ledgers.tex`
- `docs/process_flows/social_and_friends.tex`
- `docs/process_flows/system_and_sync.tex`

1.2.2 The Process Cookbook Format

Every feature within a domain must be broken down into explicit, human-readable steps that explain the complete logic loop. Use standard LaTeXlists and sections.

CRITICAL ANTI-ABSTRACTION MANDATE: Do **NOT** write code-focused abstracts for the UI/Action layers (e.g., *"The getChildren() method of the NoteProvider fires"*). You **MUST** describe the physical human action (e.g., *"The user expands the Notes folder in the sidebar"*).

BRUTAL UI GRANULARITY MANDATE: Never map flows at a surface level (e.g., "The user creates an account" or "The user logs an expense"). You **MUST** map the exact, granular physical UI elements the user interacts with. This means explicitly documenting the specific horizontal scrolling chip selectors, the exact preset labels (e.g., FNB, Bank Windhoek), the exact toggles for recurring actions (e.g., Weekly vs Monthly), and the specific text inputs (e.g., "Quantity" and "Cost Basis"). If the UI has a specific switch or dropdown, the documentation must explicitly state it. Keep mapping and "adding on until it's really all there".

Required elements for EVERY mapped feature:
1. **Trigger:** How does the process start physically? (e.g., "User swipes left on a Todo in the Inbox")
2. **Action / UI State:** What does the user see and interact with? (e.g., "Action bubble menu appears, user selects 'Bump to Tomorrow'")
3. **System Logic:** What is the intended behavior and calculation behind the scenes? (e.g., "System recalculates the due date to tomorrow at 00:00:00 and removes the item from the Today deck")
4. **Data Flow & Mutators:** Where does the data go? (e.g., "Updates local WatermelonDB SQLite -> Queues offline mutation in AsyncStorage -> Synchronizes via POST /api/sync to Drizzle ORM when online")

CRITICAL CROSS-SCREEN MANDATE: Flows are highly dynamic and rarely siloed to a single screen. You **MUST** explicitly map deep inter-screen connections (e.g., "Notes flow pushes parameters to FinanceScreen to auto-add expenses" or "Project Focus forces the global Calendar to filter by Project ID"). Never stop at the boundary of a single screen if the user journey naturally bridges into another domain.

Failure to adhere to the Domain Structure, the Brutal UI Granularity Mandate, and the Cookbook Format will result in bloated, unreadable documentation and constitutes a complete failure of the agent's architectural mandate.

1.3 Local Orchestration and Observability Standards (`orch-cli`)

All projects across the NKNGO Portals ecosystem are orchestrated locally via `orch-cli` located in `launcher/orch-cli`. Autonomous AI Agents MUST NEVER guess whether a server, bundler, or service is functioning. Agents must operate with absolute physical observability:
1. **Status Inspection:** Run `orch status` (or `orch status --json`) to verify the active daemon, port, PID, profile, and all registered child processes.
2. **Error Isolation:** Run `orch logs -e` to isolate errors, unhandled exceptions, and 500s across all frameworks without wading through routine log clutter.
3. **Browser Telemetry:** Run `orch logs BROWSER -n 50` to inspect live client-side Chrome console errors, React component crashes, and failed network requests.

4. **Service-Specific Logs:** Run `orch logs <SERVICE> -n 50` (e.g., `orch logs MOBILE-WEB` or `orch logs API`) to audit backend and bundler output.
5. **Hot Reloading:** Run `orch restart` to signal the active daemon to reload all child services upon applying code fixes.
6. **Profile Switching:** Launch targeted multi-service environments with `orch run -p "<profile>"` (e.g., `orch run -p "Pattern + Ask AI (Test Local)"`).

Part II

Vision

Chapter 2

Why Tottie Exists

2.1 The Problem: Agents Have Amnesia

Every agent on every platform wakes up stateless. It has no history, no user context, and no memory of yesterday. A year of conversations later, it still does not know who you are, what you build, or what you decided. All of that intelligence, yet it fails the baseline requirement of an actual mind: **continuity**.

The naive fix is a bigger context window. That is not memory — it is an expensive scratchpad. As input length grows, cost rises linearly, latency rises super-linearly, and accuracy *drops* (the "lost in the middle" effect). Long context is a tax with diminishing returns.

2.2 The Thesis: Intelligence at Write Time

Standard retrieval-augmented generation (RAG) applies intelligence at **read time**: the agent searches when it needs something. Tottie flips that. It applies intelligence at **write time**: memory curates itself as you live, deciding what matters *before* it is needed. The agent does not manage memory. It just remembers.

- **Observer** runs in parallel and decides what is worth keeping.
- **Scribe** structures, tags, embeds, and *reconciles* what was kept.
- **Retriever** runs on every turn and surfaces what is contextually relevant.
- **Curator** writes the compact *Context Card* the agent actually receives.

2.3 Positioning Against the 2026 Field

The field has converged on a name for this pattern: **learned consolidation**. Live capture $\rightarrow$ LLM extraction of facts and decisions $\rightarrow$ reconciliation (update vs supersede) $\rightarrow$ episodic/semantic split $\rightarrow$ dual retrieval. mem0, Zep/Graphiti, and A-Mem all instantiate it. Published figures show why it matters: mem0 reports **91% lower p95 latency** and **90% fewer tokens** than full-context, for roughly a six-point J-score trade on LOCOMO.

Tottie's two differentiators:

1. **Write-time salience + reconciliation is the product**, not a bolt-on. The system is judged on the decisions it makes at ingestion.
2. **It is transport-agnostic (MCP).** The same brain mounts into a chat client, an IDE, or any MCP host. Memory is infrastructure, not an app feature.

2.4 Why It Matters (the human framing)

The best context is the context you can *automatically* give an agent, and that context is almost always about the person using it. Tottie is one store that knows your life, your preferences, your

decisions, and your infrastructure — so a chat assistant remembers your partner's birthday and a coding agent already knows your stack and database choice before it writes a line.

Part III

The Cognition Model

Chapter 3

The Cognition Model: What to Remember, and How a Cue Recalls

This chapter is the intellectual core of Tottie. It answers two questions that a plain RAG pipeline never asks: *what is worth remembering in the first place*, and *how does the right memory come back when it is needed* — including the case of an instruction like "implement feature A", which is not a question at all.

3.1 The Core Realisation: RAG Is One Leg, Not the Animal

Retrieval-augmented generation matches **text similarity**: embed the query, take the nearest neighbours. That assumption fails the moment the input is not a question. "Implement feature A" has no textually similar neighbour in memory, yet a competent human immediately surfaces the project's conventions, past decisions about A, and known pitfalls. A mind returns the right context anyway. So Tottie's retrieval is not one similarity search; it is a **staged, associative process**.

3.2 What Is Worth Remembering: The Salience Gate

The brain retains an experience when synaptic activity is strong *and* neuromodulators (amygdala input, norepinephrine, dopamine) lower the threshold for durable long-term potentiation; weak activity produces long-term depression and is pruned. The Observer is that gate. Every candidate memory is scored:

```
salience = w1*persistence      (still true next week?)
         + w2*reusability      (applies beyond this one turn?)
         + w3*consequence      (what breaks if we forget it?)
         + w4*arousal          (emotional / task-critical in the moment?)
```

Below threshold $\rightarrow$ DISCARD. The weights are tuned by the evaluation harness.

3.3 The Taxonomy of Memory Kinds

Kind	Example	Default tier
Preference (style/tone/format)	"Oxford comma; no em-dashes; open with a TL;DR."	identity
Convention / rule	"Always run tests before commit."	identity
Binding / fact	"Project A uses Postgres; Project B uses Mongo."	knowledge

Decision (+ principle + rationale)	"Chose pgvector for C: already running locally."	knowledge
Constraint	"The service container is 1 CPU / 1 GB."	knowledge
Identity / persona	name, timezone, "her birthday is Nov 7".	identity
Episodic event	"On Oct 29 we decided X in session Y."	episodic
Lesson / procedure	`mcp.server.fastmcp` import error → pin `mcp<2`.	procedural

Per-persona emphasis: a *writer* needs preferences, conventions, and *style exemplars* (so the agent imitates voice, not just obeys rules); a *developer* needs bindings, conventions, decisions-with-principle, and lessons; a *person* needs identity, preferences, dates, and relationships.

3.4 Memory Becomes Judgment: The `principle` Field

"For project C, use project A's database because it is better" is **not recall** — it is *projecting a stored principle onto a new situation*. A decision is therefore stored as `decision + principle + rationale`, for example `principle: "prefer the database already running locally for small services"`. At recall time the Curator surfaces **principles** whenever the cue is a decision. This is the line between a memory store and something that behaves like judgment.

3.5 How a Cue Retrieves: Typing, Spreading, Completing




Figure 3.1: Retrieval is staged: understand the cue, choose a policy, seed nodes, spread activation, complete the cluster, curate the card.

3.5.1 Cue Typing — "What question is `implement feature A`?"

It is not a question. The turn is classified first, and the type selects the retrieval policy.

Cue type	Example	Retrieval policy
QUESTION	"When is her birthday?"	entity facts + identity + knowledge
COMMAND / INTENT	**"Implement feature A."**	**project bindings + conventions + past decisions on A + lessons + constraints**
STATEMENT (new info)	"I moved to Windhoek."	write path; minimal recall
CORRECTION	"Actually, it is the 8th."	recall the contradicted memory → supersede
REFERENCE	"Use that DB we discussed."	resolve the referent from recent episodic memory
CHITCHAT	"thanks!"	none (do not pollute)

3.5.2 Spreading Activation and Pattern Completion

From the seeded nodes, activation propagates along the edges of `memory_links`, decaying with each hop, and priming lowers the threshold for linked concepts. This is the mechanism behind the familiar experience of a memory from fifteen years ago surfacing the instant someone mentions a band: the band is a source node, activation crawls the old associative edges, and it clears the threshold at the target. The **Completer** then reconstructs the whole coherent cluster — *pattern completion* — rather than returning three loose chunks.

3.5.3 Three Legs, Not One

Tottie runs **semantic** (embeddings), **lexical** (full-text), and **associative** (graph activation) retrieval in parallel and fuses them. RAG is retained — it is simply no longer alone. If nothing clears the activation floor, Tottie **abstains** rather than injecting noise.

3.6 Consolidation: The Sleep Job

The brain replays the day during sleep (hippocampal sharp-wave ripples driving cortical replay), **semanticising** episodic traces into general knowledge and pruning what is never used. Tottie's **Consolidator** is an on-demand "Sleep" job that (1) replays recent episodic memories, (2) extracts recurring structure into **semantic** memories, and (3) prunes or decays unused links so capacity stays bounded. Running it on demand (rather than on a scheduler) makes the behaviour deterministic and demonstrable.

3.7 Reconsolidation: Updating on Access

When a memory is *retrieved*, it is marked labile for the remainder of the turn. If the user then supplies contradictory information, the active trace is **patched** (superseded) rather than merely appended, and adjacent nodes are co-activated so the new association forms. Supersession is therefore *retrieval-triggered*, not only write-triggered — exactly the biological mechanism.

3.8 The Ten Minds

#	Component	Job	Tier
1	Cue Classifier	intent type + entity/project extraction → policy	MUST
2	Observer	is this worth remembering?	MUST
3	Salience Scorer	the worth-remembering rubric + arousal tag	MUST
4	Scribe	structure, tag, embed, route, sparse-separate	MUST
5	Reconciler	reconsolidation: update the labile trace on contradiction	MUST
6	Retriever	seed + hybrid + graph activation	MUST
7	Activator	spreading activation over `memory_links` (1–2 hops, decay)	MUST
8	Completer	pattern completion (cluster reconstruction)	SHOULD
9	Curator	assemble the Context Card + "why surfaced"	MUST
10	Consolidator	"Sleep": replay → semanticise → prune	SHOULD

3.9 Neuroscience Basis

Mechanism (verified)	Tottie realisation
Encoding specificity (Tulving)	rich context tags stored at write time
Spreading activation + decay (Collins–Loftus)	the **Activator**
Pattern completion, CA3 autoassociative	the **Completer**
Pattern separation, dentate gyrus	sparse-separate on write (dedupe / orthogonalise)

Complementary Learning Systems + systems consolidation	the **Consolidator** (replay → semanticise)
Reconsolidation (Nader)	the **Reconciler** (update on access)
Salience / neuromodulation (amygdala, NE)	the **Salience Scorer**
Engram sizing, LTD, pruning	capacity caps + decay

Sources: researched in the NotebookLM notebook "META hackathon" (`248ae575-4f2d-4ef1-b75f-d6ce38`) sixteen sources covering hippocampal encoding, engram theory, synaptic plasticity and long-term potentiation, spreading activation, encoding specificity, memory consolidation, episodic and semantic memory, autoassociative memory, reconsolidation, and the complementary-learning-systems and hippocampal-indexing papers.

Part IV

Business and Hackathon

Chapter 4

Hackathon Rules, Dates, and Judging

This chapter records the constraints we are optimising against. It is a working extract of the **Meta Global AI Developer Hackathon Participant Guide** so the team never loses sight of the rules.

4.1 Problem Statements

Every project must build toward one of two statements:
- **Build for Your World** — bring Meta's models into a domain you know firsthand.
- **Push the Frontier** — use Meta's models to give a machine a new capability.

Tottie claims *Build for Your World*: an agent memory layer solves a problem the builder knows firsthand (agents that forget), and it generalises to everyone.

4.2 Mandatory Meta Tooling

Projects must incorporate Meta's models: the *Muse Spark* series, *Muse Wonder*, *Muse Image*, *Muse Voice Transcribe*, and *SAM 3.1* via the Meta Model API; run Meta open-weight models (*Muse Glimmer*, *Muse Spark Open*); or build faster with *Muse Code*. Tottie routes its agents (Observer/Scribe/brain) through the Meta Model API, with a local fallback so the demo never dies.

4.3 Dates (all times Eastern)

When	What
Mon Oct 26, 12:00 PM	Kickoff
Tue Oct 27, 12:00–1:00 PM	Agents 101: Build a Multimodal AI Agent
Wed Oct 28, 12:00–1:00 PM	Agents 102: Best Practices for Verifiable Agents
Fri Oct 30, 12:00–1:00 PM	Specialised Intelligence on Fireworks (Muse Open)
Tue Nov 3	Last full day for submission questions
Wed Nov 4, 9:00 PM	**Final office hours; submissions due**
Thu Nov 5 – Sun Nov 8	Judging period
Mon Nov 9, 12:00 PM	Closing ceremony; top 10 announced; winners revealed
Mon Nov 16	Community vote winner announced

Building period: **Oct 27 – Nov 4**. Tottie's initial commit is dated **2026-10-27**.

4.4 Hard Rules

- **Open source:** repositories must be public.

- **Team size:** max four; solo allowed.
- **Demo requirements:** the demo must only highlight features, code, and functionality *built during the Hackathon*. Judges must be able to identify the original contributions. Failure to do so can result in immediate disqualification.
- **New work only:** what is presented must have been built during the event. Existing codebases may be built on, but new work must be clearly identified.
- **Banned:** projects that violate policy, or that use code/data/assets you lack the rights to.

4.5 Sample Anti-Projects (things to avoid resembling)

Basic RAG applications; simple image analysers; generic "AI for education" chatbots; AI job screeners; nutrition coaches; personality analysers; sports analysers; anything political or involving war; medical advice.

4.5.1 How Tottie differs from the banned "Basic RAG Application"

Tottie is *not* a read-time RAG app. It **flips RAG to write time**: the value is the ingestion-time curation decision, and the deliverable is an **MCP server** (infrastructure), not a document-chat UI. This distinction is stated explicitly on Slide 2 of the demo deck.

4.6 Judging Rubric (equally weighted, 0–10)

Category	What it asks
Impact	Real-world potential; who benefits; could people use it; does it fit a statement.
Use of Meta AI Tooling	How creatively Meta's tooling is used — beyond a basic integration.
Technical Depth & Execution	Is the engineering sound and thoughtfully refined; real craft.
Demo	Is it working, impressive, live-safe, and genuinely cool to watch.

4.7 Prizes We Target

Indie Developer track ($400k pool: $150k / $100k / $75k / $50k / $25k), plus bonus awards: **Best Agentic Use-Case** ($5k), **Best Build on Meta Open-Weight Models** ($10k), **Most Viral Project** ($20k), **Community Vote** ($10k).

Chapter 5

Hackathon Compliance Ledger

5.1 Statement of Original Contribution

Every file, commit, and line of code in this repository was authored between **2026-10-27** and **2026-11-04** — the Hackathon building window. No product code pre-existed the event. Where this project reuses architecture, it reuses *patterns* from the author's own repositories (see the Reuse Map), never third-party code or assets the author does not own. This repository is public, satisfying the open-source rule.

5.2 Feature → Commit Ledger

This table is updated at every phase gate. Judges can verify each row against `git log`.

Feature / Component	Commit	Date
Repo scaffold, env, orch config, docs skeleton	`chore: scaffold Tottie repo`	2026-10-27
LaTeX documentation set (`docs/master.pdf`)	`docs: architecture, flows, roadmap, todo`	2026-10-27
Beamer demo deck (`presentation.pdf`)	`docs: demo deck v1`	2026-10-27
Memory engine skeleton (schema, providers, minds)	`feat(core): memory engine skeleton`	2026-10-28
MCP server surface	`feat(mcp): server surface`	2026-10-29
End-to-end memory round-trip	`feat(core): memory round-trip`	2026-10-30
Tottie UI + live Memory Panel + ablation	`feat(ui): Tottie chat + memory panel`	2026-10-31
Reconcile, tag rooms, identity pinning, Lessons	`feat(core): reconcile + tags + lessons`	2026-11-01
MCP-in-IDE integration + eval harness	`feat: mcp-in-agent integration`	2026-11-02
Demo video, README, compliance ledger	`docs: demo video + compliance`	2026-11-03

5.3 Reuse Disclosure

Tottie reuses *architectural patterns* from the author's own repositories. It copies no files. See the Reuse Map in the System Architecture part.

Part V

System Architecture

Chapter 6

System Architecture

6.1 Overview

Tottie is a memory layer that any agent can mount. The **core engine** owns the memory lifecycle; the **MCP server** is the transport that exposes it; the **Tottie UI** and any **IDE coding agent** are consumers that share the same store. The engine's behaviour is specified in the preceding part, *The Cognition Model*.




Figure 6.1: Tottie: one brain, three bodies. The UI and any IDE agent mount the same MCP server and share one memory store.

6.2 The Ten Components

Each component has exactly one job. The primary agent (the "present thought") is untouched — it receives better context and can *probe*.

#	Component	Job	Tier
1	Cue Classifier	intent type + entity/project extraction → retrieval policy	MUST
2	Observer	is this worth remembering?	MUST
3	Salience Scorer	the worth-remembering rubric + arousal tag	MUST
4	Scribe	structure, tag, embed, route, sparse-separate	MUST
5	Reconciler	reconsolidation: update the labile trace on contradiction	MUST

6	Retriever	seed + hybrid + graph activation	MUST
7	Activator	spreading activation over `memory_links` (1–2 hops, decay)	MUST
8	Completer	pattern completion (cluster reconstruction)	SHOULD
9	Curator	assemble the Context Card + "why surfaced"	MUST
10	Consolidator	"Sleep": replay → semanticise → prune	SHOULD

6.3 The Tier Model

- **Identity** — persona and permanent constraints. Pinned *raw* into the card, zero search overhead. (Example: a partner's birthday.)
- **Episodic** — chronological decisions, state changes, and history.
- **Knowledge** — ingested documents, files, and references (semantic facts).
- **Procedural ("Lessons")** — mistake → problem+solution pairs, surfaced instantly on recurrence ("autosave").

6.4 Write Path (summary)

Observe and score salience → embed and sparse-separate → reconcile `NEW/SKIP/UPDATE/SUPERSEDE` → route tier → persist, write links, and emit an event. Full granular flow in *Process Flows: Write Path*.

6.5 Recall Path (summary)

Classify the cue → choose the policy → seed nodes → run the three legs (semantic ∪ lexical ∪ associative) → spread activation with decay → complete the cluster → curate the Context Card → emit a recall event. Full granular flow in *Process Flows: Cue Typing, Spreading Activation, and Pattern Completion*.

6.6 Reuse Map (patterns, not files)

Pattern reused	Source (author's own repo)
Embedding load (FastEmbed bge-small)	`ask.nkngo/processor/utils/embeddings.py`
pgvector + HNSW + RRF hybrid search	`ask.nkngo/processor/routers/retrieval.py`
Incremental write + SHA-256 deltas	`ask.nkngo/processor/routers/sync.py`
Relevance floors / abstention	`ask.nkngo/processor/utils/grounding.py`
MCP stdio server scaffold	`Pattern/pattern-vscode-extension/src/mcp-server`
Beamer deck preamble	`Writer/Masters/presentation/.../presentation_*.`
docs/`master.tex` preamble	`Pattern/docs/master.tex`

Chapter 7

Data Model and Storage

7.1 Storage Decision (documented exception)

Local development across the NKNGO ecosystem uses SQLite. Tottie is an explicit, reasoned exception: **semantic memory requires vector search**, and the ecosystem's canonical RAG engine (`ask.nkngo`) and Pattern already run **Postgres + pgvector** locally. Tottie therefore uses a local `tottie` database on `127.0.0.1:5432`. This is a deliberate deviation, recorded here per the workspace's non-destructive documentation standard.

7.2 Schema

```
CREATE EXTENSION IF NOT EXISTS vector;

CREATE TABLE memories (
  id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  owner       text NOT NULL,                  -- user / tenant scope
  tier        text NOT NULL CHECK (tier IN
  ↪  ('identity','episodic','knowledge','procedural')),
  kind        text NOT NULL,                  -- fact | preference | decision
  ↪  | event | doc | lesson
  subject     text,                           -- e.g. 'girlfriend',
  ↪  'server_c', 'tottie'
  predicate   text,                           -- e.g. 'birthday', 'uses_db',
  ↪  'fix'
  object      text,                           -- e.g. '2026-11-07', 'pgvector'
  content     text NOT NULL,                  -- human-readable memory
  summary     text,                           -- short form for the Context
  ↪  Card
  embedding   vector(384),                    -- bge-small-en-v1.5
  tags        text[] NOT NULL DEFAULT '{}',   -- the "rooms": #person/frans,
  ↪  #project/tottie
  salience    real NOT NULL DEFAULT 0.5,      -- write-time importance 0..1
  confidence  real NOT NULL DEFAULT 1.0,
  principle   text,                           -- the reusable rule behind a
  ↪  decision (memory->judgment)
  arousal     real DEFAULT 0.0,               -- moment-of-encoding salience
  ↪  (amygdala analogue)
  access_count int DEFAULT 0,                 -- consolidation + decay
  last_access timestamptz,                    -- decay
  source      jsonb,                          -- {session_id, turn, doc, url,
  ↪  msg_id}
  supersedes  uuid REFERENCES memories(id),   -- temporal chain
  valid_from  timestamptz NOT NULL DEFAULT now(),
  valid_to    timestamptz,                    -- NULL = currently true
```

```
  hash        text,                          -- dedupe / content hash
  created_at  timestamptz NOT NULL DEFAULT now()
);

CREATE TABLE memory_events (                 -- the X-ray feed + the eval
↪  ledger
  id               uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  ts               timestamptz NOT NULL DEFAULT now(),
  session_id       text,
  turn             int,
  utterance        text,
  observer_verdict jsonb,                    -- {keep, salience, reason,
  ↪  candidates}
  scribe_action    jsonb,                    -- {op, tier, kind, tags,
  ↪  memory_id}
  cue              jsonb,                    -- {type, entities, policy} for
  ↪  recall events
  latency_ms       int,
  tokens           int
);

CREATE TABLE memory_links (                  -- the associative index
↪  (hippocampal analogue)
  id       uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  owner    text NOT NULL,
  src      uuid NOT NULL REFERENCES memories(id) ON DELETE CASCADE,
  dst      uuid NOT NULL REFERENCES memories(id) ON DELETE CASCADE,
  relation text NOT NULL,                    -- tag | entity | supersedes |
  ↪  temporal | cooccur
  weight   real NOT NULL DEFAULT 1.0,
  UNIQUE (owner, src, dst, relation)
);
```

7.3 Indexes

```
CREATE INDEX ON memories USING hnsw (embedding vector_cosine_ops);   --
↪  vector recall
CREATE INDEX ON memories USING gin (tags);                            --
↪  room/tag filter
CREATE INDEX ON memories USING gin (to_tsvector('english', content)); --
↪  full-text (lexical leg)
CREATE INDEX ON memories (owner, tier) WHERE valid_to IS NULL;        --
↪  live-slice lookup
CREATE INDEX ON memory_links (owner, src);                            --
↪  spreading activation
CREATE INDEX ON memory_links (owner, dst);
```

7.4 Why `memory_links` Exists

Tags alone give a flat “room” model. The associative leg of retrieval needs *edges*: which memories share a tag, which entities co-occur, which memory supersedes which, which are temporally adjacent. `memory_links` is that adjacency structure — the substrate the Activator walks. Links are written only on tag, entity, and supersede events (not every turn), which bounds write amplification.

7.5 Temporal Correctness

Every fact carries a validity window. When a new fact contradicts an old one — and especially when the old one was *just retrieved* — the old row's `valid_to` is set to `now()` and the new row is inserted with `supersedes = old.id`. Retrieval filters `valid_to IS NULL`, so **stale facts are never returned**. See *Process Flows: Reconsolidation on Access*.

7.6 Owner Scoping

All reads and writes are scoped by `owner`. The demo runs a single owner (`owner_local`), but the schema is multi-tenant from day one: identity, recall, probe, consolidate, and forget all take an owner key.

7.7 Embeddings

Real embeddings use FastEmbed `BAAI/bge-small-en-v1.5` (384-d), loaded from the local model cache (`../../local LLMS`). A clearly-labelled `TOTTIE_EMBEDDER=hash` dev fallback exists *only* for offline smoke tests and is never presented as production behaviour.

Chapter 8

Model Providers and the Intelligence Layer

8.1 Provider Abstraction

All model calls go through one interface, so the demo can switch models without code changes:

```
class LLMProvider:
    async def complete(self, messages, json_schema=None) -> str: ...
```

- **MetaProvider** — the Meta Model API (Muse Spark series). Configured by `META_API_KEY`, `META_BASE_URL`, `META_MODEL`.
- **LocalProvider** — an OpenAI-compatible local server (Ollama `:11434` or llama.cpp `:8080`), configured by `LOCAL_LLM_URL`, `LOCAL_LLM_MODEL`.
- **resolve_provider()** — uses Meta when a key is present and the endpoint is healthy, otherwise falls back to local. **The demo never dies on a provider outage.**

8.2 Component Model Choices

Mind	Model class	Rationale
Observer	small / fast	high-frequency; a cheap classifier wins
Scribe	small / medium	structured extraction + reconcile; JSON output
Retriever	embeddings only	no LLM in the hot path — bge-small + RRF
Curator	rules (+ optional small)	deterministic card assembly within a token budget
Brain (the agent)	strongest available	the "present thought"; quality matters here

8.3 Cost Control

Tottie's whole argument is that write-time curation is cheaper than stuffing context. The eval harness measures **tokens per query** with memory ON vs OFF to make that claim falsifiable.

8.4 Optional: MCP Sampling (flagged, off by default)

MCP sampling (`ctx.session.create_message`) would let the Observer/Scribe curate using the *host's* model, with **no server-side API key** — an elegant "surprised even us" capability. Two caveats: it is **deprecated in the 2026-07-28 specification** (SEP-2577) in favour of Multi

Round-Trip Requests, and many hosts do not declare the capability. It is therefore **flag-gated** (`TOTTIE_USE_SAMPLING=0` by default) and never the primary path.

Chapter 9

MCP Surface

Tottie ships as an MCP server over **stdio** (Python SDK, `mcp<2` with `FastMCP`). The whole point is that the same memory mounts into any host: the Tottie chat, a VS Code / Cursor agent, anything that speaks MCP.

9.1 Tools

Tool	Signature	Purpose
`memory.remember`	`(text)`	Let the Scribe decide what to keep
`memory.write`	`(tier, content, tags)`	Explicit write to a named tier
`memory.recall`	`(query, tiers?, k?)`	Cue-typed associative retrieval
`memory.probe`	`(tag|id)`	Walk into a "room" and read its memories
`memory.identity`	`()`	Return the pinned identity facts
`memory.sleep`	`()`	Run consolidation (replay → semanticise → prune)
`memory.forget`	`(id)`	Right-to-be-forgotten

9.2 Resources

- `memory://identity` — the pinned persona/constraints.
- `memory://tag/{tag}` — the contents of a room, readable without a tool call.

9.3 Prompt

`tottie_context_card` — a reusable system-prompt fragment that teaches a host how to use the memory correctly (when to trust the card, when to probe, when to abstain).

9.4 Dual-Path Recall (the design answer)

A common question is: "does the retriever hand context to the agent, or does the agent probe for it?" Tottie does **both, deliberately**:

1. **Ambient path** — the Curator injects the Context Card automatically on every turn, so the agent "just knows" without issuing a query.

2. **Deliberate path** — the card carries **pointers** (tags/rooms); when the agent needs depth it calls `memory.probe(tag)` and reads that room.

9.5 Retrieval Is Cue-Typed, Not Just Similar

The `memory.recall` tool does not run a single similarity search. It classifies the cue, chooses a policy, seeds nodes, and spreads activation across `memory_links`. See *The Cognition Model* for the full specification.

Chapter 10

Tottie UI and the Live Memory Panel

10.1 Layout

A single screen, 16:9-safe for screen-capture: chat on the left, the live Memory Panel on the right.




Figure 10.1: The Memory Panel is the hero; the sprite is the reacting character.

10.2 The Panel Is a Live Stream of `memory_events`

The UI subscribes to `GET /events?session_id=` (Server-Sent Events). Each event card shows the four things that matter, in order:

1. **What it is learning now** — the turn plus the Observer verdict (KEEP/DISCARD, salience, reason).
2. **What memories it is forming** — the Scribe operation badge (`NEW` / `UPDATE` / **`SUPERSEDE`** / `SKIP`) and the memory text (superseded ones struck through).
3. **Where it inserted them** — the tier chip and the tag/room chips, plus a live **room map** that grows as new tags appear.
4. **What it injected into context** — the literal **Context Card** the Curator built for that turn, annotated with a **"why this surfaced"** line per hit (`cue=COMMAND → seed #project/tottie → spread 1 hop (w=0.6)`). This is what makes the write-time *and* the associative-retrieval decision visible on camera.

10.3 The Sleep Button

A single **Sleep** control runs the Consolidator on demand. During the run the Panel shows a progress strip (*"replaying N episodes…"*) and then a summary (*"12 episodic → 3 semantic; 4*

pruned"). It is the only control that shows *generalisation* happening. See *Process Flows: Consolidation*.

10.4 Tottie Avatar — Drop-In Sprite (frame sets per state)

- **Built here:** a `TottieFace` component plus a state machine with five states — `idle`, `listening`, `thinking`, `remembering`, `speaking` — driven by app events (streaming tokens → `speaking`; a write event or a recall → `remembering`; the Sleep job → `remembering`).
- **Provided by the Architect:** frame sets in `ui/public/tottie/<state>/`. Drop PNGs; **no code change required**.
- **Contract:** `TottieFace` reads `{state, framesDir, fps}`. A placeholder frame set ships so the app runs before the final art lands.
- **No TTS / no lip-sync.** The sprite reacts to memory events; that is the whole job.

10.5 Ablation Toggle

A single **Tottie ON/OFF** switch. OFF = no card injected and no writes (raw model). ON = full memory. Used live in the demo to prove that a correct answer *depended on* memory rather than on the base model.

Part VI

Process Flows

Chapter 11

Process Flow: The Write Path

Every step below is what the **Memory Panel** renders in its "LEARNING NOW" block. This is the flow that proves the thesis: intelligence applied at write time.

11.1 The User Says Something Durable

Trigger: In the Tottie chat the user types *"my girlfriend's birthday is on the 7th of November"* and presses enter. (Equivalently: an IDE agent turn completes and the host forwards it.)

Action / UI State: The Tottie sprite leaves `idle`, enters `listening` for the duration of the send, then `thinking`. The Memory Panel prepends a new turn card with an empty "LEARNING NOW" row and a subtle processing shimmer.

System Logic: The host issues `POST /write` with `{text, session_id, turn, owner}`. The core hands the turn to the **Observer**, which runs *in parallel* with the agent's own response generation.

Data Flow & Mutators: The turn is not yet stored as memory; it exists only as an inbound request and a `memory_event` row in `queued` state.

11.2 The Observer Decides

Trigger: The Observer receives the turn tuple.

Action / UI State: The "LEARNING NOW" row fills in: `Observer:` KEEP (or DISCARD), a salience score (e.g. 0.82), and a short reason ("durable personal fact").

System Logic: The Observer calls the resolved LLM provider with a strict JSON contract and returns a verdict:

```
{ "keep": true, "salience": 0.82, "reason": "durable personal fact",
  "candidates": [ { "tier":"identity","kind":"fact","subject":"girlfriend",
    "predicate":"birthday","object":"2026-11-07",
    "content":"Girlfriend's birthday is 7 November",
    "tags":["#person/girlfriend","#topic/birthday"] } ] }
```

Data Flow & Mutators: The verdict JSON is written into the `observer_verdict` column of the `memory_event` and pushed to the Panel over SSE. If `keep` is false, the flow ends here and the Panel shows a greyed DISCARD chip.

11.3 The Scribe Structures and Embeds

Trigger: A non-empty candidate list from the Observer.

Action / UI State: The Panel's "MEMORIES FORMED" block gains a row per candidate, showing the operation badge and the memory text.

System Logic: For each candidate the Scribe (1) composes the human-readable memory, (2) computes its embedding with `bge-small-en-v1.5`, (3) assigns tags, and (4) hands the candidate to the reconciler (next chapter).

Data Flow & Mutators: An embedding vector (384 floats) is computed in memory; the candidate is held for the reconcile step.

11.4 Reconcile, Route, and Persist

Trigger: An embedded candidate.

Action / UI State: The Panel shows the operation badge (`NEW` / `UPDATE` / `SUPERSEDE` / `SKIP`), the tier chip (e.g. `identity`), and the room chips (e.g. `#person/girlfriend`).

System Logic: See *Process Flow: Reconcile and Temporal Correctness* for the full decision table. The routed tier is recorded, and the live row is inserted with `valid_from = now()`.

Data Flow & Mutators: `INSERT INTO memories (...)`; the `memory_event.scribe_action` column is filled; the Panel's "INSERTED WHERE" block and the **room map** update; the new memory becomes immediately retrievable.

11.5 Why This Order Matters

Because the decision is made *at write time*, no read-time query is ever needed to "know" this fact. The next time the user asks anything related, the Retriever simply finds it — the agent never had to remember to save it.

Chapter 12

Process Flow: The Recall Path

This is the "middle part": what happens between the user's utterance and the context the agent receives. Tottie answers it with the **Context Card** (ambient) plus the **probe** (deliberate).

12.1 A New Turn Arrives

Trigger: The user sends *"when is her birthday again?"* in the chat, or a fresh session opens and the agent needs context about the user.

Action / UI State: The sprite enters `thinking`; the Panel prepares a "CONTEXT INJECTED THIS TURN" block.

System Logic: The host calls `POST /recall` (or `memory.recall` over MCP).

Data Flow & Mutators: The utterance (and optionally the last assistant turn) is embedded with `bge-small-en-v1.5`.

12.2 The Identity Slice Is Always Included

Trigger: Any recall. **Action / UI State:** The Panel always shows the pinned identity line at the top of the card. **System Logic:** `SELECT ... WHERE tier='identity' AND valid_to IS NULL`. This is unconditional and cheap — identity has *zero search overhead*. **Data Flow & Mutators:** The identity facts are collected for the card header.

12.3 Hybrid Search

Trigger: The utterance embedding plus the owner scope. **Action / UI State:** Nothing yet — the Panel shows a "searching" shimmer. **System Logic:**

1. **Vector** leg: HNSW top-50 by cosine.
2. **Lexical** leg: full-text top-50.
3. **Filter**: `owner = ?` AND `valid_to IS NULL` (and any tag filter).
4. **Fusion**: Reciprocal Rank Fusion, $k = 60$, to top-8.
5. **Re-rank**: weight by salience · recency · confidence.

Data Flow & Mutators: A ranked hit list of `(id, tier, summary, tags, score)`.

12.4 The Procedural Slice

Trigger: The utterance resembles a previously-solved problem (an error signature or a similar embedding). **System Logic:** Match `kind='lesson'` rows; if a match clears the threshold, the solution is surfaced *instantly* — the "autosave" behaviour. **Data Flow & Mutators:** Matched lessons are appended to the card.

12.5 The Curator Builds the Context Card

Trigger: Identity slice + ranked hits + procedural matches. **Action / UI State:** The Panel's "CONTEXT INJECTED THIS TURN" block shows the exact card. **System Logic:** The Curator assembles a compact card (<400 tokens) with one line per hit, its tier, its source, and its tags, plus a "probe deeper" pointer line:

```
[MEMORY CARD - 3 hits]
  IDENTITY (pinned)  user=Frans - tz=CAT - girlfriend birthday = Nov 7
  EPISODIC 2026-10-29  decided: pgvector not Qdrant for Tottie    #tottie
  ↪  #decision
  KNOWLEDGE (doc: telecom-arch.pdf p.7)  Server C sits behind A/B  #telecom
  ↪  #infra
  -> probe deeper: memory.probe("#telecom") | memory.recall("server C
  ↪  topology")
```

Data Flow & Mutators: The card text is returned to the host and injected into the prompt space; a recall `memory_event` is written and streamed to the Panel.

12.6 The Deliberate Probe

Trigger: The agent decides it needs more depth than the card provides. **Action / UI State:** The Panel opens the targeted room and highlights the returned memories. **System Logic:** `memory.probe(tag)` (or `probe(id)`) returns the room's live memories. **Data Flow & Mutators:** A read-only fetch scoped by owner and `valid_to IS NULL`.

12.7 Ablation

Trigger: The Tottie ON/OFF toggle is set to OFF. **System Logic:** The recall step is skipped entirely — no identity slice, no hits, no card. The base model answers with no memory. This is the control condition used in the demo and the eval harness.

Chapter 13

Process Flow: Cue Typing, Spreading Activation, and Pattern Completion

13.1 The User Types an Instruction, Not a Question

Trigger: The user types *"implement feature A"* in the Tottie chat (or a coding agent issues the same over MCP).

Action / UI State: The sprite enters `thinking`; the Memory Panel opens a "RECALL" block with a *cue* chip showing the classified type.

System Logic: The **Cue Classifier** labels the turn `COMMAND/INTENT` and extracts entities and the project scope (`#project/A`). The retrieval **policy** for a command is not "find similar text"; it is *assemble what a competent person needs to act*: project bindings, conventions, prior decisions on A, lessons tied to A, and constraints.

Data Flow & Mutators: A retrieval request is issued with the intent, entities, and scope; a `memory_event` of kind `recall` begins.

13.2 Seeding the Associative Network

Trigger: The classified cue. **Action / UI State:** The Panel shows seed chips (e.g. `#project/A`, `feature A`). **System Logic:** Nodes are seeded directly from the parsed entities (bypassing similarity), and the three legs run in parallel: **semantic** (embedding nearest neighbours), **lexical** (full-text match), and **associative** (graph nodes for the seeded tags/entities). **Data Flow & Mutators:** A candidate set of memory ids with initial activation.

13.3 Spreading Activation

Trigger: The seeded candidate set. **Action / UI State:** The Panel renders each hop as it happens: "spread 1 hop (w = 0.6)". **System Logic:** The **Activator** walks `memory_links` outward from the seeds, propagating activation with a per-hop decay and a threshold cut-off. Linked memories that were never textually similar to the instruction still light up — because they are *associated*, exactly as a band name revives an unrelated scene from fifteen years ago. **Data Flow & Mutators:** A ranked activation vector over memory ids.

13.4 Pattern Completion

Trigger: A high-activation region of the graph. **Action / UI State:** The Panel groups the returned memories into one coherent cluster. **System Logic:** The **Completer** takes the top-activated *cluster* and reconstructs a coherent, self-consistent context — the biological analogue of CA3 recur-

rent excitation restoring a whole memory from a partial cue. **Data Flow & Mutators:** The cluster replaces the loose hit list.

13.5 Curate and Inject

Trigger: The completed cluster. **Action / UI State:** The Panel's "CONTEXT INJECTED THIS TURN" block shows the final Context Card, each line annotated with *why it surfaced* (cue type $\rightarrow$ seed $\rightarrow$ hops). **System Logic:** The **Curator** assembles the card within a token budget and appends the "probe deeper" pointers. **Data Flow & Mutators:** The card is injected into the prompt; a `recall` event is streamed to the Panel.

13.6 Inhibition and Abstention

Trigger: Nothing clears the activation floor, or everything retrieved is superseded. **System Logic:** Inhibit the results and inject *nothing*. Abstaining is a correct outcome; injecting noise is not.

Chapter 14

Process Flow: Reconcile and Temporal Correctness

Reconciliation is what separates a real memory from a pile of embeddings. It is the moment a new fact meets an old one.

14.1 The Decision Table

Trigger: An embedded candidate arrives from the Scribe.

System Logic: The reconciler searches for an existing memory for the same owner matching `(subject, predicate)` *or* a cosine similarity above `TOTTIE_RECONCILE_COSINE` (default 0.86) within the same tags, then decides:

Operation	When	What happens
`NEW`	No prior memory matches	Insert with `valid_from = now()`
`SKIP`	A matching memory already holds the same value	Bump confidence / salience; no new row
`UPDATE`	A matching memory is enriched but not contradicted	Append detail; refresh summary
`SUPERSEDE`	A matching memory holds a *different* value	Set old `valid_to = now()`; insert new with `supersedes = old.id`

Data Flow & Mutators: Any insert or update is written to `memories`; the decision is written to `memory_event.scribe_action` and streamed to the Panel, where a superseded memory is rendered with a strikethrough.

14.2 Worked Example: "I'm vegetarian now"

Trigger: The user says *"actually, I'm vegetarian now"*.

Action / UI State: The Panel's "MEMORIES FORMED" block shows a red-ish SUPERSEDE badge, the old value struck through ("diet: meat-eater"), and the new value ("diet: vegetarian").

System Logic:

1. The Observer flags a durable preference change (salience high; `kind=preference`).
2. The Scribe embeds the candidate and finds the live fact (`subject=user, predicate=diet, object=meat-eater`).
3. The values differ, so the operation is SUPERSEDE.
4. The old row's `valid_to` is set to `now()`; the new row is inserted with `valid_from = now()` and `supersedes = old.id`.

Data Flow & Mutators: Two row mutations and one event; retrieval now returns only "vegetarian" because it filters `valid_to IS NULL`. The agent never has to reconcile in-prompt, and it can never quote a stale fact.

14.3 Why This Is Hard and Why It Wins

Plain vector recall has *no update semantics*: both the old and the new fact retrieve, and the model is left to guess which is current. Tottie resolves the conflict at write time, once, and records the temporal chain. This is precisely the capability that LongMemEval's *knowledge update* category and MemoryAgentBench's *selective forgetting / conflict resolution* category probe — and it is a headline slide in the demo.

Chapter 15

Process Flow: Reconsolidation on Access

15.1 A Memory Is Retrieved

Trigger: Any recall that returns memory `M`. **Action / UI State:** The Panel subtly marks `M` as *active* (a soft highlight). **System Logic:** The **Reconciler** marks `M` labile for the remainder of the turn, records `last_access` and increments `access_count`. Biologically, a retrieved memory returns to an unstable state and must be re-stabilised. **Data Flow & Mutators:** A lightweight update of `access_count` / `last_access`.

15.2 The User Contradicts It

Trigger: The user says *"actually, it's the 8th"* while `M` ("her birthday is the 7th") is active. **Action / UI State:** The Panel shows a SUPERSEDE badge; the old value is struck through; the new value appears. **System Logic:** Because `M` is active, the write path takes the *reconsolidation* route, not a blind append: the old row's `valid_to` is set to `now()`, the new row is inserted with `supersedes = M.id`, and adjacent nodes are co-activated so the correction binds to the same context. **Data Flow & Mutators:** Two row mutations, one supersede link, one `memory_event`.

15.3 Why It Is Different

A passive store appends the correction and later returns both the old and the new fact, leaving the model to guess. A reconsolidating store resolves the conflict in the moment it is surfaced. This is the same behaviour the LongMemEval *knowledge update* category and the MemoryAgentBench *conflict resolution* category are designed to probe.

Chapter 16

Process Flow: Consolidation (the Sleep Job)

16.1 The User Presses "Sleep"

Trigger: The user clicks the **Sleep** button in the Memory Panel (or calls `POST /consolidate`, or the `memory.sleep` MCP tool).

Action / UI State: The sprite enters a calm `remembering` state; the Panel shows a progress strip reading *"replaying N episodes…"*.

System Logic: The **Consolidator** loads the recent episodic memories for the owner — the analogue of hippocampal replay during sleep.

Data Flow & Mutators: A read of `tier='episodic'` rows within the replay window.

16.2 Semanticisation

Trigger: The replayed episode set. **Action / UI State:** The Panel shows generated semantic memories appearing one by one (e.g. *"prefers X for Y"*). **System Logic:** An LLM pass extracts recurring structure across the episodes and writes **semantic** rows — the same way repeated experiences are integrated into neocortical knowledge, losing their episodic detail and becoming general. **Data Flow & Mutators:** `INSERT INTO memories (tier='knowledge', ...)` with links from the source episodes in `memory_links` (relation `cooccur`).

16.3 Pruning and Scaling

Trigger: The end of the replay pass. **Action / UI State:** The Panel prints a summary: *"12 episodic → 3 semantic; 4 pruned"*. **System Logic:** Low-activation, rarely-accessed memories and links are decayed or archived, and link weights are normalised so total capacity stays bounded (the homeostatic-scaling / long-term depression analogue). Nothing user-visible is deleted without the number being reported. **Data Flow & Mutators:** Weight decay on `memory_links`; archival flag on stale rows.

16.4 Why This Beat Exists

No other memory tool demonstrated on stage shows *generalisation* — the move from "I did this twelve times" to "I always do this". It is short (about twelve seconds), deterministic because it is on demand, and it visibly rewards keeping Tottie running.

Chapter 17

Process Flow: The Demo Click-Path

This is the exact physical sequence the presenter performs on stage and that the screen-capture video follows. Each beat is written so a second operator could run the demo cold.

17.1 Beat 1 — Cold Open (Amnesia)

Trigger: A plain agent window with no memory. **Action / UI State:** The agent greets the user and does not know their name. **System Logic:** No Tottie in the loop. **Data Flow & Mutators:** None. **On screen:** caption “A year of conversations.”

17.2 Beat 2 — Tottie Wakes (Identity Pinning)

Trigger: Open the Tottie chat. **Action / UI State:** The sprite enters `idle`; the Panel immediately shows the pinned Identity line: `girlfriend birthday = Nov 7`. **System Logic:** The Panel performs a recall; the Identity slice is returned with zero search. **Data Flow & Mutators:** A read of `tier='identity'` rows. **On screen:** caption “It just…knows.”

17.3 Beat 3 — Write-Time Magic (Supersede)

Trigger: Type *“I’m vegetarian now”*. **Action / UI State:** The Panel shows `Observer:` KEEP, then a SUPERSEDE badge with the old value struck through; the room map gains a tag. **System Logic:** The full write path plus reconcile (see the Write Path and Reconcile flows). **Data Flow & Mutators:** Old row closed; new row inserted; event streamed.

17.4 Beat 4 — Three Bodies (Cross-Agent Recall)

Trigger: Switch to VS Code; ask the coding agent about the project’s stack. **Action / UI State:** The coding agent answers with the database and architecture decisions it was never told in this session — because they were written in the Tottie chat. **System Logic:** Same MCP server, same store, different host. **Data Flow & Mutators:** A `memory.recall` over MCP from the IDE. **On screen:** the caption “one brain, three bodies.”

17.5 Beat 5 — Autosave a Mistake

Trigger: The coding agent hits a known error. **Action / UI State:** The Panel shows a NEW lesson being formed (problem → solution). **System Logic:** A `kind=lesson` memory is written under `tier=procedural`. **Data Flow & Mutators:** Insert into `memories` with the error signature for matching.

17.6 Beat 6 — Restart + Ablation

Trigger: Kill the session; reopen; ask a question answered 20 minutes ago. **Action / UI State:** It answers correctly. Flip **Tottie OFF**; the same question now returns “I don’t know”; flip **ON**; it answers again. **System Logic:** The OFF state skips the recall path entirely. **Data Flow & Mutators:** With OFF, no card is injected.

17.7 Beat 7 — The Joke and the Pitch

Trigger: Back in the chat. **On screen:** caption *“…everything I was mad at my girlfriend for — and the one thing that matters: her birthday.”* Then the universal pitch: autosave for mistakes, a personal AI that knows you, and the company brain (Server C behind Server A and B).

Part VII

Planning

Chapter 18

Roadmap

18.1 Scope Tiers (9 days, solo, alongside work and study)

Tier	Contents
MUST	Cue Classifier · Salience Scorer · Scribe (+sparse separation) · Reconciler · Retriever · Activator · Curator · MCP server · Context Card + probe · Tottie UI (chat + sprite + live Memory Panel) · ON/OFF ablation · eval harness · 3-minute video · docs + deck
SHOULD	Completer (pattern completion) · Consolidator (on-demand "Sleep") · coding-agent MCP integration (three bodies) · Autosave/Lessons · `memory_links` graph
STRETCH	Full decay/pruning scheduler · autoassociative reconstruction · relation extraction (GraphRAG-lite) · MCP-sampling curation · X/viral push

18.2 Phase Schedule

Phase	Dates	Deliverable
P0	Oct 27	Scaffold: repo, gitignore, env, orch config, docs skeleton, first commit
P1	Oct 27	Docs: all `docs/**/*.tex` → `master.pdf`
P2	Oct 27–28	Deck: `presentation.tex` → `presentation.pdf`
P3	Oct 28–29	Core: engine + schema + providers + salience/cue/scribe
P4	Oct 29	MCP: server tools/resources wired
P5	Oct 30	End-to-end memory round-trip
P6	Oct 30–31	UI: chat + sprite + live Memory Panel + ablation + why-surfaced
P7	Oct 31–Nov 1	Reconcile/reconsolidation, tag rooms, identity pinning, Lessons, `memory_links`
P8	Nov 1–2	Activator + Completer · Consolidator (on-demand) · MCP-in-IDE · eval harness
P9	Nov 3	3-minute video, README, recompile docs, compliance ledger
P10	Nov 4	Repo public, video link, credits claimed, submit by 9 PM ET

18.3 Gating

A phase does not begin until the prior phase's **docs** are written and its tests (where applicable) pass. If time runs short, cut in this order: STRETCH → **Completer** → **Consolidator** (degrades to a summary stub) → tag-rooms map. **Never cut the eval harness or the demo video.**

18.4 Mandates Honoured During the Build

Document First → Implement → Test → Conclude; atomic commits after every step; every `.tex` auto-compiled to PDF; env vars in both `orch.config.json` and `.env.example`.

Chapter 19

Master Todo

19.1 Phase 0 — Scaffold

☐ Create repo tree; `git init`; branch `main`
☐ `.gitignore`, `.env.example`, `orch.config.json`, `Makefile`
☐ `README.md`, `GEMINI.md`, `.agents/orch-directive.md`
☐ First commit dated 2026-10-27

19.2 Phase 1 — Documentation

☐ `master.tex` + every part `*.tex`
☐ Compile `master.pdf` (`latexmk -xelatex`); zero undefined refs
☐ `hackathon_rules.tex`, `hackathon_compliance.tex`

19.3 Phase 2 — Deck

☐ `presentation.tex` (Beamer, Madrid/whale, 16:9)
☐ Compile `presentation.pdf` (`pdflatex` $\times 2$)

19.4 Phase 3 — Core Engine

☐ `config.py`, `db.py`, `schema.sql`
☐ `embeddings.py` (bge-small + labelled hash fallback)
☐ `providers/` (base, meta, local, resolve)
☐ `agents/observer.py`, `scribe.py`, `retriever.py`, `curator.py`
☐ `tiers.py`

19.5 Phase 4 — MCP

☐ `mcp/server.py`: 6 tools + 2 resources + `tottie_context_card`
☐ `--list-tools` prints the surface

19.6 Phase 5 — Round-Trip

☐ `POST /write` $\rightarrow$ store $\rightarrow$ `POST /recall` $\rightarrow$ Card
☐ `GET /events` SSE stream for the Panel
☐ Preflight test: write one fact, recall it

19.7 Phase 6 — UI

☐ `TottieFace` (5-state machine + frame-set contract + placeholders)
☐ `ChatStream`, `MemoryPanel`, `RoomMap`, `AblationToggle`
☐ Panel consumes SSE; renders the four blocks

19.8 Phase 7 — Reconcile / Tags / Identity / Lessons

☐ Temporal supersede with `valid_to` / `supersedes`
☐ Hierarchical tags / rooms; identity allowlist
☐ `kind=lesson` autosave + recurrence match

19.9 Phase 8 — Integration + Eval

☐ Mount MCP in VS Code / Cursor (three bodies)
☐ `eval/harness.py` + `scenarios.jsonl` (ON/OFF ablation)
☐ All tests green

19.10 Phase 9 — Film

☐ 3-minute screen-capture video (captions + music)
☐ README final; recompile docs; update compliance ledger

19.11 Phase 10 — Submit

☐ Make repo public
☐ Video link accessible
☐ Claim Meta credits (<Wed Nov 4, 9 PM ET)
☐ Submit via the CV platform

Chapter 20

Demo Script (3 minutes, screen capture + captions + music)

Format: pure screen capture, on-screen captions, a music bed. No talking head. Total runtime **3:00**. Every caption is written to be readable on a phone.

20.1 Shot List

Time	Beat	On screen
0:00	Cold open	Black. Caption: *"A year of conversations."* A plain agent: *"Hi — I don't know you."* Music swells.
0:12	The problem	Restart = amnesia; the agent re-asks your name. Caption: *"Long context isn't memory."*
0:30	The reveal	Sprite wakes; Panel pins Identity `birthday = Nov 7`. Caption: *"It just…knows."*
0:58	Write-time magic	*"I'm vegetarian now"* → Panel: SUPERSEDE (old struck through); a new fact → Observer verdict + Scribe NEW live; room map grows.
1:22	Why this surfaced	Ask a command: *"implement feature A"*. Panel shows `cue=COMMAND → seed #project/A → spread 1 hop`. Caption: *"It doesn't search. It associates."*
1:45	Three bodies	Cut to VS Code: the coding agent already knows the stack; it hits a bug; **autosave** a lesson; a new session recalls the fix.
2:05	Sleep	Press **Sleep**. Caption: *"12 moments become 3 lessons."* Panel: *12 episodic → 3 semantic; 4 pruned*.
2:20	Restart + ablation	Kill the session, reopen, ask an old question → knows. Flip **Tottie OFF** → *"I don't know."* ON → knows.
2:45	Joke + pitch	Caption: *"…everything I was mad at my girlfriend for — and the one thing that matters: her birthday."* → the aspirational line + repo link.

20.2 Narration Captions (verbatim)

1. "A year of conversations."
2. "It still doesn't know your name."
3. "Long context isn't memory — it's a tax."
4. "Tottie applies intelligence at write time."

5. “Watch the panel. It decides what matters before you need it.”
6. “Ask it to build something. It doesn’t search — it associates.” (the spreading-activation beat)
7. “One brain. Three bodies. Your chat, your code, the panel.”
8. “Then it sleeps — and generalises.” (the consolidation beat)
9. “Turn it off, and it forgets. Turn it on, and it knows.”
10. “So — I used it to remember everything I was mad at my girlfriend for. And the one thing that actually matters: her birthday.”

20.3 Music and Pacing

Cinematic, rising, aspirational under the reveal; a small pulse on the “spreading activation” beat; a warm, calm passage under Sleep; a beat drop on the ablation flip; a warm settle under the joke. Cuts land on caption boundaries. Keep on-screen text large; assume a phone screen.

Chapter 21

Plan Audit (Numbered Outline and Method)

This chapter makes the plan *auditable*. Every part of it carries a stable ID so a second reviewer (human or agent) can judge it section by section without asking for context.

21.1 Audit Method

For each numbered item we record one verdict against six fixed axes:

Axis	Question
Feasibility	Can one person build this Oct 27–Nov 4 alongside work and study?
Dependency	What must exist first? Does it already exist (Reuse Map)?
Risk	What breaks it — live on stage, or under judge scrutiny?
Rubric	Which judging column it serves (Impact / Meta tooling / Technical depth / Demo).
Cost	Effort: S (hours) · M (a day) · L (multi-day).
Verdict	Keep · Improve · Cut · Add · Defer.

21.2 Independent-Review Questions (for third-party judges)

1. Does it satisfy the problem statement (*Build for Your World* / *Push the Frontier*)?
2. Is Meta's tooling central, not decorative?
3. Is the engineering sound and thought through?
4. Is the demo compelling *and live-safe*?
5. Is it clearly new work, distinguishable from reuse?
6. Is anything here a banned anti-project?
7. Are the claims measurable (not vibes)?
8. Is the scope honest for 9 solo days?

21.3 The Numbered Outline

1. **Meta & scope** — event/dates; repo/branch/commit rule; decision log; scope note.
2. **Strategy** — thesis; positioning vs mem0/Zep/Letta; differentiators; problem statement.
3. **Demo design** — three bodies; the money shot; video style; **the Sleep beat**.
4. **Architecture & cognition** — the ten components; tiers; write path; reconcile; tier routing; recall path; Context Card; probe/tags; concurrency; **cue classifier**; **activator**; **completer**; **consolidator**; **salience gate**; **reconsolidation**; **neuroscience basis**.

5. **Data & storage** — `memories`; `memory_events`; indexes; pgvector decision; embeddings; init; owner scoping; **`memory_links`**; **principle/arousal/access fields**.
6. **Intelligence layer** — Observer; Scribe; Curator; providers; model choice/cost; sampling; **consolidation prompts**.
7. **Interfaces** — HTTP surface (`/consolidate`); MCP tools (`memory.sleep`); resources; prompt; SSE events; error/abstention.
8. **UI/UX** — layout; panel blocks; sprite state machine; ablation; room map; typography; **why-surfaced line + Sleep button**.
9. **Evaluation** — scenario set; ablation method; metrics; harness; rubric mapping; **consolidation check**.
10. **Execution plan** — MUST/SHOULD/STRETCH; phase schedule; gating; mandates.
11. **Media** — shot list; deck; music/captions; viral plan.
12. **Repo & tooling** — tree; reuse map; orch/env; docs structure; build commands; gitignore/Makefile; **cognition modules**.
13. **Compliance** — rules mapping; contribution ledger; prize targeting; banned-avoidance.
14. **Risk** — register; live-demo mitigations; **cognition scope-creep mitigations**.
15. **Verification** — test plan; dry-run checklist; orch checks.
16. **Open items** — sprite frames; Meta keys; sampling; name/branch.
17. **Appendices** — rules extract; glossary; sources.

21.4 Audit Ledger

The per-item verdicts are maintained alongside this specification. Items are resolved to `Keep`/`Improve` before the spec is frozen for build. The cognition-model IDs added in v3 (**4.9–4.15, 5.7–5.8, 6.6, 8.6, 9.5, 3.6**) are recorded as `Add`, with the two open items resolved: the Consolidator is SHOULD/on-demand, and the Sleep beat enters the video.