Tottie Master Documentation

NKNGO AI Labs

October 26, 2026

Contents

I Documentation Standards 1

1 Agent Documentation Standards 2
- 1.1 Core Documentation Mandate . . . 2
  - 1.1.1 Rule 1: The LaTeX Mandate . . . 2
  - 1.1.2 Rule 2: The Unified Root (`master.tex`) . . . 2
  - 1.1.3 Rule 3: Post-Implementation Documentation Mandate . . . 2
- 1.2 Process Flow Mapping Standards (The Cookbook Format) . . . 2
  - 1.2.1 Structuring the `process_flows/` Directory . . . 3
  - 1.2.2 The Process Cookbook Format . . . 3
- 1.3 Local Orchestration and Observability Standards (`orch-cli`) . . . 3

II Vision 5

2 Why Tottie Exists 6
- 2.1 The Problem: Agents Have Amnesia . . . 6
- 2.2 The Thesis: Intelligence at Write Time . . . 6
- 2.3 Positioning Against the 2026 Field . . . 6
- 2.4 Why It Matters (the human framing) . . . 6

III The Cognition Model 8

3 The Cognition Model: What to Remember, and How a Cue Recalls 9
- 3.1 The Core Realisation: RAG Is One Leg, Not the Animal . . . 9
- 3.2 The Governing Principle: Simulate the Solutions, Never the Constraints . . . 9
- 3.3 Availability vs Accessibility: Redefining Forgetting . . . 10
- 3.4 Worth Remembering I: The Salience Gate . . . 10
- 3.5 Worth Remembering II: Surprise (Prediction Error) . . . 10
- 3.6 Worth Remembering III: The Content Taxonomy . . . 11
- 3.7 Memory Becomes Judgment: The `principle` Field . . . 11
- 3.8 How a Cue Retrieves: Typing, Spreading, Completing . . . 11
  - 3.8.1 Cue Typing — "What question is `implement feature A`?" . . . 11
  - 3.8.2 Spreading Activation, Priming, and Pattern Completion . . . 12
  - 3.8.3 Three Legs, Not One . . . 12
- 3.9 Retrieval Is Not a Passive Read . . . 12
- 3.10 The Ranking Model ("Forgetting") . . . 12
- 3.11 Consolidation: The Sleep Job . . . 12
- 3.12 Reconsolidation: Updating on Access . . . 13
- 3.13 Prospective Memory: Remembering Intentions . . . 13
- 3.14 Metacognition and Confidence . . . 13
- 3.15 Transactive Memory: Knowing Where . . . 13

3.16 Working Memory and Attention Gating . . . 13
3.17 The Full Memory Taxonomy, Mapped . . . 13
3.18 The Component Roster . . . 13
3.19 Neuroscience Basis, and Where We Improve On It . . . 14

IV Business and Hackathon 16

4 Hackathon Rules, Dates, and Judging 17
4.1 Problem Statements . . . 17
4.2 Mandatory Meta Tooling . . . 17
4.3 Dates (all times Eastern) . . . 17
4.4 Hard Rules . . . 17
4.5 Sample Anti-Projects (things to avoid resembling) . . . 18
4.5.1 How Tottie differs from the banned “Basic RAG Application” . . . 18
4.6 Judging Rubric (equally weighted, 0–10) . . . 18
4.7 Prizes We Target . . . 18

5 Hackathon Compliance Ledger 19
5.1 Statement of Original Contribution . . . 19
5.2 Feature → Commit Ledger . . . 19
5.3 Reuse Disclosure . . . 19

V System Architecture 20

6 System Architecture 21
6.1 Overview . . . 21
6.2 The Component Roster . . . 21
6.3 The Tier Model . . . 22
6.4 Write Path (summary) . . . 22
6.5 Recall Path (summary) . . . 22
6.6 Reuse Map (patterns, not files) . . . 22

7 Data Model and Storage 23
7.1 Storage Decision (documented exception) . . . 23
7.2 Schema . . . 23
7.3 Indexes . . . 24
7.4 Why `memory_links` Exists . . . 25
7.5 Why `utility` and `confidence` Exist . . . 25
7.6 Temporal Correctness . . . 25
7.7 Owner Scoping . . . 25
7.8 Embeddings . . . 25

8 Model Providers and the Intelligence Layer 26
8.1 Provider Abstraction . . . 26
8.2 Component Model Choices . . . 26
8.3 Cost Control . . . 26
8.4 Optional: MCP Sampling (flagged, off by default) . . . 26

9 MCP Surface **28**
9.1 Tools . . . 28
9.2 Resources . . . 28
9.3 Prompt . . . 28
9.4 Dual-Path Recall (the design answer) . . . 28
9.5 Retrieval Is Cue-Typed, Not Just Similar . . . 29
9.6 Confidence in the Response . . . 29

10 Tottie UI and the Live Memory Panel **30**
10.1 Layout . . . 30
10.2 The Panel Is a Live Stream of `memory_events` . . . 30
10.3 The Sleep Button . . . 30
10.4 Tottie Avatar — Drop-In Sprite (frame sets per state) . . . 31
10.5 Ablation Toggle . . . 31

VI Process Flows **32**

11 Process Flow: The Write Path **33**
11.1 The User Says Something Durable . . . 33
11.2 The Observer Decides . . . 33
11.3 The Scribe Structures and Embeds . . . 33
11.4 Reconcile, Route, and Persist . . . 34
11.5 Why This Order Matters . . . 34

12 Process Flow: Surprise Gating and Ranking ("Forgetting") **35**
12.1 The Attention and Surprise Gate . . . 35
12.2 A Surprising Turn Is Encoded . . . 35
12.3 Ranking, Not Deleting . . . 35
12.4 The Cue Always Works . . . 36
12.5 Interference Control . . . 36

13 Process Flow: The Recall Path **37**
13.1 A New Turn Arrives . . . 37
13.2 The Identity Slice Is Always Included . . . 37
13.3 Hybrid Search . . . 37
13.4 The Procedural Slice . . . 37
13.5 The Curator Builds the Context Card . . . 38
13.6 The Deliberate Probe . . . 38
13.7 Ablation . . . 38

14 Process Flow: Cue Typing, Spreading Activation, and Pattern Completion **39**
14.1 The User Types an Instruction, Not a Question . . . 39
14.2 Seeding the Associative Network . . . 39
14.3 Spreading Activation . . . 39
14.4 Pattern Completion . . . 39
14.5 Curate and Inject . . . 40
14.6 Inhibition and Abstention . . . 40

15 Process Flow: Reconcile and Temporal Correctness **41**
15.1 The Decision Table . . . 41
15.2 Worked Example: "I'm vegetarian now" . . . 41
15.3 Why This Is Hard and Why It Wins . . . 42

16 Process Flow: Reconsolidation on Access **43**
16.1 A Memory Is Retrieved . . . 43
16.2 The User Contradicts It . . . 43
16.3 Why It Is Different . . . 43

17 Process Flow: Consolidation (the Sleep Job) **44**
17.1 The User Presses “Sleep” . . . 44
17.2 Semanticisation . . . 44
17.3 Pruning and Scaling . . . 44
17.4 Why This Beat Exists . . . 44

18 Process Flow: The Demo Click-Path **45**
18.1 Beat 1 — Cold Open (Amnesia) . . . 45
18.2 Beat 2 — Tottie Wakes (Identity Pinning) . . . 45
18.3 Beat 3 — Write-Time Magic (Supersede) . . . 45
18.4 Beat 4 — Three Bodies (Cross-Agent Recall) . . . 45
18.5 Beat 5 — Autosave a Mistake . . . 45
18.6 Beat 6 — Restart + Ablation . . . 46
18.7 Beat 7 — The Joke and the Pitch . . . 46

VII Planning **47**

19 Roadmap **48**
19.1 Scope Tiers (9 days, solo, alongside work and study) . . . 48
19.2 Phase Schedule . . . 48
19.3 Gating . . . 49
19.4 Mandates Honoured During the Build . . . 49

20 Master Todo **50**
20.1 Phase 0 — Scaffold . . . 50
20.2 Phase 1 — Documentation . . . 50
20.3 Phase 2 — Deck . . . 50
20.4 Phase 3 — Core Engine (the gate + the minds) . . . 50
20.5 Phase 4 — MCP . . . 50
20.6 Phase 5 — Round-Trip . . . 50
20.7 Phase 6 — UI . . . 51
20.8 Phase 7 — Reconcile / Tags / Identity / Links / Decay . . . 51
20.9 Phase 8 — Cognition + Integration + Eval . . . 51
20.10 Phase 9 — Film . . . 51
20.11 Phase 10 — Submit . . . 51

21 Demo Script (3 minutes, screen capture + captions + music) **52**
21.1 Shot List . . . 52
21.2 Narration Captions (verbatim) . . . 53
21.3 Music and Pacing . . . 53

22 Plan Audit (Numbered Outline and Method) **54**
22.1 Audit Method . . . 54
22.2 Independent-Review Questions (for third-party judges) . . . 54
22.3 The Numbered Outline . . . 54
22.4 Audit Ledger . . . 55

Part I

Documentation Standards

Chapter 1

Agent Documentation Standards

1.1 Core Documentation Mandate

This document serves as the absolute source of truth for any Autonomous AI Agent (including Gemini, Loid3, or other models) operating across the ENTIRE NKNGO Portals Ecosystem (including NKNGO-LANG, LearnersQuizNamibia, Pattern, and all future projects). When asked to write, update, or analyze documentation, you MUST adhere to the following universal standardization rules without exception.

1.1.1 Rule 1: The LaTeX Mandate

- **No Markdown Allowed:** All architectural, system, and process flow documentation MUST be written in LaTeX(`.tex`) format.
- **Exceptions:** The **only** Markdown files permitted in the root directory are `README.md` (for GitHub previews) and `GEMINI.md` (the immutable core system prompt for agents).
- **Deletion Clause:** If an agent generates or discovers standalone `.md` files containing system documentation, they must convert them to `.tex`, move them into the `docs/` directory, and permanently delete the `.md` file.

1.1.2 Rule 2: The Unified Root (`master.tex`)

- All documentation lives inside the `/docs` directory.
- You must never create isolated `.tex` files. Every new file must be logically categorized into a subdirectory (e.g., `process_flows/`, `business/`, `system/`) and formally imported via an `\input{}` command inside `docs/master.tex`.

1.1.3 Rule 3: Post-Implementation Documentation Mandate

- Whenever an agent implements a new feature, refactors a system, or writes new code, they MUST immediately document the flows and architecture in the appropriate LaTeX files. Do not wait for the user to ask for documentation after coding; it is an automatic, mandatory requirement.

1.2 Process Flow Mapping Standards (The Cookbook Format)

When mapping flows, DO NOT generate massive dumps of raw code, line-by-line syntax, or meaningless high-level abstractions. Documentation must represent the **Human/System Process Journey**. We are writing cookbooks that map how a user gets from A to B so we can understand the architecture before coding.

1.2.1 Structuring the `process_flows/` Directory

Flows must be organized by logical **Domains**, not arbitrarily by file name. Example structure:
- `docs/process_flows/tasks_and_projects.tex`
- `docs/process_flows/finance_and_ledgers.tex`
- `docs/process_flows/social_and_friends.tex`
- `docs/process_flows/system_and_sync.tex`

1.2.2 The Process Cookbook Format

Every feature within a domain must be broken down into explicit, human-readable steps that explain the complete logic loop. Use standard LaTeXlists and sections.

CRITICAL ANTI-ABSTRACTION MANDATE: Do **NOT** write code-focused abstracts for the UI/Action layers (e.g., *"The getChildren() method of the NoteProvider fires"*). You **MUST** describe the physical human action (e.g., *"The user expands the Notes folder in the sidebar"*).

BRUTAL UI GRANULARITY MANDATE: Never map flows at a surface level (e.g., "The user creates an account" or "The user logs an expense"). You **MUST** map the exact, granular physical UI elements the user interacts with. This means explicitly documenting the specific horizontal scrolling chip selectors, the exact preset labels (e.g., FNB, Bank Windhoek), the exact toggles for recurring actions (e.g., Weekly vs Monthly), and the specific text inputs (e.g., "Quantity" and "Cost Basis"). If the UI has a specific switch or dropdown, the documentation must explicitly state it. Keep mapping and "adding on until it's really all there".

Required elements for EVERY mapped feature:
1. **Trigger:** How does the process start physically? (e.g., "User swipes left on a Todo in the Inbox")
2. **Action / UI State:** What does the user see and interact with? (e.g., "Action bubble menu appears, user selects 'Bump to Tomorrow'")
3. **System Logic:** What is the intended behavior and calculation behind the scenes? (e.g., "System recalculates the due date to tomorrow at 00:00:00 and removes the item from the Today deck")
4. **Data Flow & Mutators:** Where does the data go? (e.g., "Updates local WatermelonDB SQLite -> Queues offline mutation in AsyncStorage -> Synchronizes via POST /api/sync to Drizzle ORM when online")

CRITICAL CROSS-SCREEN MANDATE: Flows are highly dynamic and rarely siloed to a single screen. You **MUST** explicitly map deep inter-screen connections (e.g., "Notes flow pushes parameters to FinanceScreen to auto-add expenses" or "Project Focus forces the global Calendar to filter by Project ID"). Never stop at the boundary of a single screen if the user journey naturally bridges into another domain.

Failure to adhere to the Domain Structure, the Brutal UI Granularity Mandate, and the Cookbook Format will result in bloated, unreadable documentation and constitutes a complete failure of the agent's architectural mandate.

1.3 Local Orchestration and Observability Standards (`orch-cli`)

All projects across the NKNGO Portals ecosystem are orchestrated locally via `orch-cli` located in `launcher/orch-cli`. Autonomous AI Agents MUST NEVER guess whether a server, bundler, or service is functioning. Agents must operate with absolute physical observability:
1. **Status Inspection:** Run `orch status` (or `orch status --json`) to verify the active daemon, port, PID, profile, and all registered child processes.
2. **Error Isolation:** Run `orch logs -e` to isolate errors, unhandled exceptions, and 500s across all frameworks without wading through routine log clutter.
3. **Browser Telemetry:** Run `orch logs BROWSER -n 50` to inspect live client-side Chrome console errors, React component crashes, and failed network requests.

4. **Service-Specific Logs:** Run `orch logs <SERVICE> -n 50` (e.g., `orch logs MOBILE-WEB` or `orch logs API`) to audit backend and bundler output.
5. **Hot Reloading:** Run `orch restart` to signal the active daemon to reload all child services upon applying code fixes.
6. **Profile Switching:** Launch targeted multi-service environments with `orch run -p "<profile>"` (e.g., `orch run -p "Pattern + Ask AI (Test Local)"`).

Part II

Vision

Chapter 2

Why Tottie Exists

2.1 The Problem: Agents Have Amnesia

Every agent on every platform wakes up stateless. It has no history, no user context, and no memory of yesterday. A year of conversations later, it still does not know who you are, what you build, or what you decided. All of that intelligence, yet it fails the baseline requirement of an actual mind: **continuity**.

The naive fix is a bigger context window. That is not memory — it is an expensive scratchpad. As input length grows, cost rises linearly, latency rises super-linearly, and accuracy *drops* (the "lost in the middle" effect). Long context is a tax with diminishing returns.

2.2 The Thesis: Intelligence at Write Time

Standard retrieval-augmented generation (RAG) applies intelligence at **read time**: the agent searches when it needs something. Tottie flips that. It applies intelligence at **write time**: memory curates itself as you live, deciding what matters *before* it is needed. The agent does not manage memory. It just remembers.

- **Observer** runs in parallel and decides what is worth keeping.
- **Scribe** structures, tags, embeds, and *reconciles* what was kept.
- **Retriever** runs on every turn and surfaces what is contextually relevant.
- **Curator** writes the compact *Context Card* the agent actually receives.

2.3 Positioning Against the 2026 Field

The field has converged on a name for this pattern: **learned consolidation**. Live capture $\rightarrow$ LLM extraction of facts and decisions $\rightarrow$ reconciliation (update vs supersede) $\rightarrow$ episodic/semantic split $\rightarrow$ dual retrieval. mem0, Zep/Graphiti, and A-Mem all instantiate it. Published figures show why it matters: mem0 reports **91% lower p95 latency** and **90% fewer tokens** than full-context, for roughly a six-point J-score trade on LOCOMO.

Tottie's two differentiators:

1. **Write-time salience + reconciliation is the product**, not a bolt-on. The system is judged on the decisions it makes at ingestion.
2. **It is transport-agnostic (MCP).** The same brain mounts into a chat client, an IDE, or any MCP host. Memory is infrastructure, not an app feature.

2.4 Why It Matters (the human framing)

The best context is the context you can *automatically* give an agent, and that context is almost always about the person using it. Tottie is one store that knows your life, your preferences, your

decisions, and your infrastructure — so a chat assistant remembers your partner's birthday and a coding agent already knows your stack and database choice before it writes a line.

Part III

The Cognition Model

Chapter 3

The Cognition Model: What to Remember, and How a Cue Recalls

This chapter is the intellectual core of Tottie. It answers two questions a plain RAG pipeline never asks: *what is worth remembering*, and *how the right memory comes back*. It also records which mechanisms we **copy** from the brain, which we **refuse** to copy, and where we **improve on** the brain because we are not bounded the way it is.

3.1 The Core Realisation: RAG Is One Leg, Not the Animal

Retrieval-augmented generation matches **text similarity**. That fails the moment the input is not a question. "Implement feature A" has no textually similar neighbour, yet a competent human immediately surfaces the project's conventions, past decisions, and pitfalls. Tottie's retrieval is therefore a **staged, associative process**, not one similarity search.

3.2 The Governing Principle: Simulate the Solutions, Never the Constraints

This is the single most important design rule in the project.

> The brain forgets because it is **bounded** — finite neurons, metabolic cost, lossy reconstructive storage. Those are **constraints, not features**. We are not bounded. Storage is nearly free, search is exhaustive, and we have full control. Blindly copying Ebbinghaus decay would be copying a limitation to solve a solution problem. **Simulate the brain's solutions; never simulate its constraints.**

Biological **constraint** (do NOT copy)	Functional **solution** (DO copy)
Bounded capacity and metabolic cost	Spreading activation over an associative graph
Passive trace decay	Complementary fast/slow consolidation
Lossy reconstruction and confabulation	Autoassociative pattern completion
Interference and blending	Surprise / prediction-error gating
Tip-of-the-tongue blocking	Reconsolidation and dynamic patching
Human working-memory span (7 ± 2)	Salience and importance tagging

Concretely, Tottie **refuses** to copy: uncontrolled time-based decay of raw records; reconstructive guessing inside the store; retrieval blocking; and an artificially small working set. It **does** copy: spreading activation, consolidation, pattern completion, surprise gating, reconsolidation, and salience.

3.3 Availability vs Accessibility: Redefining Forgetting

Tulving and Pearlstone separated two states of stored information:

- **Availability** — the trace was encoded and still exists.
- **Accessibility** — the trace can be retrieved *right now*, which depends on whether the current cues match the encoding.

Retrieval failure (cue-dependent forgetting) is an available-but-inaccessible memory. The **tip-of-the-tongue** state is its poster child: you know the name is in there, you can feel its shape, and you still cannot produce it.

For a machine, **forgetting should not mean deletion at all**. It should mean **control of accessibility**. Everything stays *available* (stored, recoverable with the right cue); only the cued subset is *accessible* at any moment. The tip-of-the-tongue feeling is a *bug*; we keep the mechanism and drop the bug — the cue always works.

Traditional deletion (human / legacy stores)	Accessibility control (Tottie)
Hard physical erasure	Lower the memory's retrieval ranking
Irreversible loss of raw data	Filter it out of the attention window
"Prevents clutter" by destroying evidence	Compress it into an abstract schema

So "forgetting" in Tottie is three operations, none of which is a shredder:

1. **Ranking / salience modulation** — a utility factor lowers a stale memory's search weight, so it drops below the surface threshold but stays in the store.
2. **Attention gating** — the item is kept out of the active context window.
3. **Consolidation / compression** — a detailed episode is summarised into a durable semantic node, with the raw episode retained behind it.

The **Decayer** is therefore really a **Ranker** + **Compressor**, not a shredder. Hard deletion happens in exactly one case: an explicit right-to-be-forgotten request.

3.4 Worth Remembering I: The Salience Gate

The brain retains an experience when activity is strong *and* neuromodulators (amygdala, norepinephrine, dopamine) lower the threshold for durable long-term potentiation; weak activity produces long-term depression and is pruned. The Observer is that gate:

```
salience = surprise * (w1*persistence + w2*reusability + w3*consequence +
↪  w4*arousal)
```

Below threshold → DISCARD. The weights are tuned by the evaluation harness.

3.5 Worth Remembering II: Surprise (Prediction Error)

Under **predictive coding** the brain encodes only the *prediction error*; expected input is suppressed (repetition suppression). Tottie computes a **surprise score** before storing:

```
prediction_error = 1 - cos(turn_embedding, predicted_embedding)
encode only if prediction_error >= SURPRISE_FLOOR
```

Routine turns are suppressed; surprising ones are encoded. **Reward prediction error** tags corrections, feedback, and surprising successes or failures for immediate consolidation. Surprise is the *multiplicative* term in the salience equation — the most important mechanism the first draft lacked.

3.6 Worth Remembering III: The Content Taxonomy

Kind	Example	Default tier
Preference (style/tone/format)	"Oxford comma; no em-dashes; open with a TL;DR."	identity
Convention / rule	"Always run tests before commit."	identity
Binding / fact	"Project A uses Postgres; Project B uses Mongo."	knowledge
Decision (+ principle + rationale)	"Chose pgvector for C: already running locally."	knowledge
Constraint	"The service container is 1 CPU / 1 GB."	knowledge
Identity / persona	name, timezone, "her birthday is Nov 7".	identity
Episodic event	"On Oct 29 we decided X in session Y."	episodic
Lesson / procedure	`mcp.server.fastmcp` import error → pin `mcp<2`.	procedural
Intention (prospective)	"Remind me to ask about the deploy on Friday."	prospective

Per-persona emphasis: a *writer* needs preferences, conventions, and style exemplars; a *developer* needs bindings, conventions, decisions-with-principle, and lessons; a *person* needs identity, preferences, dates, and relationships.

3.7 Memory Becomes Judgment: The `principle` Field

"For project C, use project A's database because it is better" is **not recall** — it is projecting a stored principle onto a new situation. Decisions are stored as `decision + principle + rationale`, and the Curator surfaces **principles** whenever the cue is a decision.

3.8 How a Cue Retrieves: Typing, Spreading, Completing




Figure 3.1: Retrieval is staged: gate, classify, seed, spread, complete, curate.

3.8.1 Cue Typing — "What question is `implement feature A`?"

It is not a question. The turn is classified; the type selects the retrieval policy.

Cue type	Example	Retrieval policy
QUESTION	"When is her birthday?"	entity facts + identity + knowledge
COMMAND / INTENT	**"Implement feature A."**	**project bindings + conventions + past decisions on A + lessons + constraints**

STATEMENT (new info)	"I moved to Windhoek."	write path; minimal recall
CORRECTION	"Actually, it is the 8th."	recall the contradicted memory → supersede
REFERENCE	"Use that DB we discussed."	resolve the referent from recent episodic memory
CHITCHAT	"thanks!"	none (do not pollute)

3.8.2 Spreading Activation, Priming, and Pattern Completion

From the seeded nodes, activation propagates along the edges of `memory_links`, decaying with each hop, and priming lowers the threshold for linked concepts — why a memory from fifteen years ago surfaces the instant someone mentions a band. The **Completer** then reconstructs the whole coherent cluster (**pattern completion**) rather than three loose chunks.

3.8.3 Three Legs, Not One

Tottie runs **semantic** (embeddings), **lexical** (full-text), and **associative** (graph activation) retrieval in parallel and fuses them. RAG is retained — it is simply no longer alone. If nothing clears the activation floor, Tottie **abstains** rather than injecting noise.

3.9 Retrieval Is Not a Passive Read

- **Testing effect:** a successful recall *increments utility* — remembering makes a memory more likely to be remembered again.
- **Retrieval-induced forgetting:** a recall *down-weights the near-duplicate competitors* it passed over, sharpening subsequent searches.
- **Spacing effect:** Tottie schedules **spaced reviews** at expanding intervals rather than trusting one write.

3.10 The Ranking Model ("Forgetting")

A memory's **utility** — a *ranking* signal, never a delete signal — decays with age and rises with use:

```
utility = exp(−ln2 ∗ age / half_life) ∗ (1 + log(1 + access_count))
archive (deprioritise) when utility < MIN_UTILITY   # NOT delete
```

Low-utility memories remain **available** and simply fall out of the accessible set until a cue revives them. **Interference control** (sparse pattern separation on write, category filtering on read) keeps overlapping memories from blending, and **retrieval-induced forgetting** prunes competitors by using them.

3.11 Consolidation: The Sleep Job

The brain replays the day during sleep (hippocampal sharp-wave ripples driving cortical replay), semanticising episodic traces into general knowledge. Tottie's **Consolidator** is an on-demand "Sleep" job that (1) replays recent episodic memories, (2) extracts recurring structure into **semantic** memories, (3) schedules **spaced reviews**, and (4) compresses low-utility detail — *retaining* the raw episodes behind the summary. It can also **self-test**.

3.12 Reconsolidation: Updating on Access

When a memory is retrieved it is marked labile for the remainder of the turn. If the user then contradicts it, the active trace is **patched** (superseded) rather than merely appended, and adjacent nodes are co-activated. Supersession is *retrieval-triggered*, not only write-triggered. **Unlike the brain, nothing is lost:** the superseded version is kept and versioned — we non-destructively reconsolidate.

3.13 Prospective Memory: Remembering Intentions

Tottie adds a **Prospective Queue**: intentions carry an **event cue** or a **time cue** and fire *proactively* when the cue occurs — a genuine product feature ("remind me to…").

3.14 Metacognition and Confidence

A **Metacognitive Evaluator** computes **confidence** from the retrieval margin and selects an action: *HIGH* $\rightarrow$ generate; *LOW* $\rightarrow$ verify, ask, or abstain. This is the difference between an agent that hallucinates and one that says "I don't have that."

3.15 Transactive Memory: Knowing Where

Wegner's *transactive memory* is memory for *who knows what*. Tottie keeps a **Transactive Directory** mapping capabilities to where the knowledge lives (a tool, a document, an external system), so it routes questions instead of hoarding everything locally.

3.16 Working Memory and Attention Gating

Baddeley's model separates a limited **working memory** from long-term storage. Tottie keeps the *solution* — an **attention gate** and a binding step — but **refuses the span limit**: we do not constrain the active set to 7 ± 2 items.

3.17 The Full Memory Taxonomy, Mapped

Human system	Description	Tottie
Episodic (declarative)	dated personal events	**episodic** tier
Semantic (declarative)	general facts, meanings	**knowledge** tier
Autobiographical	episodic + personal semantic	identity + episodic
Procedural (non-decl.)	skills, habits, how-to	**procedural** (Lessons) tier
Priming (non-decl.)	lowered thresholds after exposure	**Activator** priming
Conditioning (non-decl.)	stimulus–response associations	`memory_links`
Working memory	bounded active workspace	the present thought + attention gate *(unbounded)*
Prospective	future intentions	**Prospective Queue**
Transactive	directory of who knows what	**Transactive Directory**

3.18 The Component Roster

Component	Job	Tier
Attention Gate	filter incoming turns before storage	MUST
Surprise Gate	prediction-error score; encode only the unexpected	MUST
Cue Classifier	intent type + entities → retrieval policy	MUST
Observer	is this worth remembering?	MUST
Salience Scorer	the rubric, with surprise as a multiplier	MUST
Scribe	structure, tag, embed, route, sparse-separate	MUST
Reconciler	reconsolidation: patch the labile trace (non-destructive)	MUST
Retriever	seed + hybrid + graph activation	MUST
Activator	spreading activation, priming, decay	MUST
Curator	assemble the Context Card + "why surfaced"	MUST
Completer	pattern completion (cluster reconstruction)	SHOULD
Ranker + Compressor ("Decayer")	deprioritise + compress — **never** shred	SHOULD
Metacognitive Evaluator	confidence from the retrieval margin; gate assertions	SHOULD
Prospective Queue	event/time-triggered intentions	SHOULD
Consolidator	sleep: replay → semanticise → space → compress	SHOULD
Transactive Directory	route to where knowledge lives	STRETCH

3.19 Neuroscience Basis, and Where We Improve On It

Mechanism	Tottie
Encoding specificity (Tulving)	rich context tags stored at write time
Spreading activation + decay (Collins–Loftus)	the **Activator**
Pattern completion, CA3 autoassociative	the **Completer**
Pattern separation, dentate gyrus	sparse-separate on write
Predictive coding + reward prediction error	the **Surprise Gate**
Complementary Learning Systems + replay	the **Consolidator**
Reconsolidation (Nader)	the **Reconciler**, made non-destructive
Salience / neuromodulation (amygdala, NE)	the **Salience Scorer**
Ebbinghaus curve, interference	the **Ranker** (availability vs accessibility)
Testing effect, spacing, retrieval-induced forgetting	utility boost + spaced review + competitor suppression
Prospective memory	the **Prospective Queue**
Metacognition / feeling of knowing	the **Metacognitive Evaluator**
Transactive memory (Wegner)	the **Transactive Directory**
Working memory (Baddeley)	attention gate, *without the span limit*
Human constraint we improve on	**Tottie advantage**
Bounded capacity	unbounded storage
Trace decay / permanent loss	deprioritise, never destroy
Lossy reconstruction	exact, verbatim retention
Tip-of-the-tongue blocking	the cue always works
Forgetting is involuntary	forgetting is a tunable knob we own

Sources: the NotebookLM notebook "META hackathon" (`248ae575-4f2d-4ef1-b75f-d6ce38bb514a`), now over 35 sources covering hippocampal encoding and engram theory, LTP and plasticity, spreading activation, encoding specificity, consolidation, episodic/semantic/autoassociative memory, reconsolidation, forgetting and the forgetting curve, spaced repetition, the testing effect, interference, predictive coding, working memory, prospective and transactive memory, chunking, metacognition, reconstructive memory, retrieval failure, and availability versus accessibility.

Part IV

Business and Hackathon

Chapter 4

Hackathon Rules, Dates, and Judging

This chapter records the constraints we are optimising against. It is a working extract of the **Meta Global AI Developer Hackathon Participant Guide** so the team never loses sight of the rules.

4.1 Problem Statements

Every project must build toward one of two statements:
- **Build for Your World** — bring Meta's models into a domain you know firsthand.
- **Push the Frontier** — use Meta's models to give a machine a new capability.

Tottie claims *Build for Your World*: an agent memory layer solves a problem the builder knows firsthand (agents that forget), and it generalises to everyone.

4.2 Mandatory Meta Tooling

Projects must incorporate Meta's models: the *Muse Spark* series, *Muse Wonder*, *Muse Image*, *Muse Voice Transcribe*, and *SAM 3.1* via the Meta Model API; run Meta open-weight models (*Muse Glimmer*, *Muse Spark Open*); or build faster with *Muse Code*. Tottie routes its agents (Observer/Scribe/brain) through the Meta Model API, with a local fallback so the demo never dies.

4.3 Dates (all times Eastern)

When	What
Mon Oct 26, 12:00 PM	Kickoff
Tue Oct 27, 12:00–1:00 PM	Agents 101: Build a Multimodal AI Agent
Wed Oct 28, 12:00–1:00 PM	Agents 102: Best Practices for Verifiable Agents
Fri Oct 30, 12:00–1:00 PM	Specialised Intelligence on Fireworks (Muse Open)
Tue Nov 3	Last full day for submission questions
Wed Nov 4, 9:00 PM	**Final office hours; submissions due**
Thu Nov 5 – Sun Nov 8	Judging period
Mon Nov 9, 12:00 PM	Closing ceremony; top 10 announced; winners revealed
Mon Nov 16	Community vote winner announced

Building period: **Oct 27 – Nov 4**. Tottie's initial commit is dated **2026-10-27**.

4.4 Hard Rules

- **Open source:** repositories must be public.

- **Team size:** max four; solo allowed.
- **Demo requirements:** the demo must only highlight features, code, and functionality *built during the Hackathon*. Judges must be able to identify the original contributions. Failure to do so can result in immediate disqualification.
- **New work only:** what is presented must have been built during the event. Existing codebases may be built on, but new work must be clearly identified.
- **Banned:** projects that violate policy, or that use code/data/assets you lack the rights to.

4.5 Sample Anti-Projects (things to avoid resembling)

Basic RAG applications; simple image analysers; generic "AI for education" chatbots; AI job screeners; nutrition coaches; personality analysers; sports analysers; anything political or involving war; medical advice.

4.5.1 How Tottie differs from the banned "Basic RAG Application"

Tottie is *not* a read-time RAG app. It **flips RAG to write time**: the value is the ingestion-time curation decision, and the deliverable is an **MCP server** (infrastructure), not a document-chat UI. This distinction is stated explicitly on Slide 2 of the demo deck.

4.6 Judging Rubric (equally weighted, 0–10)

Category	What it asks
Impact	Real-world potential; who benefits; could people use it; does it fit a statement.
Use of Meta AI Tooling	How creatively Meta's tooling is used — beyond a basic integration.
Technical Depth & Execution	Is the engineering sound and thoughtfully refined; real craft.
Demo	Is it working, impressive, live-safe, and genuinely cool to watch.

4.7 Prizes We Target

Indie Developer track ($400k pool: $150k / $100k / $75k / $50k / $25k), plus bonus awards: **Best Agentic Use-Case** ($5k), **Best Build on Meta Open-Weight Models** ($10k), **Most Viral Project** ($20k), **Community Vote** ($10k).

Chapter 5

Hackathon Compliance Ledger

5.1 Statement of Original Contribution

Every file, commit, and line of code in this repository was authored between **2026-10-27** and **2026-11-04** — the Hackathon building window. No product code pre-existed the event. Where this project reuses architecture, it reuses *patterns* from the author's own repositories (see the Reuse Map), never third-party code or assets the author does not own. This repository is public, satisfying the open-source rule.

5.2 Feature → Commit Ledger

This table is updated at every phase gate. Judges can verify each row against `git log`.

Feature / Component	Commit	Date
Repo scaffold, env, orch config, docs skeleton	`chore: scaffold Tottie repo`	2026-10-27
LaTeX documentation set (`docs/master.pdf`)	`docs: architecture, flows, roadmap, todo`	2026-10-27
Beamer demo deck (`presentation.pdf`)	`docs: demo deck v1`	2026-10-27
Memory engine skeleton (schema, providers, minds)	`feat(core): memory engine skeleton`	2026-10-28
MCP server surface	`feat(mcp): server surface`	2026-10-29
End-to-end memory round-trip	`feat(core): memory round-trip`	2026-10-30
Tottie UI + live Memory Panel + ablation	`feat(ui): Tottie chat + memory panel`	2026-10-31
Reconcile, tag rooms, identity pinning, Lessons	`feat(core): reconcile + tags + lessons`	2026-11-01
MCP-in-IDE integration + eval harness	`feat: mcp-in-agent integration`	2026-11-02
Demo video, README, compliance ledger	`docs: demo video + compliance`	2026-11-03

5.3 Reuse Disclosure

Tottie reuses *architectural patterns* from the author's own repositories. It copies no files. See the Reuse Map in the System Architecture part.

Part V

System Architecture

Chapter 6

System Architecture

6.1 Overview

Tottie is a memory layer that any agent can mount. The **core engine** owns the memory lifecycle; the **MCP server** is the transport that exposes it; the **Tottie UI** and any **IDE coding agent** are consumers that share the same store. The engine's behaviour is specified in the preceding part, *The Cognition Model*.




Figure 6.1: Tottie: one brain, three bodies. The UI and any IDE agent mount the same MCP server and share one memory store.

6.2 The Component Roster

Each component has exactly one job. The primary agent (the "present thought") is untouched — it receives better context and can *probe*.

Component	Job	Tier
Attention Gate	filter incoming turns before storage	MUST
Surprise Gate	prediction-error score; encode only the unexpected	MUST
Cue Classifier	intent type + entities → retrieval policy	MUST
Observer	is this worth remembering?	MUST
Salience Scorer	the rubric, with surprise as a multiplier	MUST
Scribe	structure, tag, embed, route, sparse-separate	MUST
Reconciler	reconsolidation: patch the labile trace	MUST

Retriever	seed + hybrid + graph activation	MUST
Activator	spreading activation, priming, decay	MUST
Curator	assemble the Context Card + "why surfaced"	MUST
Completer	pattern completion (cluster reconstruction)	SHOULD
Decayer	adaptive forgetting, utility decay, pruning	SHOULD
Metacognitive Evaluator	confidence from the retrieval margin; gate assertions	SHOULD
Prospective Queue	event/time-triggered intentions	SHOULD
Consolidator	sleep: replay → semanticise → space → prune	SHOULD
Transactive Directory	route to where knowledge lives	STRETCH

6.3 The Tier Model

- **Identity** — persona and permanent constraints. Pinned *raw* into the card, zero search overhead. (Example: a partner's birthday.)
- **Episodic** — chronological decisions, state changes, and history.
- **Knowledge** — ingested documents, files, and references (semantic facts).
- **Procedural ("Lessons")** — mistake → problem+solution pairs, surfaced instantly on recurrence ("autosave").
- **Prospective** — intentions with an event or time cue (see the Prospective Queue).

6.4 Write Path (summary)

Attention gate → surprise gate → observe and score salience → embed and sparse-separate → reconcile NEW/SKIP/UPDATE/SUPERSEDE → route tier → persist, write links, and emit an event. Full granular flow in *Process Flows: Write Path*.

6.5 Recall Path (summary)

Classify the cue → choose the policy → seed nodes → run the three legs (semantic ∪ lexical ∪ associative) → spread activation with decay → complete the cluster → score confidence (metacognition) → curate the Context Card → emit a recall event. Full granular flow in *Process Flows: Cue Typing, Spreading Activation, and Pattern Completion*.

6.6 Reuse Map (patterns, not files)

Pattern reused	Source (author's own repo)
Embedding load (FastEmbed bge-small)	`ask.nkngo/processor/utils/embeddings.py`
pgvector + HNSW + RRF hybrid search	`ask.nkngo/processor/routers/retrieval.py`
Incremental write + SHA-256 deltas	`ask.nkngo/processor/routers/sync.py`
Relevance floors / abstention	`ask.nkngo/processor/utils/grounding.py`
MCP stdio server scaffold	`Pattern/pattern-vscode-extension/src/mcp-server`
Beamer deck preamble	`Writer/Masters/presentation/.../presentation_*.`
docs/`master.tex` preamble	`Pattern/docs/master.tex`

Chapter 7

Data Model and Storage

7.1 Storage Decision (documented exception)

Local development across the NKNGO ecosystem uses SQLite. Tottie is an explicit, reasoned exception: **semantic memory requires vector search**, and the ecosystem's canonical RAG engine (`ask.nkngo`) and Pattern already run **Postgres + pgvector** locally. Tottie therefore uses a local `tottie` database on `127.0.0.1:5432`. This is a deliberate deviation, recorded here per the workspace's non-destructive documentation standard.

7.2 Schema

```
CREATE EXTENSION IF NOT EXISTS vector;

CREATE TABLE memories (
  id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  owner       text NOT NULL,                  -- user / tenant scope
  tier        text NOT NULL CHECK (tier IN
  ↪  ('identity','episodic','knowledge','procedural')),
  kind        text NOT NULL,                  -- fact | preference | decision
  ↪  | event | doc | lesson
  subject     text,                           -- e.g. 'girlfriend',
  ↪  'server_c', 'tottie'
  predicate   text,                           -- e.g. 'birthday', 'uses_db',
  ↪  'fix'
  object      text,                           -- e.g. '2026-11-07', 'pgvector'
  content     text NOT NULL,                  -- human-readable memory
  summary     text,                           -- short form for the Context
  ↪  Card
  embedding   vector(384),                    -- bge-small-en-v1.5
  tags        text[] NOT NULL DEFAULT '{}',   -- the "rooms": #person/frans,
  ↪  #project/tottie
  salience    real NOT NULL DEFAULT 0.5,      -- write-time importance 0..1
  surprise    real DEFAULT 0.0,               -- prediction error (surprise
  ↪  gate)
  arousal     real DEFAULT 0.0,               -- moment-of-encoding salience
  ↪  (amygdala analogue)
  confidence  real DEFAULT 1.0,               -- metacognitive confidence
  utility     real DEFAULT 1.0,               -- decayed value (Ebbinghaus +
  ↪  access boost)
  principle   text,                           -- the reusable rule behind a
  ↪  decision
  access_count int DEFAULT 0,                 -- consolidation + decay +
  ↪  retrieval practice
  last_access timestamptz,                    -- decay
```

```
  source      jsonb,                          -- {session_id, turn, doc, url,
   ↪  msg_id}
  supersedes  uuid REFERENCES memories(id),  -- temporal chain
  valid_from  timestamptz NOT NULL DEFAULT now(),
  valid_to    timestamptz,                    -- NULL = currently true
  hash        text,                           -- dedupe / content hash
  created_at  timestamptz NOT NULL DEFAULT now()
);

CREATE TABLE memory_events (                -- the X-ray feed + the eval
 ↪  ledger
  id              uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  ts              timestamptz NOT NULL DEFAULT now(),
  session_id      text, turn int, utterance text,
  observer_verdict jsonb,                     -- {keep, salience, surprise,
   ↪  reason, candidates}
  scribe_action    jsonb,                     -- {op, tier, kind, tags,
   ↪  memory_id}
  cue              jsonb,                     -- {type, entities, policy} for
   ↪  recall events
  latency_ms       int, tokens int
);

CREATE TABLE memory_links (                 -- the associative index
 ↪  (hippocampal analogue)
  id       uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  owner    text NOT NULL,
  src      uuid NOT NULL REFERENCES memories(id) ON DELETE CASCADE,
  dst      uuid NOT NULL REFERENCES memories(id) ON DELETE CASCADE,
  relation text NOT NULL,                     -- tag | entity | supersedes |
   ↪  temporal | cooccur
  weight   real NOT NULL DEFAULT 1.0,
  UNIQUE (owner, src, dst, relation)
);

CREATE TABLE intentions (                    -- prospective memory ("remind
 ↪  me to...")
  id         uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  owner      text NOT NULL,
  content    text NOT NULL,                   -- "ask about the deploy"
  event_cue  text,                            -- fire when this event occurs
  time_cue   timestamptz,                     -- fire at/after this time
  status     text NOT NULL DEFAULT 'pending',  -- pending | fired | dismissed
  created_at timestamptz NOT NULL DEFAULT now(),
  fired_at   timestamptz
);
```

7.3 Indexes

```
CREATE INDEX ON memories USING hnsw (embedding vector_cosine_ops);   --
 ↪  vector recall
CREATE INDEX ON memories USING gin (tags);                           --
 ↪  room/tag filter
CREATE INDEX ON memories USING gin (to_tsvector('english', content)); --
 ↪  full-text (lexical leg)
CREATE INDEX ON memories (owner, tier) WHERE valid_to IS NULL;       --
 ↪  live-slice lookup
CREATE INDEX ON memories (owner, utility);                           --
 ↪  decay / pruning
```

```
CREATE INDEX ON memory_links (owner, src);                                  --
↪  spreading activation
CREATE INDEX ON memory_links (owner, dst);
CREATE INDEX ON intentions (owner, status, time_cue);                       --
↪  prospective trigger scan
```

7.4 Why `memory_links` Exists

Tags alone give a flat "room" model. The associative leg of retrieval needs *edges*: which memories share a tag, which entities co-occur, which memory supersedes which, which are temporally adjacent. `memory_links` is that adjacency structure — the substrate the Activator walks. Links are written only on tag, entity, and supersede events (not every turn), which bounds write amplification.

7.5 Why `utility` and `confidence` Exist

`utility` carries the **adaptive forgetting** model: it decays with age and rises with access (the testing effect), and the Decayer archives rows below the floor. `confidence` is the **metacognitive** signal computed from the retrieval margin, so the agent can choose to generate, verify, or abstain.

7.6 Temporal Correctness

Every fact carries a validity window. When a new fact contradicts an old one — and especially when the old one was *just retrieved* — the old row's `valid_to` is set to `now()` and the new row is inserted with `supersedes = old.id`. Retrieval filters `valid_to IS NULL`, so **stale facts are never returned**. See *Process Flows: Reconsolidation on Access*.

7.7 Owner Scoping

All reads and writes are scoped by `owner`. The demo runs a single owner (`owner_local`), but the schema is multi-tenant from day one: identity, recall, probe, consolidate, and forget all take an owner key.

7.8 Embeddings

Real embeddings use FastEmbed `BAAI/bge-small-en-v1.5` (384-d), loaded from the local model cache (`../../local LLMS`). A clearly-labelled `TOTTIE_EMBEDDER=hash` dev fallback exists *only* for offline smoke tests and is never presented as production behaviour.

Chapter 8

Model Providers and the Intelligence Layer

8.1 Provider Abstraction

All model calls go through one interface, so the demo can switch models without code changes:

```
class LLMProvider:
    async def complete(self, messages, json_schema=None) -> str: ...
```

- **MetaProvider** — the Meta Model API (Muse Spark series). Configured by `META_API_KEY`, `META_BASE_URL`, `META_MODEL`.
- **LocalProvider** — an OpenAI-compatible local server (Ollama `:11434` or llama.cpp `:8080`), configured by `LOCAL_LLM_URL`, `LOCAL_LLM_MODEL`.
- **resolve_provider()** — uses Meta when a key is present and the endpoint is healthy, otherwise falls back to local. **The demo never dies on a provider outage.**

8.2 Component Model Choices

Mind	Model class	Rationale
Observer	small / fast	high-frequency; a cheap classifier wins
Scribe	small / medium	structured extraction + reconcile; JSON output
Retriever	embeddings only	no LLM in the hot path — bge-small + RRF
Curator	rules (+ optional small)	deterministic card assembly within a token budget
Brain (the agent)	strongest available	the "present thought"; quality matters here

8.3 Cost Control

Tottie's whole argument is that write-time curation is cheaper than stuffing context. The eval harness measures **tokens per query** with memory ON vs OFF to make that claim falsifiable.

8.4 Optional: MCP Sampling (flagged, off by default)

MCP sampling (`ctx.session.create_message`) would let the Observer/Scribe curate using the *host's* model, with **no server-side API key** — an elegant "surprised even us" capability. Two caveats: it is **deprecated in the 2026-07-28 specification** (SEP-2577) in favour of Multi

Round-Trip Requests, and many hosts do not declare the capability. It is therefore **flag-gated** (`TOTTIE_USE_SAMPLING=0` by default) and never the primary path.

Chapter 9

MCP Surface

Tottie ships as an MCP server over **stdio** (Python SDK, `mcp<2` with `FastMCP`). The whole point is that the same memory mounts into any host: the Tottie chat, a VS Code / Cursor agent, anything that speaks MCP.

9.1 Tools

Tool	Signature	Purpose
`memory.remember`	`(text)`	Let the Scribe decide what to keep
`memory.write`	`(tier, content, tags)`	Explicit write to a named tier
`memory.recall`	`(query, tiers?, k?)`	Cue-typed associative retrieval
`memory.probe`	`(tag|id)`	Walk into a "room" and read its memories
`memory.identity`	`()`	Return the pinned identity facts
`memory.intend`	`(content, event_cue?, time_cue?)`	Register a prospective intention
`memory.sleep`	`()`	Consolidation (replay $\rightarrow$ semanticise $\rightarrow$ prune)
`memory.forget`	`(id)`	Right-to-be-forgotten (hard delete)

9.2 Resources

- `memory://identity` — the pinned persona/constraints.
- `memory://tag/{tag}` — the contents of a room, readable without a tool call.

9.3 Prompt

`tottie_context_card` — a reusable system-prompt fragment that teaches a host how to use the memory correctly (when to trust the card, when to probe, when to abstain).

9.4 Dual-Path Recall (the design answer)

A common question is: "does the retriever hand context to the agent, or does the agent probe for it?" Tottie does **both, deliberately**:

1. **Ambient path** — the Curator injects the Context Card automatically on every turn, so the agent "just knows" without issuing a query.
2. **Deliberate path** — the card carries **pointers** (tags/rooms); when the agent needs depth it calls `memory.probe(tag)` and reads that room.

9.5 Retrieval Is Cue-Typed, Not Just Similar

The `memory.recall` tool does not run a single similarity search. It classifies the cue, chooses a policy, seeds nodes, and spreads activation across `memory_links`. See *The Cognition Model* for the full specification.

9.6 Confidence in the Response

Alongside the card, `memory.recall` returns a **confidence** derived from the retrieval margin. A low-confidence result is an instruction to the host to verify or abstain rather than assert — the metacognitive gate.

Chapter 10

Tottie UI and the Live Memory Panel

10.1 Layout

A single screen, 16:9-safe for screen-capture: chat on the left, the live Memory Panel on the right.




Figure 10.1: The Memory Panel is the hero; the sprite is the reacting character.

10.2 The Panel Is a Live Stream of `memory_events`

The UI subscribes to `GET /events?session_id=` (Server-Sent Events). Each event card shows the four things that matter, in order:

1. **What it is learning now** — the turn plus the Observer verdict (KEEP/DISCARD, salience, reason).
2. **What memories it is forming** — the Scribe operation badge (`NEW` / `UPDATE` / **`SUPERSEDE`** / `SKIP`) and the memory text (superseded ones struck through).
3. **Where it inserted them** — the tier chip and the tag/room chips, plus a live **room map** that grows as new tags appear.
4. **What it injected into context** — the literal **Context Card** the Curator built for that turn, annotated with a **"why this surfaced"** line per hit (`cue=COMMAND → seed #project/tottie → spread 1 hop (w=0.6)`). This is what makes the write-time *and* the associative-retrieval decision visible on camera.

10.3 The Sleep Button

A single **Sleep** control runs the Consolidator on demand. During the run the Panel shows a progress strip (*"replaying N episodes…"*) and then a summary (*"12 episodic → 3 semantic; 4*

pruned"). It is the only control that shows *generalisation* happening. See *Process Flows: Consolidation*.

10.4 Tottie Avatar — Drop-In Sprite (frame sets per state)

- **Built here:** a `TottieFace` component plus a state machine with five states — `idle`, `listening`, `thinking`, `remembering`, `speaking` — driven by app events (streaming tokens → `speaking`; a write event or a recall → `remembering`; the Sleep job → `remembering`).
- **Provided by the Architect:** frame sets in `ui/public/tottie/<state>/`. Drop PNGs; **no code change required**.
- **Contract:** `TottieFace` reads `{state, framesDir, fps}`. A placeholder frame set ships so the app runs before the final art lands.
- **No TTS / no lip-sync.** The sprite reacts to memory events; that is the whole job.

10.5 Ablation Toggle

A single **Tottie ON/OFF** switch. OFF = no card injected and no writes (raw model). ON = full memory. Used live in the demo to prove that a correct answer *depended on* memory rather than on the base model.

Part VI

Process Flows

Chapter 11

Process Flow: The Write Path

Every step below is what the **Memory Panel** renders in its "LEARNING NOW" block. This is the flow that proves the thesis: intelligence applied at write time.

11.1 The User Says Something Durable

Trigger: In the Tottie chat the user types *"my girlfriend's birthday is on the 7th of November"* and presses enter. (Equivalently: an IDE agent turn completes and the host forwards it.)

Action / UI State: The Tottie sprite leaves `idle`, enters `listening` for the duration of the send, then `thinking`. The Memory Panel prepends a new turn card with an empty "LEARNING NOW" row and a subtle processing shimmer.

System Logic: The host issues `POST /write` with `{text, session_id, turn, owner}`. The core hands the turn to the **Observer**, which runs *in parallel* with the agent's own response generation.

Data Flow & Mutators: The turn is not yet stored as memory; it exists only as an inbound request and a `memory_event` row in `queued` state.

11.2 The Observer Decides

Trigger: The Observer receives the turn tuple.

Action / UI State: The "LEARNING NOW" row fills in: `Observer:` KEEP (or DISCARD), a salience score (e.g. 0.82), and a short reason ("durable personal fact").

System Logic: The Observer calls the resolved LLM provider with a strict JSON contract and returns a verdict:

```
{ "keep": true, "salience": 0.82, "reason": "durable personal fact",
  "candidates": [ { "tier":"identity","kind":"fact","subject":"girlfriend",
    "predicate":"birthday","object":"2026-11-07",
    "content":"Girlfriend's birthday is 7 November",
    "tags":["#person/girlfriend","#topic/birthday"] } ] }
```

Data Flow & Mutators: The verdict JSON is written into the `observer_verdict` column of the `memory_event` and pushed to the Panel over SSE. If `keep` is false, the flow ends here and the Panel shows a greyed DISCARD chip.

11.3 The Scribe Structures and Embeds

Trigger: A non-empty candidate list from the Observer.

Action / UI State: The Panel's "MEMORIES FORMED" block gains a row per candidate, showing the operation badge and the memory text.

System Logic: For each candidate the Scribe (1) composes the human-readable memory, (2) computes its embedding with `bge-small-en-v1.5`, (3) assigns tags, and (4) hands the candidate to the reconciler (next chapter).

Data Flow & Mutators: An embedding vector (384 floats) is computed in memory; the candidate is held for the reconcile step.

11.4 Reconcile, Route, and Persist

Trigger: An embedded candidate.

Action / UI State: The Panel shows the operation badge (`NEW` / `UPDATE` / `SUPERSEDE` / `SKIP`), the tier chip (e.g. `identity`), and the room chips (e.g. `#person/girlfriend`).

System Logic: See *Process Flow: Reconcile and Temporal Correctness* for the full decision table. The routed tier is recorded, and the live row is inserted with `valid_from = now()`.

Data Flow & Mutators: `INSERT INTO memories (...)`; the `memory_event.scribe_action` column is filled; the Panel's "INSERTED WHERE" block and the **room map** update; the new memory becomes immediately retrievable.

11.5 Why This Order Matters

Because the decision is made *at write time*, no read-time query is ever needed to "know" this fact. The next time the user asks anything related, the Retriever simply finds it — the agent never had to remember to save it.

Chapter 12

Process Flow: Surprise Gating and Ranking ("Forgetting")

12.1 The Attention and Surprise Gate

Trigger: Any inbound turn, before it reaches the Observer. **Action / UI State:** The Panel does *not* render routine turns; a suppressed turn shows a dimmed "surprise 0.12 → skipped" chip, while a surprising one lights up. **System Logic:** The **Attention Gate** discards noise (tool heartbeats, acknowledgements), and the **Surprise Gate** computes a prediction error — the cosine distance between the turn's embedding and the observer's expectation. Turns below `SURPRISE_FLOOR` are not encoded. **Data Flow & Mutators:** A suppressed turn produces no `memories` row; a `memory_event` records the decision so the panel and the eval ledger can show *why* nothing was stored.

12.2 A Surprising Turn Is Encoded

Trigger: A turn whose surprise clears the floor. **Action / UI State:** The Panel shows the surprise score alongside the Observer verdict. **System Logic:** Surprise enters the salience equation as a multiplier, so an unexpected fact outranks a routine one at equal persistence and consequence. A user *correction* triggers the reward-prediction-error path and is consolidated immediately. **Data Flow & Mutators:** `memories.surprise` is set; the row enters the write path with elevated salience.

12.3 Ranking, Not Deleting

Trigger: The Ranker runs (on consolidation, or periodically). **Action / UI State:** The Panel reports the ranking summary ("4 memories dropped out of the active set"), and each can be clicked to prove it is *still there*. **System Logic:** Each memory's `utility` is recomputed:

```
utility = exp(−ln2 ∗ age / half_life) ∗ (1 + log(1 + access_count))
# low utility −> lower retrieval rank + leave the attention window (STILL
↪  AVAILABLE)
```

Crucially, nothing is destroyed. A deprioritised memory is available but not accessible; the moment a matching cue arrives, the Activator revives it and it surfaces again. Hard deletion happens only on an explicit right-to-be-forgotten request. **Data Flow & Mutators:** `memories.utility` updated; the memory's *rank* changes, not its existence.

12.4 The Cue Always Works

Trigger: A later turn whose cue overlaps a deprioritised memory. **Action / UI State:** The Panel shows the memory returning with a "revived (utility 0.08 $\rightarrow$ served)" note. **System Logic:** This is the deliberate inversion of the human tip-of-the-tongue failure. Human memory fails because a weak cue cannot cross the access threshold; Tottie's search is exhaustive, so the right cue always retrieves. The memory was never lost — it was waiting. **Data Flow & Mutators:** A read; `access_count` increments, which raises utility and promotes the memory back into the active set (the testing effect).

12.5 Interference Control

Trigger: Two memories with overlapping embeddings. **System Logic:** On write, **sparse pattern separation** decorrelates near-identical representations; on read, category/namespace filters keep unrelated domains from polluting each other. This is the artificial analogue of proactive and retroactive interference control — and unlike the brain, it is a deliberate, tunable design choice. **Data Flow & Mutators:** A separation key or namespace is recorded on the row; conflicting rows are merged or superseded rather than stacked.

Chapter 13

Process Flow: The Recall Path

This is the "middle part": what happens between the user's utterance and the context the agent receives. Tottie answers it with the **Context Card** (ambient) plus the **probe** (deliberate).

13.1 A New Turn Arrives

Trigger: The user sends *"when is her birthday again?"* in the chat, or a fresh session opens and the agent needs context about the user.

Action / UI State: The sprite enters `thinking`; the Panel prepares a "CONTEXT INJECTED THIS TURN" block.

System Logic: The host calls `POST /recall` (or `memory.recall` over MCP).

Data Flow & Mutators: The utterance (and optionally the last assistant turn) is embedded with `bge-small-en-v1.5`.

13.2 The Identity Slice Is Always Included

Trigger: Any recall. **Action / UI State:** The Panel always shows the pinned identity line at the top of the card. **System Logic:** `SELECT ... WHERE tier='identity' AND valid_to IS NULL`. This is unconditional and cheap — identity has *zero search overhead*. **Data Flow & Mutators:** The identity facts are collected for the card header.

13.3 Hybrid Search

Trigger: The utterance embedding plus the owner scope. **Action / UI State:** Nothing yet — the Panel shows a "searching" shimmer. **System Logic:**

1. **Vector** leg: HNSW top-50 by cosine.
2. **Lexical** leg: full-text top-50.
3. **Filter**: `owner = ?` AND `valid_to IS NULL` (and any tag filter).
4. **Fusion**: Reciprocal Rank Fusion, $k = 60$, to top-8.
5. **Re-rank**: weight by salience · recency · confidence.

Data Flow & Mutators: A ranked hit list of `(id, tier, summary, tags, score)`.

13.4 The Procedural Slice

Trigger: The utterance resembles a previously-solved problem (an error signature or a similar embedding). **System Logic:** Match `kind='lesson'` rows; if a match clears the threshold, the solution is surfaced *instantly* — the "autosave" behaviour. **Data Flow & Mutators:** Matched lessons are appended to the card.

13.5 The Curator Builds the Context Card

Trigger: Identity slice + ranked hits + procedural matches. **Action / UI State:** The Panel's "CONTEXT INJECTED THIS TURN" block shows the exact card. **System Logic:** The Curator assembles a compact card (<400 tokens) with one line per hit, its tier, its source, and its tags, plus a "probe deeper" pointer line:

```
[MEMORY CARD - 3 hits]
  IDENTITY (pinned)  user=Frans - tz=CAT - girlfriend birthday = Nov 7
  EPISODIC 2026-10-29  decided: pgvector not Qdrant for Tottie    #tottie
  ↪  #decision
  KNOWLEDGE (doc: telecom-arch.pdf p.7)  Server C sits behind A/B  #telecom
  ↪  #infra
  -> probe deeper: memory.probe("#telecom") | memory.recall("server C
  ↪  topology")
```

Data Flow & Mutators: The card text is returned to the host and injected into the prompt space; a recall `memory_event` is written and streamed to the Panel.

13.6 The Deliberate Probe

Trigger: The agent decides it needs more depth than the card provides. **Action / UI State:** The Panel opens the targeted room and highlights the returned memories. **System Logic:** `memory.probe(tag)` (or `probe(id)`) returns the room's live memories. **Data Flow & Mutators:** A read-only fetch scoped by owner and `valid_to IS NULL`.

13.7 Ablation

Trigger: The Tottie ON/OFF toggle is set to OFF. **System Logic:** The recall step is skipped entirely — no identity slice, no hits, no card. The base model answers with no memory. This is the control condition used in the demo and the eval harness.

Chapter 14

Process Flow: Cue Typing, Spreading Activation, and Pattern Completion

14.1 The User Types an Instruction, Not a Question

Trigger: The user types *"implement feature A"* in the Tottie chat (or a coding agent issues the same over MCP).

Action / UI State: The sprite enters `thinking`; the Memory Panel opens a "RECALL" block with a *cue* chip showing the classified type.

System Logic: The **Cue Classifier** labels the turn `COMMAND/INTENT` and extracts entities and the project scope (`#project/A`). The retrieval **policy** for a command is not "find similar text"; it is *assemble what a competent person needs to act*: project bindings, conventions, prior decisions on A, lessons tied to A, and constraints.

Data Flow & Mutators: A retrieval request is issued with the intent, entities, and scope; a `memory_event` of kind `recall` begins.

14.2 Seeding the Associative Network

Trigger: The classified cue. **Action / UI State:** The Panel shows seed chips (e.g. `#project/A`, `feature A`). **System Logic:** Nodes are seeded directly from the parsed entities (bypassing similarity), and the three legs run in parallel: **semantic** (embedding nearest neighbours), **lexical** (full-text match), and **associative** (graph nodes for the seeded tags/entities). **Data Flow & Mutators:** A candidate set of memory ids with initial activation.

14.3 Spreading Activation

Trigger: The seeded candidate set. **Action / UI State:** The Panel renders each hop as it happens: "spread 1 hop (w = 0.6)". **System Logic:** The **Activator** walks `memory_links` outward from the seeds, propagating activation with a per-hop decay and a threshold cut-off. Linked memories that were never textually similar to the instruction still light up — because they are *associated*, exactly as a band name revives an unrelated scene from fifteen years ago. **Data Flow & Mutators:** A ranked activation vector over memory ids.

14.4 Pattern Completion

Trigger: A high-activation region of the graph. **Action / UI State:** The Panel groups the returned memories into one coherent cluster. **System Logic:** The **Completer** takes the top-activated *cluster* and reconstructs a coherent, self-consistent context — the biological analogue of CA3 recur-

rent excitation restoring a whole memory from a partial cue. **Data Flow & Mutators:** The cluster replaces the loose hit list.

14.5 Curate and Inject

Trigger: The completed cluster. **Action / UI State:** The Panel's "CONTEXT INJECTED THIS TURN" block shows the final Context Card, each line annotated with *why it surfaced* (cue type $\rightarrow$ seed $\rightarrow$ hops). **System Logic:** The **Curator** assembles the card within a token budget and appends the "probe deeper" pointers. **Data Flow & Mutators:** The card is injected into the prompt; a `recall` event is streamed to the Panel.

14.6 Inhibition and Abstention

Trigger: Nothing clears the activation floor, or everything retrieved is superseded. **System Logic:** Inhibit the results and inject *nothing*. Abstaining is a correct outcome; injecting noise is not.

Chapter 15

Process Flow: Reconcile and Temporal Correctness

Reconciliation is what separates a real memory from a pile of embeddings. It is the moment a new fact meets an old one.

15.1 The Decision Table

Trigger: An embedded candidate arrives from the Scribe.

System Logic: The reconciler searches for an existing memory for the same owner matching `(subject, predicate)` *or* a cosine similarity above `TOTTIE_RECONCILE_COSINE` (default 0.86) within the same tags, then decides:

Operation	When	What happens
`NEW`	No prior memory matches	Insert with `valid_from = now()`
`SKIP`	A matching memory already holds the same value	Bump confidence / salience; no new row
`UPDATE`	A matching memory is enriched but not contradicted	Append detail; refresh summary
`SUPERSEDE`	A matching memory holds a *different* value	Set old `valid_to = now()`; insert new with `supersedes = old.id`

Data Flow & Mutators: Any insert or update is written to `memories`; the decision is written to `memory_event.scribe_action` and streamed to the Panel, where a superseded memory is rendered with a strikethrough.

15.2 Worked Example: "I'm vegetarian now"

Trigger: The user says *"actually, I'm vegetarian now"*.

Action / UI State: The Panel's "MEMORIES FORMED" block shows a red-ish SUPERSEDE badge, the old value struck through ("diet: meat-eater"), and the new value ("diet: vegetarian").

System Logic:

1. The Observer flags a durable preference change (salience high; `kind=preference`).
2. The Scribe embeds the candidate and finds the live fact (`subject=user, predicate=diet, object=meat-eater`).
3. The values differ, so the operation is SUPERSEDE.
4. The old row's `valid_to` is set to `now()`; the new row is inserted with `valid_from = now()` and `supersedes = old.id`.

Data Flow & Mutators: Two row mutations and one event; retrieval now returns only "vegetarian" because it filters `valid_to IS NULL`. The agent never has to reconcile in-prompt, and it can never quote a stale fact.

15.3 Why This Is Hard and Why It Wins

Plain vector recall has *no update semantics*: both the old and the new fact retrieve, and the model is left to guess which is current. Tottie resolves the conflict at write time, once, and records the temporal chain. This is precisely the capability that LongMemEval's *knowledge update* category and MemoryAgentBench's *selective forgetting / conflict resolution* category probe — and it is a headline slide in the demo.

Chapter 16

Process Flow: Reconsolidation on Access

16.1 A Memory Is Retrieved

Trigger: Any recall that returns memory `M`. **Action / UI State:** The Panel subtly marks `M` as *active* (a soft highlight). **System Logic:** The **Reconciler** marks `M` labile for the remainder of the turn, records `last_access` and increments `access_count`. Biologically, a retrieved memory returns to an unstable state and must be re-stabilised. **Data Flow & Mutators:** A lightweight update of `access_count` / `last_access`.

16.2 The User Contradicts It

Trigger: The user says *"actually, it's the 8th"* while `M` ("her birthday is the 7th") is active. **Action / UI State:** The Panel shows a `SUPERSEDE` badge; the old value is struck through; the new value appears. **System Logic:** Because `M` is active, the write path takes the *reconsolidation* route, not a blind append: the old row's `valid_to` is set to `now()`, the new row is inserted with `supersedes = M.id`, and adjacent nodes are co-activated so the correction binds to the same context. **Data Flow & Mutators:** Two row mutations, one supersede link, one `memory_event`.

16.3 Why It Is Different

A passive store appends the correction and later returns both the old and the new fact, leaving the model to guess. A reconsolidating store resolves the conflict in the moment it is surfaced. This is the same behaviour the LongMemEval *knowledge update* category and the MemoryAgentBench *conflict resolution* category are designed to probe.

Chapter 17

Process Flow: Consolidation (the Sleep Job)

17.1 The User Presses "Sleep"

Trigger: The user clicks the **Sleep** button in the Memory Panel (or calls `POST /consolidate`, or the `memory.sleep` MCP tool).

Action / UI State: The sprite enters a calm `remembering` state; the Panel shows a progress strip reading *"replaying N episodes…"*.

System Logic: The **Consolidator** loads the recent episodic memories for the owner — the analogue of hippocampal replay during sleep.

Data Flow & Mutators: A read of `tier='episodic'` rows within the replay window.

17.2 Semanticisation

Trigger: The replayed episode set. **Action / UI State:** The Panel shows generated semantic memories appearing one by one (e.g. *"prefers X for Y"*). **System Logic:** An LLM pass extracts recurring structure across the episodes and writes **semantic** rows — the same way repeated experiences are integrated into neocortical knowledge, losing their episodic detail and becoming general. **Data Flow & Mutators:** `INSERT INTO memories (tier='knowledge', ...)` with links from the source episodes in `memory_links` (relation `cooccur`).

17.3 Pruning and Scaling

Trigger: The end of the replay pass. **Action / UI State:** The Panel prints a summary: *"12 episodic → 3 semantic; 4 pruned"*. **System Logic:** Low-activation, rarely-accessed memories and links are decayed or archived, and link weights are normalised so total capacity stays bounded (the homeostatic-scaling / long-term depression analogue). Nothing user-visible is deleted without the number being reported. **Data Flow & Mutators:** Weight decay on `memory_links`; archival flag on stale rows.

17.4 Why This Beat Exists

No other memory tool demonstrated on stage shows *generalisation* — the move from "I did this twelve times" to "I always do this". It is short (about twelve seconds), deterministic because it is on demand, and it visibly rewards keeping Tottie running.

Chapter 18

Process Flow: The Demo Click-Path

This is the exact physical sequence the presenter performs on stage and that the screen-capture video follows. Each beat is written so a second operator could run the demo cold.

18.1 Beat 1 — Cold Open (Amnesia)

Trigger: A plain agent window with no memory. **Action / UI State:** The agent greets the user and does not know their name. **System Logic:** No Tottie in the loop. **Data Flow & Mutators:** None. **On screen:** caption “A year of conversations.”

18.2 Beat 2 — Tottie Wakes (Identity Pinning)

Trigger: Open the Tottie chat. **Action / UI State:** The sprite enters `idle`; the Panel immediately shows the pinned Identity line: `girlfriend birthday = Nov 7`. **System Logic:** The Panel performs a recall; the Identity slice is returned with zero search. **Data Flow & Mutators:** A read of `tier='identity'` rows. **On screen:** caption “It just…knows.”

18.3 Beat 3 — Write-Time Magic (Supersede)

Trigger: Type *“I’m vegetarian now”*. **Action / UI State:** The Panel shows `Observer:` KEEP, then a SUPERSEDE badge with the old value struck through; the room map gains a tag. **System Logic:** The full write path plus reconcile (see the Write Path and Reconcile flows). **Data Flow & Mutators:** Old row closed; new row inserted; event streamed.

18.4 Beat 4 — Three Bodies (Cross-Agent Recall)

Trigger: Switch to VS Code; ask the coding agent about the project’s stack. **Action / UI State:** The coding agent answers with the database and architecture decisions it was never told in this session — because they were written in the Tottie chat. **System Logic:** Same MCP server, same store, different host. **Data Flow & Mutators:** A `memory.recall` over MCP from the IDE. **On screen:** the caption “one brain, three bodies.”

18.5 Beat 5 — Autosave a Mistake

Trigger: The coding agent hits a known error. **Action / UI State:** The Panel shows a NEW lesson being formed (problem → solution). **System Logic:** A `kind=lesson` memory is written under `tier=procedural`. **Data Flow & Mutators:** Insert into `memories` with the error signature for matching.

18.6 Beat 6 — Restart + Ablation

Trigger: Kill the session; reopen; ask a question answered 20 minutes ago. **Action / UI State:** It answers correctly. Flip **Tottie OFF**; the same question now returns "I don't know"; flip **ON**; it answers again. **System Logic:** The OFF state skips the recall path entirely. **Data Flow & Mutators:** With OFF, no card is injected.

18.7 Beat 7 — The Joke and the Pitch

Trigger: Back in the chat. **On screen:** caption *"…everything I was mad at my girlfriend for — and the one thing that matters: her birthday."* Then the universal pitch: autosave for mistakes, a personal AI that knows you, and the company brain (Server C behind Server A and B).

Part VII

Planning

Chapter 19

Roadmap

19.1 Scope Tiers (9 days, solo, alongside work and study)

Tier	Contents
MUST	Attention Gate · **Surprise Gate** · Salience Scorer · Cue Classifier · Scribe (+sparse separation) · Reconciler · Retriever · Activator · Curator · MCP server · Context Card + probe · Tottie UI · ON/OFF ablation · eval harness · 3-minute video · docs + deck
SHOULD	**Ranker + Compressor** (adaptive forgetting) · **Metacognitive Evaluator** · **Prospective Queue** · Completer · Consolidator (on-demand "Sleep") · coding-agent MCP integration · Autosave/Lessons · `memory_links` graph
STRETCH	**Transactive Directory** · self-testing during idle · spaced-review scheduler · full relation extraction · autoassociative reconstruction · MCP-sampling curation · X/viral push

19.2 Phase Schedule

Phase	Dates	Deliverable
P0	Oct 27	Scaffold: repo, gitignore, env, orch config, docs skeleton, first commit
P1	Oct 27	Docs: all `docs/**/*.tex` → `master.pdf`
P2	Oct 27–28	Deck: `presentation.tex` → `presentation.pdf`
P3	Oct 28–29	Core: engine + schema + providers + attention/surprise/salience/cue/scribe
P4	Oct 29	MCP: server tools/resources wired
P5	Oct 30	End-to-end memory round-trip
P6	Oct 30–31	UI: chat + sprite + live Memory Panel + ablation + why-surfaced
P7	Oct 31–Nov 1	Reconciler/reconsolidation, tag rooms, identity pinning, Lessons, `memory_links`, Ranker + Compressor
P8	Nov 1–2	Activator + Completer · Metacognitive Evaluator · Prospective Queue · Consolidator · MCP-in-IDE · eval harness
P9	Nov 3	3-minute video, README, recompile docs, compliance ledger
P10	Nov 4	Repo public, video link, credits claimed, submit by 9 PM ET

19.3 Gating

A phase does not begin until the prior phase's **docs** are written and its tests (where applicable) pass. If time runs short, cut in this order: STRETCH → Completer → Consolidator (degrades to a summary stub) → Prospective Queue → Ranker + Compressor. **Never cut the Surprise Gate, the eval harness, or the demo video.**

19.4 Mandates Honoured During the Build

Document First → Implement → Test → Conclude; atomic commits after every step; every `.tex` auto-compiled to PDF; env vars in both `orch.config.json` and `.env.example`.

Chapter 20

Master Todo

20.1 Phase 0 — Scaffold

☐ Create repo tree; `git init`; branch `main`
☐ `.gitignore`, `.env.example`, `orch.config.json`, `Makefile`
☐ `README.md`, `GEMINI.md`, `.agents/orch-directive.md`
☐ First commit dated 2026-10-27

20.2 Phase 1 — Documentation

☐ `master.tex` + every part `*.tex` (incl. the cognition model)
☐ Compile `master.pdf` (`latexmk -xelatex`); zero undefined refs

20.3 Phase 2 — Deck

☐ `presentation.tex` (Beamer, Madrid/whale, 16:9)
☐ Compile `presentation.pdf` (`pdflatex` $\times 2$)

20.4 Phase 3 — Core Engine (the gate + the minds)

☐ `config.py`, `db.py`, `schema.sql` (memories, events, links, intentions)
☐ `embeddings.py` (bge-small + labelled hash fallback)
☐ `providers/` (base, meta, local, resolve)
☐ `agents/attention.py`, `surprise.py`, `salience.py`, `cue_classifier.py`
☐ `agents/observer.py`, `scribe.py` (+sparse separation), `retriever.py`, `curator.py`

20.5 Phase 4 — MCP

☐ `mcp/server.py`: 8 tools + 2 resources + `tottie_context_card`
☐ `--list-tools` prints the surface

20.6 Phase 5 — Round-Trip

☐ `POST /write` $\rightarrow$ gated store $\rightarrow$ `POST /recall` $\rightarrow$ Card + confidence
☐ `GET /events` SSE stream for the Panel

20.7 Phase 6 — UI

☐ `TottieFace` (5-state machine + frame-set contract + placeholders)
☐ `ChatStream`, `MemoryPanel`, `RoomMap`, `AblationToggle`, why-surfaced line, Sleep button

20.8 Phase 7 — Reconcile / Tags / Identity / Links / Decay

☐ Reconsolidation (`valid_to` / `supersedes`); labile-on-access
☐ Hierarchical tags / rooms; identity allowlist
☐ `memory_links` written on tag/entity/supersede events
☐ Ranker + Compressor: utility decay + pruning; access boosts utility (testing effect)

20.9 Phase 8 — Cognition + Integration + Eval

☐ Activator (spreading activation, priming, decay) + Completer (pattern completion)
☐ Metacognitive Evaluator (confidence) + Prospective Queue (`memory.intend`)
☐ Consolidator (on-demand Sleep: replay $\rightarrow$ semanticise $\rightarrow$ prune)
☐ Mount MCP in VS Code / Cursor (three bodies)
☐ `eval/harness.py` + `scenarios.jsonl` (ON/OFF ablation + consolidation check)

20.10 Phase 9 — Film

☐ 3-minute screen-capture video (captions + music), incl. the Sleep beat
☐ README final; recompile docs; update the compliance ledger

20.11 Phase 10 — Submit

☐ Make repo public; video link accessible
☐ Claim Meta credits ($<$ Wed Nov 4, 9 PM ET)
☐ Submit via the CV platform

Chapter 21

Demo Script (3 minutes, screen capture + captions + music)

Format: pure screen capture, on-screen captions, a music bed. No talking head. Total runtime **3:00**. Every caption is written to be readable on a phone.

21.1 Shot List

Time	Beat	On screen
0:00	Cold open	Black. Caption: *"A year of conversations."* A plain agent: *"Hi — I don't know you."* Music swells.
0:12	The problem	Restart = amnesia; the agent re-asks your name. Caption: *"Long context isn't memory."*
0:30	The reveal	Sprite wakes; Panel pins Identity `birthday = Nov 7`. Caption: *"It just…knows."*
0:52	Write-time magic	*"I'm vegetarian now"* → Panel: `SUPERSEDE` (old struck through); a new fact → Observer verdict + Scribe `NEW` live.
1:14	Why this surfaced	Command: *"implement feature A"*. Panel: `cue=COMMAND` → `seed #project/A` → `spread 1 hop`. Caption: *"It doesn't search. It associates."*
1:32	**The constraint we refused**	**A memory drops out of the active set: "utility 0.06 → archived" (greyed, but present). Then the cue arrives — it returns instantly. Caption: *"We didn't copy the forgetting. We copied the finding."* Then: *"Not a better memory — a memory without the bug."***
1:52	Three bodies	Cut to VS Code: the coding agent already knows the stack; it hits a bug; **autosave** a lesson; a new session recalls the fix.
2:08	Sleep	Press **Sleep**. Caption: *"12 moments become 3 lessons."* Panel: *12 episodic → 3 semantic; 4 ranked out*.
2:20	Restart + ablation	Kill the session, reopen, ask an old question → knows. Flip **Tottie OFF** → *"I don't know."* ON → knows.
2:42	Joke + pitch	Caption: *"…everything I was mad at my girlfriend for — and the one thing that matters: her birthday."* → the aspirational line + repo link.

21.2 Narration Captions (verbatim)

1. “A year of conversations.”
2. “It still doesn’t know your name.”
3. “Long context isn’t memory — it’s a tax.”
4. “Tottie applies intelligence at write time.”
5. “It decides what matters before you ever need it.”
6. “Ask it to build something. It doesn’t search — it associates.”
7. “Human memory forgets because it is bounded. Ours isn’t.” (the constraint scene)
8. “We didn’t copy the forgetting. We copied the finding.”
9. “Not a better memory — a memory without the bug.”
10. “One brain. Three bodies. Your chat, your code, the panel.”
11. “Then it sleeps — and generalises.”
12. “Turn it off, and it forgets. Turn it on, and it knows.”
13. “So — I used it to remember everything I was mad at my girlfriend for. And the one thing that actually matters: her birthday.”

21.3 Music and Pacing

Cinematic and rising under the reveal; a small pulse on the “spreading activation” beat; a *brief quiet* under the constraint scene (let the words land), then a lift on “memory without the bug”; a calm passage under Sleep; a beat drop on the ablation flip; a warm settle under the joke. Cuts land on caption boundaries. Keep on-screen text large; assume a phone screen.

Chapter 22

Plan Audit (Numbered Outline and Method)

This chapter makes the plan *auditable*. Every part of it carries a stable ID so a second reviewer (human or agent) can judge it section by section without asking for context.

22.1 Audit Method

For each numbered item we record one verdict against six fixed axes:

Axis	Question
Feasibility	Can one person build this Oct 27–Nov 4 alongside work and study?
Dependency	What must exist first? Does it already exist (Reuse Map)?
Risk	What breaks it — live on stage, or under judge scrutiny?
Rubric	Which judging column it serves (Impact / Meta tooling / Technical depth / Demo).
Cost	Effort: S (hours) · M (a day) · L (multi-day).
Verdict	Keep · Improve · Cut · Add · Defer.

22.2 Independent-Review Questions (for third-party judges)

1. Does it satisfy the problem statement (*Build for Your World* / *Push the Frontier*)?
2. Is Meta's tooling central, not decorative?
3. Is the engineering sound and thought through?
4. Is the demo compelling *and live-safe*?
5. Is it clearly new work, distinguishable from reuse?
6. Is anything here a banned anti-project?
7. Are the claims measurable (not vibes)?
8. Is the scope honest for 9 solo days?

22.3 The Numbered Outline

1. **Meta & scope** — event/dates; repo/branch/commit rule; decision log; scope note.
2. **Strategy** — thesis; positioning vs mem0/Zep/Letta; differentiators; problem statement.
3. **Demo design** — three bodies; the money shot; video style; **the Sleep beat**.
4. **Architecture & cognition** — the ten components; tiers; write path; reconcile; tier routing; recall path; Context Card; probe/tags; concurrency; **cue classifier**; **activator**; **completer**; **consolidator**; **salience gate**; **reconsolidation**; **neuroscience basis**.

5. **Data & storage** — `memories`; `memory_events`; indexes; pgvector decision; embeddings; init; owner scoping; **`memory_links`**; **principle/arousal/access fields**.
6. **Intelligence layer** — Observer; Scribe; Curator; providers; model choice/cost; sampling; **consolidation prompts**.
7. **Interfaces** — HTTP surface (`/consolidate`); MCP tools (`memory.sleep`); resources; prompt; SSE events; error/abstention.
8. **UI/UX** — layout; panel blocks; sprite state machine; ablation; room map; typography; **why-surfaced line + Sleep button**.
9. **Evaluation** — scenario set; ablation method; metrics; harness; rubric mapping; **consolidation check**.
10. **Execution plan** — MUST/SHOULD/STRETCH; phase schedule; gating; mandates.
11. **Media** — shot list; deck; music/captions; viral plan.
12. **Repo & tooling** — tree; reuse map; orch/env; docs structure; build commands; gitignore/Makefile; **cognition modules**.
13. **Compliance** — rules mapping; contribution ledger; prize targeting; banned-avoidance.
14. **Risk** — register; live-demo mitigations; **cognition scope-creep mitigations**.
15. **Verification** — test plan; dry-run checklist; orch checks.
16. **Open items** — sprite frames; Meta keys; sampling; name/branch.
17. **Appendices** — rules extract; glossary; sources.

22.4 Audit Ledger

The per-item verdicts are maintained alongside this specification. Items are resolved to `Keep`/`Improve` before the spec is frozen for build. The cognition-model IDs added in v3 (**4.9–4.15, 5.7–5.8, 6.6, 8.6, 9.5, 3.6**) are recorded as `Add`, with the two open items resolved: the Consolidator is SHOULD/on-demand, and the Sleep beat enters the video.