

Spatial Data I: Working with Spatial Data

Francisco Villamil

Applied Quantitative Methods II
MA in Social Sciences, Spring 2026

Today's goals

- Understand why location matters in social science research

Today's goals

- Understand why location matters in social science research
- Learn the main types of spatial data: vector and raster

Today's goals

- Understand why location matters in social science research
- Learn the main types of spatial data: vector and raster
- Grasp what a coordinate reference system (CRS) is and why it matters

Today's goals

- Understand why location matters in social science research
- Learn the main types of spatial data: vector and raster
- Grasp what a coordinate reference system (CRS) is and why it matters
- Work with spatial data in R using the `sf` package

Today's goals

- Understand why location matters in social science research
- Learn the main types of spatial data: vector and raster
- Grasp what a coordinate reference system (CRS) is and why it matters
- Work with spatial data in R using the `sf` package
- Visualize spatial data with `ggplot2`

Roadmap

Why Spatial Data?

Types of Spatial Data


Coordinate Reference Systems

The sf Package

Visualization with ggplot2

Wrap-up

Location matters



Spatial questions in political science

- **Conflict:** Do armed events cluster? Does violence diffuse across borders?

Spatial questions in political science

- **Conflict:** Do armed events cluster? Does violence diffuse across borders?
 - Data: ACLED event locations (lat/lon coordinates)

Spatial questions in political science

- **Conflict:** Do armed events cluster? Does violence diffuse across borders?
 - Data: ACLED event locations (lat/lon coordinates)
- **Elections:** How does vote share vary across districts?

Spatial questions in political science

- **Conflict:** Do armed events cluster? Does violence diffuse across borders?
 - Data: ACLED event locations (lat/lon coordinates)
- **Elections:** How does vote share vary across districts?
 - Data: municipality-level polygons with electoral results

Spatial questions in political science

- **Conflict:** Do armed events cluster? Does violence diffuse across borders?
 - Data: ACLED event locations (lat/lon coordinates)
- **Elections:** How does vote share vary across districts?
 - Data: municipality-level polygons with electoral results
- **Environment:** Do voters near polluting facilities vote differently?

Spatial questions in political science

- **Conflict:** Do armed events cluster? Does violence diffuse across borders?
 - Data: ACLED event locations (lat/lon coordinates)
- **Elections:** How does vote share vary across districts?
 - Data: municipality-level polygons with electoral results
- **Environment:** Do voters near polluting facilities vote differently?
 - Data: facility locations + electoral district polygons

Spatial questions in political science

- **Conflict:** Do armed events cluster? Does violence diffuse across borders?
 - Data: ACLED event locations (lat/lon coordinates)
- **Elections:** How does vote share vary across districts?
 - Data: municipality-level polygons with electoral results
- **Environment:** Do voters near polluting facilities vote differently?
 - Data: facility locations + electoral district polygons
- **Inequality:** How does poverty vary within a city?


Spatial questions in political science

- **Conflict:** Do armed events cluster? Does violence diffuse across borders?
 - Data: ACLED event locations (lat/lon coordinates)
- **Elections:** How does vote share vary across districts?
 - Data: municipality-level polygons with electoral results
- **Environment:** Do voters near polluting facilities vote differently?
 - Data: facility locations + electoral district polygons
- **Inequality:** How does poverty vary within a city?
 - Data: census tract polygons + socioeconomic attributes

Think about your own research topic.

What is its **spatial dimension**?

What data would you need — points, lines, or polygons?



Roadmap

Why Spatial Data?

Types of Spatial Data


Coordinate Reference Systems

The sf Package

Visualization with ggplot2

Wrap-up


Two families of spatial data



- Today we'll focus more on **vector** data and how to work with it (more common in social science)


Vector data: three geometry types

Points




Cities
Events
Survey respondents

Lines




Roads
Rivers
Administrative borders


Polygons



Countries
Municipalities
Electoral districts







How does it look internally: geometry + attributes

name	population	vote_share	gdp_pc	geometry
Madrid	3,305,408	0.34	38,200	POLYGON((-3.8 40.7, ...))
Barcelona	1,620,343	0.21	41,500	POLYGON((2.0 41.2, ...))
Valencia	814,208	0.29	29,100	POLYGON((-0.4 39.4, ...))
Sevilla	690,566	0.41	24,800	POLYGON((-6.0 37.3, ...))

- A spatial object is a **data frame** with a geometry column

How does it look internally: geometry + attributes

name	population	vote_share	gdp_pc	geometry
Madrid	3,305,408	0.34	38,200	POLYGON((-3.8 40.7, ...))
Barcelona	1,620,343	0.21	41,500	POLYGON((2.0 41.2, ...))
Valencia	814,208	0.29	29,100	POLYGON((-0.4 39.4, ...))
Sevilla	690,566	0.41	24,800	POLYGON((-6.0 37.3, ...))

- A spatial object is a **data frame** with a geometry column
- All regular data operations work as usual

How does it look internally: geometry + attributes

name	population	vote_share	gdp_pc	geometry
Madrid	3,305,408	0.34	38,200	POLYGON((-3.8 40.7, ...))
Barcelona	1,620,343	0.21	41,500	POLYGON((2.0 41.2, ...))
Valencia	814,208	0.29	29,100	POLYGON((-0.4 39.4, ...))
Sevilla	690,566	0.41	24,800	POLYGON((-6.0 37.3, ...))


- A spatial object is a **data frame** with a geometry column
- All regular data operations work as usual
- Geometry encodes the shape: coordinates of vertices for polygons

How does it look internally: geometry + attributes

name	population	vote_share	gdp_pc	geometry
Madrid	3,305,408	0.34	38,200	POLYGON((-3.8 40.7, ...))
Barcelona	1,620,343	0.21	41,500	POLYGON((2.0 41.2, ...))
Valencia	814,208	0.29	29,100	POLYGON((-0.4 39.4, ...))
Sevilla	690,566	0.41	24,800	POLYGON((-6.0 37.3, ...))



- A spatial object is a **data frame** with a geometry column
- All regular data operations work as usual
- Geometry encodes the shape: coordinates of vertices for polygons
- One row = one spatial feature (a city, a district, a country)

Raster data: a brief preview






Each cell stores one value

- Grid of equal-size cells, each storing a value (elevation, precipitation, ...), which are **georeferenced**
- **Continuous surface**: the entire area is covered
- In R: terra package (`rast()` objects)



Legend






44°N

42°N

40°N

38°N

36°N



8°W

6°W

4°W


2°W

0°

2°E

4°E

value



10

5

0

-5


44°N

42°N

40°N

38°N

36°N



8°W

6°W

4°W

2°W

0°

2°E

4°E

value

10

5

0

-5


44°N

42°N

40°N

38°N

36°N



8°W

6°W

4°W


2°W

0°

2°E

4°E

value



10

5

0

-5

44°N

42°N

40°N

38°N

36°N



value

10

5

0

-5

8°W

6°W

4°W

2°W

0°

2°E

4°E


44°N

42°N

40°N

38°N

36°N




value


10

5

0

-5





Project Edit View Layer Settings Plugins Vector Raster Database Web Mesh Processing Help



Layers

- ☒ Gettysburg Original_modified
- ☒ OSM Standard



QGIS

Coordinate Reference System: EPSG:3857
Scale: 1:100000
Projection: EPSG:3857
Rotation: 0.0°
Render: EPSG:3857




Figure 6.1: AMS 1301 map NE-44, edition 7, covering Hyderabad in 1954.





Figure 6.7: Final digitized road network (in green) superimposed on the original scanned map image.



Roadmap

Why Spatial Data?

Types of Spatial Data

Coordinate Reference Systems

The sf Package

Visualization with ggplot2

Wrap-up

How do we locate things on Earth?

- The Earth is a (roughly) spherical three-dimensional object

How do we locate things on Earth?

- The Earth is a (roughly) spherical three-dimensional object
- We need a system to assign coordinates to locations on its surface

How do we locate things on Earth?

- The Earth is a (roughly) spherical three-dimensional object
- We need a system to assign coordinates to locations on its surface
- A **Coordinate Reference System (CRS)** defines:

How do we locate things on Earth?

- The Earth is a (roughly) spherical three-dimensional object
- We need a system to assign coordinates to locations on its surface
- A **Coordinate Reference System (CRS)** defines:
 - The **origin** and **axes** of the coordinate system

How do we locate things on Earth?

- The Earth is a (roughly) spherical three-dimensional object
- We need a system to assign coordinates to locations on its surface
- A **Coordinate Reference System (CRS)** defines:
 - The **origin** and **axes** of the coordinate system
 - The **shape** of the Earth used (datum / ellipsoid)

How do we locate things on Earth?

- The Earth is a (roughly) spherical three-dimensional object
- We need a system to assign coordinates to locations on its surface
- A **Coordinate Reference System (CRS)** defines:
 - The **origin** and **axes** of the coordinate system
 - The **shape** of the Earth used (datum / ellipsoid)
 - How coordinates map to the actual surface

How do we locate things on Earth?

- The Earth is a (roughly) spherical three-dimensional object
- We need a system to assign coordinates to locations on its surface
- A **Coordinate Reference System (CRS)** defines:
 - The **origin** and **axes** of the coordinate system
 - The **shape** of the Earth used (datum / ellipsoid)
 - How coordinates map to the actual surface
- Two main families:


How do we locate things on Earth?

- The Earth is a (roughly) spherical three-dimensional object
- We need a system to assign coordinates to locations on its surface
- A **Coordinate Reference System (CRS)** defines:
 - The **origin** and **axes** of the coordinate system
 - The **shape** of the Earth used (datum / ellipsoid)
 - How coordinates map to the actual surface
- Two main families:
 - **Geographic CRS**: longitude and latitude on a sphere

How do we locate things on Earth?


- The Earth is a (roughly) spherical three-dimensional object
- We need a system to assign coordinates to locations on its surface
- A **Coordinate Reference System (CRS)** defines:
 - The **origin** and **axes** of the coordinate system
 - The **shape** of the Earth used (datum / ellipsoid)
 - How coordinates map to the actual surface
- Two main families:
 - **Geographic CRS**: longitude and latitude on a sphere
 - **Projected CRS**: Cartesian x/y on a flat surface

Geographic CRS: longitude and latitude




- **Longitude:** degrees East/West from the Prime Meridian (−180 to +180)

Geographic CRS: longitude and latitude




- **Longitude:** degrees East/West from the Prime Meridian (-180 to $+180$)
- **Latitude:** degrees North/South from the Equator (-90 to $+90$)

Geographic CRS: longitude and latitude




- **Longitude:** degrees East/West from the Prime Meridian (-180 to $+180$)
- **Latitude:** degrees North/South from the Equator (-90 to $+90$)
- **WGS84** (EPSG:4326): the universal standard — used by GPS, Google Maps

Projected CRS: flattening the Earth




- Converts degrees to meters (or feet) on a flat surface

Projected CRS: flattening the Earth




- Converts degrees to meters (or feet) on a flat surface
- **Mercator** (EPSG:3857): shapes preserved, areas hugely distorted at poles

Projected CRS: flattening the Earth



- Converts degrees to meters (or feet) on a flat surface
- **Mercator** (EPSG:3857): shapes preserved, areas hugely distorted at poles
- **UTM zones**: accurate locally, 60 zones worldwide

Projected CRS: flattening the Earth



- Converts degrees to meters (or feet) on a flat surface
- **Mercator** (EPSG:3857): shapes preserved, areas hugely distorted at poles
- **UTM zones**: accurate locally, 60 zones worldwide
- Use projected CRS for **distance and area calculations**

EPSG codes: the practical shorthand

EPSG	Name	Use case
4326	WGS84 (geographic)	GPS, raw CSV coordinates, global data
3857	Web Mercator	Google Maps, web tiles (not for analysis)
3035	ETRS89-LAEA	Europe: equal-area, good for area/distance
32630	UTM Zone 30N	Spain and Portugal (local accuracy)
5070	Albers Equal Area	USA (equal-area for national maps)

- Always check the CRS of your data with `st_crs()`

EPSG codes: the practical shorthand

EPSG	Name	Use case
4326	WGS84 (geographic)	GPS, raw CSV coordinates, global data
3857	Web Mercator	Google Maps, web tiles (not for analysis)
3035	ETRS89-LAEA	Europe: equal-area, good for area/distance
32630	UTM Zone 30N	Spain and Portugal (local accuracy)
5070	Albers Equal Area	USA (equal-area for national maps)

- Always check the CRS of your data with `st_crs()`
- All layers in an analysis must use the **same CRS**

EPSG codes: the practical shorthand

EPSG	Name	Use case
4326	WGS84 (geographic)	GPS, raw CSV coordinates, global data
3857	Web Mercator	Google Maps, web tiles (not for analysis)
3035	ETRS89-LAEA	Europe: equal-area, good for area/distance
32630	UTM Zone 30N	Spain and Portugal (local accuracy)
5070	Albers Equal Area	USA (equal-area for national maps)

- Always check the CRS of your data with `st_crs()`
- All layers in an analysis must use the **same CRS**
- Transform with `st_transform(data, crs = 3035)`

Roadmap

Why Spatial Data?

Types of Spatial Data

Coordinate Reference Systems

The `sf` Package

Visualization with `ggplot2`

Wrap-up

sf: Simple Features for R

- **Simple Features** is an open standard for vector spatial data (ISO 19125)

sf: Simple Features for R

- **Simple Features** is an open standard for vector spatial data (ISO 19125)
- The `sf` package is the modern R implementation

sf: Simple Features for R

- **Simple Features** is an open standard for vector spatial data (ISO 19125)
- The `sf` package is the modern R implementation
 - Replaced the older `sp` + `rgdal` + `rgeos` ecosystem

sf: Simple Features for R

- **Simple Features** is an open standard for vector spatial data (ISO 19125)
- The `sf` package is the modern R implementation
 - Replaced the older `sp` + `rgdal` + `rgeos` ecosystem
 - Seamless `dplyr` and `ggplot2` integration

sf: Simple Features for R

- **Simple Features** is an open standard for vector spatial data (ISO 19125)
- The `sf` package is the modern R implementation
 - Replaced the older `sp` + `rgdal` + `rgeos` ecosystem
 - Seamless `dplyr` and `ggplot2` integration
- An `sf` object is a **data frame** with:

sf: Simple Features for R

- **Simple Features** is an open standard for vector spatial data (ISO 19125)
- The `sf` package is the modern R implementation
 - Replaced the older `sp` + `rgdal` + `rgeos` ecosystem
 - Seamless `dplyr` and `ggplot2` integration
- An `sf` object is a **data frame** with:
 - Regular attribute columns (any type)

sf: Simple Features for R

- **Simple Features** is an open standard for vector spatial data (ISO 19125)
- The `sf` package is the modern R implementation
 - Replaced the older `sp` + `rgdal` + `rgeos` ecosystem
 - Seamless `dplyr` and `ggplot2` integration
- An `sf` object is a **data frame** with:
 - Regular attribute columns (any type)
 - A geometry column (type `sfc`) storing the shapes

sf: Simple Features for R

- **Simple Features** is an open standard for vector spatial data (ISO 19125)
- The `sf` package is the modern R implementation
 - Replaced the older `sp` + `rgdal` + `rgeos` ecosystem
 - Seamless `dplyr` and `ggplot2` integration
- An `sf` object is a **data frame** with:
 - Regular attribute columns (any type)
 - A geometry column (type `sfc`) storing the shapes
 - CRS metadata attached to the object

sf: Simple Features for R

- **Simple Features** is an open standard for vector spatial data (ISO 19125)
- The `sf` package is the modern R implementation
 - Replaced the older `sp` + `rgdal` + `rgeos` ecosystem
 - Seamless `dplyr` and `ggplot2` integration
- An `sf` object is a **data frame** with:
 - Regular attribute columns (any type)
 - A geometry column (type `sfc`) storing the shapes
 - CRS metadata attached to the object
- All geometry types: `POINT`, `LINestring`, `POLYGON` and their multi-variants

What does an sf object look like?

```
Console output: print(world[1:3,])
```

```
Simple feature collection with 3 features and 5 fields
```

```
Geometry type:  MULTIPOLYGON
```

```
CRS: EPSG 4326 (WGS84)
```

	name_long	continent	pop	geom
1	Afghanistan	Asia	32564342	MULTIPOLYGON(((61.2 35.6...
2	Angola	Africa	24227524	MULTIPOLYGON(((16.3 -5.8...
3	Albania	Europe	2893654	MULTIPOLYGON(((20.6 41.9...

- Header: feature count, geometry type, CRS — always shown first

What does an sf object look like?

```
Console output: print(world[1:3,])
```

```
Simple feature collection with 3 features and 5 fields
```

```
Geometry type: MULTIPOLYGON
```

```
CRS: EPSG 4326 (WGS84)
```

	name_long	continent	pop	geom
1	Afghanistan	Asia	32564342	MULTIPOLYGON(((61.2 35.6...
2	Angola	Africa	24227524	MULTIPOLYGON(((16.3 -5.8...
3	Albania	Europe	2893654	MULTIPOLYGON(((20.6 41.9...

- Header: feature count, geometry type, CRS — always shown first
- Rows = features; geom column stores the shapes (truncated in display)

What does an sf object look like?

```
Console output: print(world[1:3,])
```

```
Simple feature collection with 3 features and 5 fields
```

```
Geometry type: MULTIPOLYGON
```

```
CRS: EPSG 4326 (WGS84)
```

	name_long	continent	pop	geom
1	Afghanistan	Asia	32564342	MULTIPOLYGON(((61.2 35.6...
2	Angola	Africa	24227524	MULTIPOLYGON(((16.3 -5.8...
3	Albania	Europe	2893654	MULTIPOLYGON(((20.6 41.9...

- Header: feature count, geometry type, CRS — always shown first
- Rows = features; geom column stores the shapes (truncated in display)
- Otherwise: a regular data frame — dplyr verbs work immediately

Reading spatial data

From a shapefile or GeoPackage

```
library(sf)
world = st_read("data/world.shp")
munis = st_read("data/municipalities.gpkg")
```

- `st_read()` handles: shapefiles (.shp), GeoPackage (.gpkg), GeoJSON, and more

Reading spatial data

From a CSV with coordinate columns

```
df = read.csv("events.csv")
# df has columns: lon, lat, event_type, casualties
events = st_as_sf(df,
  coords = c("lon", "lat"),
  crs = 4326)
```

Inspecting an sf object

```
class(world)
# [1] "sf" "data.frame"
```

```
st_crs(world)$epsg
# [1] 4326
```

```
st_geometry_type(world, by_geometry = FALSE)
# [1] MULTIPOLYGON
```

```
nrow(world) # number of features
ncol(world) # number of columns (incl. geometry)
```

```
head(world) # shows first rows with geometry
```

Attribute operations: dplyr works as usual

```
# Filter to European countries
europe = world %>% filter(continent == "Europe")

# Select columns + compute log population
world = world %>%
  select(name, pop, gdp_pc, geometry) %>%
  mutate(log_pop = log(pop))

# Summarize: total population by continent
cont = world %>%
  group_by(continent) %>%
  summarize(total_pop = sum(pop, na.rm = TRUE))

# Geometry is ‘‘sticky’’ --- always retained
# To get a plain data frame: st_drop_geometry()
world_df = st_drop_geometry(world)
```

CRS operations

Check the CRS

```
st_crs(world) # full CRS info  
st_crs(world)$epsg # just the EPSG code
```

Transform to a different CRS

```
# Reproject to ETRS89-LAEA (Europe equal-area)  
europe_proj = st_transform(europe, crs = 3035)
```

- **Always** transform before computing distances or areas

CRS operations

Check the CRS

```
st_crs(world) # full CRS info  
st_crs(world)$epsg # just the EPSG code
```

Transform to a different CRS

```
# Reproject to ETRS89-LAEA (Europe equal-area)  
europe_proj = st_transform(europe, crs = 3035)
```

- **Always** transform before computing distances or areas
- **Always** ensure all layers share the same CRS before spatial joins

CRS operations

Check the CRS

```
st_crs(world) # full CRS info  
st_crs(world)$epsg # just the EPSG code
```

Transform to a different CRS

```
# Reproject to ETRS89-LAEA (Europe equal-area)  
europe_proj = st_transform(europe, crs = 3035)
```

- **Always** transform before computing distances or areas
- **Always** ensure all layers share the same CRS before spatial joins
- `st_transform()` reprojects precisely — do not manually change coordinates

Geometric operations

- `st_area(polygons)` — area of each polygon (in m^2 if projected)

Geometric operations

- `st_area(polygons)` — area of each polygon (in m^2 if projected)
- `st_distance(pts, pts)` — pairwise distance matrix between features

Geometric operations

- `st_area(polygons)` — area of each polygon (in m^2 if projected)
- `st_distance(pts, pts)` — pairwise distance matrix between features
- `st_centroid(polygons)` — centroid point of each polygon

Geometric operations

- `st_area(polygons)` — area of each polygon (in m^2 if projected)
- `st_distance(pts, pts)` — pairwise distance matrix between features
- `st_centroid(polygons)`— centroid point of each polygon
- `st_buffer(pts, dist = 5000)`— 5 km buffer around each point

Geometric operations

- `st_area(polygons)` — area of each polygon (in m^2 if projected)
- `st_distance(pts, pts)` — pairwise distance matrix between features
- `st_centroid(polygons)`— centroid point of each polygon
- `st_buffer(pts, dist = 5000)`— 5 km buffer around each point
- `st_intersects(x, y)` — which features of `x` overlap with `y`?

Geometric operations

- `st_area(polygons)` — area of each polygon (in m^2 if projected)
- `st_distance(pts, pts)` — pairwise distance matrix between features
- `st_centroid(polygons)` — centroid point of each polygon
- `st_buffer(pts, dist = 5000)` — 5 km buffer around each point
- `st_intersects(x, y)` — which features of `x` overlap with `y`?
- `st_union(polygons)` — merge all polygons into one

Spatial joins: `st_join()`

Attach polygon attributes to points

```
# events:  sf with POINT geometry (conflict events)
# munis:   sf with POLYGON geometry (municipalities)
events_muni = st_join(events, munis,
                      join = st_within)
```

- Default: `st_intersects` (any overlap)

Spatial joins: `st_join()`

Attach polygon attributes to points

```
# events:  sf with POINT geometry (conflict events)
# munis:   sf with POLYGON geometry (municipalities)
events_muni = st_join(events, munis,
                      join = st_within)
```

- Default: `st_intersects` (any overlap)
- `st_within`: point must fall *inside* the polygon

Spatial joins: `st_join()`

Attach polygon attributes to points

```
# events:  sf with POINT geometry (conflict events)
# munis:   sf with POLYGON geometry (municipalities)
events_muni = st_join(events, munis,
                      join = st_within)
```

- Default: `st_intersects` (any overlap)
- `st_within`: point must fall *inside* the polygon
 - Passed as a function object: `join = st_within`, not `st_within()`

Spatial joins: `st_join()`

Attach polygon attributes to points

```
# events:  sf with POINT geometry (conflict events)
# munis:   sf with POLYGON geometry (municipalities)
events_muni = st_join(events, munis,
                      join = st_within)
```

- Default: `st_intersects` (any overlap)
- `st_within`: point must fall *inside* the polygon
 - Passed as a function object: `join = st_within`, not `st_within()`
- `st_nearest_feature`: attach nearest polygon (even if no overlap)

Spatial joins: `st_join()`

Attach polygon attributes to points

```
# events:  sf with POINT geometry (conflict events)
# munis:   sf with POLYGON geometry (municipalities)
events_muni = st_join(events, munis,
                      join = st_within)
```

- Default: `st_intersects` (any overlap)
- `st_within`: point must fall *inside* the polygon
 - Passed as a function object: `join = st_within`, not `st_within()`
- `st_nearest_feature`: attach nearest polygon (even if no overlap)
- Result: events data frame + municipality attributes appended

Spatial joins: `st_join()`

Attach polygon attributes to points

```
# events:  sf with POINT geometry (conflict events)
# munis:   sf with POLYGON geometry (municipalities)
events_muni = st_join(events, munis,
                      join = st_within)
```

- Default: `st_intersects` (any overlap)
- `st_within`: point must fall *inside* the polygon
 - Passed as a function object: `join = st_within`, not `st_within()`
- `st_nearest_feature`: attach nearest polygon (even if no overlap)
- Result: events data frame + municipality attributes appended
- Use case: “which district does each conflict event belong to?”

Worked example: events per municipality

1. Ensure same CRS

```
events = st_transform(events, crs = 3035)
```

```
munis = st_transform(munis, crs = 3035)
```

2. Spatial join: assign each event to a municipality

```
events_m = st_join(events, munis, join = st_within)
```

3. Count events per municipality

```
event_counts = events_m %>%
```

```
  st_drop_geometry() %>%
```

```
  group_by(muni_code) %>%
```

```
  summarize(n_events = n())
```

4. Merge back to municipality polygons

```
munis = left_join(munis, event_counts, by = "muni_code")
```

Roadmap

Why Spatial Data?

Types of Spatial Data

Coordinate Reference Systems

The `sf` Package

Visualization with `ggplot2`

Wrap-up

geom_sf(): maps in ggplot2

Basic map of world countries

```
library(ggplot2)
ggplot(world) + geom_sf() + theme_void()
```

- `geom_sf()` automatically detects geometry type (points, lines, polygons)

geom_sf(): maps in ggplot2

Basic map of world countries

```
library(ggplot2)
ggplot(world) + geom_sf() + theme_void()
```

- `geom_sf()` automatically detects geometry type (points, lines, polygons)
- Works within the full `ggplot2` grammar: `aes()`, `scale_*`(), `theme_*`()

geom_sf(): maps in ggplot2

Basic map of world countries

```
library(ggplot2)
ggplot(world) + geom_sf() + theme_void()
```

- `geom_sf()` automatically detects geometry type (points, lines, polygons)
- Works within the full `ggplot2` grammar: `aes()`, `scale_*`(), `theme_*`()
- `theme_void()` removes axes, gridlines, background — ideal for maps

geom_sf(): maps in ggplot2

Basic map of world countries

```
library(ggplot2)
ggplot(world) + geom_sf() + theme_void()
```

- `geom_sf()` automatically detects geometry type (points, lines, polygons)
- Works within the full `ggplot2` grammar: `aes()`, `scale_*`(), `theme_*`()
- `theme_void()` removes axes, gridlines, background — ideal for maps
- `coord_sf()` controls projection and extent:

geom_sf(): maps in ggplot2

Basic map of world countries

```
library(ggplot2)
ggplot(world) + geom_sf() + theme_void()
```

- `geom_sf()` automatically detects geometry type (points, lines, polygons)
- Works within the full `ggplot2` grammar: `aes()`, `scale_*()`, `theme_*()`
- `theme_void()` removes axes, gridlines, background — ideal for maps
- `coord_sf()` controls projection and extent:
`coord_sf(crs = 3035) # reproject for display`

geom_sf(): maps in ggplot2

Basic map of world countries

```
library(ggplot2)
ggplot(world) + geom_sf() + theme_void()
```

- `geom_sf()` automatically detects geometry type (points, lines, polygons)
- Works within the full `ggplot2` grammar: `aes()`, `scale_*()`, `theme_*()`
- `theme_void()` removes axes, gridlines, background — ideal for maps
- `coord_sf()` controls projection and extent:

```
coord_sf(crs = 3035) # reproject for display
```

```
coord_sf(xlim = c(-10, 40), ylim = c(35, 72))
```

Choropleth maps

Countries colored by GDP per capita

```
ggplot(world) +  
  geom_sf(aes(fill = gdp_pc), color = "white", size = 0.1) +  
  scale_fill_viridis_c(  
    name = "GDP per capita",  
    na.value = "grey80",  
    option = "magma") +  
  theme_void() +  
  labs(title = "GDP per capita (USD)")
```

- Map fill to a continuous variable $\Rightarrow$ choropleth

Choropleth maps

Countries colored by GDP per capita

```
ggplot(world) +  
  geom_sf(aes(fill = gdp_pc), color = "white", size = 0.1) +  
  scale_fill_viridis_c(  
    name = "GDP per capita",  
    na.value = "grey80",  
    option = "magma") +  
  theme_void() +  
  labs(title = "GDP per capita (USD)")
```

- Map fill to a continuous variable $\Rightarrow$ choropleth
- color = "white", size = 0.1: thin white borders between polygons

Choropleth maps

Countries colored by GDP per capita

```
ggplot(world) +  
  geom_sf(aes(fill = gdp_pc), color = "white", size = 0.1) +  
  scale_fill_viridis_c(  
    name = "GDP per capita",  
    na.value = "grey80",  
    option = "magma") +  
  theme_void() +  
  labs(title = "GDP per capita (USD)")
```

- Map fill to a continuous variable $\Rightarrow$ choropleth
- color = "white", size = 0.1: thin white borders between polygons
- na.value: color for missing data

Layering: polygons + points

Country outlines + conflict event locations

```
ggplot() +  
  geom_sf(data = world,  
    fill = "grey90", color = "white", size = 0.2) +  
  geom_sf(data = events,  
    aes(color = event_type),  
    size = 0.8, alpha = 0.6) +  
  scale_color_manual(values = c(...)) +  
  coord_sf(xlim = c(-18, 52), ylim = c(-35, 38)) +  
  theme_void()
```

- Add multiple `geom_sf()` layers with `data =` argument

Layering: polygons + points

Country outlines + conflict event locations

```
ggplot() +  
  geom_sf(data = world,  
    fill = "grey90", color = "white", size = 0.2) +  
  geom_sf(data = events,  
    aes(color = event_type),  
    size = 0.8, alpha = 0.6) +  
  scale_color_manual(values = c(...)) +  
  coord_sf(xlim = c(-18, 52), ylim = c(-35, 38)) +  
  theme_void()
```

- Add multiple `geom_sf()` layers with `data =` argument
- Each layer can use a different `sf` object

Layering: polygons + points

Country outlines + conflict event locations

```
ggplot() +  
  geom_sf(data = world,  
    fill = "grey90", color = "white", size = 0.2) +  
  geom_sf(data = events,  
    aes(color = event_type),  
    size = 0.8, alpha = 0.6) +  
  scale_color_manual(values = c(...)) +  
  coord_sf(xlim = c(-18, 52), ylim = c(-35, 38)) +  
  theme_void()
```

- Add multiple `geom_sf()` layers with `data =` argument
- Each layer can use a different `sf` object
- Order matters: later layers drawn on top

A complete example: European unemployment

```
library(sf); library(dplyr); library(ggplot2)

# Read NUTS-2 regions (Eurostat shapefile)
nuts2 = st_read("data/NUTS_RG_20M_2021.shp") %>%
  filter(LEVL_CODE == 2)

# Join unemployment data
nuts2 = left_join(nuts2, unemp_df, by = "NUTS_ID")

# Map
ggplot(nuts2) +
  geom_sf(aes(fill = unemp_rate),
    color = "white", size = 0.1) +
  scale_fill_distiller(palette = "YlOrRd",
    direction = 1, name = "Unemployment (%)") +
  coord_sf(xlim = c(-25, 45), ylim = c(34, 72)) +
  theme_void()
```

Map aesthetics: quick tips

- **Color scales for continuous data**, some options:

Map aesthetics: quick tips

- **Color scales for continuous data**, some options:
 - Sequential: `scale_fill_viridis_c()` for one-direction variables

Map aesthetics: quick tips

- **Color scales for continuous data**, some options:
 - Sequential: `scale_fill_viridis_c()` for one-direction variables
 - Diverging: `scale_fill_distiller(type = "div")` for +/- variables

Map aesthetics: quick tips

- **Color scales for continuous data**, some options:
 - Sequential: `scale_fill_viridis_c()` for one-direction variables
 - Diverging: `scale_fill_distiller(type = "div")` for +/- variables
- **Borders**, subtle: `color = "white", linewidth = 0.1`

Map aesthetics: quick tips

- **Color scales for continuous data**, some options:
 - Sequential: `scale_fill_viridis_c()` for one-direction variables
 - Diverging: `scale_fill_distiller(type = "div")` for +/- variables
- **Borders**, subtle: `color = "white", linewidth = 0.1`
- **Theme**: `theme_void()` for clean maps; add `theme(legend.position = "bottom")`

Map aesthetics: quick tips

- **Color scales for continuous data**, some options:
 - Sequential: `scale_fill_viridis_c()` for one-direction variables
 - Diverging: `scale_fill_distiller(type = "div")` for +/- variables
- **Borders**, subtle: `color = "white", linewidth = 0.1`
- **Theme**: `theme_void()` for clean maps; add `theme(legend.position = "bottom")`
- **Missing data**: always set `na.value = "grey80"` in scale

Map aesthetics: quick tips

- **Color scales for continuous data**, some options:
 - Sequential: `scale_fill_viridis_c()` for one-direction variables
 - Diverging: `scale_fill_distiller(type = "div")` for +/- variables
- **Borders**, subtle: `color = "white", linewidth = 0.1`
- **Theme**: `theme_void()` for clean maps; add `theme(legend.position = "bottom")`
- **Missing data**: always set `na.value = "grey80"` in scale
- **Projection**, some are useful: e.g. use `coord_sf(crs = 3035)` for Europe without reprojecting data

Roadmap

Why Spatial Data?

Types of Spatial Data

Coordinate Reference Systems

The sf Package

Visualization with ggplot2

Wrap-up

Key takeaways

- **Spatial data** = regular data + geometry column

Key takeaways

- **Spatial data** = regular data + geometry column
 - Vector: points, lines, polygons — discrete objects with attributes

Key takeaways

- **Spatial data** = regular data + geometry column
 - Vector: points, lines, polygons — discrete objects with attributes
- **CRS**: always check, always match before joining

Key takeaways

- **Spatial data** = regular data + geometry column
 - Vector: points, lines, polygons — discrete objects with attributes
- **CRS**: always check, always match before joining
 - EPSG:4326 (WGS84) for raw data; project before computing distances

Key takeaways

- **Spatial data** = regular data + geometry column
 - Vector: points, lines, polygons — discrete objects with attributes
- **CRS**: always check, always match before joining
 - EPSG:4326 (WGS84) for raw data; project before computing distances
- **sf package**: the modern R standard

Key takeaways

- **Spatial data** = regular data + geometry column
 - Vector: points, lines, polygons — discrete objects with attributes
- **CRS**: always check, always match before joining
 - EPSG:4326 (WGS84) for raw data; project before computing distances
- **sf package**: the modern R standard
 - `st_read()`, `st_as_sf()`, `st_transform()`, `st_join()`

Key takeaways

- **Spatial data** = regular data + geometry column
 - Vector: points, lines, polygons — discrete objects with attributes
- **CRS**: always check, always match before joining
 - EPSG:4326 (WGS84) for raw data; project before computing distances
- **sf package**: the modern R standard
 - `st_read()`, `st_as_sf()`, `st_transform()`, `st_join()`
 - Works seamlessly with `dplyr` and `ggplot2`

Key takeaways

- **Spatial data** = regular data + geometry column
 - Vector: points, lines, polygons — discrete objects with attributes
- **CRS**: always check, always match before joining
 - EPSG:4326 (WGS84) for raw data; project before computing distances
- **sf package**: the modern R standard
 - `st_read()`, `st_as_sf()`, `st_transform()`, `st_join()`
 - Works seamlessly with `dplyr` and `ggplot2`
- **Visualization**: `geom_sf()` inside `ggplot2`

Key takeaways

- **Spatial data** = regular data + geometry column
 - Vector: points, lines, polygons — discrete objects with attributes
- **CRS**: always check, always match before joining
 - EPSG:4326 (WGS84) for raw data; project before computing distances
- **sf package**: the modern R standard
 - `st_read()`, `st_as_sf()`, `st_transform()`, `st_join()`
 - Works seamlessly with `dplyr` and `ggplot2`
- **Visualization**: `geom_sf()` inside `ggplot2`
 - Choropleth: `aes(fill = variable) + scale_fill_viridis_c()`

Key takeaways

- **Spatial data** = regular data + geometry column
 - Vector: points, lines, polygons — discrete objects with attributes
- **CRS**: always check, always match before joining
 - EPSG:4326 (WGS84) for raw data; project before computing distances
- **sf package**: the modern R standard
 - `st_read()`, `st_as_sf()`, `st_transform()`, `st_join()`
 - Works seamlessly with `dplyr` and `ggplot2`
- **Visualization**: `geom_sf()` inside `ggplot2`
 - Choropleth: `aes(fill = variable) + scale_fill_viridis_c()`
- **Workflow**: read → check CRS → transform → join → visualize

For next session

- Complete Assignment 7 (spatial data in R)
 - Load a shapefile, inspect CRS, reproject, make a choropleth
 - Perform a spatial join: assign event points to municipality polygons
- Next session (Spatial data II):
 - Spatial autocorrelation: Moran's I
 - Spatial weights matrices
 - Spatial regression models (SAR, SEM, SLM)

Questions?