

# Q Joint sealing tape 300

greenteQ joint sealing tape 300 is a watertight soft polyurethane foam with acrylic-dispersion-impregnated sealing tape for connection joints.

Properties:

- a. Window manufacture (watertight connection joints, thermal insulation between window frame and masonry, profile couplings, backing, mullion installations)

b. Facade technology (facing for in-situ concrete / concrete placement, formwork connection in the case of concrete placement)

c. Interior work (light-weight partition walls, separating double floors)
- d. Sloped roof (skylight, pantile sealing, ridge/arris/valley/dormer window)

• Watertightness (EN 1027) II 300 Pa  
(fulfils BG 2 requirement for watertightness according to DIN 18542)

Product picture:



Technical data:

	STANDARD	CLASSIFICATION
Colour		Anthracite
Fire behaviour	DIN 4102, Part 1	B2 (MPA, Hannover)
Temperature range		-20°C to +60°C
Joint permeability coefficient	DIN EN 1026	$a_v < 1,0 \text{ m}^3/[\text{h} \cdot \text{m} \cdot (\text{daPa})^{2/3}]$
Watertightness of joints	DIN EN 1027	$\geq 300 \text{ Pa}$
sd-value	DIN EN ISO 12572	$\leq 0,5 \text{ m}$
Storage stability		Approx. 18 months after date of production

Name	Joint width	Supply unit
10 / 2	2 mm	375.0 m
15 / 2-3	2 - 3 mm	250.0 m
15 / 3-5	3 - 5 mm	200.0 m
15 / 4-7	4 - 7 mm	160.0 m
20 / 6-10	6 - 10 mm	84.0 m
20 / 8-13	8 - 13 mm	64.5 m

Application:

Please consult the assembly manual provided in each box.

Cleaning:

Clean skin with soap and water.

## PRODUCT DATA SHEET

FOILS AND TAPES - Joint sealing tape 300

