

greenteQ Joint sealing tape 300

greenteQ joint sealing tape 300 is a watertight soft polyurethane foam with acrylic-dispersion-impregnated sealing tape for connection joints.

Properties:

- a. Window manufacture (watertight connection joints, thermal insulation between window frame and masonry, profile couplings, backing, mullion installations)
- b. Facade technology (facing for in-situ concrete / concrete placement, formwork connection in the case of concrete placement)
- c. Interior work (light-weight partition walls, separating double floors)
- d. Sloped roof (skylight, pantile sealing, ridge/arris/valley/dormer window)
 - Watertightness (EN 1027) ≥ 300 Pa (fulfils BG 2 requirement for watertightness according to DIN 18542)

Product picture:



Technical data:

	STANDARD	CLASSIFICATION
Colour		Anthracite
Fire behaviour	DIN 4102, Part 1	B2 (MPA, Hannover)
Temperature range		-20°C to +60°C
Joint permeability coefficient	DIN EN 1026	$a_n < 1,0 \text{ m}^3/[\text{h} \cdot \text{m} \cdot (\text{daPa})^{2/3}]$
Watertightness of joints	DIN EN 1027	$\geq 300 \text{ Pa}$
sd-value	DIN EN ISO 12572	$\leq 0,5 \text{ m}$
Storage stability		Approx. 18 months after date of production

Name	Joint width	Supply unit	VBH Item Number
10 / 2	2 mm	375.0 m	180.020 / 0031
15 / 2-3	2 - 3 mm	250.0 m	180.020 / 0032
15 / 3-5	3 - 5 mm	200.0 m	180.020 / 0033
15 / 4-7	4 - 7 mm	160.0 m	180.020 / 0034
20 / 6-10	6 - 10 mm	84.0 m	180.020 / 0035
20 / 8-13	8 - 13 mm	64.5 m	180.020 / 0036

Application:

Please consult the assembly manual provided in each box.

Cleaning:

Clean skin with soap and water.

PRODUCT DATA SHEET

FOILS AND TAPES - Joint sealing tape 300

The instructions for use, service and product details as well as other technical information for our greenteQ products are general guidelines. These serve only to describe the properties and performance features of our products and do not constitute a guarantee as per Section 443 of the BGB (German Civil Code). Due to the variety of possible applications, it is incumbent upon the user to test whether or not it is suitable for the desired application. Technical application advice provided by us verbally, in writing or through tests is for your information only and is absolutely non-binding.

Edition 07/2011 | www.vbh.de

greenteQ

Dichtungsband 300

greenteQ joint sealing tape 300 is a watertight soft polyurethane foam with acrylic-dispersion-impregnated sealing tape for connection joints.

Safety notice:



Based on existing data and experience, this product is not a hazardous substance as per the Chemicals Act or comparable EC directives.

Form of delivery:



Pre-compressed, in rolls, self-adhesive on one side (roll length: depends on thickness, widths: 10 mm and above)

Disposal:



Left-over tape can be disposed of with domestic waste. Observe local regulations.

General information:



All previous versions of this data sheet are no longer valid.