VM Performance Evaluation with Functional Models

An Optimist's Outlook

TECHNISCHE UNIVERSITÄT DARMSTADT

Jan Sinschek

3rd International Workshop on Virtual Machines and Intermediate Languages
Oct 25th 2009

The Status of VM Performance Assessment

TECHNISCHE UNIVERSITÄT DARMSTADT



- Cascading effects
- Chaotic Behaviour

- Some nondeterminism is accepted
  - Noise
  - ...which is where bias hides

“Statistically Rigorous Java Performance Analysis”

TECHNISCHE UNIVERSITÄT DARMSTADT





“Wake up and smell the coffee”

TECHNISCHE UNIVERSITÄT DARMSTADT

- Advocates diverse Benchmarks

the DaCapo benchmark suite



- Proposes ways to control nondeterminism

- Demands meaningful baseline and publishing the implementation

„Producing Wrong Data Without Doing Anything Obviously Wrong“

TECHNISCHE UNIVERSITÄT DARMSTADT



Suggestions for dealing with bias

- Setup randomization
- Causal analysis of an intervention

Functional Performance Models

TECHNISCHE UNIVERSITÄT DARMSTADT

$$P_\gamma(n) = S_\gamma + F_\gamma(n)$$



Functional Performance Models

TECHNISCHE UNIVERSITÄT DARMSTADT

$$P_\gamma(n) = S_\gamma + F_\gamma(n)$$

Mean Value



Functional Performance Models

TECHNISCHE UNIVERSITÄT DARMSTADT

$$P_\gamma(n) = S_\gamma + F_\gamma(n)$$

Confidence Interval



A Case Study Proposal

TECHNISCHE UNIVERSITÄT DARMSTADT

Scenario: Edge Profiling in Jikes VM

- Some counters are redundant
  - JIT compilation could lessen it
  - Values can be reconstructed afterwards
- This might we worthwhile
  - But it would cause overhead
  - We want to determine what strategy to use for overhead reduction



The Model for Counter Cost

TECHNISCHE UNIVERSITÄT DARMSTADT

- What to model
  - Counters necessary and safeable
  - Their respective performance contributions

- Specific Model:
  - Cost of counters in baseline code (γ)
  - Counter frequency (m_i)

$$P(n) = P(0) + \gamma \sum_{i \in n} placed?_i * m_i$$



A More Realistic Model

TECHNISCHE UNIVERSITÄT DARMSTADT

- Put counters into a broader model context
  - Based on recompilation plans, with r_0 opt-compiling nothing

$$P_{steady}(r,n) = P_{steady}(r_0,n_0) - \gamma \sum_{i \in n} m_i$$

  - The approach works as part of a rigorous recompilation setup

- Benefits to expect
  - Increased confidence in evaluation
  - Knowledge about the behaviour of profiling counters and the benchmarks
    - Helps to predict what optimization can pay off

What are Feasible Applications?

TECHNISCHE UNIVERSITÄT DARMSTADT

- Code Instrumentation
- Security Label Checking
- Execution Sampling
- GC Barrier Instrumentation

- Adaptive Compilation
- Pretenuring
- Thread Interactions
- Inlining

Summary

TECHNISCHE UNIVERSITÄT DARMSTADT

- Functional Models geared towards transferable research results

$$P(n) = P(0) + \gamma \sum_{i \in n} placed_i * m_i$$

- The discovery of bias still depends on the variety in the benchmarking environment



- Scope needs to be explored

- Applies to new functionality as well

?